

RF Exposure Evaluation of

E.U.T. : BL4012 5.8GHz WLAN ODU

FCC ID. : QZGBL4012-001

MODEL : BL4012

for

APPLICANT : K-Best Technology Inc.

ADDRESS : 2FI-1, No.185, Ko Wang Rd., Kau Yuan Tsun,
Lung Tan Hsiang, Tao Yuan Hsien, Taiwan

Prepared by

ELECTRONICS TESTING CENTER, TAIWAN

NO. 34, LIN 5, DING FU TSUN, LINKOU HSIANG,
TAIPEI HSIEN, TAIWAN, R.O.C.

Tel:(02)26023052

Fax:(02)26010910

<http://www.etc.org.tw> ; e-mail: etcemi@seed.net.tw

Report Number : ET93R-02-049

Product Information:

Type of EUT : BL4012 5.8GHz WLAN ODU
 FCC ID : QZGBL3006F-001
 Manufacturer : K-Best Technology Inc.
 Model : BL4012
 Description : 1. 5725~5850 MHz unlicensed ISM Band
 2. IEEE 802.11 Standard
 3. Provides DC Power to the ODU with PoE (Power over Ethernet)
 4. 23dBm output power levels
 5. 20 dB receive gain for the ODU
 6. Bi-directional TDD technology
 7. Transmitter and receiver LED
 8. Waterproof housing
 9. The Z-COM WLAN Access Point is currently certified with FCC ID:M4Y-000325

Maximum conducted output power (measured): **22.5** dBm or **177.83** mW

The following table lists the provided authorized antennas: Antenna Gain (dBi)

Antenna Model	Antenna type	Antenna Gain	
		(dBi)	Numeric
KBNT5824-16	Flat Panel	24	251.2
KBNT5826-13	Grid	26	398.1

Below is an example of the RF Exposure Statement:

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment when installed as directed. This equipment should be installed and operated with fix-mounted antennas that are installed with a minimum of **2 meters** of separation distance between the antenna and all persons' body during normal operation.

Relative Requirement for Compliance

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following:

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0 mW/cm² uncontrolled exposure limit. The formula shown in OET Bulletin 65 is used in the calculation.

Equation from page 19 of OET Bulletin 65, Edition 97-01 is:

$$S = PG / 4 \pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm²)
 P = power input to the antenna (in appropriate units, e.g., mW)
 G = power gain of the antenna in the direction of interest relative to an isotropic radiator
 R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

hence

$$R = (PG / 4 \pi S)^{1/2}$$

For our device

P = 177.83 mW

G = 398.1

S = Exposure limit = 1.0 mW/cm²

$$R = ((177.83 * 398.1) / (4 * \pi * 1.0))^{1/2}$$

$$= \underline{\underline{75.1 \text{ cm}}}$$

For complying the FCC limits for general population/uncontrolled exposure, the minimum MPE distance is **75.1 cm**.

The minimum distance declared by the manufacturer is **2 meters**, which is greater than the minimum MPE distance.

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of 47 CFR Part 15.247 (b)(5).