

# The description of the equipment label

■The description of the equipment label is shown as followings.

Ground Color:White  
Font Color:Black

MODEL : EM-G21  
INPUT : 12V  $\overline{=}$  1.3A  
CONFORMS TO ANSI / UL STD 60950-1  
FCC ID : R2BEMG21  
This device complies with Part 15 of the FCC Rules.  
Operation is subject to the following two conditions:(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

<Default>  
SSID-1 : emg21-XXXXXX-1  
Security Encryption Key1 : XXXXXXXXXXXXXXXX  
SSID-2 : emg21-XXXXXX-2  
Security Encryption Key2 : XXXXXXXXXXXXXXXX  
PIN Code : PPPPPPPP  
LAN side MAC address XX:XX:XX:XX:XX:XX  
WAN side MAC address XX:XX:XX:XX:XX:XX

1次元バーコード  
(MACアドレス)

\*AAAAAA-AAAA\*

DATE : MMM-12  
Product No. XXXXXXXXXXXXXXXX  
HITACHI,Ltd.,JAPAN

CAUTION

ETL us  
Intertek  
4006371  
FC

2次元コード

## Constant Items

- MODEL:EM-G21
- INPUT:12V(Direct Current Symbol)1.3A
- DATE: Month(abbreviated) + Year(2-digit years)
- MANUFACTURER: HITACHI,LTD.,JAPAN
- Statement on UL certification:  
CONFORMS TO ANSI/UL STD 60950-1
- Control Number:  
(ETL Verified Certificate of Conformance Number)
- FCC ID:R2BEMG21
- Statement on FCC Compliance:  
This device complies with Part 15 of the FCC Rules.  
Operation is subject to the following two conditions:  
(1) this device may not cause harmful interference,  
and(2) this device must accept any interference  
that may cause undesired operation.

## Variable Items

- <Default Value>
- SSID-1 : emg21-\*\*\*\*\*-1
  - Password1 : \*\*\*\*\*
  - SSID-2 : emg21-\*\*\*\*\*-2
  - Password2 : \*\*\*\*\*
  - LAN side MAC address \*\*:\*:\*:\*:\*:\*:\*
  - WAN side MAC address \*\*:\*:\*:\*:\*:\*:\*
  - PIN Code : PPPPPPPP
  - Product No. \*\*\*\*\*

## Displayed Symbols



# The position of the equipment label pasted

- The equipment label is pasted in the center of the right side of the equipment.

