



683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080

Tel: +82-31-321-2664 Fax: +82-31-321-1664

<http://www.digitalemcc.com>**CERTIFICATE OF COMPLIANCE**
FCC Part 22, 24 CertificationDates of Tests: January 2 ~ 23, 2008
Test Report S/N: DR50110801AK
Test Site : DIGITAL EMC CO., LTD.

Model No.

R2NSEC-7089

APPLICANT

Epivalley CO.,LTD.

Classification	:	Licensed Portable Transmitter (PCB)
FCC Rule Part(s)	:	§22(H), §24(E), §2
EUT Type	:	CDMA 1X EvDo USB Modem
CDMA EvDo Protocol Rev.	:	A
Model name	:	SEC-7089
Serial number	:	Identical prototype
TX Frequency Range	:	824.70 ~848.31 MHz (Cellular band) 1851.25 ~ 1908.75MHz (PCS band)
RX Frequency Range	:	869.70 ~893.31 MHz (Cellular band) 1931.25 ~ 1988.75MHz (PCS band)
Max. RF Output Power	:	0.393W ERP CDMA Cellular Band (25.94dBm) 0.403W EIRP CDMA PCS Band (26.05dBm)
Max. SAR Measurement	:	0.820W/kg CDMA Cellular Band Body SAR 0.644W/kg CDMA PCS Band Body SAR
Emission Designators:	:	CDMA Cellular Band - 1M28F9W CDMA PCS Band - 1M28F9W
Date of Issue	:	January 24, 2008

TABLE OF CONTENTS

◆ AUTHORIZATION LETTER	
◆ CONFIDENTIALITY LETTER(S)	
◆ TEST REPORT	
1.1 SCOPE	3
2.1 GENERAL INFORMATION	4
3.1 DESCRIPTION OF TESTS	5
4.1 TEST DATA	8
4.1.1 CONDUCTED OUTPUT POWER	8
4.1.2 EFFECTIVE RADIATED POWER OUTPUT	9
4.1.3 CDMA RADIATED MEASUREMENTS	10
4.1.4 FREQUENCY STABILITY(CDAM)	16
5.1 PLOTS OF EMISSIONS	20
6.1 LIST OF TEST EQUIPMENT	21
7.1 SAMPLE CALCULATIONS	23
8.1 CONCLUSION	24
◆ TEST PLOTS	
◆ FCC ID LABEL & LOCATION	
◆ TEST SETUP PHOTOGRAPHS	
◆ EXTERNAL PHOTOGRAPHS	
◆ INTERNAL PHOTOGRAPHS	
◆ BLOCK DIAGRAM(S)	
◆ SCHEMATIC DIAGRAM(S)	
◆ OPERATIONAL DESCRIPTION	
◆ PARTS LIST	
◆ PARTS LOCATION	
◆ USER'S MANUAL	

MEASUREMENT REPORT

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

§2.1033 General Information

Applicant: Epivalley CO.,LTD.

**Address: Lordland EZ Tower #511, 153, Gumi-Dong, Bundang-Gu,
SEONGNAMCITY, GYUNGGI, KOREA**

Attention: Woo Won Choung

- FCC ID: R2NSEC-7089
- Quantity: Quantity production is planned
- Emission Designators: CDMA Cellular Band - 1M28F9W
CDMA PCS Band - 1M28F9W
- Tx Freq. Range: 824.70 ~ 848.31 MHz (Cellular Band)
1851.25 ~ 1908.75MHz (MHz Band)
- Rx Freq. Range: 869.70 - 893.31 MHz (Cellular Band)
1931.25 ~ 1988.75MHz (PCS Band)
- Max. Power Rating: 0.393W ERP CDMA Cellular Band(25.94dBm)
0.403W ERP CDMA PCS Band (26.05dBm)
- FCC Classification(s): Licensed Portable Transmitter (PCB)
- Equipment (EUT) Type: CDMA 1X EvDo USB Modem
- CDMA EvDo Protocol Rev. A
- Modulation(s): CDMA
- Frequency Tolerance: $\pm 0.00025\%$ (2.5ppm)
- FCC Rule Part(s): §22(H), §24(E), §2
- Dates of Tests: January 2 ~ 23, 2008
- Place of Tests: DIGITAL EMC
- Test Report S/N: DR50110801AK

2.1. General Information

This report contains the result of tests performed by:

DIGITAL EMC CO., LTD.

Address : 683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080

<http://www.digitalemcc.com> E-mail : harveysung@digitalemcc.com

Tel: +82-31-321-2664 Fax: +82-31-321-1664

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200559-0.

Test operator: engineer

January 24, 2008

Won-Jung LEE

Data

Name

Signature

Report Reviewed By: manager

January 24, 2008

Harvey Sung

Data

Name

Signature

Ordering party:

Company name : SUNGIL TELECOM CO., LTD.
 Address : Loadland EZ Tower #511, 513, Gumi-dong, Bundang-Gu,
 Zipcode : 463-500
 City/town : SEONGNAM-CITY, KYUNGKI
 Country : KOREA
 Date of order : January 2, 2008

3.1 DESCRIPTION OF TESTS

3.1.1 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- (b) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (c) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

3.1.2 Occupied Bandwidth

The 99% power bandwidth was measured with a calibrated spectrum analyzer.

3.1.3 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz.

At the input terminals of the spectrum analyzer, an isolator(RF circulator with one port terminated with 50ohms) and an 870 MHz to 890 MHz band pass filter is connected between the test transceiver(for conducted tests)or the receive antenna(for radiated tests) and the analyzer . The rejection of the band pass filter to signals in the 825-845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than -90dBm. Calibration of the test receiver is performed in the 870-890 MHz range to insure accuracy to allow variation in the band pass filter insertion loss to be calibrated.

3.1.4 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

3.1.5 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

3.1 DESCRIPTION OF TESTS

(Continued...)

3.1.6 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

- a) **Temperature** :The temperature is varied from -30°C to $+60^{\circ}\text{C}$ using an environmental chamber.
- b) **Primary Supply Voltage** :The primary supply voltage is varied from 85% to 115% of the voltage Normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification –The minimum frequency stability shall be $\pm 0.00025\%$ at any time during normal operation.

Specification — The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025 (\pm 2.5\text{ppm})$ of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27°C to provide a reference)
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight ”soak” at -30°C (usually 14-16 hours),the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency to the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements is made at 10°C interval up to room temperature. At least a period of one and one half hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency were made at 10 intervals starting at -30°C up to $+50^{\circ}\text{C}$ allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

3.1 DESCRIPTION OF TESTS

(Continued...)

3.1.7 Radiated Emission

Final test was performed according to ANSI C63.4-2003 at the open field test site. There are no deviations from the standard.

The EUT was placed in a 0.8m high table along with the peripherals. The turn table was separated from the antenna distance 3meters. Cables were placed in a position to produce maximum emissions as determined by experimentation, and operation mode was selected for maximum.

The frequencies and amplitudes of maximum emission were measured at varying azimuths, antenna heights and antenna polarities. Reported are maximized emission levels.

These tests were performed at 120kHz of 6dB bandwidth.

3.1.8 Conducted Emission

The power line conducted interference measurements were performed according to ANSI C63.4-2003 in a shielded enclosure with peripherals placed on a table, 0.8m high over a metal floor. It was located more than required distance away from the shielded enclosure wall. There are no deviations from the standard.

The EUT was plugged into the LISN and the frequency range of interest scanned.

Reported are maximized emission levels.

These tests were performed at 9kHz of 6dB bandwidth.

4.1 TEST DATA

4.1.1 Conducted Output Power

The output power was measured under all R.C.s and S.O.s which are listed below measurement data. The worst case output power is reported with SO55 of RC3 for CELLULAR band and SO55 of RC1 for PCS band. Therefore this device was tested under SO55 of RC3 for CELLULAR band and SO55 of RC1 for PCS band.

SAR Measurement Procedures for 3G Devices(Released October 2007)

- verify maximum output power
 - on high, middle and low channels
 - according to 3GPP2 C.S0011 / TIA-98-E, Sec. 4.4.5
- Power measurement configurations
 1. 1X RRT
 - Test Mode 1(C.S0011 Table 4.4.5.2-1), SO55, RC1, Traffic Channel @9600bps
 - Test Mode 3(C.S0011 Table 4.4.5.2-2), SO55 or SO32, RC3, FCH @9600bps
 - Test Mode 3(C.S0011 Table 4.4.5.2-2), SO32, RC3, FCH+SCH @9600bps
 - other configurations supported by the DUT
 - power control
 - Bits Hold for FCH+SCH
 - otherwise ALL Bits Up
 2. Ev-DO Rev.0
 - FTAP: 2 slot version of 307.2Kbps(ACK in all slots)
 - RTAP: 153.6Kbps in sub type 0/1 PHY Configuration
 3. Ev-DO Rev.A
 - FTAP: 2 slot version of 307.2Kbps(ACK in all slots)
 - RTAP: 4096 bits payload with 16 slot termination targeter

- Measurement data

Band	Channel	1X RRT						EvDO (Rev. 0)	EvDO (Rev. A)
		RC1	RC1	RC3	RC3	RC3	RC3		
		SO2	SO55	SO2	SO55	SO32 (Only FCH)	SO32 (TDSO)		
Cellular	1013	24.51	24.48	24.58	24.57	24.55	24.55	23.83	23.17
	384	24.44	24.45	24.57	24.58	24.61	24.62	23.88	23.04
	777	23.91	23.91	24.01	24.05	23.99	23.99	22.98	22.42
PCS	25	25.62	25.66	25.55	25.56	25.55	25.54	24.19	23.86
	600	23.74	23.74	23.56	23.68	23.58	23.60	23.93	23.59
	1175	23.86	23.94	24.09	24.16	23.91	23.95	24.13	23.76

4.1.2 Effective Radiated Power Output

A. POWER: High (Cellular Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	Supplied Power	Note
824.70	-15.31	V	0.307	24.87	DC 5V	RC3 SO55
836.52	-13.73	V	0.393	25.94	DC 5V	RC3 SO55
848.31	-14.36	V	0.297	24.73	DC 5V	RC3 SO55

B. POWER: High (PCS Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	EIRP (W)	EIRP (dBm)	Supplied Power	Note
1851.25	-13.01	V	0.403	26.05	DC 5V	RC1 SO55
1880.00	-14.41	V	0.264	24.22	DC 5V	RC1 SO55
1908.75	-15.10	V	0.257	24.10	DC 5V	RC1 SO55

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

4.1.3 CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 824.7 MHz
 CHANNEL : 1013(Low)
 MEASURED OUTPUT POWER : 24.87 dBm = 0.307 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 37.87 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-46.07	6.84	-39.23	H	64.10
1649.40	-47.32	6.84	-40.48	V	65.35
-	-	-	-	-	-

- No other emissions were detected at a level greater than 10dB below limit.

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

4.1.3 CDMA Radiated Measurements

(Continued...)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 836.52 MHz
 CHANNEL : 384(Mid)
 MEASURED OUTPUT POWER : 25.94 dBm = 0.393 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 38.94 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-44.17	6.54	-37.63	H	63.57
1673.04	-45.56	6.54	-39.02	V	64.96
-	-	-	-	-	-

- No other emissions were detected at a level greater than 10dB below limit.

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

4.1.3 CDMA Radiated Measurements

(Continued...)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 848.31 MHz
 CHANNEL : 777(High)
 MEASURED OUTPUT POWER : 24.73 dBm = 0.297 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 37.73 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-46.51	6.57	-39.94	H	64.67
1696.62	-45.41	6.57	-38.84	V	63.57
-	-	-	-	-	-

- No other emissions were detected at a level greater than 10dB below limit.

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

4.1.3 CDMA Radiated Measurements

(Continued...)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 1851.25 MHz
 CHANNEL : 25(Low)
 MEASURED OUTPUT POWER : 26.05 dBm = 0.403 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 39.05 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-47.69	9.37	-38.32	H	64.37
3702.50	-47.80	9.37	-38.43	V	64.48
-	-	-	-	-	-

- No other emissions were detected at a level greater than 10dB below limit.

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

4.1.3 CDMA Radiated Measurements

(Continued...)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 1880.00 MHz
 CHANNEL : 600(Mid)
 MEASURED OUTPUT POWER : 24.22 dBm = 0.264 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 37.22 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-47.98	9.25	-38.73	H	62.95
3760.00	-47.66	9.25	-38.41	V	62.63
-	-	-	-	-	-

- No other emissions were detected at a level greater than 10dB below limit.

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

4.1.3 CDMA Radiated Measurements

(Continued...)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 1908.75 MHz
 CHANNEL : 1175(High)
 MEASURED OUTPUT POWER : 24.10 dBm = 0.257 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 37.10 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-47.76	9.15	-38.61	H	62.71
3817.50	-44.88	9.15	-35.73	V	59.83
-	-	-	-	-	-

- No other emissions were detected at a level greater than 10dB below limit.

NOTE

Radiated Spurious Emission Measurements by Substitution Method
 according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



4.1.4 Frequency Stability (CDMA)

OPERATING FREQUENCY : 836,520,014 Hz
 CHANNEL : 0384(Mid)
 REFERENCE VOLTAGE : 5 VDC
 DEVIATION LIMIT : ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (dB)	FREQ (Hz)	Deviation (%)
100%	5	+25(Ref)	836,520,014	0.000000
100%		-30	836,520,024	0.000001
100%		-20	836,520,021	0.000001
100%		-10	836,520,018	0.000000
100%		0	836,519,990	-0.000003
100%		+10	836,519,988	-0.000003
100%		+20	836,519,989	-0.000003
100%		+25	836,520,014	0.000000
100%		+30	836,520,018	0.000000
100%		+40	836,520,017	0.000000
100%		+50	836,520,018	0.000000
100%		+60	836,520,023	0.000001
85%	4.25	+25	836,519,992	-0.000003
115%	5.75	+25	836,519,977	-0.000004
BATT.ENDPOINT	2.45	+25	836,519,932	-0.000010

4.1.4 Frequency Stability (CDMA)

(Continued...)



4.1.4 Frequency Stability (CDMA)



(Continued...)

OPERATING FREQUENCY : 1,879,999,979 Hz
CHANNEL : 600(Mid)
REFERENCE VOLTAGE : 5 VDC
DEVIATION LIMIT : ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (dB)	FREQ (Hz)	Deviation (%)
100%	5	+25(Ref)	1,879,999,979	0.000000
100%		-30	1,879,999,959	-0.000001
100%		-20	1,879,999,962	-0.000001
100%		-10	1,879,999,952	-0.000001
100%		0	1,879,999,979	0.000000
100%		+10	1,879,999,969	-0.000001
100%		+20	1,879,999,972	0.000000
100%		+25	1,879,999,979	0.000000
100%		+30	1,880,000,018	0.000002
100%		+40	1,880,000,038	0.000003
100%		+50	1,880,000,029	0.000003
100%		+60	1,880,000,041	0.000003
85%	4.25	+25	1,880,000,028	0.000003
115%	5.75	+25	1,880,000,035	0.000003
BATT.ENDPOINT	2.45-	+25	1,879,999,924	-0.000003

4.1.4 Frequency Stability (CDMA)

(Continued...)



5.1 PLOTS OF EMISSIONS

(SEE ATTACHMENT “Test Plots”)

6.1 LIST OF TEST EQUIPMENT

	Type	Manufacturer	Model	Cal.Due.Date (dd/mm/yy)	Next.Due.Date (dd/mm/yy)	S/N
01	Spectrum Analyzer	Agilent	E4404B	17/04/07	17/04/08	US41061134
02	Spectrum Analyzer	Agilent	E4440A	15/11/07	15/11/08	MY45304199
03	Spectrum Analyzer	H.P	8563E	09/10/07	09/10/08	3551A04634
04	Spectrum Analyzer	H.P	8591E	16/04/07	16/04/08	3649A05889
05	EMI Test Receiver	R&S	ESCI	27/04/07	27/04/08	100364
06	EMI Test Receiver	R&S	ESU	25/01/07	25/01/08	100014
07	Power Meter	H.P	EPM-442A	10/07/07	10/07/08	GB37170413
08	Power Sensor	H.P	8481A	11/07/07	11/07/08	3318A96332
09	Frequency Counter	H.P	5342A	06/09/07	06/09/08	2119A04450
10	Multifunction Synthesizer	H.P	8904A	23/11/07	23/11/08	3633A08404
11	Signal Generator	Rohde Schwarz	SMR20	21/03/07	21/03/08	101251
12	Signal Generator	H.P	E4421A	10/07/07	10/07/08	US37230529
13	Audio Analyzer	H.P	8903B	10/07/07	10/07/08	3011A09448
14	Modulation Analyzer	H.P	8901B	14/07/07	14/07/08	3028A03029
15	8960 Series 10 Wireless Comms Test Set	Agilent	Z5515C	18/07/07	18/07/09	GB43461134
16	Universal Radio Communication Test	Rohde Schwarz	CMU200	24/04/07	24/04/08	107631
17	Multi system UE Tester	Japan Radid Co., Ltd	NJZ-2000	N/A	N/A	ET00095
18	Power Splitter	WEINSCHEL	1593	05/10/07	05/10/08	332
19	BAND Reject Filter	Microwave Circuits	N0308372	18/10/07	18/10/08	3125- 01DC0312
20	BAND Reject Filter	Wainwright	WRCG1750	18/10/07	18/10/08	SN2
21	AC Power supply	DAEKWANG	5KVA	20/03/07	20/03/08	N/A
22	DC Power Supply	H.P	6622A	20/03/07	20/03/08	465487
23	HORN ANT	EMCO	3115	10/08/07	10/08/08	6419
24	HORN ANT	EMCO	3115	09/10/07	09/10/08	21097
25	HORN ANT	A.H.Systems	SAS-574	20/08/07	20/08/08	154
26	HORN ANT	A.H.Systems	SAS-574	20/08/07	20/08/08	155
27	Dipole Antenna	Schwarzbeck	VHA9103	27/11/07	27/11/08	2116
28	Dipole Antenna	Schwarzbeck	VHA9103	27/11/07	27/11/08	2117
29	Dipole Antenna	Schwarzbeck	UHA9105	27/11/07	27/11/08	2261
30	Dipole Antenna	Schwarzbeck	UHA9105	27/11/07	27/11/08	2262
31	Loop Antenna	ETS	6502	30/10/07	30/10/08	3471

	Type	Manufacturer	Model	Cal.Due.Date (dd/mm/yy)	Next.Due.Date (dd/mm/yy)	S/N
32	TEMP & HUMIDITY Chamber	JISCO	J-RHC2	02/10/07	02/10/08	021031
33	Oscilloscope	Tektronix	TDS3052	02/11/07	02/11/08	B016821
34	Frequency Converter	Kyorits	KCV-604C	21/07/07	21/07/08	4-230-3
35	Log Periodic Antenna	Schwarzbeck	UHALP9108A1	08/06/07	08/06/08	1098
36	Biconical Antenna	Schwarzbeck	VHA9103	01/10/07	01/10/08	2233
37	Digital Multimeter	H.P	34401A	20/03/07	20/03/08	3146A13475
38	Attenuator (10dB)	WEINSCHL	23-10-34	05/10/07	05/10/08	BP4386
39	High-Pass Filter	ANRITSU	MP526D	08/10/07	08/10/08	M27756
40	Attenuator (3dB)	Agilent	8491B	12/07/07	12/07/08	58177
41	Attenuator (10dB)	WEINSCHL	23-10-34	26/01/07	26/01/08	BP4387
42	Amplifier (25dB)	Agilent	8447D	08/08/07	08/08/08	2443A03690
43	Amplifier (30dB)	Agilent	8449B	25/10/07	25/10/08	3008A01590
44	Position Controller	TOKIN	5901T	N/A	N/A	14173
45	Driver	TOKIN	5902T2	N/A	N/A	14174
46	Spectrum Analyzer	H.P	8591E	16/04/07	16/04/08	3649A05889
47	RFI/FIELD Intensity Meter	Kyorits	KNW-2402	06/09/07	06/09/08	4N-170-3
48	LISN	Kyorits	KNW-407	30/08/07	30/08/08	8-317-8
49	LISN	Kyorits	KNW-242	06/10/07	06/10/08	8-654-15
50	CVCF	NF Electronic	4400	N/A	N/A	344536 4420064
51	Software	ToYo EMI	EP5/RE	N/A	N/A	Ver 2.0.800
52	Software	ToYo EMI	EP5/CE	N/A	N/A	Ver 2.0.801
53	Software	AUDIX	e3	N/A	N/A	Ver 3.0
54	Software	Agilent	Benchlink	N/A	N/A	A.01.09 021211

7.1 SAMPLE CALCULATIONS

A. Emission Designator

- Cellular Band

Emission Designator = 1M28F9W

CDMA BW = 1.2794 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

- PCS Band

Emission Designator = 1M28F9W

CDMA BW = 1.2760 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

8.1 CONCLUSION

The data collected shows that the **Epivalley CO., LTD.** CDMA 1x EvDo USB Modem (**FCC ID: R2NSEC-7089**) complies with all the requirements of Parts 2 and 22, 24 of the FCC rules.