



## Maximum Permissible Exposure (MPE) Requirement

**Applicant: Control4 Corporation**

**Control4 Model: C4-SKC**

**FCC ID: R33C4SKC**

This document was prepared using data collected during testing and information provided by the applicant. The maximum power density requirements for the General Public (Uncontrolled Environment) listed in FCC Part 1.1310 were used. The power density is calculated using the following equation.

$$P_d = \frac{P_t G^*}{4\pi r^2}$$

Pd = power density in watts

Pt = transmit power in milliwatts

G = numeric antenna gain

r = distance between body and transmitter in centimeters

\*  $P_t G$  = EIRP

The calculated power density of the EUT listed in this application is calculated below. This calculation considers the potential for simultaneous operation, although not typical, of both the transmitter included in this application and the transmitter that was previously certified (WiFi Module) and included in this device. Both transmitters are located in the same unit with the same separation distance.

### Transceiver (ZigBee)

The Maximum source-based time averaged conducted output power is based on the worst case conducted output power as reported in Nemko-CCL, Inc. test report 294992-2.2 section 6.2.4, and declared maximum variation for the output power during manufacturing testing (tune-up procedure) is  $\pm 0.5$  dB.

Max Transmit Power ERP (dBm):	12.85	Tune-up variance (dB):	0.5
Max Transmit Power EIRP (mW):	31.26	Max Antenna Gain (dBi):	1.60
Operating Frequency (MHz):	2405-2475	(Numeric Antenna Gain):	1.45
Min Operating Distance (cm):	20	Duty Cycle (%):	100
Power Density (mW/cm <sup>2</sup> ):	0.00622		
Limit (mW/cm <sup>2</sup> ):	1.0		

### CONCLUSION:

Therefore our device complies with the FCC's RF radiation exposure limits for general population without SAR evaluation.

Best Regards

Roger Midgley  
Sr. Regulatory Compliance Engineer