



EMC TEST REPORT

Report No.: SET2018-05877
Product Name: Smartphone
FCC ID: R38YL3310A
Model No. : Coolpad 3310A
Applicant: Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address: Coolpad Information Harbor, 2nd Mengxi Road, Northern Part of Science&Technology Park, Nanshan, Shenzhen, China
Received Date: 2018-05-08
Tested Date: 2018-05-08—2018-07-19
Issued by: CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.
Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Jiedao, Nanshan District, Shenzhen, Guangdong, China
Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of **23** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name : Smartphone

Model No. : Coolpad 3310A

Applicant..... : Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Applicant Address..... : Coolpad Information Harbor, 2nd Mengxi Road,Northern Part of Science&Technology Park, Nanshan, Shenzhen,China

Manufacturer..... : Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Manufacturer Address : Coolpad Information Harbor, 2nd Mengxi Road,Northern Part of Science&Technology Park, Nanshan, Shenzhen,China

Test Standards..... : 47 CFR Part 15 Subpart B: Radio Frequency Devices

Test Result : PASS

Tested by : Chris You
Chris You Test Engineer 2018.07.25

Reviewed by..... : Zhu Qi
Zhu Qi Senior Engineer 2018.07.25

Approved by : Smart Li
Smart Li, Manager 2018.07.25



TABLE OF CONTENTS

- 1. GENERAL INFORMATION4**
- 1.1 EUT Description4**
- 1.2 Test Standards and Results5**
- 1.3 Facilities and Accreditations6**
- 1.3.1 Facilities6
- 1.3.2 Test Environment Conditions6
- 1.3.3 Measurement Uncertainty6
- 2. TEST CONDITIONS SETTING.....7**
- 2.1 Test Peripherals7**
- 2.2 Test Mode7**
- 2.3 Test Setup and Equipments List.....7**
- 2.3.1 Conducted Emission.....7
- 2.3.2 Radiated Emission.....9
- 3. 47 CFR PART 15B REQUIREMENTS 11**
- 3.1 Conducted Emission 11**
- 3.1.1 Requirement 11
- 3.1.2 Test Description 11
- 3.1.3 Test Result 11
- 3.2 Radiated Emission16**
- 3.2.1 Requirement16
- 3.2.2 Test Description 17
- 3.2.3 Test Result 17

Change History		
Issue	Date	Reason for change
1.0	2018.07.25	First edition



1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B 2017	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE:

(1) The EUT has been tested according to 47 CFR Part 15 Subpart B, Class B. The test procedure is according to ANSI C63.4:2014.



1.3 Facilities and Accreditations

1.3.1 Facilities

NVLAP Lab Code: 201008-0

CCIC-SET is a third party testing organization accredited by NVLAP according to ISO/IEC 17025. The accreditation certificate number is 201008-0.

FCC- Designation Number: CN5031

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN5031, valid time is until December 31, 2018.

ISED Registration: 11185A-1

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Aug. 03, 2019

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15°C - 35°C
Relative Humidity (%):	25% -75%
Atmospheric Pressure (kPa):	86kPa-106kPa

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	Uc = 3.6 dB (k=2)
Uncertainty of Radiated Emission:	Uc = 4.5 dB (k=2)



2. TEST CONDITIONS SETTING

2.1 Test Peripherals

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Support Equipment:

Description	Brand name	Model	Serial No.	FCCID
Notebook	ThinkPad	E430C	A131101550	N/A
Micro SD card	SanDisk	N/A	N/A	N/A
Mouse	Logitech	M100r	25011051	DOC

Support Cable:


Description	Shield Type	Ferrite Core	Length
PC Power adapter Cable	Un- shielding	No	1.2m
Mouse Cable	Un- shielding	No	1m

2.2 Test Mode

The EUT configuration of the emission tests is EUT + T Flash Card+ PC+Power Supply.

2.3 Test Setup and Equipments List

2.3.1 Conducted Emission

A. Test Setup:


The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.


B. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Due Date	Calibration Date
Test Receiver	KEYSIGHT	N9038A	A141202036	2018.12.13	2017.12.13
LISN	ROHDE&SCHWARZ	ENV216	A140701847	2019.01.08	2018.01.08
Cable	MATCHING PAD	W7	/	2019.04.01	2018.04.02


2.3.2 Radiated Emission

A. Test Setup:

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz



**B. Test Procedure**

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

C. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	ROHDE&SCHWARZ	ESIB7	A0501375	2017.08.05	2018.08.05
Semi-Anechoic Chamber	Albatross	9m*6m*6m	A0412372	2018.05.09	2019.05.09
Test Antenna - Bi-Log	ETC	MCTD 2786	A150402239	2017.06.10	2018.06.10
Test Antenna – Horn	ROHDE&SCHWARZ	HF906	A0304225	2018.05.26	2019.05.26
Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4 m	A0304210	2018.05.09	2019.05.09
Amplifier 1G~18GHz	ROHDE&SCHWARZ	MITEQ AFS42-0010 1800	A0509366	2017.06.04	2018.06.04
Amplifier 20M~3GHz	Compliance Direction System	PAP-0203H	A0509377	2017.06.04	2018.06.04
Cable	SUNHNER	SUCOFLEX 100	/	2017.06.04	2018.06.04
Cable	SUNHNER	SUCOFLEX 104	MY1758/4	2017.06.04	2018.06.04



3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description

See section 2.3.1 of this report.

3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

Note:

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a Nominal 120V AC,50/60Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Test voltage and frequency (120V AC,60Hz)


A. Mains terminal disturbance voltage, L phase (Battery 1)



(Plot A: L Phase)

Conducted Disturbance at Mains Terminals							
L Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.17250	64.80	49.58	15.26	0.17250	54.80	37.90	16.94
0.25800	61.50	44.49	17.01	0.25800	51.50	35.08	16.42
0.44250	57.00	40.16	16.85	0.44250	47.00	31.71	15.30
0.74400	56.00	38.20	17.80	0.74400	46.00	28.41	17.59
4.26300	56.00	44.69	11.31	4.26300	46.00	35.31	10.69
21.3810	60.00	36.80	23.20	21.3810	50.00	22.67	27.33


B. Mains terminal disturbance voltage, N phase (Battery 1)



(Plot B: N Phase)


Conducted Disturbance at Mains Terminals							
N Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.1770	64.6	44.68	19.95	0.1770	54.6	35.06	19.57
0.2580	61.5	41.16	20.34	0.2580	51.5	34.28	17.22
0.4785	56.4	35.74	20.63	0.4785	46.4	28.91	17.46
1.9680	56.0	34.29	21.71	1.9680	46.0	27.11	18.89
4.3305	56.0	38.40	17.60	4.3305	46.0	31.07	14.93
9.5145	60.0	32.37	27.63	9.5145	50.0	21.88	28.12

C. Mains terminal disturbance voltage, L phase (Battery 2)



Conducted Disturbance at Mains Terminals							
L Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.2625	61.40	41.56	19.79	0.2625	51.40	34.42	16.93
0.3705	58.50	38.49	20.00	0.3705	48.50	31.32	17.17
0.6495	56.00	34.46	21.54	0.6495	46.00	27.29	18.71
2.8680	56.00	38.65	17.35	2.8680	46.00	27.13	18.87
3.6960	56.00	39.11	16.89	3.6960	46.00	27.77	18.23
4.6185	56.00	41.53	14.47	4.6185	46.00	29.80	16.20

D. Mains terminal disturbance voltage, N phase (Battery 2)



Conducted Disturbance at Mains Terminals							
N Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.2670	61.20	41.29	19.92	0.2670	51.20	34.41	16.80
0.3615	58.70	43.68	15.01	0.3615	48.70	32.22	16.47
0.4470	56.90	39.43	17.50	0.4470	46.90	30.44	16.49
1.9995	56.00	36.33	19.67	1.9995	46.00	25.14	20.86
3.0165	56.00	36.58	19.42	3.0165	46.00	23.97	22.03
4.7130	56.00	40.75	15.25	4.7130	46.00	27.02	18.98

Test Result: PASS



3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	$\mu\text{V/m}$	Dist	(uV/m)	(dBuV/m)
0.009 - 0.490	2400/F(kHz)	300m	10000* 2400/F(kHz)	20log 2400/F(kHz) + 80
0.490 - 1.705	2400/F(kHz)	30m	100* 2400/F(kHz)	20log 2400/F(kHz) + 40
1.705 - 30.00	30	30m	100*30	20log 30 + 40
30.0 - 88.0	100	3m	100	20log 100
88.0 - 216.0	150	3m	150	20log 150
216.0 - 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

- a) As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.
- b) Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
- c) For below 1G :QP detector RBW 120kHz ,VBW 300kHz.
- d) For Above 1G: PK detector RBW 1MHz,VBW 3MHz for PK value ;AV detector RBW 1MHz, VBW 10Hz for AV value.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by $20\log \text{Emission Level}(\text{uV/m})$.
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$.

Example:

F.S Limit at 30m distance is 30uV/m , then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\text{uV/m} * (10)^2 = 100 * 30\text{uV/m}.$$



3.2.2 Test Description

See section 2.3.2 of this report.

3.2.3 Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.



E. Radiation disturbances, antenna polarization:Vertical (Battery 1)




(Plot C: Test Antenna Vertical 30M - 1G)

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Verdict
30.00	31.10	120.000	208.0	40.00	8.90	Vertical	Pass
43.61	30.44	120.000	129.0	40.00	9.56	Vertical	Pass
166.02	31.26	120.000	147.0	43.50	12.24	Vertical	Pass
438.22	30.21	120.000	241.0	46.00	15.79	Vertical	Pass
659.82	32.45	120.000	169.0	46.00	13.55	Vertical	Pass
885.31	36.62	120.000	207.0	46.00	9.38	Vertical	Pass



F. Radiation disturbances, antenna polarization: Horizontal (Battery 1)




(Plot D: Test Antenna Horizontal 30M - 1G)

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Verdict
30.00	30.43	120.000	223.0	40.00	9.57	Horizontal	Pass
169.96	25.46	120.000	209.0	43.50	18.04	Horizontal	Pass
329.36	29.78	120.000	126.0	46.00	16.22	Horizontal	Pass
467.37	30.36	120.000	268.0	46.00	15.64	Horizontal	Pass
628.72	32.44	120.000	214.0	46.00	13.56	Horizontal	Pass
828.94	35.33	120.000	364.0	46.00	10.67	Horizontal	Pass




G. Radiation disturbances, antenna polarization:Vertical (Battery 2)



Frequency (MHz)	QuasiPeak (dB µ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB µ V/m)	Margin (dB)	Antenna	Verdict
30.00	30.10	120.000	208.0	40.00	9.90	Vertical	Pass
43.61	26.44	120.000	129.0	40.00	13.56	Vertical	Pass
157.11	23.05	120.000	147.0	43.50	20.45	Vertical	Pass
379.85	26.78	120.000	241.0	46.00	19.22	Vertical	Pass
687.46	31.45	120.000	169.0	46.00	12.55	Vertical	Pass
875.91	36.62	120.000	207.0	46.00	9.38	Vertical	Pass



H. Radiation disturbances, antenna polarization: Horizontal (Battery 2)




Frequency (MHz)	QuasiPeak (dB µ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB µ V/m)	Margin (dB)	Antenna	Verdict
31.94	30.43	120.000	223.0	40.00	9.57	Horizontal	Pass
43.26	26.46	120.000	209.0	40.00	13.54	Horizontal	Pass
85.22	22.16	120.000	126.0	40.00	17.84	Horizontal	Pass
147.66	23.88	120.000	268.0	43.50	19.62	Horizontal	Pass
663.44	32.44	120.000	214.0	46.00	13.56	Horizontal	Pass
828.94	35.33	120.000	364.0	46.00	10.67	Horizontal	Pass

Test Result: PASS




I. Radiation disturbances, antenna polarization: Horizontal (Battery 1)




(Plot E: Test Antenna Horizontal 1G – 18G)

J. Radiation disturbances, antenna polarization: Vertical (Battery 1)




(Plot F: Test Antenna Vertical 1G – 18G)

K. Radiation disturbances, antenna polarization: Horizontal (Battery 2)



(Plot E: Test Antenna Horizontal 1G – 18G)

L. Radiation disturbances, antenna polarization: Vertical (Battery 2)



(Plot F: Test Antenna Vertical 1G – 18G)