





Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm)	Duty Factor (dB)	Total PSD (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	Ant1	-22.97	2.52	-20.45	11	Pass
NVNT	a	5200	Ant1	-20.32	2.51	-17.81	11	Pass
NVNT	a	5240	Ant1	-19.17	2.52	-16.65	11	Pass
NVNT	a	5260	Ant1	-20.18	2.52	-17.66	11	Pass
NVNT	a	5280	Ant1	-17.22	2.52	-14.7	11	Pass
NVNT	a	5320	Ant1	-18.05	2.52	-15.53	11	Pass
NVNT	a	5500	Ant1	-17.13	2.51	-14.62	11	Pass
NVNT	a	5600	Ant1	-19.24	2.51	-16.73	11	Pass
NVNT	a	5700	Ant1	-18.83	2.51	-16.32	11	Pass
NVNT	a	5745	Ant1	-24.16	2.51	-21.65	30	Pass
NVNT	a	5785	Ant1	-24.37	2.51	-21.86	30	Pass
NVNT	a	5825	Ant1	-23.66	2.52	-21.14	30	Pass
NVNT	n20	5180	Ant1	-19.47	2.39	-17.08	11	Pass
NVNT	n20	5200	Ant1	-21.08	2.39	-18.69	11	Pass
NVNT	n20	5240	Ant1	-17.15	2.39	-14.76	11	Pass
NVNT	n20	5260	Ant1	-19.86	2.39	-17.47	11	Pass
NVNT	n20	5280	Ant1	-18.03	2.39	-15.64	11	Pass
NVNT	n20	5320	Ant1	-20.56	2.39	-18.17	11	Pass
NVNT	n20	5500	Ant1	-15.26	2.39	-12.87	11	Pass
NVNT	n20	5600	Ant1	-15.03	2.39	-12.64	11	Pass
NVNT	n20	5700	Ant1	-16.74	2.38	-14.36	11	Pass
NVNT	n20	5745	Ant1	-21.87	2.38	-19.49	30	Pass
NVNT	n20	5785	Ant1	-21.4	2.38	-19.02	30	Pass
NVNT	n20	5825	Ant1	-24.11	2.39	-21.72	30	Pass
NVNT	n40	5190	Ant1	-26.85	3.34	-23.51	11	Pass
NVNT	n40	5230	Ant1	-29.33	3.33	-26	11	Pass
NVNT	n40	5270	Ant1	-26.5	3.33	-23.17	11	Pass
NVNT	n40	5310	Ant1	-28.71	3.33	-25.38	11	Pass
NVNT	n40	5510	Ant1	-27.19	3.33	-23.86	11	Pass
NVNT	n40	5550	Ant1	-27.14	3.33	-23.81	11	Pass
NVNT	n40	5670	Ant1	-28.64	3.33	-25.31	11	Pass
NVNT	n40	5755	Ant1	-29.38	3.33	-26.05	30	Pass
NVNT	n40	5795	Ant1	-31.89	3.32	-28.57	30	Pass
NVNT	ac80	5210	Ant1	-33.26	3.84	-29.42	11	Pass
NVNT	ac80	5290	Ant1	-34	3.85	-30.15	11	Pass
NVNT	ac80	5530	Ant1	-31.96	3.84	-28.12	11	Pass
NVNT	ac80	5610	Ant1	-33.79	3.84	-29.95	11	Pass
NVNT	ac80	5775	Ant1	-32.76	3.98	-28.78	30	Pass

























