

TEST REPORT

Report No.: SRTC2020-9003(F)-0038
Product Name: Smartphone
Model Name: CP3669AS
Applicant: Yulong Computer Telecommunication Scientific
(Shenzhen) Co., Ltd
Manufacturer: Yulong Computer Telecommunication Scientific
(Shenzhen) Co., Ltd
Specification: FCC Part15B (Certification)
(2019 edition)
FCC ID: R38YLCP3669AS

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. General information	3
1.1 Notes of the test report	3
1.2 Information about the testing laboratory.....	3
1.3 Applicant's details	3
1.4 Manufacturer's details.....	3
1.5 Application details	4
1.6 Reference specification.....	4
1.7 Information of EUT	4
1.7.1 General information.....	4
1.7.2EUT details	5
1.7.3 Auxiliary equipment details.....	5
2. Test information	6
2.1 Summary of the test results	7
2.2 Test result.....	8
2.2.1Conducted Emissions-FCC Part15.107	8
2.2.2RadiatedEmissions-FCC Part15.109.....	14
2.3. List of test equipments	21

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Address: 15th Building, No.30 Shixing Street, Shijingshan District
Testing location: No.80, Zhaojiachang, BeizangCun, Daxing District, Beijing, China.
City: Beijing
Country or Region: China
Contacted person: Liu Jia
Tel: +86 10 57996183
Fax: +86 10 57996388
Email: liujiarf@srtc.org.cn

1.3 Applicant's details

Company: Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address: Building B, Boton Science Park, Chaguang Road, Xili Town, Nanshan District, Shenzhen
City: Shenzhen
Country or Region: China
Contacted person: Yentl Chen
Tel: 15927320221
Email: chenyanting@yulong.com

1.4 Manufacturer's details

Company: Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address: Building B, Boton Science Park, Chaguang Road, Xili Town, Nanshan District, Shenzhen
City: Shenzhen
Country or Region: China
Contacted person: Yentl Chen
Tel: 15927320221
Email: chenyanting@yulong.com

1.5 Application details

Date of reception of test sample: 19th Aug. 2020

Date of test: 20th Aug. 2020 to 7th Sept. 2020

1.6 Reference specification

FCC Part 15B, 2019 (Certification)

1.7 Information of EUT

1.7.1 General information

Name of EUT	Smartphone
Model Name	CP3669AS
FCC ID	R38YLCP3669AS
Frequency Range	GSM: GSM850/PCS1900 WCDMA: FDD II / FDD IV / FDD V LTE:FDD 2/ FDD 4/ FDD 5/ FDD 7/ FDD 12/ FDD 13/ FDD 25/ FDD 26/ TDD 41/ / FDD 66/ FDD 71 Bluetooth: 2.4~2.4835GHz WiFi: 2.4~2.4835GHz/ 5.15-5.25GHz/5.25-5.35GHz 5.475-5.725GHz/5.725-5.85GHz
Equipment Class	Class B
Power Supply	Battery or Charger
Rated Power Supply Voltage	3.85V
Extreme Temperature	Lowest: -20°C Highest: +60°C
Extreme Voltage	Minimum: 3.6V Maximum: 4.4V
HW Version	P0
SW Version	10.0.047.P0.200914.CP3669AS

1.7.2EUT details

Product Name	Model Name	IMEI
Smartphone	CP3669AS	860084050001885

1.7.3 Auxiliary equipment details

AE (Auxiliary Equipment) 1#: Laptop

Manufacturer	Lenovo
Model Number	E40-70
S/N	MP06WE9U
Input Voltage	100V-240V AC

AE (Auxiliary Equipment) 2#: USB Cable

Manufacturer	Lishi
Model Number	LS-KP003

AE (Auxiliary Equipment) 3#: USB Cable

Manufacturer	Saibao
Model Number	SYL-A173A

AE (Auxiliary Equipment)4#: Battery

Type	Li-Lon
Manufacturer	Ganfeng
Model Number	CPLD-438

AE (Auxiliary Equipment)5#: Battery

Type	Li-Lon
Manufacturer	Tianmao
Model Number	CPLD-438

AE (Auxiliary Equipment) 6#: Charger1

Manufacturer	Ruide
Model Number	RD0502000-USBA-87MG
S/N	/
Input Voltage	100V-240VAC 300mA
Output Voltage	5VDC 2000mA




Note1: As the information described in these above tables, the relevant tests have been performed in order to verify in which supply would have the worst features. When the EUT exercised with 2# USB Cable, 4# Battery, 6# Charger is the worst feature, and record the results in the test report.

Note2: AE1# Laptop was selected by testing laboratory and was only cooperated with this test, not for sale.

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	Conducted emissions	15.107	Pass
2	Radiated emissions	15.109	Pass

Approved By: Mr. Liu Wei Director of the test department 	Checked By: Mr. Guo Yu Vice director of the test department 
Tested by: Mr. Liu Jian Test engineer 	Issued date: 2020.09.21

2.2 Test result

2.2.1 Conducted Emissions-FCC Part15.107

Ambient condition:

Temperature	Relative humidity	Pressure
24.3°C	40.1%	100.9kPa

Test Setup with laptop:




Figure 1

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and transferred the data by copying large files from laptop to the EUT. The laptop's LAN port is connected with another laptop via cable. And the data transferring between two laptops is maintained.

The AC main power supply of the laptop is connected to LISN and LISN is connected to the reference ground. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

Test Setup with charger:




Figure 2

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The EUT is connected with LISN via the charger. The LISN is connected to the reference ground. The accessories of the EUT are connected with the EUT such as headset etc. Open the following functions of EUT: Camera, flash lamp, FM, GPS and video.

The test set-up and the test methods are performed according to ANSI C63.4:2014. Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

A "reference path loss" Corr.(dB) is established and the $L_{cable} + ATT + VDF$ is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{result} = P_{mea} + Corr.(dB)$$

Sample calculation: $(46.18dB\mu V) = (16.5dB\mu V) + (29.6dB)$, the corresponding frequency is 0.414919MHz.


Limit:

Frequency of Emission(MHz)	Limits(dB μ V)	
	Quasi-peak	Average
0.15~0.5	66 to 56*	56 to 46*
0.5~5	56	46
5~30	60	50

Note: * Decreases with the logarithm of the frequency


Test result:

Noise Level of the Measuring Instrument



Pic1. Conducted emission L and N Line


EUT + Charger: AC240V



Pic2. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pme a Quas	Pme a Aver
0.414919	---	46.18	47.55	1.37	L1	29.6	---	16.5
0.414919	53.74	---	57.55	3.81	L1	29.6	24.1	---
0.455962	---	34.92	46.77	11.84	N	29.6	---	5.32
0.455962	43.80	---	56.77	12.97	L1	29.6	14.2	---
0.582825	---	35.35	46.00	10.65	L1	29.6	---	5.75
0.582825	43.25	---	56.00	12.75	N	29.6	13.6	---
0.832819	44.79	---	56.00	11.21	N	29.6	15.1	---
0.832819	---	35.75	46.00	10.25	L1	29.6	---	6.15
1.459669	44.40	---	56.00	11.60	L1	29.7	14.7	---
1.459669	---	34.74	46.00	11.26	L1	29.7	---	5.04
1.832794	---	33.91	46.00	12.09	L1	29.7	---	4.21
1.832794	44.59	---	56.00	11.41	L1	29.7	14.8	---


EUT + Charger: AC120V



Pic3. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)	Pme a Quas	Pme a Aver
0.388800	46.40	---	58.09	11.69	L1	29.6	16.8	---
0.411188	---	33.24	47.62	14.39	L1	29.6	---	3.64
0.414919	46.20	---	57.55	11.35	N	29.6	16.6	---
0.422381	40.37	---	57.40	17.03	L1	29.6	10.7	---
0.437306	---	42.99	47.11	4.12	L1	29.6	---	13.3
0.437306	51.25	---	57.11	5.87	L1	29.6	21.6	---
0.463425	---	39.45	46.63	7.18	L1	29.6	---	9.85
0.463425	47.15	---	56.63	9.48	L1	29.6	17.5	---
0.881325	---	36.50	46.00	9.50	N	29.6	---	6.9
0.881325	44.26	---	56.00	11.74	L1	29.6	14.6	---
0.929831	---	35.94	46.00	10.06	N	29.7	---	6.24
1.347731	---	35.23	46.00	10.77	L1	29.7	---	5.53

EUT + Laptop:



Pic4. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pme a Quas	Pme a Aver
0.154664	---	25.76	55.75	29.99	L1	29.6	---	-3.84
0.154664	43.00	---	65.75	22.75	L1	29.6	13.4	---
0.163992	41.33	---	65.26	23.93	L1	29.6	11.7	---
0.583758	---	24.77	46.00	21.23	L1	29.6	---	-4.83
22.169039	---	29.46	50.00	20.54	L1	29.8	---	-0.34
22.169039	36.28	---	60.00	23.72	N	29.8	6.48	---
23.498297	37.52	---	60.00	22.48	L1	29.8	7.72	---
23.498297	---	31.23	50.00	18.77	L1	29.8	---	1.43
23.941383	37.13	---	60.00	22.87	L1	29.8	7.33	---
23.941383	---	30.01	50.00	19.99	N	29.8	---	0.21
24.244547	---	29.04	50.00	20.96	L1	29.8	---	-0.76
24.244547	35.62	---	60.00	24.38	L1	29.8	5.82	---

2.2.2 Radiated Emissions-FCC Part15.109

Ambient condition:

Temperature	Relative humidity	Pressure
24.2°C	40.7%	100.9kPa

Test Setup:




Figure 3

Test Procedure:

EUT+Laptop:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and transferred the data by copying large files from laptop to the EUT. The test set-up and the test methods are performed according to ANSI C63.4:2014

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with

orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.
The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing.

EUT + Charger:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The EUT should work in idle mode. The accessories of the EUT are connected with the EUT such as headset etc. Open the following functions of EUT: Camera, flash lamp, FM, GPS and video. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing. All test results are performed with max hold at the horizontal and vertical polarity.

RBW=120kHz, VBW=300kHz, when the test frequency: 30MHz<f<1GHz

RBW=1MHz, VBW=3MHz, when the test frequency: f>1GHz

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Limit:

Frequency of Emission(MHz)	Limits	
	Detector	Unit (dB μ V/m)
30~88	Quasi-peak	40
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46
960~1000	Quasi-peak	54
1000~5th harmonic of the highest	Average	54

frequency or 40GHz, whichever is lower	Peak	74
--	------	----

Test result:

Sample calculation: $(28.46\text{dB}\mu\text{V/m}) = (49.36\text{dB}\mu\text{V/m}) + (-20.9\text{dB})$, the corresponding frequency is 30.739MHz.

EUT + Laptop:


Frequency(MHz)	Result(dB μ V/m)	Limit (dB μ V/m)	ARpl (dB)	Pmea (dB μ V/m)	Polarity
30.739	28.46	40.00	-20.9	49.36	V
59.4025	31.35	40.00	-18.3	49.65	V
100.345	22.88	43.50	-18.6	41.48	V
258.312	28.70	46.00	-16.2	44.9	V
553.1325	25.36	46.00	-7.8	33.16	V
958.687	31.08	46.00	-0.8	31.88	V

EUT + Charger:

Frequency(MHz)	Result(dB μ V/m)	Limit (dB μ V/m)	ARpl (dB)	Pmea (dB μ V/m)	Polarity
52.495000	17.78	40.00	-17.4	35.18	V
83.256000	30.26	40.00	-22.8	53.06	V
97.243500	16.56	43.50	-19.1	35.66	V
199.344500	15.57	43.50	-18.3	33.87	V
545.880500	15.08	46.00	-8.0	23.08	V
932.231500	21.05	46.00	-1.1	22.15	V

EUT + Laptop: refer to Pic4, Pic5, Pic6, Pic7


Full Spectrum



Pic5. Radiated emission(30MHz – 1GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical


Full Spectrum



Pic6. Radiated emission (1GHz –6GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum



Pic7. Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum




Pic8. Radiated emission (18GHz – 40GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

EUT + Charger: refer to Pic8, Pic9, Pic10, Pic11


Full Spectrum



Pic9. Radiated emission(30MHz – 1GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical


Full Spectrum



Pic10. Radiated emission (1GHz –6GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum



Pic11. Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum



Pic12. Radiated emission (18GHz – 40GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60mS emi-AnechoicChamber	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
2	ESW EMI test receiver	R&S	101574	20th Aug. 2021	20th Aug. 2020
3	ESR3EMI test receiver	R&S	102361	21th Apr. 2021	21th Apr. 2020
4	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
5	VULB 9163 Ultra log test antenna	schwarzbeck	867	25th Mar. 2021	25th Mar. 2020
6	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	25th Mar. 2021	25th Mar. 2020
7	SAS-574 Horn Antenna	schwarzbeck	535	20th Aug. 2021	20th Aug. 2020
8	ENV216 AMN	R&S	3560.6550. 12	20th Aug. 2021	20th Aug. 2020
9	EMC32EMI test software	R&S	-----	-----	-----