

# FCC Test Report

**FCC ID** : R3USCBT19  
**Equipment** : Bluetooth speakerphone  
**Model No.** : SCBT19  
**Brand Name** : EPOS  
**Applicant** : Sennheiser Communications  
**Address** : Industriparken 27, Ballerup 2750 , Denmark  
**Standard** : 47 CFR FCC Part 15.247  
**Received Date** : Nov. 13, 2019  
**Tested Date** : May 16 ~ Jun. 26, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

Reviewed by:

  
\_\_\_\_\_  
Along Chen / Assistant Manager

Approved by:

  
\_\_\_\_\_  
Gary Chang / Manager



## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Local Support Equipment List .....	9
1.3	Test Setup Chart .....	9
1.4	The Equipment List .....	10
1.5	Test Standards .....	11
1.6	Reference Guidance .....	11
1.7	Deviation from Test Standard and Measurement Procedure.....	11
1.8	Measurement Uncertainty .....	11
<b>2</b>	<b>TEST CONFIGURATION.....</b>	<b>12</b>
2.1	Testing Condition .....	12
2.2	Testing Facility .....	12
2.3	The Worst Test Modes and Channel Details .....	12
<b>3</b>	<b>TRANSMITTER TEST RESULTS .....</b>	<b>13</b>
3.1	Conducted Emissions.....	13
3.2	Unwanted Emissions into Restricted Frequency Bands .....	16
3.3	Unwanted Emissions into Non-Restricted Frequency Bands .....	33
3.4	Conducted Output Power .....	37
3.5	Number of Hopping Frequency .....	40
3.6	20dB and Occupied Bandwidth.....	43
3.7	Channel Separation.....	47
3.8	Number of Dwell Time.....	51
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>57</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FR9N1302AD	Rev. 01	Initial issue	Jul. 13, 2020

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.159MHz 45.47(Margin -20.05dB) - QP	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2483.50MHz 43.55 (Margin -10.45dB) - AV	Pass
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: 8.01	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

# 1 General Description

## 1.1 Information

### 1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product name	Product description	Description
EPOS	SCBT19	EXPAND 80	Bluetooth speakerphone	-
EPOS	SCBT19	EXPAND 80T	Bluetooth speakerphone	SW for MS Teams. Buttons have different icons

† The **EXPAND 80** was selected as a representative for the final test and only its data was recorded in this report.

### 1.1.2 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.  
 Note 2: Bluetooth BR uses a GFSK.  
 Note 3: Bluetooth EDR uses  $\pi/4$ -DQPSK.

### 1.1.3 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	PIFA	N/A	3.7	---

### 1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from adapter
-------------------	-------------------

### 1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	Adapter	Brand: EPOS Model: GS5V-2.4C-DC I/P: 100-240Vac, 50/60Hz, 0.5A Max O/P: 5Vdc, 2.4A Power Line: 1.3m shielded without core
2	USB-C cable	Brand: EPOS Model: EP-UC-L150-1 Power Line: 1.5m shielded without core
3	USB-C to -A adapter	Brand: EPOS Model: SCUCL01
4	USB dongle	Brand: EPOS Model: BTD 800 USB

### 1.1.6 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

### 1.1.7 Test Tool and Duty Cycle

Test Tool	CBT Test	
Duty Cycle and Duty Factor	Duty Cycle (%)	Duty Factor (dB)
DH5	78.61	1.05
2DH5	78.61	1.05

### 1.1.8 Power Index of Test Tool


Modulation Mode	Test Frequency (MHz)		
	2402	2441	2480
GFSK/1Mbps	8	8	8
$\pi/4$ -DQPSK /2Mbps	8	8	8



## 1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude E5470	DoC	---
2	Extension microphones (x2)	EPOS	EPWD1	---	Provided by applicant.

## 1.3 Test Setup Chart



## 1.4 The Equipment List

<b>Test Item</b>	Conducted Emission				
<b>Test Site</b>	Conduction room 1 / (CO01-WS)				
<b>Tested Date</b>	Jun. 26, 2020				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Receiver	R&S	ESR3	101658	Dec. 12, 2019	Dec. 11, 2020
LISN	R&S	ENV216	101579	Mar. 12, 2020	Mar. 11, 2021
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 22, 2019	Oct. 21, 2020
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

<b>Test Item</b>	Radiated Emission				
<b>Test Site</b>	966 chamber 1 / (03CH01-WS)				
<b>Tested Date</b>	Jun. 22, 2020				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101498	Dec. 17, 2019	Dec. 16, 2020
Receiver	R&S	ESR3	101657	Feb. 14, 2020	Feb. 13, 2021
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 12, 2019	Dec. 11, 2020
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2019	Nov. 14, 2020
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2019	Nov. 12, 2020
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 08, 2019	Oct. 07, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF Cable	EMC	EMC104-SM-SM-8000	181106	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 07, 2019	Oct. 06, 2020
LF cable 1M	EMC	EMCCFD400-NM-NM-1000	160502	Oct. 07, 2019	Oct. 06, 2020
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 07, 2019	Oct. 06, 2020
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 07, 2019	Oct. 06, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	(TH01-WS)				
<b>Tested Date</b>	May 16, 2020				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101063	Apr. 30, 2020	Apr. 29, 2021
Power Meter	Anritsu	ML2495A	1241002	Oct. 23, 2019	Oct. 22, 2020
Power Sensor	Anritsu	MA2411B	1207366	Oct. 23, 2019	Oct. 22, 2020
DC POWER SOURCE	GW INSTEK	GPC-6030D	GES855395	Oct. 29, 2019	Oct. 28, 2020
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

## 1.5 Test Standards

47 CFR FCC Part 15.247  
ANSI C63.10-2013

## 1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

## 1.7 Deviation from Test Standard and Measurement Procedure

None

## 1.8 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ( $k=2$ )).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	$\pm 34.130$ Hz
Conducted power	$\pm 0.808$ dB
Power density	$\pm 0.583$ dB
Conducted emission	$\pm 2.715$ dB
AC conducted emission	$\pm 2.92$ dB
Radiated emission $\leq 1$ GHz	$\pm 3.41$ dB
Radiated emission $> 1$ GHz	$\pm 4.90$ dB
Time	$\pm 0.1\%$

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	21°C / 69%	Akun Chung
Radiated Emissions	03CH01-WS	23-24°C / 66-68%	Akun Chung
RF Conducted	TH01-WS	24°C / 67%	Aska Huang

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

### 2.2 Testing Facility

<b>Test Laboratory</b>	International Certification Corp.
<b>Test Site</b>	CO01-WS, 03CH01-WS, TH01-WS
<b>Address of Test Site</b>	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

### 2.3 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
Conducted Emissions	$\pi/4$ -DQPSK	2441	2Mbps	---
Radiated Emissions $\leq$ 1GHz	$\pi/4$ -DQPSK	2441	2Mbps	---
Radiated Emissions $>$ 1GHz	GFSK $\pi/4$ -DQPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps	---
Conducted Output Power	GFSK $\pi/4$ DQPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps	---
Number of Hopping Channels	GFSK $\pi/4$ DQPSK	2402~2480 2402~2480	1Mbps 2Mbps	---
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK $\pi/4$ DQPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps	---
Dwell Time	GFSK $\pi/4$ DQPSK	2402 2402	1Mbps 2Mbps	---

**NOTE:**

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.

## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

#### 3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

#### 3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.4 Test Result of Conducted Emissions

Modulation Mode	$\pi/4$ -DQPSK	Test Freq. (MHz)	2441
Power Phase	Line		


  



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.159	23.05	55.52	-32.47	13.19	9.64	0.05	Average
2*	0.159	45.47	65.52	-20.05	35.61	9.64	0.05	QP
3	0.171	22.25	54.89	-32.64	12.39	9.64	0.05	Average
4	0.171	44.47	64.89	-20.42	34.61	9.64	0.05	QP
5	0.196	20.17	53.77	-33.60	10.29	9.63	0.06	Average
6	0.196	41.85	63.77	-21.92	31.97	9.63	0.06	QP
7	0.211	18.77	53.17	-34.40	8.89	9.63	0.06	Average
8	0.211	40.15	63.17	-23.02	30.27	9.63	0.06	QP
9	4.439	17.52	46.00	-28.48	7.20	9.65	0.30	Average
10	4.439	31.25	56.00	-24.75	20.93	9.65	0.30	QP
11	19.444	12.85	50.00	-37.15	1.88	9.72	0.65	Average
12	19.444	18.46	60.00	-41.54	7.49	9.72	0.65	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).  
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

<b>Modulation Mode</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2441
<b>Power Phase</b>	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.153	24.88	55.81	-30.93	15.05	9.66	0.05	Average
2*	0.153	45.66	65.81	-20.15	35.83	9.66	0.05	QP
3	0.167	23.32	55.12	-31.80	13.48	9.66	0.05	Average
4	0.167	43.98	65.12	-21.14	34.14	9.66	0.05	QP
5	0.184	21.85	54.28	-32.43	12.00	9.65	0.06	Average
6	0.184	42.15	64.28	-22.13	32.30	9.65	0.06	QP
7	0.201	19.75	53.56	-33.81	9.89	9.65	0.06	Average
8	0.201	40.56	63.56	-23.00	30.70	9.65	0.06	QP
9	4.482	16.66	46.00	-29.34	6.41	9.68	0.30	Average
10	4.482	30.56	56.00	-25.44	20.31	9.68	0.30	QP
11	19.530	14.44	50.00	-35.56	3.44	9.84	0.65	Average
12	19.530	22.21	60.00	-37.79	11.21	9.84	0.65	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).  
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

## 3.2 Unwanted Emissions into Restricted Frequency Bands

### 3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.



### 3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. Radiated emission above 1GHz / Peak value  
RBW=1MHz, VBW=3MHz and Peak detector  
Radiated emission above 1GHz / Average value for harmonics  
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:
3.
$$20\log(\text{Duty cycle}) = 20\log \frac{1\text{s} / 1600 * 5}{100\text{ ms}} = -30.1\text{dB}$$
4. Radiated emission above 1GHz / Average value for other emissions  
RBW=1MHz, VBW=1/T and Peak detector

### 3.2.3 Test Setup

#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### 3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

<b>Modulation Mode</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2441
<b>Polarization</b>	Horizontal		




The graph displays the radiated unwanted emission levels in dBuV/m across a frequency range from 30 MHz to 1000 MHz. A red step function represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 MHz to 100 MHz, 45 dBuV/m from 100 MHz to 200 MHz, and 46 dBuV/m from 200 MHz to 1000 MHz. Six blue vertical lines indicate specific emission peaks, labeled 1 through 6, with their respective frequencies and levels.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	53.30	25.46	40.00	-14.54	33.89	-8.43	Peak	---	---
2	98.79	27.25	43.50	-16.25	40.48	-13.23	Peak	---	---
3	186.26	27.31	43.50	-16.19	38.12	-10.81	Peak	---	---
4	239.49	27.39	46.00	-18.61	37.64	-10.25	Peak	---	---
5	377.33	28.84	46.00	-17.16	34.84	-6.00	Peak	---	---
6	467.55	31.56	46.00	-14.44	35.25	-3.69	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).  
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Modulation Mode</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2441
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	62.26	27.79	40.00	-12.21	37.02	-9.23	Peak	---	---
2	164.75	30.85	43.50	-12.65	39.46	-8.61	Peak	---	---
3	186.26	27.35	43.50	-16.15	38.16	-10.81	Peak	---	---
4	232.66	28.49	46.00	-17.51	39.66	-11.17	Peak	---	---
5	395.54	34.31	46.00	-11.69	39.89	-5.58	Peak	---	---
6	498.49	34.85	46.00	-11.15	37.99	-3.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK	Test Freq. (MHz)	2402						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	39.42	54.00	-14.58	42.24	-2.82	Average	100	288
2	2390.00	49.50	74.00	-24.50	52.32	-2.82	Peak	100	288
3	4804.00	22.23	54.00	-31.77	18.71	3.52	Average	102	147
4	4804.00	52.33	74.00	-21.67	48.81	3.52	Peak	102	147
5	12010.00	27.21	54.00	-26.79	13.41	13.80	Average	100	289
6	12010.00	57.31	74.00	-16.69	43.51	13.80	Peak	100	289
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2402
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.87	54.00	-14.13	42.69	-2.82	Average	253	262
2	2390.00	49.86	74.00	-24.14	52.68	-2.82	Peak	253	262
3	4804.00	22.74	54.00	-31.26	19.22	3.52	Average	102	334
4	4804.00	52.84	74.00	-21.16	49.32	3.52	Peak	102	334
5	12010.00	27.23	54.00	-26.77	13.43	13.80	Average	100	332
6	12010.00	57.33	74.00	-16.67	43.53	13.80	Peak	100	332

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2441
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.32	54.00	-14.68	42.14	-2.82	Average	100	282
2	2390.00	49.40	74.00	-24.60	52.22	-2.82	Peak	100	282
3	2483.50	39.24	54.00	-14.76	42.20	-2.96	Average	100	282
4	2483.50	49.29	74.00	-24.71	52.25	-2.96	Peak	100	282
5	4880.00	20.35	54.00	-33.65	16.76	3.59	Average	100	146
6	4880.00	50.45	74.00	-23.55	46.86	3.59	Peak	100	146
7	7320.00	25.38	54.00	-28.62	16.22	9.16	Average	100	289
8	7320.00	55.48	74.00	-18.52	46.32	9.16	Peak	100	289

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2441
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.62	54.00	-14.38	42.44	-2.82	Average	258	271
2	2390.00	49.66	74.00	-24.34	52.48	-2.82	Peak	258	271
3	2483.50	39.39	54.00	-14.61	42.35	-2.96	Average	258	271
4	2483.50	49.53	74.00	-24.47	52.49	-2.96	Peak	258	271
5	4880.00	21.75	54.00	-32.25	18.16	3.59	Average	102	336
6	4880.00	51.85	74.00	-22.15	48.26	3.59	Peak	102	336
7	7320.00	28.26	54.00	-25.74	19.10	9.16	Average	100	328
8	7320.00	58.36	74.00	-15.64	49.20	9.16	Peak	100	328


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.37	54.00	-14.63	42.33	-2.96	Average	100	287
2	2483.50	51.10	74.00	-22.90	54.06	-2.96	Peak	100	287
3	4960.00	19.21	54.00	-34.79	15.40	3.81	Average	100	141
4	4960.00	49.31	74.00	-24.69	45.50	3.81	Peak	100	141
5	7440.00	24.05	54.00	-29.95	15.12	8.93	Average	100	287
6	7440.00	54.15	74.00	-19.85	45.22	8.93	Peak	100	287

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.44	54.00	-13.56	43.40	-2.96	Average	251	266
2	2483.50	53.86	74.00	-20.14	56.82	-2.96	Peak	251	266
3	4960.00	20.99	54.00	-33.01	17.18	3.81	Average	110	337
4	4960.00	51.09	74.00	-22.91	47.28	3.81	Peak	110	337
5	7440.00	27.17	54.00	-26.83	18.24	8.93	Average	100	327
6	7440.00	57.27	74.00	-16.73	48.34	8.93	Peak	100	327

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for $\pi/4$ -DQPSK

Modulation	$\pi/4$ -DQPSK	Test Freq. (MHz)	2402						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	39.56	54.00	-14.44	42.36	-2.80	Average	100	265
2	2390.00	49.66	74.00	-24.34	52.46	-2.80	Peak	100	265
3	4804.00	19.04	54.00	-34.96	15.51	3.53	Average	110	151
4	4804.00	49.14	74.00	-24.86	45.61	3.53	Peak	110	151
5	12010.00	27.25	54.00	-26.75	13.53	13.72	Average	100	279
6	12010.00	57.35	74.00	-16.65	43.63	13.72	Peak	100	279
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

<b>Modulation</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2402
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.71	54.00	-14.29	42.51	-2.80	Average	260	267
2	2390.00	49.68	74.00	-24.32	52.48	-2.80	Peak	260	267
3	4804.00	19.74	54.00	-34.26	16.21	3.53	Average	100	335
4	4804.00	49.84	74.00	-24.16	46.31	3.53	Peak	100	335
5	12010.00	26.88	54.00	-27.12	13.16	13.72	Average	100	339
6	12010.00	56.98	74.00	-17.02	43.26	13.72	Peak	100	339

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

<b>Modulation</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2441
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.51	54.00	-14.49	42.31	-2.80	Average	100	277
2	2390.00	49.51	74.00	-24.49	52.31	-2.80	Peak	100	277
3	2483.50	39.23	54.00	-14.77	42.26	-3.03	Average	100	277
4	2483.50	49.29	74.00	-24.71	52.32	-3.03	Peak	100	277
5	4880.00	19.00	54.00	-35.00	15.37	3.63	Average	100	151
6	4880.00	49.10	74.00	-24.90	45.47	3.63	Peak	100	151
7	7320.00	24.33	54.00	-29.67	15.11	9.22	Average	100	295
8	7320.00	54.43	74.00	-19.57	45.21	9.22	Peak	100	295

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2441
<b>Polarization</b>	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.81	54.00	-14.19	42.61	-2.80	Average	265	278
2	2390.00	49.66	74.00	-24.34	52.46	-2.80	Peak	265	278
3	2483.50	39.58	54.00	-14.42	42.61	-3.03	Average	265	278
4	2483.50	49.43	74.00	-24.57	52.46	-3.03	Peak	265	278
5	4880.00	19.85	54.00	-34.15	16.22	3.63	Average	105	333
6	4880.00	49.95	74.00	-24.05	46.32	3.63	Peak	105	333
7	7320.00	25.84	54.00	-28.16	16.62	9.22	Average	100	325
8	7320.00	55.94	74.00	-18.06	46.72	9.22	Peak	100	325

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	42.43	54.00	-11.57	45.46	-3.03	Average	100	295
2	2483.50	56.43	74.00	-17.57	59.46	-3.03	Peak	100	295
3	4960.00	18.39	54.00	-35.61	14.56	3.83	Average	100	141
4	4960.00	48.49	74.00	-25.51	44.66	3.83	Peak	100	141
5	7440.00	23.33	54.00	-30.67	14.12	9.21	Average	100	281
6	7440.00	53.43	74.00	-20.57	44.22	9.21	Peak	100	281

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	$\pi/4$ -DQPSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	43.55	54.00	-10.45	46.58	-3.03	Average	255	261
2	2483.50	58.61	74.00	-15.39	61.64	-3.03	Peak	255	261
3	4960.00	19.04	54.00	-34.96	15.21	3.83	Average	105	333
4	4960.00	49.14	74.00	-24.86	45.31	3.83	Peak	102	333
5	7440.00	25.76	54.00	-28.24	16.55	9.21	Average	100	330
6	7440.00	55.86	74.00	-18.14	46.65	9.21	Peak	100	330

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



### 3.3 Unwanted Emissions into Non-Restricted Frequency Bands

#### 3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

#### 3.3.2 Test Procedures


##### Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level


##### Emission level measurement


1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

#### 3.3.3 Test Setup




### 3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands






**BT-BR(1Mbps)**  
**2441MHz**  
**Hopping Ch Bandedge (Non-restricted Band)**



**BT-EDR(2Mbps)**  
**2441MHz**  
**Hopping Ch Bandedge (Non-restricted Band)**



## 3.4 Conducted Output Power


### 3.4.1 Limit of Conducted Output Power

- 1 Watt  
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
- 0.125 Watt  
For all other frequency hopping systems in the 2400–2483.5 MHz band.
- 0.125 Watt  
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

### 3.4.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power sensor and meter is 50MHz
2. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

### 3.4.3 Test Setup



### 3.4.4 Test Result of Conducted Output Power

#### Summary of Peak Conducted Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	7.96	0.00625
BT-EDR(2Mbps)	8.01	0.00632

#### Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	3.70	6.18	21.00
2441MHz	Pass	3.70	7.96	21.00
2480MHz	Pass	3.70	7.57	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	3.70	6.51	21.00
2441MHz	Pass	3.70	8.01	21.00
2480MHz	Pass	3.70	7.75	21.00

### Summary of Conducted (Average) Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	7.69	0.00587
BT-EDR(2Mbps)	6.12	0.00409

### Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	3.70	5.80	-
2441MHz	Pass	3.70	7.69	-
2480MHz	Pass	3.70	7.24	-
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	3.70	4.31	-
2441MHz	Pass	3.70	6.12	-
2480MHz	Pass	3.70	5.65	-

Note: Average power is for reference only.

## 3.5 Number of Hopping Frequency


### 3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

### 3.5.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2. Allow trace to stabilize.

### 3.5.3 Test Setup





### 3.5.4 Test Result of Number of Hopping Frequency

#### Summary


Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(2Mbps)	79

#### Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2441MHz	Pass	79	15

**BT-BR(1Mbps)**  
**2441MHz**

**Hopping Ch**



Port 1

Hopping No  
79

Span  
83.5MHz

RBW  
100kHz

VBW  
300kHz


Sweep  
1.2ms

Detector  
Peak

Hopping No	Limit
79	15

**BT-EDR(2Mbps)**  
**2441MHz**

**Hopping Ch**



Port 1

Hopping No  
79

Span  
83.5MHz

RBW  
100kHz

VBW  
300kHz

Sweep  
1.2ms

Detector  
Peak

Hopping No	Limit
79	15

## 3.6 20dB and Occupied Bandwidth

### 3.6.1 Test Procedures


#### 20dB Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Peak , Trace max hold
2. Allow trace to stabilize
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

#### Occupied Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Sample , Trace max hold
2. Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

### 3.6.2 Test Setup



### 3.6.3 Test result of 20dB and Occupied Bandwidth

#### Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	920.29k	868.307k	868KF1D	920.29k	864.689k
BT-EDR(2Mbps)	1.373M	1.216M	1M22G1D	1.268M	1.19M


**Max-N dB** = Maximum20dB downbandwidth;**Max-OBW** = Maximum99% occupied bandwidth;

**Min-N dB** = Minimum20dB downbandwidth;**Min-OBW** = Minimum99% occupied bandwidth;

#### Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	920.29k	864.689k
2441MHz	Pass	Inf	920.29k	868.307k
2480MHz	Pass	Inf	920.29k	868.307k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.268M	1.198M
2441MHz	Pass	Inf	1.373M	1.19M
2480MHz	Pass	Inf	1.344M	1.216M


**Port X-N dB** = Port X20dB downbandwidth; **Port X-OBW** = Port X99% occupied bandwidth;



### BT-EDR(2Mbps)

EBW


2402MHz



### BT-EDR(2Mbps)

EBW


2441MHz



### BT-EDR(2Mbps)

EBW

2480MHz



## 3.7 Channel Separation


### 3.7.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 3.7.2 Test Procedures

1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
2. Allow trace to stabilize
3. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

### 3.7.3 Test Setup



### 3.7.4 Test result of Channel Separation

#### Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1M	995.652174k
BT-EDR(2Mbps)	1.004348M	1M

#### Result

Mode	Result	Fl (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.401991G	2.402991G	1M	612.91314k
2441MHz	Pass	2.440991G	2.441991G	1M	612.91314k
2480MHz	Pass	2.478996G	2.479991G	995.652174k	612.91314k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.401991G	2.402996G	1.004348M	844.488k
2441MHz	Pass	2.440991G	2.441996G	1.004348M	914.418k
2480MHz	Pass	2.478996G	2.479996G	1M	895.104k



### BT-BR(1Mbps)

### Channel Separation

2.402G/2.403GHz




F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.401991G	2.402991G	1M	612.91314k

### BT-BR(1Mbps)

### Channel Separation

2.441G/2.442GHz



F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440991G	2.441991G	1M	612.91314k

### BT-BR(1Mbps)

### Channel Separation

2.48G/2.479GHz




F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478996G	2.479991G	995.652174k	612.91314k

### BT-EDR(2Mbps)

### Channel Separation

2.402G/2.403GHz




F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.401991G	2.402996G	1.004348M	844.488k

### BT-EDR(2Mbps)

### Channel Separation

2.441G/2.442GHz




F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440991G	2.441996G	1.004348M	914.418k

### BT-EDR(2Mbps)

### Channel Separation

2.48G/2.479GHz



F1(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478996G	2.479996G	1M	895.104k

## 3.8 Number of Dwell Time


### 3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 3.8.2 Test Procedures

1. Set RBW=100 kHz, VBW=300 kHz, Sweep time=5 ms, Detector=Peak, Span=0 Hz, Trace max hold.
2. Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. Set RBW=100 kHz, VBW=300 kHz, Sweep time=5 s / 2 s, Detector=Peak, Span=0 Hz, Trace max hold.
4. Enable gating and trigger function of spectrum analyzer to measure burst on number of transmission.
5. Set RBW=100 kHz, VBW=300 kHz, Sweep time=31.6 s / 8 s, Detector=Peak, Span=0 Hz, Trace max hold.
6. Enable gating and trigger function of spectrum analyzer to measure burst on number of transmission of entire time cycle.

### 3.8.3 Test Setup



### 3.8.4 Test Result of Dwell Time

#### Result/ Non AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (ms)	Number of transmission in a 5 s
BT-BR(1Mbps)	-	-	-	-	-	-
2402MHz-1DH5	PASS	31.6	0.3548364	0.4	2.95500	19
BT-EDR(2Mbps)	-	-	-	-	-	-
2402MHz-2DH5	PASS	31.6	0.3584388	0.4	2.98500	19

Note 1: Dwell time =Number of transmission in a 5 second x Tx On Time x 6.32

Note 2: DH5 was the worst mode.

#### Result/ AFH mode


Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (ms)	Number of transmission in a 2 s
BT-BR(1Mbps)	-	-	-	-	-	-
2402MHz-1DH5	PASS	8	0.2832	0.4	2.95000	24
BT-EDR(2Mbps)	-	-	-	-	-	-
2402MHz-2DH5	PASS	8	0.30836	0.4	2.96500	26

Note 1: Dwell time =Number of transmission in a 2 second x Tx On Time x 4


Note 2: DH5 was the worst mode.

**Result/ Non AFH mode**


**DH5-1Mbps**




**DH5-2Mbps**



**Result/ AFH mode  
DH5-1Mbps**



### DH5-2Mbps





## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin  
Kou District, New Taipei City,  
Taiwan, R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,  
Kwei Shan District, Tao Yuan City  
333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan District, Tao Yuan  
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==