



A D T

RF EXPOSURE REPORT

REPORT NO.: SA140515D01

MODEL NO.: V5US14

FCC ID: R48V5US

RECEIVED: Jun. 26, 2014

TESTED: Sep. 10 ~ Oct. 8, 2014

ISSUED: Oct. 14, 2014

APPLICANT: MEILOON INDUSTRIAL CO., LTD

ADDRESS: No. 77, Lane 1775, Chuen-Ryh Road, Taoyuan City,
Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C.)

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA	5
4. CLASSIFICATION	5
5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140515D01	Original release	Oct. 14, 2014



A D T

1. CERTIFICATION

PRODUCT: Universal Wireless Speaker

MODEL NO.: V5US14

BRAND: WREN

APPLICANT: MEILOON INDUSTRIAL CO., LTD

TESTED: Sep. 10 ~ Oct. 8, 2014

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Jessica Cheng , **DATE:** Oct. 14, 2014
(Jessica Cheng / Senior Specialist)

APPROVED BY : Rex Lai , **DATE:** Oct. 14, 2014
(Rex Lai / Assistant Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Function	FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
(Bluetooth EDR)	2402 ~ 2480	1.71	-0.29	20	0.0003	1.00
WLAN (2.4G)	2412 ~ 2462	22.45	2.79	20	0.0665	1.00
WLAN (5.0G)	5180 ~ 5240	13.42	6.62	20	0.0201	1.00
	5260 ~ 5320	13.09	6.62	20	0.0186	1.00
	5500 ~ 5700	13.04	6.62	20	0.0184	1.00
	5745 ~ 5825	13.18	6.62	20	0.0190	1.00

CONCLUSION:

Both of the modules can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. BLUETOOTH + WLAN = $0.0003 / 1 + 0.0665 / 1 = 0.0668$

FREQUENCY BAND (MHz)	MAX POWER (dBm)			TOTAL POWER (dBm)	POWER LIMIT (dBm)
	WIFI (2.4G)	WIFI (5.0G)	Bluetooth EDR		
2400	22.45	-	1.71	22.49	30
5180 ~ 5240	-	13.42	-	13.42	30
5260 ~ 5320	-	13.09	-	13.09	30
5500 ~ 5700	-	13.04	-	13.04	30
5745 ~ 5825	-	13.18	-	13.18	30

--- END ---