

Certification Exhibit

FCC ID: R4N-AW5802MR IC: 5303A-AW5802MR

FCC Rule Part: 15.247
IC Radio Standards Specification: RSS-210

ACS Project Number: 12-2135

Manufacturer: AvaLAN Wireless Systems Model: AW5802MR

RF Exposure

Model: AW5802MR FCC ID: R4N-AW5802MR IC: 5303A-AW5802MR

General Information:

Applicant: AvaLAN Wireless Systems

ACS Project: 12-2135 Device Category: Mobile

Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type 1: Panel Antenna

Antenna Gain 1: 22 dBi

Antenna Type 2: Dipole Antenna

Antenna Gain 2: 5 dBi

Maximum Transmitter Conducted Power: 13.91 dBm, 24.6 mW

Maximum System EIRP: 35.91 dBm, 3899.42 mW Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment							
Limits for General Population/Uncontrolled Exposure*							
Transmit	Radio	Power	Radio	Antenna	Antenna	Distance	Power Density
Frequency	Power	Density Limit	Power	Gain	Gain (mW		(mW/cm^2)
(MHz)	(dBm)	(mW/Cm2)	(mW)	(dBi)	eq.)	(cm)	(IIIVV/CIII^2)
5787.517	13.91	1.00	24.60	22	158.489	20	0.776

Installation Guidelines

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

RF Exposure

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.

^{*} Note: The maximum EIRP and Power Density are calculated using the highest antenna gain.