

**Date: January 11, 2021** 

## **DTS-UNII Device Declaration Letter**

To whom it may concern, we declare below featured for equipment authorization regarding

10 Whom it may	oblicent, we decide below leatured for equipmen	it datiforization regarding	,
FCC ID: R5SX2	00		
(1) DFS Devi capability	ce ⊠ Master, □ Client with Radar detection cap , □ N/A	oability, □ Client without	radar detection
(2) Active /	Passive Scanning		
Frequency Band(MHz)	Active Scanning (able to select a channel and initiate a network by sending enabling signals to other devices)	Passive scanning (not able to initiate a network)	Non Applicable
2412 - 2462	☐ Yes , ☐ No	☐ Yes , ☐ No	⊠
5150 - 5250	☐ Yes , ☐ No	☐ Yes , ☐ No	⊠
5250 - 5350	□ Yes , □ No	☐ Yes , ☐ No	⊠
5470 - 5725	⊠ Yes , □ No	☐ Yes , ☒ No	
5725 - 5850	⊠ Yes , □ No	☐ Yes , ☒ No	
<ul> <li>(3) Country code selection ability - ⋈ Yes , □ No</li> <li>If yes, pls explain how it was implemented : Country code is factory set in the UI and cannot be changed by end users.</li> <li>(4) Meet 15.202 requirement - ⋈ Yes , □ No</li> </ul>			
pls check below	:		
	rice is defined as a device operating in a mode in vabling signal. In this mode it is able to select a chadevices.	•	•
	e is defined as a device operating in a mode in whaster. A device in client mode is not able to initiate		the device are under
-	Lulu Sta ): Alessandro Erta		

Title: Manager Engineering

On behalf of Company: Cisco Systems

Telephone: 1-408-527-1446

Address: 125 West Tasman Drive, San Jose, California, United States, 95134-1706