



# ComplianceTesting.com

Previously Flom Test Lab

**EMI, EMC, RF Testing Experts Since 1963**

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

Date: April 14, 2009

Applicant: Lantronix  
15353 Barranca Parkway  
Irvine, California 92618

Attention of: Daryl Miller  
(800) 526-8766; Fax: (949) 453-3995  
E-mail: [daryl.miller@lantronix.com](mailto:daryl.miller@lantronix.com)

Equipment: Lantronix  
FCC ID: R68MPBGPRO  
FCC Rules: Radio Frequency Radiation Exposure Limits  
47 CFR 1.1310  
MPE - Mobiles   X   Fixed Based Station           

Gentlemen:

Enclosed please find your copy of the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

Please allow from 8-12 weeks to hear from the Commission, who may request additional data or information, and even a sample for pre-grant audit testing.

Should you need any clarification, just fax or phone. Thank you again for this order - it has been a pleasure to be of service.

Sincerely yours,

John Erhard: Engineering Manager



ComplianceTesting.com

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

Date: April 14, 2009

Federal Communications Commission

Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Lantronix  
 Equipment: MatchPort b/g Pro  
 FCC ID: R68MPBGPRO  
 FCC Rules: Radio Frequency Radiation Exposure Limits  
 47 CFR 1.1310  
 MPE - Mobiles  X  Fixed Based Station \_\_\_\_\_

Gentlemen:

On behalf of the Applicant, enclosed please find the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,



ComplianceTesting.com

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

## Environmental Assessment

for

**Mobiles**

for

**FCC ID:** R68MPBGPRO

**Model:** MatchPort b/g Pro  
to

**Federal Communications Commission**

**47 CFR 1.1310**

Radio Frequency Radiation Exposure Limits

**Date Of Report:** April 14, 2009

**On the Behalf of the Applicant:** Lantronix Inc.

**At the Request of:** Lantronix Inc.  
15353 Barranca Parkway  
Irvine, California 92618

**Attention of:** Daryl Miller  
(800) 526-8766; Fax: (949) 453-3995  
E-mail: [daryl.miller@lantronix.com](mailto:daryl.miller@lantronix.com)

Supervised By:

## Table of Contents

| Rule   | Description  | Page |
|--------|--|------|
|        | Test Report  | 1    |
|        | Identification of the Equipment Under Test         | 2    |
|        | Standard Test Conditions and Engineering Practices | 4    |
| 1.1310 | Environmental Assessment                           | 5    |

Required information per ISO 17025-2005, paragraph 5.10:

a) **Test Report (Supplemental)**

b) Laboratory: Compliance Testing  
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107  
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0940008

d) Client: Lantronix  
15353 Barranca Parkway  
Irvine, California 92618

e) Identification: MatchPort b/g Pro

Description: Digital Transmission System

f) EUT Condition: Not required unless specified in individual tests.


g) Report Date: April 14, 2009

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with CT internal quality manual.

m) Supervised by:



John Erhard: Engineering Manager

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

### Identification of the Equipment Under Test (EUT)

**Name and Address of Applicant:** Lantronix  
 15353 Barranca Parkway  
 Irvine, California 92618

**Manufacturer:** Lantronix  
 15353 Barranca Parkway  
 Irvine, California 92618

**FCC ID:** R68MPBGPRO

**Model Number:** MatchPort b/g Pro

**Description:** Digital Transmission System

**Type of Emission:** DTS

**Frequency Range, MHz:** 2412 - 2462

**Power Rating, Watts:** 0.109 W  
 Switchable       Variable       N/A

**Modulation:**
  
 AMPS
   
 TDMA
   
 CDMA
   
 OTHER

**Antenna:**
  
 Helical
   
 Monopole
   
 Whip
   
 Other

**Note:** For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.

**A2LA**

“A2LA has accredited Compliance Testing in Chandler, AZ for technical competence in the field of Electrical testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO 17025:2005 ‘General Requirements for the Competence of Testing and Calibration Laboratories’ and any additional program requirements in the identified field of testing.”

Please refer to [www.a2la.org](http://www.a2la.org) for current scope of accreditation.

Certificate number: 2152.01



## Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-2003 and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.



**Name of Test:** Environmental Assessment

**Specification:** FCC: 47 CFR 1.1310

**Measurement Guide:** ANSI/IEEE C95.1 1992

**Name of Test:** R.F. Radiation Exposure

**FCC Rules:** 1.1307, 1.1310, 1.1311, 2.1091

|                               |                   |   |
|-------------------------------|-------------------|---|
| Limits: Uncontrolled Exposure | 0.3-1.234 MHz:    | Limit [mW/cm <sup>2</sup> ] = 100                   |
| 47 CFR 1.1310                 | 1.34-30 MHz:      | Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> ) |
| Table 1, (B)                  | 30-300 MHz:       | Limit [mW/cm <sup>2</sup> ] = 0.2                   |
|                               | 300-1500 MHz:     | Limit [mW/cm <sup>2</sup> ] = f/1500                |
|                               | 1500-100,000 MHz: | Limit [mW/cm <sup>2</sup> ] = 1.0                   |

|                          |         |
|--------------------------|---------|
| Test Frequencies, MHz    | 2462    |
| Power, Conducted, W (P)  | 0.109 W |
| Antenna Gain Isotropic   | 0 dBi   |
| Antenna Gain Numeric (G) | 1       |
| Antenna Type             | Patch   |
| Distance (R)             | 20 cm   |

|                            |                     |                     |
|----------------------------|---------------------|---------------------|
| Power Density Calculations | Formula =           | $S = PG / 4\pi R^2$ |
|                            | Power Density (S) = | 0.0216              |
|                            | Limit =             | 1.0                 |

FCC ID: VHARAD24 (co-located transmitter)


|                          |             |
|--------------------------|-------------|
| Test Frequencies, MHz    | 2440        |
| Power, Conducted, W (P)  | 0.0000126 W |
| Antenna Gain Isotropic   | 0 dBi       |
| Antenna Gain Numeric (G) | 1           |
| Antenna Type             | patch       |
| Distance (R)             | 20 cm       |

|                            |                     |                     |
|----------------------------|---------------------|---------------------|
| Power Density Calculations | Formula =           | $S = PG / 4\pi R^2$ |
|                            | Power Density (S) = | 0.00024             |
|                            | Limit =             | 1.0                 |

**Summed Power Density**

| VHARAD24 | R68MPBGPRO | Co-located Power Density | Limit | Result |
|----------|------------|--------------------------|-------|--------|
| 0.00024  | 0.0216     | 0.02184                  | 1.0   | Pass   |

Supervised By:



## Testimonial and Statement of Certification

**This is to certify that:**

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:

