



FCC Part 1 Subpart I
FCC Part 2 Subpart J
INDUSTRY CANADA RSS 102 ISSUE 4

RF EXPOSURE REPORT

FOR

MOBILE, BTLE PROXIMITY ENABLING DEVICE

MODEL NUMBER: FYX Beacon

FCC ID: R6CFYX1
IC: 10756A-FYX1

REPORT NUMBER: 12U14557-4, Revision A

ISSUE DATE: FEBRUARY 15, 2013

Prepared for
QUALCOMM LABS, INC.
5775 MOREHOUSE DRIVE
SAN DIEGO, CA 92121, U.S.A.

Prepared by
UL CCS
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	12/28/12	Initial Issue	F. Ibrahim
A	02/15/13	Revised section 6	F. Ibrahim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. REFERENCES	5
4. FACILITIES AND ACCREDITATION	5
5. MOBILE CONFIGURATION RF EXPOSURE.....	6
5.1. <i>FCC RULES</i>	<i>6</i>
5.2. <i>IC RULES</i>	<i>7</i>
5.3. <i>EQUATIONS.....</i>	<i>8</i>
5.4. <i>LIMITS.....</i>	<i>9</i>
5.5. <i>RESULTS</i>	<i>9</i>
6. PORTABLE CONFIGURATION RF EXPOSURE	10
6.1. <i>FCC SAR TEST EXCLUSION THRESHOLD LIMITS</i>	<i>10</i>
6.2. <i>FCC RESULTS.....</i>	<i>10</i>
6.3. <i>IC SAR EXEMPTION LIMITS</i>	<i>11</i>
6.4. <i>IC RESULTS.....</i>	<i>11</i>

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: QUALCOMM LABS, INC
5775 MOREHOUSE DRIVE
SAN DIEGO, CA 92121, U.S.A.

EUT DESCRIPTION: MOBILE, BTLE PROXIMITY ENABLING DEVICE

MODEL: FYX Beacon

SERIAL NUMBER: Radiated Emission Samples: 3QTW-YEB88, C3NH-WQPAV,
JPUZ-WHRVW. Conducted Samples: N10GMGF2N,
N10GMGG7D, N10GMGFXV, N10GMGG0M.

DATE TESTED: NOVEMBER 19 - DECEMBER 19, 2012

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Pass
INDUSTRY CANADA RSS 102 ISSUE 4	Pass

UL CCS calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL CCS By:



FRANK IBRAHIM
WiSE PROJECT LEAD
UL CCS

Tested By:



OLIVER SU
EMC ENGINEER
UL CCS

2. TEST METHODOLOGY

All calculations and evaluations were made in accordance with FCC OET Bulletin 65 Edition 97-01, KDB 447498 D01 General RF Exposure Guidance v05, IC RSS 102 Issue 4 and IC Safety Code 6.

3. REFERENCES

All measurements were made as documented in test report UL CCS Document 12U14557-2 for operation in the 2.4 GHz band.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Antenna gain data is excerpted from the applicable test reports.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

5. MOBILE CONFIGURATION RF EXPOSURE

5.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

5.2. IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 5
Exposure Limits for Persons Not Classified As RF and Microwave Exposed Workers (Including the General Public)

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m ²)	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	$280/f$	$2.19/f$		6
10–30	28	$2.19/f$		6
30–300	28	0.073	2*	6
300–1 500	$1.585f^{0.5}$	$0.0042f^{0.5}$	$f/150$	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	$616\,000/f^{1.2}$
150 000–300 000	$0.158f^{0.5}$	$4.21 \times 10^{-4}f^{0.5}$	$6.67 \times 10^{-5}f$	$616\,000/f^{1.2}$

* Power density limit is applicable at frequencies greater than 100 MHz.

Notes: 1. Frequency, f , is in MHz.
2. A power density of 10 W/m² is equivalent to 1 mW/cm².
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μT) or 12.57 milligauss (mG).

5.3. EQUATIONS

POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * D^2)$$

Where

S = Power density in mW/cm²

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

DISTANCE

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in W

5.4. LIMITS

VARIABLE LIMITS

For mobile radio equipment operating in the cellular phone band, the lowest power density limit is calculated using the lowest frequency:

$$824 \text{ MHz} / 1500 = 0.55 \text{ mW/cm}^2 \text{ (FCC)}$$

$$824 \text{ MHz} / 150 = 5.5 \text{ W/m}^2 \text{ (IC)}.$$

FIXED LIMITS

For operation in the PCS band, the 2.4 GHz band and the 5 GHz bands:

From FCC §1.1310 Table 1 (B), the maximum value of $S = 1.0 \text{ mW/cm}^2$

From IC Safety Code 6, Section 2.2 Table 5 Column 4, $S = 10 \text{ W/m}^2$

INDUSTRY CANADA EXEMPTION LIMITS

RSS-102 Clause 2.5.2: RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 2.5 W;
- at or above 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 5 W.

5.5. RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

Single Chain and non-colocated transmitters								
Band	Mode	Separation Distance (cm)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (mW)	FCC Power Density (mW/cm ²)	IC Power Density (W/m ²)
2.4 GHz	BLE	20	-0.44	1.00	100.0	1.1	0.0002	0.002

The device operates above 1.5 GHz and the maximum e.i.r.p. is less than 5 W therefore the device is exempt from Industry Canada RF exposure evaluation.

6. PORTABLE CONFIGURATION RF EXPOSURE

6.1. FCC SAR TEST EXCLUSION THRESHOLD LIMITS

Section 4.3.1 of KDB 447498 D01 General RF Exposure Guidance v05: the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test sep. distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where:

max. power of channel is rounded to the nearest mW

min. test separation distance is the greater of 5 mm and the actual minimum separation distance (rounded to the nearest mm)

6.2. FCC RESULTS

An assessment was made using the above-stated formula to determine Bluetooth's eligibility for SAR test exclusion, and this process is illustrated in the table below:

1. Determining values for the variables				
	Max. Power of Channel		Min. Test Separation Distance (mm)	Frequency (GHz)
	(dBm)	(mW)		
Measured or Actual Value	-0.44	0.90	0.0	2.441
Value used for Computation	N/A	1	5	2.441
2. Assigning the determined values to the formula, arriving at:				
Expression			Result	
$[(1\text{mW})/(5\text{ mm})] [\sqrt{2.441(\text{GHz})}]$			0.3	

The computed value is < 3 ; therefore the device qualifies for FCC Standalone SAR test exclusion.

6.3. IC SAR EXEMPTION LIMITS

RSS-102 Clause 2.5.1 SAR evaluation is required if the separation distance between the user and the radiating element of the device is less than or equal to 20 cm, except when the device operates as follows:

- from 3 kHz up to 1 GHz inclusively, and with output power (i.e. the higher of the conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 200 mW for general public use and 1000 mW for controlled use;
- above 1 GHz and up to 2.2 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 100 mW for general public use and 500 mW for controlled use;
- above 2.2 GHz and up to 3 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 20 mW for general public use and 100 mW for controlled use;
- above 3 GHz and up to 6 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 10 mW for general public use and 50 mW for controlled use.

6.4. IC RESULTS

The device operates between 2.2 and 3 GHz and the higher of the conducted and radiated (e.i.r.p.) source-based, time-averaged output power is less than 100 mW therefore the device is exempt from Industry Canada SAR evaluation.

END OF REPORT