



FCC Part 1 Subpart I
FCC Part 2 Subpart J

RF EXPOSURE REPORT

FOR

USB Beacon

MODEL NUMBER: 900-0004-000

**FCC ID: R6CGUS5
IC: 10756A-GUS5**

REPORT NUMBER: 10648794D

ISSUE DATE: April 16, 2015

Prepared for
Gimbal Inc
12526 High Bluff Dr.
San Diego, CA 92130

Prepared by
UL LLC
333 Pfingsten Rd.
Northbrook, IL 60062
TEL: (847) 272-8800



NVLAP Lab code: 100414-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	4/16/15	Initial Issue	M.Ferrer

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. REFERENCES	5
4. FACILITIES AND ACCREDITATION	5
5. MAXIMUM PERMISSIBLE RF EXPOSURE	Error! Bookmark not defined.
5.1. FCC RULES	Error! Bookmark not defined.
5.2. IC RULES	Error! Bookmark not defined.
5.3. EQUATIONS.....	Error! Bookmark not defined.
5.4. LIMITS AND IC EXEMPTION	Error! Bookmark not defined.
6. RF EXPOSURE RESULTS.....	Error! Bookmark not defined.
6.1. INDUSTRY CANADA.....	Error! Bookmark not defined.

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Gimbal Inc
12526 High Bluff Dr.
San Diego, CA 92130

EUT DESCRIPTION: USB Beacon

MODEL: 900-0004-000

SERIAL NUMBER: Prototype

DATE TESTED: January 22, 2015 – February 11, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Pass

UL LLC calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL LLC based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL LLC By:



Bart Mucha
Staff Engineer
UL LLC

Calculated By:



MICHAEL FERRER
Program Manager
UL LLC

2. TEST METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01.

3. REFERENCES

All measurements were made as documented in test report UL LLC Document 10648794A for operation in the 2.4 GHz band.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 333 Pfingsten Road, Northbrook, IL 60062 USA.

UL NBK is accredited by NVLAP, Laboratory Code 100414-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/Standards/scopes/1004140.htm>

4.1. SAR exclusion

From KDB 447498

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* $\leq$ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is $\leq$ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Max Power = 1mW

Min distance = 5mm

$f(\text{GHz}) = 2.450$ GHz

$[(1\text{mW})/(5\text{mm})] \cdot [2.450 \text{ GHz}] = 0.3626 < 3.0$

Therefore SAR testing is exempt

END OF REPORT