

Test Report of FCC Part 15 C for FCC Certificate

On Behalf of

YINRUN PLASTIC CRAFTS CO.,LTD

Product description: R/C Airplane

Model No.: 6024

FCC ID: R6U6024-49M

Prepared for: YINRUN PLASTIC CRAFTS CO.,LTD

Yinrun Ind, Garden, Laimei, Zone,Chenghai,Shantou City,
Guangdong, China

Prepared by: Bontek Compliance Laboratory Ltd

Rm 802~804, 8/F, Jinmin Bld., Zizhu 6th Rd.,Zhuzi Lin, Futian,
Shenzhen 518040, P.R. China.

Tel: 86-755-82871080 Fax: 86-755-82871368

Issue Date: August 21, 2006

Test Date: August 15 ~20, 2006

Test by:

Reviewed By:



Kendy Wang



Tony Wu

TABLE OF CONTENTS

1. GENERAL INFORMATION..... 3

1.1 Product Description for Equipment Under Test (EUT)..... 3

1.2 Related Submittal(s) / Grant (s) 3

1.3 Test Methodology 3

1.4 Test Facility 4

2. SYSTEM TEST CONFIGURATION 5

2.1 EUT Configuration 5

2.2 EUT Exercise 5

2.3 General Test Procedures..... 5

2.4 List of Measuring Equipments Used 5

3. SUMMARY OF TEST RESULTS 6

4. TEST OF CONDUCTED EMISSION 7

4.1 Applicable Standard..... 7

4.2 Test Setup Diagram 7

5- RADIATED EMISSIONS 8

5.1 Limit of Radiated Emissions..... 8

5.2 Test Equipment Used 8

5.3 EUT Setup 9

5.4 Test Procedure 9

5.5 Test Result..... 10

6- OCCUPIED BANDWIDTH 12

6.1 Limit of Occupied Bandwidth 12

6.2 Test Equipment Used 12

6.3 Test Procedure 12

6.4 Occupied Bandwidth Test Result..... 12

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Applicant:	YINRUN PLASTIC CRAFTS CO.,LTD
Address of applicant:	Yinrun Ind, Garden, Laimei, Zone,Chenghai,Shantou City, Guangdong, China
Manufacturer:	YINRUN PLASTIC CRAFTS CO.,LTD
Address of manufacturer:	Yinrun Ind, Garden, Laimei, Zone,Chenghai,Shantou City, Guangdong, China
EUT Description:	R/C Airplane
Trade Name:	N/A
Model No.:	6024
Rated Voltage	DC 9V (6 x1.5VAA alkaline battery) for Transmitter
Frequency range	49.86MHz
Number of channels	1
Channel Separation	None
Product Class:	Low Power Communication Device Transmitter
Measurement Procedure	ANSI C63.4-2003

Remark: * The test data gathered are from the production sample provided by the manufacturer.

1.2 Related Submittal(s) / Grant (s)

This submittal(s) is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4 - 2003.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.235 rules.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 - 2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Test Facility

All measurement required was performed at laboratory of Solid Industrial (Shenzhen) Co., Ltd. at 333 Bulong Highway, Buji, Longgang, Shenzhen, Guangdong, China.

The test facility is recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 759397

Solid Industrial., Ltd, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 759397, Nov 04, 2003.

2. SYSTEM TEST CONFIGURATION

The tests documented in this report were performed in accordance with ANSI C63.4-2003 and FCC CFR 47 Part 15 Subpart C.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

2.3 General Test Procedures

Conducted Emissions The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

Radiated Emissions The EUT is placed on as turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

2.4 List of Measuring Equipments Used

Items	Equipment	Manufacturer	Model No.	Last Cal	Calibration Period
1	Spectrum Analyzer	HP	8594A	2006/8	1 year
2	EMI Test Receiver	R&S	ESS	2006/8	1 year
3	RF Selector	TOYO	NS4901A	2006/8	1 year
4	Pre Amplifier	Anritsu	MH648A	2006/8	1 year
5	Bilog Antenna	CHASE	CBL6111A	2006/8	1 year
6	Turn Disc	HD	DS4150S	2006/8	1 year
7	Antenna Mast	HD	MA2400	2006/8	1 year

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
15.207	Disturbance Voltage at The Mains Terminals	N/A, without AC power supply
15.235	Radiation Emission	Pass
15.235	Occupied Bandwidth	Pass


4. TEST OF CONDUCTED EMISSION

4.1 Applicable Standard

Section 15.207: For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency Range (MHz)	Limits (dBuV)	
	Quasi-Peak	Average
0.150 ~ 0.500	66 ~ 56	56 ~ 46
0.500 ~ 5.000	56	46
5.000 ~ 30.00	60	50

4.2 Test Setup Diagram



- Remark: 1. The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC 15.207 limits.
2. The EUT is excluded from investigation of Disturbance Voltage at The Mains Terminals, for it is powered by DC 9V (6 x1.5VAA alkaline) battery. According to the Section 15.207(d), measurement to demonstrate compliance with the limits of Disturbance Voltage at The Mains Terminals are not required to the devices which only employed battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

5- RADIATED EMISSIONS

5.1 Limit of Radiated Emissions

Limits of Spurious Emissions (Fcc 47 Cfr 15.209 Class B):

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dB μ V/m)
30 ~ 88	3	40
88~216	3	43.5
216 ~ 960	3	46
960 ~ 1000	3	54

Note: (1) The tighter limit shall apply at the edge between two frequency bands.

- (2) The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

5.2 Test Equipment Used

Equipment	Manufacturer	Model No.	Last Cal	Calibration Period
EMI Test Receiver	ROHDE & SCHWARZ	ESS	2006/8	1 year
RF Selector	TOYO	NS4901A	2006/8	1 year
Pre Amplifier	Anritsu	MH648A	2006/8	1 year
Bilog Antenna	CHASE	CBL6111A	2006/8	1 year
Turn Disc	HD	DS4150S	2006/8	1 year
Antenna Mast	HD	MA2400	2006/8	1 year

5.3 EUT Setup

Radiated Measurement Setup




Figure 1 : Frequencies measured below 1 GHz configuration

5.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

- 1). Configure the EUT according to ANSI C63.4:2003.
- 2). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3). The receiving antenna was placed 3 meters far away from the turntable.
- 4). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 5). For Spurious Emissions test, The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization. For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.

5.5 Test Result

Temperature (): 22~23

EUT: R/C Airplane

Humidity (%RH): 50~54

M/N: 6024

Barometric Pressure (mbar): 950~1000

Operation Condition: Continuous Transmitting

Fundamental Emission Test Data

Peak Measurement					
Test Frequency (MHz)	Measuring Level (dB μ V/m)		Limits (dB μ V/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
49.8595	88.2	74.3	100	11.8	25.7
Average Measurement					
49.8595	77.8	69.5	80	2.2	10.5

Result: The field strength of any emission within the operation band did not exceed 80 dB μ V/m for average value or 100 dB μ V/m for peak value.

Harmonics & Spurious Emission

49.86MHz Spurious Emission						
Maximum Frequency (MHz)	Position and Level				Limit	Margin
	Polarity	Value dB μ V/m	Transd	Result dB μ V/m	dB μ V/m	dB μ V/m
99.719	V	30.1	11.7	41.8	43.5	1.7
149.579	V	19.7	10.8	30.5	43.5	13.0
199.438	V	25.6	11.1	36.7	43.5	6.8
249.296	V	26.5	12.9	39.4	46	6.6
299.157	V	16.1	16.2	32.3	46	13.7
349.016	V	13.1	20.3	33.4	46	12.6
398.876	V	8.7	22.9	31.6	46	14.4
448.736	V	12.6	23.2	35.8	46	10.2
498.595	V	13.0	22.6	35.6	46	10.4
---	---	---	---	---	---	---
Maximum Frequency (MHz)	Position and Level				Limit	Margin
	Polarity	Value dB μ V/m	Transd	Result dB μ V/m	dB μ V/m	dB μ V/m
99.719	H	22.9	11.6	34.4	43.5	9.1
149.579	H	15.6	10.9	26.5	43.5	17.0
199.438	H	17.6	10.7	28.3	43.5	15.2
249.296	H	13.8	12.5	26.3	46	19.7
299.157	H	14.5	14.0	28.5	46	17.5
349.016	H	9.4	20.5	29.9	46	16.1
398.876	H	3.8	23.8	27.6	46	18.4
448.736	H	3.9	24.2	28.1	46	17.9
498.595	H	5.6	24.5	30.1	46	15.9
---	---	---	---	---	---	---
Remark: --- Means that The emission level of the rest measuring harmonic up to 5GHz are so low below applicable limit in operation mode, so the result were not recorded.						

6- OCCUPIED BANDWIDTH

6.1 Limit of Occupied Bandwidth

The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the un-modulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

6.2 Test Equipment Used

Equipment	Manufacturer	Model No.	Last Cal	Calibration Period
Spectrum Analyzer	HP	8594A	2006/8	1 year
RF Selector	TOYO	NS4901A	2006/8	1 year
Pre Amplifier	Anritsu	MH648A	2006/8	1 year
Bilog Antenna	CHASE	CBL6111A	2006/8	1 year
Turn Disc	HD	DS4150S	2006/8	1 year
Antenna Mast	HD	MA2400	2006/8	1 year

6.3 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

- 1). Configure the EUT according to ANSI C63.4:2003.
- 2). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3). The receiving antenna was placed 3 meters far away from the turntable.
- 4). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 5). For Spurious Emissions test, The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization. For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.

6.4 Occupied Bandwidth Test Result

Temperature () : 22~23

EUT: R/C Airplane

Humidity (%RH) : 50~54

M/N: 6024

Barometric Pressure (mbar) : 950~1000

Operation Condition: Continuous Transmitting

Test plots see following:

