

# SAR EVALUATION REPORT

For

## SHENZHEN HYT SCIENCE&TECHNOLOGY CO.,LTD

R2-High-Tech Industrial Park  
ShenZhen, China

**FCC ID: R74TC3000**

|                                                                                                                                                              |                                         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| <b>This Report Concerns:</b><br><input checked="" type="checkbox"/> Original Report                                                                          | <b>Equipment Type:</b><br>Two-way Radio |
| <b>Test Engineer:</b> Daniel Deng /                                       |                                         |
| <b>Report No.:</b> R0406283S                                                                                                                                 |                                         |
| <b>Report Date:</b> 2004-07-01                                                                                                                               |                                         |
| <b>Reviewed By:</b> Ling Zhang /                                         |                                         |
| <b>Prepared By:</b> Bay Area Compliance Laboratory Corporation<br>230 Commercial Street<br>Sunnyvale, CA 94085<br>Tel: (408) 732-9162<br>Fax: (408) 732 9164 |                                         |

**Note:** This test report is specially limited to the above client company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

**TABLE OF CONTENTS**

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>SUMMARY.....</b>                                              | <b>3</b>  |
| <b>1 - REFERENCE.....</b>                                        | <b>4</b>  |
| <b>2 - TESTING EQUIPMENT.....</b>                                | <b>5</b>  |
| 2.2 EQUIPMENT CALIBRATION CERTIFICATE .....                      | 5         |
| 2.3 DIPOLE CALIBRATION .....                                     | 15        |
| <b>3 - EUT DESCRIPTION.....</b>                                  | <b>22</b> |
| <b>4 - SYSTEM TEST CONFIGURATION.....</b>                        | <b>23</b> |
| 4.1 JUSTIFICATION .....                                          | 23        |
| 4.2 EUT EXERCISE PROCEDURE .....                                 | 23        |
| 4.3 EQUIPMENT MODIFICATIONS .....                                | 23        |
| <b>5 – CONDUCTED OUTPUT POWER.....</b>                           | <b>24</b> |
| 5.1 PROVISION APPLICABLE.....                                    | 24        |
| 5.2 TEST PROCEDURE .....                                         | 24        |
| 5.3 TEST EQUIPMENT .....                                         | 24        |
| 5.4 TEST RESULTS .....                                           | 24        |
| <b>6 - DOSIMETRIC ASSESSMENT SETUP.....</b>                      | <b>25</b> |
| 6.1 MEASUREMENT SYSTEM DIAGRAM .....                             | 26        |
| 6.2. SYSTEM COMPONENTS .....                                     | 27        |
| 6.3 MEASUREMENT UNCERTAINTY .....                                | 31        |
| <b>7 - SYSTEM EVALUATION .....</b>                               | <b>32</b> |
| 7.1 SIMULATED TISSUE LIQUID PARAMETER CONFIRMATION .....         | 32        |
| 7.2 EVALUATION PROCEDURES.....                                   | 32        |
| 7.3 SYSTEM ACCURACY VERIFICATION .....                           | 33        |
| 7.4 SAR EVALUATION PROCEDURE.....                                | 36        |
| 7.5 EXPOSURE LIMITS.....                                         | 37        |
| <b>8 - TEST RESULTS .....</b>                                    | <b>38</b> |
| 8.1 SAR TEST DATA.....                                           | 38        |
| 8.2 PLOTS OF TEST RESULT .....                                   | 38        |
| <b>EXHIBIT A - SAR SETUP PHOTOGRAPHS .....</b>                   | <b>41</b> |
| BODY-WORN WITH BELT CLIP & HEADSET IN TOUCHING WITH PHANTOM..... | 41        |
| 2.5CM SEPARATION TO FLAT PHANTOM.....                            | 41        |
| <b>EXHIBIT B - EUT PHOTOGRAPHS .....</b>                         | <b>42</b> |
| EUT – FRONT VIEW .....                                           | 42        |
| EUT – REAR VIEW .....                                            | 42        |
| EUT – TOP VIEW.....                                              | 43        |
| ANTENNA VIEW .....                                               | 43        |
| EUT – BOARD AND HOUSING VIEW .....                               | 44        |
| CHARGER VIEW .....                                               | 44        |
| ADAPTER VIEW .....                                               | 45        |
| HEADSET SIMULATOR.....                                           | 45        |
| TC3000-1 COVER OFF VIEW.....                                     | 46        |
| TC3000-1 BOARD VIEW 1 .....                                      | 46        |
| TC3000-1 BOARD VIEW 2 .....                                      | 47        |
| TC3000-1 BOARD VIEW 3 .....                                      | 47        |
| TC3000-2 BOARD VIEW 1 .....                                      | 48        |
| TC3000-2 BOARD VIEW 2 .....                                      | 48        |
| TC3000-2 BOARD VIEW 3 .....                                      | 49        |
| TC3000-2 BOARD VIEW 4 .....                                      | 49        |
| TC3000-2 BOARD VIEW 5 .....                                      | 50        |
| <b>EXHIBIT C – Z-AXIS.....</b>                                   | <b>51</b> |

## SUMMARY

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1].

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.3-1992 [6] for an uncontrolled environment and 8 mW/g for occupational population (Paragraph 65). According to the Supplement C of OET Bulletin 65 (01-2001) "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g for uncontrolled environment and 8 mW/g for occupational population average over 1 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

The investigation was limited to the worst-case scenario from the device usage point of view. For the clarity of data analysis, and clarity of presentation, only one tissue simulation was used for the head and body simulation. This means that if SAR was found at the headset position, the magnitude of SAR would be overestimated comparing to SAR to a headset placed in the ear region.

There was no SAR of any concern measured on the device for any of the investigated configurations, please see following table for testing result summary:

Ambient Temperature (°C): 23.0

Relative Humidity (%): 49.3

Worst case SAR reading

| EUT position                        | Frequency (MHz) | Output Power (W) | Test Type | Antenna Type | Liquid | Phantom | Notes / Accessories | Measured (mW/g) |                 | Limit (mW/g) | Plot # |
|-------------------------------------|-----------------|------------------|-----------|--------------|--------|---------|---------------------|-----------------|-----------------|--------------|--------|
|                                     |                 |                  |           |              |        |         |                     | 50% duty cycle  | 100% duty cycle |              |        |
| Back touching phantom               | 455             | 4.295            | Body worn | Built-in     | body   | flat    | Headset             | 2.49            | 4.98            | 8            | 1      |
| Face 2.5 cm separation from phantom | 455             | 4.295            | Face-held | Built-in     | head   | flat    | None                | 2.155           | 4.31            | 8            | 2      |

## 1 - REFERENCE

---

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM \_ 97, Dubrovnik, October 15{17, 1997, pp. 120-24.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172-175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865-1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

## 2 - TESTING EQUIPMENT

| Type / Model                         | Cal. Date | S/N:            |
|--------------------------------------|-----------|-----------------|
| DASY3 Professional Dosimetric System | N/A       | N/A             |
| Robot RX60L                          | N/A       | F00/5H31A1/A/01 |
| Robot Controller                     | N/A       | F01/5J72A1/A/01 |
| Dell Computer Optiplex GX110         | N/A       | N/A             |
| Pentium III, Windows NT              | N/A       | N/A             |
| SPEAG EDC3                           | N/A       | N/A             |
| SPEAG DAE3                           | 6/04      | 456             |
| SPEAG E-Field Probe ET3DV6           | 9/7/02    | 1604            |
| SPEAG Dummy Probe                    | N/A       | N/A             |
| SPEAG Generic Twin Phantom           | N/A       | N/A             |
| SPEAG Light Alignment Sensor         | N/A       | 278             |
| Apprel Validation Dipole D-1800-S-2  | 11/6/04   | BCL-049         |
| SPEAG Validation Dipole D900V2       | 9/3/04    | 122             |
| Brain Equivalent Matter (800MHz)     | Daily     | N/A             |
| Brain Equivalent Matter (1900MHz)    | Daily     | N/A             |
| Brain Equivalent Matter (2450MHz)    | Daily     | N/A             |
| Muscle Equivalent Matter (800MHz)    | Daily     | N/A             |
| Muscle Equivalent Matter (1900MHz)   | Daily     | N/A             |
| Muscle Equivalent Matter (2450MHz)   | Daily     | N/A             |
| Robot Table                          | N/A       | N/A             |
| Phone Holder                         | N/A       | N/A             |
| Phantom Cover                        | N/A       | N/A             |
| HP Spectrum Analyzer HP8593GM        | 6/20/04   | 3009A00791      |
| Microwave Amp. 8349B                 | N/A       | 2644A02662      |
| Power Meter HP436A                   | 4/2/04    | 2709A29209      |
| Power Sensor HP8482A                 | 4/2/04    | 2349A08568      |
| Signal Generator RS SMIQ O3          | 2/10/04   | 1084800403      |
| Network Analyzer HP-8753ES           | 7/30/04   | 820079          |
| Dielectric Probe Kit HP85070A        | N/A       | N/A             |
| Apprel Validation Dipole D-2450-S-1  | 10/1/04   | BCL-141         |
| Dipole Antenna AD-100 (450MHz)       | 5/7/04    | 02220           |

### 2.2 Equipment Calibration Certificate

Please see the attached file.

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland

**Client** Bay Area Comp. Lab (BACL)

## CALIBRATION CERTIFICATE

Object(s) E33DV2 - SN:3019

Calibration procedure(s) QA CAL-01.v2  
 Calibration procedure for dosimetric E-field probes

Calibration date: October 9, 2003

Condition of the calibrated item In Tolerance (according to the specific calibration document)

This calibration statement documents traceability of M&TE used in the calibration procedures and conformity of the procedures with the ISO/IEC 17025 international standard.

All calibrations have been conducted in the closed laboratory facility: environment temperature 22 +/- 2 degrees Celsius and humidity < 75%.

Calibration Equipment used (M&TE critical for calibration)

| Model Type                        | ID #           | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration  |
|-----------------------------------|----------------|-------------------------------------------|------------------------|
| Power meter EPM E4419B            | GB41293874     | 2-Apr-03 (METAS, No 252-0250)             | Apr-04                 |
| Power sensor E4412A               | MY41495277     | 2-Apr-03 (METAS, No 252-0250)             | Apr-04                 |
| Reference 20 dB Attenuator        | SN: 5066 (20b) | 3-Apr-03 (METAS No. 251-0340)             | Apr-04                 |
| Fluke Process Calibrator Type 702 | SN: 6295803    | 8-Sep-03 (Sintrel SCS No. E-030020)       | Sep-04                 |
| Power sensor HP 8461A             | MY41092180     | 18-Sep-02 (Agilent, No. 20020918)         | In house check: Oct 03 |
| RF generator HP 8684C             | US3642U01700   | 4-Aug-99 (SPEAG, in house check Aug-02)   | In house check: Aug-05 |
| Network Analyzer HP 8753E         | US37390585     | 18-Oct-01 (Agilent, No. 24BR1033101)      | In house check: Oct 03 |

Calibrated by: Name Nico Vetter Function Technician Signature 

Approved by: Name Katja Rokovic Function Laboratory Director Signature 

Date issued: October 9, 2003

This calibration certificate is issued as an intermediate solution until the accreditation process (based on ISO/IEC 17025 International Standard) for Calibration Laboratory of Schmid & Partner Engineering AG is completed.

Leugnausstrasse 43, 8004 Zurich, Switzerland  
Phone +41 1 245 9700, Fax +41 1 245 9779  
info@speag.com, <http://www.speag.com>

# Probe ES3DV2

## SN:3019

### Additional Conversion Factors

|                   |                  |
|-------------------|------------------|
| Manufactured:     | December 5, 2002 |
| Last calibration: | July 12, 2003    |
| Add. calibration: | October 9, 2003  |

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

**DASY - Parameters of Probe: ES3DV2 SN:3019****Sensitivity in Free Space**

|       |                                                 |
|-------|-------------------------------------------------|
| NormX | <b>1.05</b> $\mu\text{V}/(\text{V}/\text{m})^2$ |
| NormY | <b>1.14</b> $\mu\text{V}/(\text{V}/\text{m})^2$ |
| NormZ | <b>0.98</b> $\mu\text{V}/(\text{V}/\text{m})^2$ |


**Diode Compression**

|       |           |
|-------|-----------|
| DCP X | <b>99</b> |
| DCP Y | <b>99</b> |
| DCP Z | <b>99</b> |

**Sensor Offset**

|                            |            |           |
|----------------------------|------------|-----------|
| Probe Tip to Sensor Center | <b>2.1</b> | <b>mm</b> |
|----------------------------|------------|-----------|

## Conversion Factor Assessment



Head 835 MHz  $\epsilon_r = 41.5 \pm 5\%$   $\sigma = 0.90 \pm 5\%$  mho/m

Valid for f=793-877 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X


|         |                       |                  |      |
|---------|-----------------------|------------------|------|
| ConvF X | 6.5 $\pm 9.5\%$ (k=2) | Boundary effect: |      |
| ConvF Y | 6.5 $\pm 9.5\%$ (k=2) | Alpha            | 0.35 |
| ConvF Z | 6.5 $\pm 9.5\%$ (k=2) | Depth            | 1.46 |

Head 1900 MHz  $\epsilon_r = 40.0 \pm 5\%$   $\sigma = 1.40 \pm 5\%$  mho/m

Valid for f=1805-1995 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X

|         |                       |                  |      |
|---------|-----------------------|------------------|------|
| ConvF X | 4.7 $\pm 9.5\%$ (k=2) | Boundary effect: |      |
| ConvF Y | 4.7 $\pm 9.5\%$ (k=2) | Alpha            | 0.22 |
| ConvF Z | 4.7 $\pm 9.5\%$ (k=2) | Depth            | 3.48 |

## Conversion Factor Assessment



**Body**                      **835 MHz**                       $\epsilon_r = 55.2 \pm 5\%$                        $\sigma = 0.97 \pm 5\% \text{ mho/m}$

Valid for f=793-877 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C


|         |                              |                   |
|---------|------------------------------|-------------------|
| ConvF X | <b>6.1</b> $\pm 9.5\%$ (k=2) | Boundary effect:  |
| ConvF Y | <b>6.1</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.24</b> |
| ConvF Z | <b>6.1</b> $\pm 9.5\%$ (k=2) | Depth <b>2.00</b> |

**Body**                      **1900 MHz**                       $\epsilon_r = 53.3 \pm 5\%$                        $\sigma = 1.52 \pm 5\% \text{ mho/m}$

Valid for f=1805-1995 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C

|         |                              |                   |
|---------|------------------------------|-------------------|
| ConvF X | <b>4.6</b> $\pm 9.5\%$ (k=2) | Boundary effect:  |
| ConvF Y | <b>4.6</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.24</b> |
| ConvF Z | <b>4.6</b> $\pm 9.5\%$ (k=2) | Depth <b>2.64</b> |

## Conversion Factor Assessment



Body 900 MHz  $\epsilon_r = 55.0 \pm 5\%$   $\sigma = 1.05 \pm 5\%$  mho/m

Valid for f=855-945 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C


|         |                      |                  |
|---------|----------------------|------------------|
| ConvF X | 6.1 $\pm$ 9.5% (k=2) | Boundary effect: |
| ConvF Y | 6.1 $\pm$ 9.5% (k=2) | Alpha 0.27       |
| ConvF Z | 6.1 $\pm$ 9.5% (k=2) | Depth 1.82       |

Body 1800 MHz  $\epsilon_r = 53.3 \pm 5\%$   $\sigma = 1.52 \pm 5\%$  mho/m

Valid for f=1710-1890 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C

|         |                      |                  |
|---------|----------------------|------------------|
| ConvF X | 4.7 $\pm$ 9.5% (k=2) | Boundary effect: |
| ConvF Y | 4.7 $\pm$ 9.5% (k=2) | Alpha 0.23       |
| ConvF Z | 4.7 $\pm$ 9.5% (k=2) | Depth 2.99       |

## Conversion Factor Assessment



**Head**      **2450 MHz**       $\epsilon_r = 39.2 \pm 5\%$        $\sigma = 1.80 \pm 5\%$  mho/m

Valid for f=2400-2500 MHz with Head Tissue Simulating Liquid according to EN 60381, P1528-200X

|         |                              |                   |
|---------|------------------------------|-------------------|
| ConvF X | <b>4.5</b> $\pm 9.5\%$ (k=2) | Boundary effect:  |
| ConvF Y | <b>4.5</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.40</b> |
| ConvF Z | <b>4.5</b> $\pm 9.5\%$ (k=2) | Depth <b>1.62</b> |

**Body**      **2450 MHz**       $\epsilon_r = 52.7 \pm 5\%$        $\sigma = 1.95 \pm 5\%$  mho/m

Valid for f=2400-2500 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C

|         |                              |                   |
|---------|------------------------------|-------------------|
| ConvF X | <b>4.2</b> $\pm 9.5\%$ (k=2) | Boundary effect:  |
| ConvF Y | <b>4.2</b> $\pm 9.5\%$ (k=2) | Alpha <b>0.32</b> |
| ConvF Z | <b>4.2</b> $\pm 9.5\%$ (k=2) | Depth <b>1.98</b> |

Zeughausstrasse 43, 8004 Zurich, Switzerland  
Phone +41 1 245 9700, Fax +41 1 245 9779  
info@speag.com, http://www.speag.com

## Additional Conversion Factors for Dosimetric E-Field Probe

Type:

ES3DV2

Serial Number:

3019

Place of Assessment:

Zurich

Date of Assessment:

October 13, 2003

Probe Calibration Date:

October 9, 2003

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. Since the evaluation is coupled with measured conversion factors, it has to be recalculated yearly, i.e., following the re-calibration schedule of the probe. The uncertainty of the numerical assessment is based on the extrapolation from measured value at 900 MHz or at 1800 MHz.

Assessed by:



ES3DV2-SN:3019

October 13, 2003

Zeughausstrasse 43, 8004 Zurich, Switzerland  
Phone +41 1 245 9700, Fax +41 1 245 9779  
info@speag.com, <http://www.speag.com>

### Dosimetric E-Field Probe ES3DV2 SN:3019

Conversion factor ( $\pm$  standard deviation)

**150 MHz**      ConvF       **$8.7 \pm 8\%$**

$\epsilon_r = 52.3 \pm 5\%$   
 $\sigma = 0.76 \pm 5\% \text{ mho/m}$   
(head tissue)

**150 MHz**      ConvF       **$8.3 \pm 8\%$**

$\epsilon_r = 61.9 \pm 5\%$   
 $\sigma = 0.80 \pm 5\% \text{ mho/m}$   
(body tissue)

**450 MHz**      ConvF       **$7.4 \pm 8\%$**

$\epsilon_r = 43.5 \pm 5\%$   
 $\sigma = 0.87 \pm 5\% \text{ mho/m}$   
(head tissue)

**450 MHz**      ConvF       **$7.3 \pm 8\%$**

$\epsilon_r = 56.7 \pm 5\%$   
 $\sigma = 0.94 \pm 5\% \text{ mho/m}$   
(body tissue)

**ES3DV2-SN:3019**

**October 13, 2003**

## 2.3 Dipole Calibration

Please see the attached file.

### Certificate of Calibration Verification

|                    |                      |
|--------------------|----------------------|
| Description of EUT | Tuned Dipole Antenna |
| EUT Model Number   | D450V2               |
| EUT Serial Number  | 1010                 |
| Center Frequency   | 450 MHz              |

Calibration Date: 1 April 2004

### Testing conditions:

per P1528/D1.2:2003:

Ambient Temperature (18-25 °C) 19 °C

Ambient Humidity 45%

Liquid Temperature at start of measurements:( $\pm$ °C) 18.5 °C

Liquid temperature at end of measurements: 18.5 °C

Date and time at beginning of test: 2004-04-01-16:20 PST

Date and time at beginning of test: 2004-04-01-19:40 PST

### Equipment used for measurements

|                                |                                                      |             |             |
|--------------------------------|------------------------------------------------------|-------------|-------------|
| Network Analyzer               | HP                                                   | 8752C       | 1 Nov 2002  |
| Impedance adapter              | AGILENT                                              | 43961A      | 31 Oct 2003 |
| Short Reference                | HP                                                   | 04191-85300 | 31 Oct 2003 |
| Open Reference                 | HP                                                   | 04191-85302 | 31 Oct 2003 |
| Load Reference                 | HP                                                   | 04191-85301 | 31 Oct 2003 |
| Signal Generator               | HP                                                   | 83650B      | 29 Feb 2004 |
| Calibration Cable:             | SMA Utiflex, 3.05 meter cable S/N 99E1206 (Number 8) |             |             |
| Phantom Model:                 | Flat                                                 |             |             |
| Liquid:                        | 450 MHz, Head Liquid                                 |             |             |
| Liquid Validation Date:        | 1 April 2004                                         |             |             |
| Quantity of Liquid in Phantom: | 19.8 Liters                                          |             |             |

### Measurement Procedure

In accordance with IEEE P1528/D1.2:2003, 8.3.4, 8.2.3 through 8.2.4

## Liquid Validation

| Instrument                 | ManufacturerModel |        | Calibrated |
|----------------------------|-------------------|--------|------------|
| Network Analyzer           | HP                | 4396B  | 1 Nov 2002 |
| Dielectric Probe Kit,      | Agilent           | 85070C | Each Use   |
| H <sub>2</sub> O, 18 M-Ohm | BACL              |        | Each Use   |
| Probe, SAR 10 kHz - 6 GHz  | SPEAG             | ES3DV2 | 9 Oct 2003 |

### Attestation:

I hereby attest that the equipment are suitable for the performance requirements of IEEE P1528/D1.2:2003 and the personnel operating the test equipment and measurements are properly trained to perform the verification of this calibration procedure set forth in IEEE P1528/D1.2:2003.

The validation antenna herein meets the minimum requirements of 20 dB insertion loss

  
\_\_\_\_\_  
Hans T. Mellberg  
Engineering Manager

1 APR 2004  
\_\_\_\_\_  
Date

450MHZ Head Liquid validation Ambient Temp = 23 °C , Liquid Temp = 22 °C , Date : 4-1-2004

| Frequency      | $\epsilon'$ | $\epsilon''$ | $\sigma (\sigma = 2\pi f \epsilon'' \epsilon')$ |
|----------------|-------------|--------------|-------------------------------------------------|
| 400000000.0000 | 47.0741     | 37.0458      |                                                 |
| 402000000.0000 | 46.9285     | 36.9126      |                                                 |
| 404000000.0000 | 46.9148     | 36.7377      |                                                 |
| 406000000.0000 | 46.7700     | 36.5998      |                                                 |
| 408000000.0000 | 46.6560     | 36.4571      |                                                 |
| 410000000.0000 | 46.5144     | 36.3600      |                                                 |
| 412000000.0000 | 46.5640     | 36.1548      |                                                 |
| 414000000.0000 | 46.3147     | 36.1139      |                                                 |
| 416000000.0000 | 46.3675     | 35.8883      |                                                 |
| 418000000.0000 | 46.1897     | 35.7819      |                                                 |
| 420000000.0000 | 46.1260     | 35.7120      |                                                 |
| 422000000.0000 | 46.0450     | 35.7659      |                                                 |
| 424000000.0000 | 45.9349     | 35.5439      |                                                 |
| 426000000.0000 | 45.9866     | 35.4514      |                                                 |
| 428000000.0000 | 45.8519     | 35.2826      |                                                 |
| 430000000.0000 | 45.7126     | 35.2557      |                                                 |
| 432000000.0000 | 45.6660     | 35.1799      |                                                 |
| 434000000.0000 | 45.6577     | 35.0455      |                                                 |
| 436000000.0000 | 45.5362     | 34.9879      |                                                 |
| 438000000.0000 | 45.4105     | 35.0042      |                                                 |
| 440000000.0000 | 45.3932     | 34.7596      |                                                 |
| 442000000.0000 | 45.3127     | 34.7457      |                                                 |
| 444000000.0000 | 45.2511     | 34.6851      |                                                 |
| 446000000.0000 | 45.0985     | 34.5960      |                                                 |
| 448000000.0000 | 45.0891     | 34.4475      |                                                 |
| 450000000.0000 | 45.0920     | 34.3537      | 0.86                                            |
| 452000000.0000 | 45.0366     | 34.2809      |                                                 |
| 454000000.0000 | 44.9343     | 34.1844      |                                                 |
| 456000000.0000 | 44.9365     | 34.1765      |                                                 |
| 458000000.0000 | 44.8407     | 34.1634      |                                                 |
| 460000000.0000 | 44.7601     | 34.0021      |                                                 |
| 462000000.0000 | 44.7440     | 33.9995      |                                                 |
| 464000000.0000 | 44.6917     | 33.9572      |                                                 |
| 466000000.0000 | 44.7270     | 33.7312      |                                                 |
| 468000000.0000 | 44.6845     | 33.7290      |                                                 |
| 470000000.0000 | 44.5403     | 33.6083      |                                                 |
| 472000000.0000 | 44.5331     | 33.5784      |                                                 |
| 474000000.0000 | 44.5213     | 33.5566      |                                                 |
| 476000000.0000 | 44.5188     | 33.4589      |                                                 |
| 478000000.0000 | 44.4619     | 33.3014      |                                                 |
| 480000000.0000 | 44.4198     | 33.2614      |                                                 |
| 482000000.0000 | 44.4075     | 33.1219      |                                                 |
| 484000000.0000 | 44.3243     | 33.0731      |                                                 |
| 486000000.0000 | 44.3347     | 33.0550      |                                                 |
| 488000000.0000 | 44.3348     | 32.9936      |                                                 |
| 490000000.0000 | 44.1957     | 33.0055      |                                                 |
| 492000000.0000 | 44.2071     | 32.9878      |                                                 |
| 494000000.0000 | 44.1550     | 32.8686      |                                                 |
| 496000000.0000 | 44.1839     | 32.8149      |                                                 |
| 498000000.0000 | 44.1281     | 32.6530      |                                                 |
| 500000000.0000 | 44.1630     | 32.6245      |                                                 |

Transmit power set to 127 mW

### System validation


Flat Phantom v4.4 Phantom; Flat Section; Position: (90°, 90°); Frequency: 450 MHz

Probe: ES3DV2 - 5N3019; ConvF(7.40, 7.40, 7.40); Crest factor: 1.0; Head 450 MHz:  $\sigma = 0.86 \text{ mho/m}$ ,  $\epsilon_r = 45.1$ ,  $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7; SAR (1g): 0.487 mW/g; SAR (10g): 0.348 mW/g. (Worst-case extrapolation)

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.02 dB





## 450MHz Body Liquid Validation

Ambient Temp=23 Deg C , Liquid Temp=22 Deg C , 6/29/2004

| frequency      | e'      | e''     |
|----------------|---------|---------|
| 400000000.0000 | 59.1023 | 39.9522 |
| 402000000.0000 | 59.0135 | 39.8907 |
| 404000000.0000 | 58.9022 | 39.8663 |
| 406000000.0000 | 58.9705 | 39.7159 |
| 408000000.0000 | 58.9324 | 39.6890 |
| 410000000.0000 | 58.8897 | 39.5637 |
| 412000000.0000 | 58.8620 | 39.4011 |
| 414000000.0000 | 58.8156 | 39.3965 |
| 416000000.0000 | 58.7452 | 39.3259 |
| 418000000.0000 | 58.7018 | 39.2147 |
| 420000000.0000 | 58.6624 | 39.1860 |
| 422000000.0000 | 58.4983 | 39.1105 |
| 424000000.0000 | 58.5568 | 39.0026 |
| 426000000.0000 | 58.4029 | 38.9672 |
| 428000000.0000 | 58.3562 | 38.9100 |
| 430000000.0000 | 58.2301 | 38.8634 |
| 432000000.0000 | 58.1944 | 38.8001 |
| 434000000.0000 | 58.1348 | 38.7146 |
| 436000000.0000 | 58.0983 | 38.6703 |
| 438000000.0000 | 58.0122 | 38.5546 |
| 440000000.0000 | 57.9906 | 38.5639 |
| 442000000.0000 | 57.9684 | 38.4501 |
| 444000000.0000 | 57.9235 | 38.3088 |
| 446000000.0000 | 57.8966 | 38.3267 |
| 448000000.0000 | 57.8025 | 38.2512 |
| 450000000.0000 | 57.7809 | 38.2398 |
| 452000000.0000 | 57.7649 | 38.2306 |
| 454000000.0000 | 57.6833 | 38.1567 |
| 456000000.0000 | 57.6029 | 38.0986 |
| 458000000.0000 | 57.5328 | 38.0034 |
| 460000000.0000 | 57.4680 | 37.9573 |
| 462000000.0000 | 57.3002 | 37.8960 |
| 464000000.0000 | 57.2385 | 37.8011 |
| 466000000.0000 | 57.1064 | 37.7840 |
| 468000000.0000 | 57.0279 | 37.7733 |
| 470000000.0000 | 56.9803 | 37.6891 |
| 472000000.0000 | 56.8672 | 37.6002 |
| 474000000.0000 | 56.7389 | 37.5493 |
| 476000000.0000 | 56.6450 | 37.5022 |
| 478000000.0000 | 56.4538 | 37.4537 |
| 480000000.0000 | 56.5032 | 37.4120 |
| 482000000.0000 | 56.4826 | 37.3966 |
| 484000000.0000 | 56.4640 | 37.3807 |
| 486000000.0000 | 56.3271 | 37.2951 |
| 488000000.0000 | 56.2016 | 37.2134 |
| 490000000.0000 | 56.1022 | 37.1697 |
| 492000000.0000 | 55.9834 | 37.1500 |
| 494000000.0000 | 55.8673 | 37.0964 |
| 496000000.0000 | 55.7830 | 37.1007 |
| 498000000.0000 | 55.6582 | 37.0887 |
| 500000000.0000 | 55.4680 | 37.0005 |

$$\sigma = \omega \varepsilon_0 \varepsilon'' = 2 \pi f \varepsilon_0 \varepsilon'' = 0.9573$$

$$\text{where } f = 450 \times 10^6$$

$$\varepsilon_0 = 8.854 \times 10^{-12}$$

$$\varepsilon'' = 38.2398$$

## 450MHz Head Liquid validation

Ambient Temp=23 Deg C , Liquid Temp=22 Deg C , 6/29/2004

| frequency      | e'      | e''     |
|----------------|---------|---------|
| 400000000.0000 | 47.9881 | 36.3209 |
| 402000000.0000 | 47.7980 | 36.3258 |
| 404000000.0000 | 47.6589 | 36.2239 |
| 406000000.0000 | 47.5013 | 36.2107 |
| 408000000.0000 | 47.4560 | 36.1264 |
| 410000000.0000 | 47.3459 | 36.1026 |
| 412000000.0000 | 47.2033 | 36.0237 |
| 414000000.0000 | 47.1102 | 35.9782 |
| 416000000.0000 | 46.9828 | 35.8329 |
| 418000000.0000 | 46.7459 | 35.8015 |
| 420000000.0000 | 46.5267 | 35.7709 |
| 422000000.0000 | 46.3125 | 35.7556 |
| 424000000.0000 | 46.1022 | 35.7122 |
| 426000000.0000 | 45.9165 | 35.7059 |
| 428000000.0000 | 45.8920 | 35.6716 |
| 430000000.0000 | 45.6891 | 35.6568 |
| 432000000.0000 | 45.5266 | 35.5127 |
| 434000000.0000 | 45.3167 | 35.4679 |
| 436000000.0000 | 45.0132 | 35.4058 |
| 438000000.0000 | 44.8927 | 35.3991 |
| 440000000.0000 | 44.9015 | 35.3259 |
| 442000000.0000 | 44.7811 | 35.3014 |
| 444000000.0000 | 44.5628 | 35.2681 |
| 446000000.0000 | 44.3157 | 35.0168 |
| 448000000.0000 | 44.2659 | 35.1389 |
| 450000000.0000 | 44.1215 | 35.1512 |
| 452000000.0000 | 44.1083 | 35.0983 |
| 454000000.0000 | 44.0598 | 35.0026 |
| 456000000.0000 | 43.8978 | 34.9821 |
| 458000000.0000 | 43.7921 | 34.8847 |
| 460000000.0000 | 43.7689 | 34.7692 |
| 462000000.0000 | 43.6890 | 34.6483 |
| 464000000.0000 | 43.5026 | 34.5628 |
| 466000000.0000 | 43.5131 | 34.4537 |
| 468000000.0000 | 43.4026 | 34.3021 |
| 470000000.0000 | 43.4166 | 34.2164 |
| 472000000.0000 | 43.3589 | 34.1650 |
| 474000000.0000 | 43.3364 | 34.0379 |
| 476000000.0000 | 43.1358 | 33.8976 |
| 478000000.0000 | 43.0151 | 33.8860 |
| 480000000.0000 | 42.9768 | 33.7983 |
| 482000000.0000 | 42.9255 | 33.6701 |
| 484000000.0000 | 42.8790 | 33.6049 |
| 486000000.0000 | 42.7982 | 33.5491 |
| 488000000.0000 | 42.6389 | 33.4680 |
| 490000000.0000 | 42.5690 | 33.4322 |
| 492000000.0000 | 42.5501 | 33.3167 |
| 494000000.0000 | 42.4683 | 33.2384 |
| 496000000.0000 | 42.3975 | 33.1672 |
| 498000000.0000 | 42.3566 | 33.1154 |
| 500000000.0000 | 42.2067 | 33.1029 |

$$\sigma = \omega \varepsilon_0 \varepsilon'' = 2 \pi f \varepsilon_0 \varepsilon'' = 0.8800$$

$$\text{where } f = 450 \times 10^6$$

$$\varepsilon_0 = 8.854 \times 10^{-12}$$

$$\varepsilon'' = 35.1512$$

### 3 - EUT DESCRIPTION

---

|                          |                                         |
|--------------------------|-----------------------------------------|
| Applicant:               | SHENZHEN HYT SCIENCE&TECHNOLOGY CO.,LTD |
| Product Description:     | Two-way Radio                           |
| FCC ID:                  | R74TC3000                               |
| Serial Number:           | TC3000-001                              |
| Transmitter Frequency:   | 440 - 470 MHz                           |
| Maximum Output Power:    | 4.29 W                                  |
| Dimension:               | 5.8cmL x 3.2cmW x 19cmH                 |
| RF Exposure environment: | Occupational Population                 |
| Power Supply:            | Battery                                 |
| Applicable Standard      | FCC CFR 47, Part 90                     |
| Application Type:        | Certification                           |

<sup>1</sup>Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).

<sup>2</sup>IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

*Note: The test data gathered are from production sample, serial number: TC3000-001, provided by the manufacturer.*

## **4 - SYSTEM TEST CONFIGURATION**

---

### **4.1 Justification**

The system was configured for testing in a typical fashion (as normally used by a typical user).

### **4.2 EUT Exercise Procedure**

The EUT exercising program used during SAR testing was designed to exercise the various system components in a manner similar to a typical use. The EUT was tested by pushing the PTT bottom during the testing.

### **4.3 Equipment Modifications**

No modification(s) were made to the EUT.

## 5 – CONDUCTED OUTPUT POWER

### 5.1 Provision Applicable

Per FCC §2.1046 and FCC § 95.639 (d), no FRS unit, under any condition of modulation, shall exceed 0.500W effective radiated power (ERP).

Per FCC §2.1046 and FCC § 95.639 (a) (1), no GMRS unit, under any condition of modulation, shall exceed 50W Carrier Power (average TP during one unmodulated RF cycle) when transmission type A1D, F1D, G1D, A3E, F3E or G3E.

### 5.2 Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

### 5.3 Test equipment

Hewlett Packard HP8564E Spectrum Analyzer, Calibration Date: 2003-08-01.

Hewlett Packard HP 7470A Plotter, Calibration not required.

A.H. Systems SAS200 Horn Antenna, Calibration Date: 2003-05-31


Com-Power AB-100 Dipole Antenna, Calibration Date: 2003-09-05

### 5.4 Test Results

| Frequency (MHz) | Output Power in dBm | Output Power in W |
|-----------------|---------------------|-------------------|
| 455.013         | 36.33               | 4.295             |

Note: The output power measured is conducted. During SAR, it is more convenient to measure conducted power rather than EIRP. EMC measurements only required EIRP and results are within 9% between EIRP and conducted.

Please refer to the following plots.



## 6 - DOSIMETRIC ASSESSMENT SETUP


These measurements were performed with the automated near-field scanning system DASY3 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9m) which positions the probes with a positional repeatability of better than  $\pm 0.02\text{mm}$ . Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The system is described in detail in [3].

The SAR measurements were conducted with the dosimetric probe ET3DV6 SN: 1604 (manufactured by SPEAG), designed in the classical triangular configuration [3] and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [7] with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure described in [8] and found to be better than  $\pm 0.25\text{dB}$ .

The phantom used was the "Generic Twin Phantom" described in [4]. The ear was simulated as a spacer of 4 mm thickness between the earpiece of the phone and the tissue simulating liquid. The Tissue simulation liquid used for each test is in according with the FCC OET65 supplement C as listed below.

| Ingredients<br>(% by weight) | Frequency (MHz) |       |       |      |       |       |       |      |      |      |
|------------------------------|-----------------|-------|-------|------|-------|-------|-------|------|------|------|
|                              | 450             |       | 835   |      | 915   |       | 1900  |      | 2450 |      |
| Tissue Type                  | Head            | Body  | Head  | Body | Head  | Body  | Head  | Body | Head | Body |
| Water                        | 38.56           | 51.16 | 41.45 | 52.4 | 41.05 | 56.0  | 54.9  | 40.4 | 62.7 | 73.2 |
| Salt (Nacl)                  | 3.95            | 1.49  | 1.45  | 1.4  | 1.35  | 0.76  | 0.18  | 0.5  | 0.5  | 0.04 |
| Sugar                        | 56.32           | 46.78 | 56.0  | 45.0 | 56.5  | 41.76 | 0.0   | 58.0 | 0.0  | 0.0  |
| HEC                          | 0.98            | 0.52  | 1.0   | 1.0  | 1.0   | 1.21  | 0.0   | 1.0  | 0.0  | 0.0  |
| Bactericide                  | 0.19            | 0.05  | 0.1   | 0.1  | 0.1   | 0.27  | 0.0   | 0.1  | 0.0  | 0.0  |
| Triton x-100                 | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 0.0   | 0.0  | 36.8 | 0.0  |
| DGBE                         | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 44.92 | 0.0  | 0.0  | 26.7 |
| Dielectric Constant          | 43.42           | 58.0  | 42.54 | 55.2 | 42.0  | 55.9  | 39.9  | 53.3 | 39.8 | 53.6 |
| Conductivity (s/m)           | 0.85            | 0.83  | 0.91  | 0.97 | 1.0   | 0.98  | 1.42  | 1.52 | 1.88 | 1.81 |

## 6.1 Measurement System Diagram



The DAS3 system for performing compliance tests consist of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software.
2. An arm extension for accommodating the data acquisition electronics (DAE).
3. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
4. A data acquisition electronic (DAE), which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
5. A unit to operate the optical surface detector, which is connected to the EOC. The Electro-optical coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the PC plug-in card. The functions of the PC plug-in card based on a DSP is to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.
6. A computer operating Windows 95 or larger
7. DAS3 software
8. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling testing left-hand and right-hand usage.
10. The device holder for handheld EUT.
11. Tissue simulating liquid mixed according to the given recipes (see Application Note).
12. System validation dipoles to validate the proper functioning of the system.

## 6.2. System Components

### ES3DV2 Probe Specification

|               |                                                                                                                                                                                                        |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core<br>Interleafed sensors<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., glycol)                   |
| Calibration   | In air from 10 MHz to 3 GHz<br>In brain and muscle simulating tissue at frequencies of 450 MHz, 900 MHz and 1.8 GHz (accuracy $\pm 8\%$ )<br>Calibratin for other liquids and frequencies upon request |
| Frequency     | 10 MHz to > 6GHz; Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)                                                                                                                                            |
| Directivity   | $\pm 0.2$ dB in brain tissue (rotation around probe axis)<br>$\pm 0.3$ dB in brain tissue (rotation normal to probe axis)                                                                              |
| Dynamic Range | $5\mu\text{W/g}$ to > 100 mW/g; Linearity: $\pm 0.2$ dB                                                                                                                                                |
| Dimensions    | Overall length: 330 mm<br>Tip length: 20 mm<br>Body diameter: 12 mm<br>Tip diameter: 3.9 mm<br>Distance from probe tip to dipole centers: 2.7 mm                                                       |
| Application:  | General dosimetry up to 5 GHz<br>Dosimetry in strong gradient fields<br>Compliance tests of mobile phones                                                                                              |

The SAR measurements were conducted with the dosimetric probe ET3DV2 designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY3 software reads the reflection during a software approach and looks for the maximum using a 2 nd order fitting. The approach is stopped when reaching the maximum.



**Photograph of the probe**



**Inside view of  
ES3DV2 E-field Probe**

## E-Field Probe Calibration Process

Each probe is calibrated according to a dosimetric assessment procedure described in [6] with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in [7] and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

## Data Evaluation

The DASY3 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

|                   |                          |                                                                         |
|-------------------|--------------------------|-------------------------------------------------------------------------|
| Probe Parameter:  | -Sensitivity             | Norm <sub>i</sub> , a <sub>i0</sub> , a <sub>i1</sub> , a <sub>i2</sub> |
|                   | -Conversion Factor       | ConvFi                                                                  |
|                   | -Diode compression point | Dcp <sub>i</sub>                                                        |
| Device parameter: | -Frequency               | f                                                                       |
|                   | -Crest Factor            | cf                                                                      |
| Media parameter:  | -Conductivity            | σ                                                                       |
|                   | -Density                 | ρ                                                                       |

These parameters must be set correctly in the software. They can either be found in the component documents or be imported into the software from the configuration files issued for the DASY3 components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + (U_i)^2 \text{ cf} / \text{dcp}_i$$

With  $V_i$  = compensated signal of channel i (i=x, y, z)  
 $U_i$  = input signal of channel i (i=x, y, z)  
 cf = crest factor of exciting field (DASY parameter)  
 $\text{dcp}_i$  = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\begin{aligned} \text{E-field probes:} \quad E_i &= \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}} \\ \text{H-field probes:} \quad H_i &= \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f} \end{aligned}$$

With  $V_i$  = compensated signal of channel i (i=x, y, z)  
 $\text{Norm}_i$  = sensor sensitivity of channel i (i=x, y, z)  
 $\mu\text{V}/(\text{V/m})^2$  for E-field probes  
 $\text{ConvF}$  = sensitivity enhancement in solution  
 $a_{ij}$  = sensor sensitivity factors for H-field probes  
 $f$  = carrier frequency [GHz]  
 $E_i$  = electric field strenggy of channel i in V/m  
 $H_i$  = diode compression point (DASY parameter)

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = \text{Square Root} [(E_x)^2 + (E_y)^2 + (E_z)^2]$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = (E_{\text{tot}})^2 \cdot \sigma / (\rho \cdot 1000)$$

With  $\text{SAR}$  = local specific absorption rate in mW/g  
 $E_{\text{tot}}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in  $\text{g/cm}^3$

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{\text{pwe}} = (E_{\text{tot}})^2 / 3770 \text{ or } P_{\text{pwe}} = (H_{\text{tot}})^2 \cdot 37.7$$

With  $P_{\text{pwe}}$  = equivalent power density of a plane wave in mW/cm<sup>3</sup>  
 $E_{\text{tot}}$  = total electric filed strength in V/m  
 $H_{\text{tot}}$  = total magnetic filed strength in V/m


### Generic Twin Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [9][10]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allows the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness  $2 \pm 0.1$  mm

Filling Volume Approx. 20 liters

Dimensions 810 x 1000 x 500 mm (H x L x W)




**Generic Twin Phantom**

### Device Holder

In combination with the Generic Twin Phantom V3.0, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

\* Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations [10]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



**Device Holder**

### 6.3 Measurement Uncertainty

The uncertainty budget has been determined for the DASY3 measurement system according to the NIS81 [13] and the NIST1297 [14] documents and is given in the following Table.

| Measurement Uncertainty Analysis per IEEE P1528-2002                 |            |                       |                               |         |          |                |          |                       |
|----------------------------------------------------------------------|------------|-----------------------|-------------------------------|---------|----------|----------------|----------|-----------------------|
| Description                                                          | Section    | Reported Variance (%) | Probability Distribution type | Divisor | Ci (1g)  | Ui (1g)        | Vi       | welc/satt series term |
| Probe Calibration                                                    | E.2.1      | 4.80                  | N                             | 1       | 1        | 4.80           | 1.00E+09 | 5.30842E-07           |
| Axial isotropy                                                       | E.2.2      | 4.70                  | R                             | 1.732   | 0.707107 | 1.92           | 1.00E+09 | 1.35563E-08           |
| Hemispherical isotropy                                               | E.2.2      | 9.60                  | R                             | 1.732   | 0.707107 | 3.92           | 1.00E+09 | 2.35957E-07           |
| Boundary effects                                                     | E.2.3      | 8.30                  | R                             | 1.732   | 1        | 4.79           | 1.00E+09 | 5.27377E-07           |
| Linearity                                                            | E.2.4      | 4.70                  | R                             | 1.732   | 1        | 2.71           | 1.00E+09 | 5.4225E-08            |
| System Detection Limit                                               | E.2.5      | 1.00                  | R                             | 1.732   | 1        | 0.58           | 1.00E+09 | 1.11124E-10           |
| Readout Electronics                                                  | E.2.6      | 0.00                  | N                             | 1       | 1        | 0.00           | 1.00E+09 | 0                     |
| Response time                                                        | E.2.7      | 0.00                  | R                             | 1.732   | 1        | 0.00           | 1.00E+09 | 0                     |
| Integration time                                                     | E.2.8      | 0.00                  | R                             | 1.732   | 1        | 0.00           | 1.00E+09 | 0                     |
| RF Ambient conditions                                                | E.6.1      | 3.00                  | R                             | 1.732   | 1        | 1.73           | 1.00E+09 | 9.00106E-09           |
| Probe positioning mechanical tolerance                               | E.6.2      | 0.40                  | R                             | 1.732   | 1        | 0.23           | 1.00E+09 | 2.84478E-12           |
| Probe positioning wrt phantom shell                                  | E.6.3      | 2.90                  | R                             | 1.732   | 1        | 1.67           | 1.00E+09 | 7.8596E-09            |
| Extra/inter-polation & integration algorithms for max SAR evaluation | E.5.2      | 3.90                  | R                             | 1.732   | 1        | 2.25           | 1.00E+09 | 2.57079E-08           |
| Test sample positioning                                              | 8, E.4.2   | 6.00                  | R                             | 1.732   | 1        | 3.46           | 1.00E+09 | 1.44017E-07           |
| Device holder distance tolerance                                     | E.4.1      | 5.00                  | N                             | 1       | 1        | 5.00           | 1.00E+09 | 0.000000625           |
| Output power and SAR drift measurement                               | 8, E.6.6.2 | 5.00                  | R                             | 1.732   | 1        | 2.89           | 1.00E+09 | 6.94526E-08           |
| Phantom uncertainty, shell thickness tolerance                       | E.3.1      | 4.00                  | R                             | 1.732   | 1        | 2.31           | 1.00E+09 | 2.84478E-08           |
| Liquid conductivity, deviation from target values                    | E.3.2      | 5.00                  | R                             | 1.732   | 0.64     | 1.85           | 1.00E+09 | 1.16522E-08           |
| Liquid conductivity, measurement uncertainty                         | E.3.3      | 5.00                  | N                             | 1       | 0.64     | 3.20           | 5        | 20.97152              |
| Liquid permittivity, deviation from target values                    | E.3.2      | 5.00                  | R                             | 1.732   | 0.6      | 1.73           | 1.00E+09 | 9.00106E-09           |
| Liquid permittivity, measurement uncertainty                         | E.3.3      | 5.00                  | N                             | 1       | 0.6      | 3.00           | 5        | 16.2                  |
|                                                                      |            |                       |                               |         |          |                |          | 689                   |
| <b>Probe isotropy sensitivity coefficient</b>                        | <b>0.5</b> |                       |                               |         |          |                |          |                       |
| <b>Combined Standard Uncertainty</b>                                 |            |                       |                               |         |          | <b>12.65 %</b> |          |                       |
| <b>Expanded Uncertainty, 95% confidence</b>                          |            | <b>k=</b>             | <b>2.004</b>                  |         |          | <b>25.34 %</b> |          |                       |

## 7 - SYSTEM EVALUATION

---

### 7.1 Simulated Tissue Liquid Parameter Confirmation

The dielectric parameters were checked prior to assessment using the HP85070A dielectric probe kit. The dielectric parameters measured are reported in each correspondent section:

### 7.2 Evaluation Procedures

#### Maximum Search

The maximum search is automatically performed after each coarse scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacings. After the coarse scan measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations.

#### Extrapolation

The extrapolation can be used in z-axis scans with automatic surface detection. The SAR values can be extrapolated to the inner phantom surface. The extrapolation distance is the sum of the probe sensor offset, the surface detection distance and the grid offset. The extrapolation is based on fourth order polynomial functions. The extrapolation is only available for SAR values.

#### Boundary Corrections

The correction of the probe boundary effect in the vicinity of the phantom surface can be done in two different ways. In the standard (worse case) evaluation, the boundary effect is reduced by different weights for the lowest measured points in the extrapolation routine. The result is a slight overestimation of the extrapolated SAR values (2% to 8%) depending on the SAR distribution and gradient. The advanced evaluation makes a full compensation of the boundary effect before doing the extrapolation. This is only possible of probes with specifications on the boundary effect.

#### Peak Search for 1g and 10g cube averaged SAR

The 1g and 10g peak evaluations are only available for the predefined cube 4x4x7 and cube 5x5x7 scans. The routine are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 32x32x35mm contains about 35g of tissue. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation get all points within the measured volume in a 1mm grid (35000 points). In the last step, a 1g cube is place numerically into the volume and its averaged SAR is calculated. This cube is the moved around until the highest averaged SAR is found. This last procedure is repeated for a 10g cube. If the highest SAR is found at the edge of the measured volume, the system will issue a warning,; higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

### 7.3 System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm 10\%$ . The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

IEEE P1528 recommended reference value

| Frequency (MHz) | 1 g SAR | 10 g SAR | Local SAR at surface (above feed point) | Local SAR at surface (v=2cm offset from feed point) |
|-----------------|---------|----------|-----------------------------------------|-----------------------------------------------------|
| 300             | 3.0     | 2.0      | 4.4                                     | 2.1                                                 |
| 450             | 4.9     | 3.3      | 7.2                                     | 3.2                                                 |
| 835             | 9.5     | 6.2      | 14.1                                    | 4.9                                                 |
| 900             | 10.8    | 6.9      | 16.4                                    | 5.4                                                 |
| 1450            | 29.0    | 16.0     | 50.2                                    | 6.5                                                 |
| 1800            | 38.1    | 19.8     | 69.5                                    | 6.8                                                 |
| 1900            | 39.7    | 20.5     | 72.1                                    | 6.6                                                 |
| 2000            | 41.1    | 21.1     | 74.6                                    | 6.5                                                 |
| 2450            | 52.4    | 24.0     | 104.2                                   | 7.7                                                 |
| 3000            | 63.8    | 25.7     | 140.2                                   | 9.5                                                 |

#### Validation Dipole SAR Reference Test Result for Body (450 MHz)

| Validation Measurement | SAR @ 9.225mW Input averaged over 1g | SAR @ 1W Input averaged over 1g | SAR @ 9.225mW Input averaged over 10g | SAR @ 1W Input averaged over 10g |
|------------------------|--------------------------------------|---------------------------------|---------------------------------------|----------------------------------|
| Test 1                 | 0.0451                               | 4.89                            | 0.0315                                | 3.4                              |
| Test 2                 | 0.0447                               | 4.85                            | 0.0312                                | 3.38                             |
| Test 3                 | 0.0448                               | 4.86                            | 0.0313                                | 3.39                             |
| Test 4                 | 0.0450                               | 4.88                            | 0.0313                                | 3.39                             |
| Test 5                 | 0.0451                               | 4.89                            | 0.0313                                | 3.39                             |
| Test 6                 | 0.0450                               | 4.88                            | 0.0315                                | 3.4                              |
| Test 7                 | 0.0451                               | 4.89                            | 0.0314                                | 3.4                              |
| Test 8                 | 0.0449                               | 4.87                            | 0.0312                                | 3.38                             |
| Test 9                 | 0.0449                               | 4.87                            | 0.0312                                | 3.38                             |
| Test 10                | 0.0448                               | 4.86                            | 0.0311                                | 3.37                             |
| Average                | 0.0449                               | 4.874                           | 0.0313                                | 3.388                            |

#### System validation result

Ambient Temperature (°C): 23.0

Relative Humidity (%): 49.3

| Simulant | Freq [MHz] | Parameters | Liquid Temp [°C] | Target Value | Measured Value | Deviation [%] | Limits [%] |
|----------|------------|------------|------------------|--------------|----------------|---------------|------------|
| Body     | 450        | $\epsilon$ | 22               | 56.7         | 57.8           | 1.9           | $\pm 5$    |
|          |            | $\sigma$   | 22               | 0.94         | 0.96           | 2.1           | $\pm 5$    |
|          |            | 1g SAR     | 22               | 4.874        | 5.05           | 3.6           | $\pm 10$   |
| Head     | 450        | $\epsilon$ | 22               | 43.5         | 44.1           | 1.4           | $\pm 5$    |
|          |            | $\sigma$   | 22               | 0.87         | 0.88           | 1.1           | $\pm 5$    |
|          |            | 1g SAR     | 22               | 4.9          | 4.74           | -3.3          | $\pm 10$   |

$\epsilon$  = relative permittivity,  $\sigma$  = conductivity and  $\rho=1000\text{kg/m}^3$

Note: Body Forward power = 20.5 dBm = 112.2mW

Head Forward power = 20.2 dBm = 104.7 mW

450 MHz Body Liquid System Validation (Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, Forward Power = 20.5 dBm, 6/29/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 450 MHz

Probe: ES3DV2 - SN3019; ConvF(7.30,7.30,7.30); Crest factor: 1.0; (Body liquid) 450 MHz:  $\sigma = 0.96 \text{ mho/m}$ ,  $\epsilon_r = 57.8$ ,  $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.567 mW/g, SAR (10g): 0.360 mW/g, (Worst-case extrapolation)

Coarse: Dx = 13.0, Dy = 12.0, Dz = 10.0

Powerdrift: 0.01 dB



## 450 MHz Head Liquid System Validation (Ambient Temp = 23 Deg C, Liquid Temp = 22

Deg C, Forward Power = 20.2 dBm, 6/29/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 450 MHz

Probe: ES3DV2 - SN3019; ConvF(7.40,7.40,7.40); Crest factor: 1.0; (Head liquid) 450 MHz:  $\sigma = 0.88 \text{ mho/m}$ ,  $\epsilon_r = 44.1$ ,  $\rho = 1.00 \text{ g/cm}^3$ 

Cube 5x5x7: SAR (1g): 0.496 mW/g, SAR (10g): 0.314 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 10.0

Powerdrift: -0.00 dB



## 7.4 SAR Evaluation Procedure

- a. The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For device held to the head during normal operation, both the left and right ear positions were evaluated in accordance with FCC OET Bulletin 65, Supplement C (Edition 01-01) using the SAM phantom. For body-worn and face-held devices a planar phantom was used. The EUT in the test setup for body-worn and face-held devices was placed in three different positions (relative to the phantom): with belt clip, without belt clip and 2.5cm facing left head side and 2.5cm facing right head side.
- b. The SAR was determined by a pre-defined procedure within the DASY3 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 20mm x 20mm.
- c. A 5x5x7 matrix was performed around the greatest special SAR distribution found during the area scan of the applicable exposed region. SAR values were then calculated using a 3-D spline interpolation algorithm and averaged over spatial volumes of 1 and 10 grams.
- d. The depth of the simulating tissue in the planar used for the SAR evaluation and system validation was no less than 15.0cm.
- e. For this particular evaluation, a stack of low-density, low-loss dielectric foamed polystyrene was used in place of the device holder.
- f. Re-measurement of the SAR value at the same location as in a. If the value changed by more than 5%, the evaluation was repeated.

## 7.5 Exposure Limits

Table 1: Limits for Occupational/Controlled Exposure (W/kg)

| Whole-Body | Partial-Body | Hands. Wrists. Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.4        | 8.0          | 20.0                           |

Table 2: Limits for General Population/Uncontrolled Exposure (W/kg)

| Whole-Body | Partial-Body | Hands. Wrists. Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.08       | 1.6          | 4.0                            |

*Note: Whole-body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.*

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

*Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).*

*Occupational/Controlled environments Partial-body limit 8mW/kg applied to the EUT.*

## 8 - TEST RESULTS

This page summarizes the results of the performed dosimetric evaluation. The plots with the corresponding SAR distributions, which reveal information about the location of the maximum SAR with respect to the device could be found in the following pages.

According to the data in section 8.1, the EUT complied with the FCC 2.1093 RF Exposure standards, with worst case of 2.49mW/g.

### 8.1 SAR Test Data

Ambient Temperature (°C): 23.0

Relative Humidity (%): 49.3

Worst case SAR reading

| EUT position                        | Frequency (MHz) | Output Power (W) | Test Type | Antenna Type | Liquid | Phantom | Notes / Accessories | Measured (mW/g) |                 | Limit (mW/g) | Plot # |
|-------------------------------------|-----------------|------------------|-----------|--------------|--------|---------|---------------------|-----------------|-----------------|--------------|--------|
|                                     |                 |                  |           |              |        |         |                     | 50% duty cycle  | 100% duty cycle |              |        |
| Back touching phantom               | 455             | 4.295            | Body worn | Built-in     | body   | flat    | Headset simulator   | 2.49            | 4.98            | 8            | 1      |
| Face 2.5 cm separation from phantom | 455             | 4.295            | Face-held | Built-in     | head   | flat    | None                | 2.155           | 4.31            | 8            | 2      |

### 8.2 Plots of Test Result

The plots of test result were attached as reference.

HYT Science & Technology Co., Ltd , Model: TC3000 (Body-worn , Back touch flat phantom with accessory (headset) ,Mid channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, 6/29/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 455 MHz

Probe: ES3DV2 - SN3019; ConvF(7.40,7.40,7.40); Crest factor: 1.0; 450 MHz Head liquid:  $\sigma = 0.88 \text{ mho/m}$ ,  $\epsilon_r = 44.1$ ,  $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 4.98 mW/g, SAR (10g): 3.64 mW/g, (Worst-case extrapolation)

Coarse: Dx = 16.0, Dy = 16.0, Dz = 10.0

Powerdrift: -0.01 dB



HYT Science & Technology Co., Ltd, Model: TC3000 (Face 2.5 cm separation to flat phantom , Mid channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, 6/29/2004)


SAM Phantom; Flat Section; Position: (90°,90°); Frequency: 455 MHz

Probe: ES3DV2 - SN3019; ConvF(7.30,7.30,7.30); Crest factor: 1.0; 450 MHz body liquid:  $\sigma = 0.96 \text{ mho/m}$   $\epsilon_r = 57.8$   $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 4.31 mW/g, SAR (10g): 3.17 mW/g, (Worst-case extrapolation)

Coarse: Dx = 16.0, Dy = 16.0, Dz = 10.0

Powerdrift: -0.01 dB



## EXHIBIT A - SAR SETUP PHOTOGRAPHS

### Body-Worn with Belt Clip & Headset in Touching with Phantom



### 2.5cm Separation to Flat Phantom




**EXHIBIT B - EUT PHOTOGRAPHS**


---

**EUT – Front View****EUT – Rear View**

**EUT – Top View****Antenna View**


**EUT – Board and Housing View****Charger View**



### Adapter View







### Headset Simulator




**TC3000-1 Cover off View****TC3000-1 Board View 1**

**TC3000-1 Board View 2****TC3000-1 Board View 3**

**TC3000-2 Board View 1****TC3000-2 Board View 2**

**TC3000-2 Board View 3****TC3000-2 Board View 4**

**TC3000-2 Board View 5**

## EXHIBIT C – Z-Axis

HYT Science & Technology Co., Ltd , Model: TC3000 (Body-worn , Back touch flat phantom with accessory (headset) , Mid channel, Ambient Temp = 23 Deg C, Liquid Temp = 22 Deg C, 6/29/2004)

SAM Phantom; Section; Position: ; Frequency: 455 MHz

Probe: ES3DV2 - SN3019; ConvF(7.40,7.40,7.40); Crest factor: 1.0; 450 MHz Head liquid:  $\sigma = 0.88 \text{ mho/m}$   $\epsilon_r = 44.1$   $\rho = 1.00 \text{ g/cm}^3$

: , 0

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 2.0

