

# MPE TEST RESULT

Equipment Under Test: Mobile Radio

Model No.: TM-610U1

Date of Test(s): 2006-11-11

Standards: FCC 47CFR 2.1091(b)

**Tested by : Army**

The details of the testing results carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

TABLE OF CONTENTS

1. Description..... 3

2. Antenna Information..... 3

3. Test site..... 3

4. Measurement System.....3

5. Measurement Uncertainty.....4

6. Method of measurement.....4

7. Test result..... 6

8. Conclusion.....9

## 1. Description

HYT'S TM-610U1 mobile radio are Compatible, Conventional radio system operation. The operation and functions for the TM-610U1 Series radios are described in this manual. TM-610U1 has a compact size with a various features in range of 400 MHz ~ 470 MHz. TM-610U1 has a various features shown as below.

- Wideband frequency separation, Programmable output power
- Programmable 12.5 / 25 kHz channel spacing
- Programmable On / Off hook function, Talk Around
- Scanning, Priority Scanning
- Look Back, Scan list editing
- CTCSS / CDDCS (Conventional operation), Busy channel lockout
- Time-out timer

## 2. Antenna Information

Whip Antenna for vehicle : 400 ~ 470 MHz, 1/4 wave 3 dBi antenna gain

## 3. Test site

Accurate Technology Co. Ltd.

F1, Bldg, A, Changyuan New Meterial Port, Keyuan Rd. Science & Industry Park, Nanshan District, 518057, Shenzhen P.R. China.

## 4. Measurement System

- Automobile: Hyundai Verna(2000)
  - E-Field Survey Meter & Probe - NARDA Model EMC 20 (100kHz~3GHz)
- Calibration due date: 2007-5-4
- Antennas - (1/4 wave 3 dBi)

## 5. Measurement Uncertainty

The information below presents an estimate of the possible errors that are associated with the measurement system.

Description	Error
NARDA Survey Meter:	± 4%
Repeatability Accuracy:	± 7%

## **6. Method of measurement**

### **6.1 MPE measurements made on trunk mounted antennas**

#### **6.1.1 External vehicle MPE measurement**

(Antenna mounted in trunk center)

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 60 cm to the antenna, from the back of the vehicle in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters.

#### **6.1.2 Internal vehicle MPE measurement**

(Antenna mounted in trunk center)

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

### **6.2 MPE measurements made on center roof mounted antennas**

#### **6.2.1 External vehicle MPE measurement**

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 60 cm from the vehicle-mounted antenna, in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters; this would be representative of a person standing next to a vehicle during a mobile radio transmission.

#### **6.2.2 Internal vehicle MPE measurement**

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

### **6.3 Presentation of Result**

**Average Over Body = The average value of all the measurement points ( Expressed in Percentage of the controlled limits)**

**Power Density= The maximum value of all the measure points / 2 ( The Duty Cycle of 50% was considered by deviding the maximum value by 2 and Expressed in mW/ cm<sup>2</sup>)**

## 7. Test result

Measurement Information			
Measurement Freq.(MHz)	400.15	435.15	469.85
Raw Data Power(W)	24.49	24.10	23.99
Controlled Limit	1.33	1.45	1.56
Uncontrolled Limit	0.26	0.29	0.31
Cal. Factor	1	1	1
Antenna / gain(dBi)	Whip / 3	Whip / 3	Whip / 3
External Vehicle Power Density (50% Duty)	Average over body/2		
Internal Vehicle Power Density(50% Duty)	Average over (head/chest/leg)/2		

External Vehicle MPE Assessment At 400.15 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Power. Density (mW/cm <sup>2</sup> )
Trunk	Whip/3	60	E	1	11.4 % of Controlled Limit	15% / 2 = 0.0998 mW/cm <sup>2</sup>
Measurement Grid						
Test Position	Height	% of controlled Limit	Test Position	Height (cm)	% of controlled limit	
1	20	9	6	120	10	
2	40	9	7	140	11	
3	60	9	8	160	10	
4	80	13	9	180	14	
5	100	14	10	200	15	

External Vehicle MPE Assessment At 435.15 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Power. Density (mW/cm <sup>2</sup> )
Trunk	Whip/3	60	E	1	14.1 % of Controlled Limit	19 % / 2 = 0.138 mW/cm <sup>2</sup>
Measurement Grid						
Test Position	Height	% of controlled Limit	Test Position	Height (cm)	% of controlled limit	
1	20	11	6	120	12	
2	40	11	7	140	13	
3	60	10	8	160	15	
4	80	15	9	180	18	
5	100	17	10	200	19	

External Vehicle MPE Assessment At 469.85 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Power. Density (mW/cm <sup>2</sup> )
Trunk	Whip/3	60	E	1	13.3 % of Controlled Limit	18% / 2 = 0.14mW/cm <sup>2</sup>
Measurement Grid						
Test Position	Height	% of controlled Limit	Test Position	Height (cm)	% of controlled limit	
1	20	12	6	120	12	
2	40	11	7	140	13	
3	60	11	8	160	11	
4	80	15	9	180	14	
5	100	18	10	200	16	

External Vehicle MPE Assessment At 400.15 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Power. Density (mW/cm <sup>2</sup> )
Roof	Whip/3	60	E	1	6.4% of Controlled Limit	9% / 2 = 0.06 mW/cm <sup>2</sup>
Measurement Grid						
Test Position	Height	% of controlled Limit	Test Position	Height (cm)	% of controlled limit	
1	20	5	6	120	8	
2	40	7	7	140	7	
3	60	8	8	160	9	
4	80	4	9	180	5	
5	100	6	10	200	5	

Internal Vehicle MPE Assessment At 400.15 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Head, Chest, Leg Back / Front Seats(mW/cm <sup>2</sup> )	Power Density HigherLevel (mW/cm <sup>2</sup> )
Trunk	Whip/3	Highest Reading	E	1	15.7 % of Controlled Limit = 0.209 mW/cm <sup>2</sup>	28% / 2= 0.186mW/cm <sup>2</sup>
Measurement Grid						
Test Position	% of controlled Limit Head		% of controlled Limit Chest		% of controlled Limit Leg	
Front	12		11		7	
Back	28		22		14	

Internal Vehicle MPE Assessment At 435.15 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Head, Chest, Leg Back / Front Seats(mW/cm <sup>2</sup> )	Power Density HigherLevel (mW/cm <sup>2</sup> )
Trunk	Whip/3	Highest Reading	E	1	15.83 % of Controlled Limit = 0.23 mW/cm <sup>2</sup>	26% / 2 = 0.189mW/cm <sup>2</sup>
Measurement Grid						
Test Position	% of controlled Limit Head		% of controlled Limit Chest		% of controlled Limit Leg	
Front	12		11		9	
Back	26		24		13	

Internal Vehicle MPE Assessment At 469.85 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Head, Chest, Leg Back / Front Seats(mW/cm <sup>2</sup> )	Power Density HigherLevel (mW/cm <sup>2</sup> )
Trunk	Whip/3	Highest Reading	E	1	14.5 % of Controlled Limit = 0.226 mW/cm <sup>2</sup>	25 % / 2 = 0.195mW/cm <sup>2</sup>
Measurement Grid						
Test Position	% of controlled Limit Head		% of controlled Limit Chest		% of controlled Limit Leg	
Front	11		9		8	
Back	25		21		13	

Internal Vehicle MPE Assessment At 400.15 MHz						
Antenna Location	Antenna / Gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Head, Chest, Leg Back / Front Seats(mW/cm <sup>2</sup> )	Power Density HigherLevel (mW/cm <sup>2</sup> )
Roof	Whip/3	Highest Reading	E	1	6.2 % of Controlled Limit = 0.082 mW/cm <sup>2</sup>	12% / 2 = 0.08 mW/cm <sup>2</sup>
Measurement Grid						
Test Position	% of controlled Limit Head		% of controlled Limit Chest		% of controlled Limit Leg	
Front	8		4		3	
Back	12		6		4	

## 8. Conclusion

The measurement results complies with the FCC Limit Per 47 CFR 2.1091 (b) for the Uncontrolled RF Exposure.