

## **Certification Exhibit**

FCC ID: R7PEC6R1S1 IC: 5294A-EC6R1S1

### FCC Rule Part: 15.247 IC Radio Standards Specification: RSS-210

ACS Project Number: 13-0144

Manufacturer: Landis+Gyr Technology Inc. Model: GPR

# **RF Exposure**

#### **General Information:**

| Applicant:       | Landis+Gyr Technology Inc.               |
|------------------|--|
| Device Category: | Mobile                                   |
| Environment:     | General Population/Uncontrolled Exposure |

#### Technical Information:

Antenna Type: F-type antenna Antenna Gain: 2dBi gain Maximum Transmitter Conducted Power: 25.03 dBm, 318.42 mW Maximum System EIRP: 27.03 dBm, 504.66 mW Exposure Conditions: Greater than 20 centimeters

#### MPE Calculation

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

| MPE Calculator for Mobile Equipment                  |       |               |        |         |          |                  |           |  |  |
|--|-------|---------------|--------|---------|----------|------------------|-----------|--|--|
| Limits for General Population/Uncontrolled Exposure* |       |               |        |         |          |                  |           |  |  |
| Transmit   | Radio | Power         | Radio  | Antenna | Antenna  | Distance<br>(cm) | Power     |  |  |
| Frequency  | Power | Density Limit | Power  | Gain    | Gain     |                  | Density   |  |  |
| (MHz)  | (dBm) | (mW/Cm2)      | (mW)   | (dBi)   | (mW eq.) | (em)             | (mW/cm^2) |  |  |
| 927.9  | 25.03 | 0.62          | 318.42 | 2       | 1.585    | 20               | 0.100     |  |  |

#### Installation Guidelines

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

#### RF Exposure

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

#### **Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.