

Certification Test Report

FCC ID: R7PEC6R1S2

IC: 5294A-EC6R1S2

FCC Rule Part: 15.247

IC Radio Standards Specification: RSS-210

ACS Report Number: 15-0028.W04.1A

Manufacturer: Landis+Gyr Technology, Inc.

Model: Gridstream RF Enhanced A3

Test Begin Date: January 22, 2015

Test End Date: January 22, 2015

Report Issue Date: February 12, 2015



FOR THE SCOPE OF ACCREDITATION UNDER LAB Code 200612-0

This report is not be used to claim certification, approval, or endorsement by NVLAP, NIST or any government agency.

Reviewed by: 

Kirby Munroe
Director, Wireless Certifications
ACS, Inc.

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

This report contains 13 pages

TABLE OF CONTENTS

1	GENERAL	3
1.1	PURPOSE.....	3
1.2	PRODUCT DESCRIPTION	3
1.3	TEST METHODOLOGY AND CONSIDERATIONS.....	4
2	TEST FACILITIES.....	5
2.1	LOCATION	5
2.2	LABORATORY ACCREDITATIONS/RECOGNITIONS/CERTIFICATIONS.....	5
2.3	RADIATED EMISSIONS TEST SITE DESCRIPTION.....	6
2.3.1	<i>Semi-Anechoic Chamber Test Site</i>	6
2.3.2	<i>Open Area Tests Site (OATS)</i>	7
2.4	CONDUCTED EMISSIONS TEST SITE DESCRIPTION	8
3	APPLICABLE STANDARD REFERENCES	8
4	LIST OF TEST EQUIPMENT.....	9
5	SUPPORT EQUIPMENT.....	10
6	EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM	10
7	SUMMARY OF TESTS.....	11
7.1	ANTENNA REQUIREMENT – FCC: SECTION 15.203.....	11
7.2	RADIATED SPURIOUS EMISSIONS - FCC 15.205, 15.209; IC RSS-210 2.2, RSS-GEN 8.9/8.10.....	11
7.2.1	<i>Measurement Procedure</i>	11
7.2.2	<i>Measurement Results</i>	11
7.2.3	<i>Sample Calculation:</i>	12
8	CONCLUSION	13

1 GENERAL

1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-210 for a class II permissive change.

The purpose of this Class II Permissive Change is to add a new antenna type/host combination to the 900 MHz LAN frequency-hopping spread spectrum radio.

1.2 Product description

The Gridstream RF Enhanced A3 is an electronic endpoint module that will be integrated into the Elster A2 C&I meter. This device contains two separate radios on a single PCB: a 900 MHz ISM band frequency-hopping spread spectrum (FHSS) transceiver and a 2.4 MHz ISM band transceiver employing 802.15.4/Zigbee.

The Gridstream RF Enhanced A3 is a composite device. The 900 MHz LAN radio and the 2.4 GHz Zigbee radio operate under CFR 47 Part 15.247 and IC RSS-210. This report addresses the addition of the new antenna to the 900 MHz LAN radio only.

Technical Details:

The Gridstream RF Enhanced A3 provides 3 distinct frequency hopping modes of operation as outlined below.

Mode of Operation	Frequency Range (MHz)	Number of Channels	Channel Separation (kHz)	Data Rates Supported (kbps)
1	902.3 - 927.8	86	300	9.6, 19.2, 38.4, 115.2
2	904.0 - 927.9	240	100	9.6, 19.2, 38.4
3	902.2 – 927.8	129	200	50.0

Modulation Format: FSK/GFSK
 Antenna Type/Gain: PCB Inverted F (Module), +1dBi
 Antenna Type/Gain: Patch Antenna (External Adhesive Patch Coupler) – New to C2PC
 Antenna/Type/Gain: Omni Whip Antenna, 5.5 dBi gain (External) – New to C2PC
 Operating Voltage: 4VDC (Host 120VAC)

Manufacturer Information:
 Landis+Gyr Technology, Inc.
 30000 Mill Creek Ave., Suite 100
 Alpharetta, GA 30022

EUT Serial Numbers: 810C0004

Test Sample Condition: The test samples were provided in good working order with no visible defects.

1.3 Test Methodology and Considerations

The antenna included in this filing is connected to the EUT host via an adhesive patch antenna. The intention of the patch antenna is to couple to the EUT 900 MHz LAN antenna over-the-air. The coupled signal is then to be routed, via coax, to the antenna described in this filing. The Gridstream RF Enhanced A3 module was integrated into a representative host for showing compliance with the new antenna configuration.

Software power setting during test: 138

2 TEST FACILITIES

2.1 Location

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions
5015 B.U. Bowman Drive
Buford, GA 30518
Phone: (770) 831-8048
Fax: (770) 831-8598

2.2 Laboratory Accreditations/Recognitions/Certifications

ACS is accredited to ISO/IEC 17025 by the National Institute of Standards and Technology under their National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 200612-0. Unless otherwise specified, all tests methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

The Semi-Anechoic Chamber Test Site, Open Area Test Site (OATS) and Conducted Emissions Site have been fully described, submitted to, and accepted by the FCC, Industry Canada and the Japanese Voluntary Control Council for Interference by information technology equipment.

FCC Registration Number: 511277

Industry Canada Lab Code: IC 4175A

VCCI Member Number: 1831

- VCCI OATS Registration Number R-1526
- VCCI Conducted Emissions Site Registration Number: C-1608

2.3 Radiated Emissions Test Site Description

2.3.1 Semi-Anechoic Chamber Test Site

The Semi-Anechoic Chamber Test Site consists of a 20' x 30' x 18' shielded enclosure. The chamber is lined with Toyo Ferrite Grid Absorber, model number FFG-1000. The ferrite tile grid is 101 x 101 x 19mm thick and weighs approximately 550 grams. These tiles are mounted on steel panels and installed directly on the inner walls of the chamber.

The turntable is 150cm in diameter and is located 160cm from the back wall of the chamber. The chamber is grounded via 1 – 8' copper ground rod, installed at the center of the back wall, it is bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is all steel, flush mounted table installed in an all steel frame. The table is remotely operated from inside the control room located 25' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Behind the turntable is a 3' x 6' x 4' deep shielded pit used for support equipment if necessary. The pit is equipped with 1 – 4" PVC chases from the turntable to the pit that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit.

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3-1 below:




Figure 2.3-1: Semi-Anechoic Chamber Test Site

2.3.2 Open Area Tests Site (OATS)

The open area test site consists of a 40' x 66' concrete pad covered with a perforated electro-plated galvanized sheet metal. The perforations in the sheet metal are 1/8" holes that are staggered every 3/16". The individual sheets are placed to overlap each other by 1/4" and are riveted together to provide a continuous seam. Rivets are spaced every 3" in a 3 x 20 meter perimeter around the antenna mast and EUT area. Rivets in the remaining area are spaced as necessary to properly secure the ground plane and maintain the electrical continuity.

The entire ground plane extends 12' beyond the turntable edge and 16' beyond the antenna mast when set to a 10 meter measurement distance. The ground plane is grounded via 4 – 8' copper ground rods, each installed at a corner of the ground plane and bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is an all aluminum 10' flush mounted table installed in an all aluminum frame. The table is remotely operated from inside the control room located 40' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Adjacent to the turntable is a 7' x 7' square and 4' deep concrete pit used for support equipment if necessary. The pit is equipped with 5 – 4" PVC chases from the pit to the control room that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit. The pit is covered with 2 sheets of 1/4" diamond style re-enforced steel sheets. The sheets are painted to match the perforated steel ground plane; however the underside edges have been masked off to maintain the electrical continuity of the ground plane. All reflecting objects are located outside of the ellipse defined in ANSI C63.4.

A diagram of the Open Area Test Site is shown in Figure 2.3-2 below:




Figure 2.3-2: Open Area Test Site

2.4 Conducted Emissions Test Site Description

The AC mains conducted EMI site is located in the main EMC lab. It consists of an 8' x 8' solid aluminum horizontal ground reference plane (GRP) bonded every 3" to an 8' X 8' vertical ground plane.

The site is of sufficient size to test table top and floor standing equipment in accordance with section 6.1.4 of ANSI C63.4.

A diagram of the room is shown below in figure 2.4-1:




Figure 2.4-1: AC Mains Conducted EMI Site

3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2015
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2015
- ❖ Industry Canada Radio Standards Specification: RSS-210 – Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Issue 8, December 2010
- ❖ Industry Canada Radio Standards Specification: RSS-GEN – General Requirements for Compliance of Radio Apparatus, Issue 4, Nov 2014.

4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

Table 4-1: Test Equipment

AssetID	Manufacturer	Model #	Equipment Type	Serial #	Last Calibration Date	Calibration Due Date
1	Rohde & Schwarz	ESMI - Display	Spectrum Analyzers	833771/007	7/11/2014	7/11/2015
2	Rohde & Schwarz	ESMI-Receiver	Spectrum Analyzers	839587/003	7/11/2014	7/11/2015
30	Spectrum Technologies	DRH-0118	Antennas	970102	4/23/2013	4/23/2015
40	EMCO	3104	Antennas	3211	2/14/2013	2/14/2015
73	Agilent	8447D	Amplifiers	2727A05624	7/15/2014	7/15/2015
167	ACS	Chamber EMI Cable Set	Cable Set	167	10/28/2014	10/28/2015
292	Florida RF Cables	SMR-290AW-480.0-SMR	Cables	None	3/17/2014	3/17/2015
337	Microwave Circuits	H1G513G1	Filters	282706	6/2/2014	6/2/2015
338	Hewlett Packard	8449B	Amplifiers	3008A01111	7/30/2013	7/30/2015
412	Electro Metrics	LPA-25	Antennas	1241	7/24/2014	7/24/2016
422	Florida RF	SMS-200AW-72.0-SMR	Cables	805	11/5/2014	11/5/2015
616	Florida RF Cables	SMRE-200W-12.0-SMRE	Cables	N/A	9/10/2014	9/10/2015

5 SUPPORT EQUIPMENT

Table 5-1: Support Equipment

Item	Equipment Type	Manufacturer	Model Number	Serial Number
1	FM 3S Electric Utility Meter	Elster	CL20	TRG014979657
2	DC Power Supply	Hewlett Packard	E3630A	KR64308603

6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM




Figure 6-1: Test Setup Block Diagram

7 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

7.1 Antenna Requirement – FCC: Section 15.203

The external antenna is connected to the EUT via an adhesive coupling patch antenna. Professional installation is utilized. The antenna is an omni-directional whip antenna with a maximum gain of +5.5 dBi.

7.2 Radiated Spurious Emissions - FCC 15.205, 15.209; IC RSS-210 2.2, RSS-Gen 8.9/8.10

7.2.1 Measurement Procedure

Radiated emissions tests were made over the frequency range of 30MHz to 10GHz, 10 times the highest fundamental frequency.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000MHz, peak and average measurements were made with RBW and VBW of 1 MHz and 3MHz respectively.

The EUT was caused to generate a continuous modulated carrier on the hopping channel.

Each emission found to be in a restricted band was compared to the applicable radiated emission limits.

7.2.2 Measurement Results

Radiated spurious emissions found in the band of 30MHz to 10GHz are reported in the Table 7.2.2-1 below.

Table 7.2.2-1: Radiated Spurious Emissions Tabulated Data

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
2706.3	50.14	43.21	H	-4.44	45.70	38.77	74.0	54.0	28.3	15.2
2706.3	51.36	45.88	V	-4.44	46.92	41.44	74.0	54.0	27.1	12.6
3608.4	49.35	40.75	H	-1.16	48.19	39.59	74.0	54.0	25.8	14.4
3608.4	48.41	38.33	V	-1.16	47.25	37.17	74.0	54.0	26.7	16.8
4510.5	48.58	39.40	H	0.97	49.55	40.37	74.0	54.0	24.5	13.6
4510.5	49.16	40.42	V	0.97	50.13	41.39	74.0	54.0	23.9	12.6
5412.6	48.16	42.14	H	3.47	51.63	45.61	74.0	54.0	22.4	8.4
5412.6	49.27	43.11	V	3.47	52.74	46.58	74.0	54.0	21.3	7.4
8118.9	47.05	37.06	H	7.80	54.85	44.86	74.0	54.0	19.1	9.1
8118.9	46.45	36.35	V	7.80	54.25	44.15	74.0	54.0	19.7	9.8
Middle Channel										
2745	50.63	44.17	H	-4.30	46.33	39.87	74.0	54.0	27.7	14.1
2745	50.13	43.29	V	-4.30	45.83	38.99	74.0	54.0	28.2	15.0
3660	47.12	36.73	H	-0.97	46.15	35.76	74.0	54.0	27.9	18.2
8235	46.45	36.78	H	7.87	54.32	44.65	74.0	54.0	19.7	9.4
8235	46.18	36.43	V	7.87	54.05	44.30	74.0	54.0	20.0	9.7
High Channel										
960.05		35.63	H	2.00	-----	37.63	-----	54.0	-----	16.4
960.05		39.48	V	2.00	-----	41.48	-----	54.0	-----	12.5
2783.7	51.44	46.38	H	-4.16	47.28	42.22	74.0	54.0	26.7	11.8
2783.7	53.36	49.38	V	-4.16	49.20	45.22	74.0	54.0	24.8	8.8

7.2.3 Sample Calculation:

$$R_C = R_U + CF_T$$

Where:

- CF_T = Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)
 R_U = Uncorrected Reading
 R_C = Corrected Level
 AF = Antenna Factor
 CA = Cable Attenuation
 AG = Amplifier Gain
 DC = Duty Cycle Correction Factor

Example Calculation: Peak

Corrected Level: $50.14 - 4.44 = 45.70\text{dBuV/m}$
 Margin: $74\text{dBuV/m} - 45.70\text{dBuV/m} = 28.3\text{dB}$

Example Calculation: Average

Corrected Level: $43.21 - 4.44 - 0 = 38.77\text{dBuV}$
 Margin: $54\text{dBuV} - 38.77\text{dBuV} = 15.2\text{dB}$

8 CONCLUSION

In the opinion of ACS, Inc. the Gridstream RF Enhanced A3, manufactured by Landis+Gyr Technology, Inc. meets the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-210.

END REPORT