

Certification Exhibit

FCC ID: R7PNG6R2S4 IC: 5294A-NG6R2S4

FCC Rule Part: 15.247 IC Radio Standards Specification: RSS-210

ACS Project Number: 11-0448

Manufacturer: Cellnet Technology, Inc. Model: Mesh Extender R240

RF Exposure

General Information:

Applicant:	Cellnet Technologies Inc.
Device Category:	Mobile
Environment:	General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Omni-directional collinear whip antenna Antenna Gain: +5.5 dBi Maximum Transmitter Conducted Power: 29.81 dBm, 957.2 mW Maximum System EIRP: 35.31 dBm, 3.396 W Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*								
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)	
927.9	29.81	0.62	957.19	5.5	3.548	22	0.558	

Installation Guidelines

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

RF Exposure

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 22 centimeters will be maintained.

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.