



Certification Exhibit

FCC ID: R7PS5WNODE

FCC Rule Part: 47 CFR Part 2.1091

Project Number: 72157009

Manufacturer: Landis+Gyr Technology, Inc.
Model: Water 520 Mi.Node/IP

RF Exposure

General Information:

Applicant: Landis+Gyr Technology, Inc.
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Wire Antenna
 Antenna Gain: 0.0dBi
 Maximum Transmitter Conducted Power: 27.80dBm, 602.56mW
 Maximum System EIRP: 27.80dBm, 602.56mW
 Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm²)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: MPE Calculation

Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/cm ²)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm ²)
902.2	27.8	0.60	602.56	0	1.000	20	0.1199