

# **FCC Part 15 Subpart C Transmitter Certification**

**Direct Sequence Spread Spectrum Transmitter**

## **Test Report**

**FCC ID: R7PUWE-PIT**

**FCC Rule Part: 15.247**

**ACS Report Number: 05-0412 - 15C**

Manufacturer: Cellnet Technology, Inc.  
Model: Cellnet Water Endpoint – Pit

## **RF Exposure Information**

**General Information:**

Applicant: Cellnet  
 ACS Project: 05-0412  
 FCC ID: R7PUWE-PIT  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information:**

Antenna Type: External Patch  
 Antenna Gain: 2.5 dBi  
 Transmitter Conducted Power: 24.16dBm  
 Maximum System EIRP: 26.66dBm  
 Operating Configuration: Fixed mounted  
 Exposure Conditions: Greater than 20 centimeters

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm2)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

<b>MPE Calculator for Mobile Equipment</b>							
<b>Limits for General Population/Uncontrolled Exposure*</b>							
<b>Transmit Frequency (MHz)</b>	<b>Radio Power (dBm)</b>	<b>Power Density Limit (mW/Cm2)</b>	<b>Radio Power (mW)</b>	<b>Antenna Gain (dBi)</b>	<b>Antenna Gain (mW eq.)</b>	<b>Distance (cm)</b>	<b>Power Density (mW/cm^2)</b>
917.58	24.16	0.61	260.62	2.5	1.778	20	0.092

**Installation Guidelines**

The installation manual contains the following text advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**“RF Exposure (Intentional Radiators Only)**

In accordance with FCC requirements of human exposure to radiofrequency fields, the radiating element shall be installed such that a minimum separation distance of 20cm is maintained from the general population.”

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.