

**FCC ID: R7TF162000010**

Issue date: 2005-05-23



**Test Report**  
**acc. to the relevant standard:**  
**47 CFR Part 15 C – Intentional Radiators**  
**Measurement Procedure:**  
**ANSI C63.4 - 1992**  
**relating to**  
**AMBER wireless GmbH**  
**F16200000 / 01**  
**(Transceivermodule)**

**Measurement of Radio- Noise Emissions**  
**from Low- Voltage Electrical and Electronic Equipment**  
**Technical characteristics and test methods for radio equipment**  
**in the frequency range 9 kHz to 40 GHz**

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

<b>Manufacturer's details</b>	
Manufacturer	AMBER wireless GmbH
Manufacturer's grantee code	R7T
Manufacturer's address	AMBER wireless GmbH
	Albin-Köbis-Straße 18
	D-51147 Köln
	Germany
	Tel.: +49 2203 6991950
	Fax : +49 2203 459883
	E-mail: <a href="mailto:wolfgang.esch@amber-wireless.de">wolfgang.esch@amber-wireless.de</a>
Relevant standard used	47 CFR Part 15C - Intentional Radiators
	ANSI C63.4-1992

<b>Test Report prepared by</b>	
Technical engineer	Ralf Trepper
	m.dudde hochfrequenz-technik (Labor)
	Rottland 5a
	D-51429 Bergisch Gladbach
	Germany
	Phone: +49 2207 96890
	Fax : +49 2207 968920
	E-mail: <a href="mailto:m.duddelabor@t-online.de">m.duddelabor@t-online.de</a>

<b>Equipment Under Test (EUT)</b>	
Equipment category	Transceiver module
Trade name	KaVo
Type designation	F16200000 / 01
Serial no.	---
Testing Variants	KaVo Radio Master
	KaVo Radio Slave

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**0 Test result**

CFR Section	Report Chapter	Requirements Headline	Test result		
			OK		
15.203	10.1	Antenna requirement	pass	<del>fail</del>	<del>na</del>
15.249 (a)	10.2	Field strength limits (fundamental)	pass	<del>fail</del>	<del>na</del>
15.249(d) 15.209	10.2	Radiated spurious emissions	pass	<del>fail</del>	<del>na</del>
15.207	10.3	Conducted emissions	pass	<del>fail</del>	<del>na</del>
15.215 (c)	10.4	20 dB bandwidth	pass	<del>fail</del>	<del>na</del>

Test requirements kept	yes	no

Signature test personnel



.....  
 Ralf Trepper

Signature of the company official



.....  
 Manfred Dudde

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

<b>List of contents</b>	<b>Page</b>
0 <b>Test result</b> .....	3
1 <b>Testing laboratory</b> .....	5
2 <b>Introduction</b> .....	5
3 <b>Product</b> .....	6
4 <b>Test schedule</b> .....	6
5 <b>Product and measurement documentation</b> .....	7
6 <b>Observations and comments</b> .....	7
7 <b>Summary</b> .....	7
8 <b>Conclusions</b> .....	8
9 <b>Operation description</b> .....	9
10.1 <b>Antenna requirement</b> .....	10
10.1.1 Regulation.....	10
10.1.2 Result.....	10
10.2 <b>Radiated emissions</b> .....	11
10.2.1 Regulation.....	11
10.2.2 Test equipment.....	13
10.2.2 Test procedures.....	13
10.2.3 Calculation of field strength Section 15.209 below 30 MHz.....	14
10.2.3 Calculation of field strength Section 15.209 above 30 MHz.....	14
10.2.4 Calculation of average correction factor.....	14
10.2.5 Calculation of the field strength Section 15.249.....	15
10.2.6 Result.....	16
10.3 <b>Conducted emissions</b> .....	24
10.3.1 Regulation.....	24
10.3.2 Test equipment.....	25
10.3.3 Test procedures.....	25
10.3.4 Test results.....	26
10.4 <b>Banwidth</b> .....	28
10.4.1 Regulation.....	28
10.4.2 Calculation of the 20 dB bandwidth limit.....	28
10.4.3 Test equipment.....	28
10.4.4 Test procedure.....	28
10.4.5 Test result.....	29
11 <b>Additional information to this test report</b> .....	30

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 1 Testing laboratory

Company name: m.dudde hochfrequenz-technik  
Street: Rottland 5a  
City: 51429 Bergisch Gladbach  
Country: Germany

Laboratory:

FCC Registration Number: 699717

This site has been fully described in a report submitted to the FCC, and  
accepted with letter dated

Registration Number .699717

Phone: +49-2207-9689-0  
Fax: +49-2207-9689-20  
E-mail: manfred.dudde@t-online.de  
Web: http://www.dudde.com

## 2 Introduction

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of m. dudde hochfrequenz - technik.

This report contains the result of tests performed by m. dudde hochfrequenz - technik for the purpose of a type approval. The order for carrying out these tests had been placed by:

### Manufacturer

Company name : AMBER wireless GmbH  
Address : Albin-Köbis-Straße 18  
Postcode : D 51147  
City/town : Köln  
Country : Germany  
Telephone : +49 2203 6991950  
Telefax : +49 2203 459883  
E-mail : [wolfgang.esch@amber-wireless.de](mailto:wolfgang.esch@amber-wireless.de)  
Date of order : 2005-02-08  
References : Mr. Wolfgang Esch

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

### 3 Product

Samples of the following apparatus were submitted for testing:

Type of equipment	: Transceiver module
Trademark	: KaVo
Type designation	: F16200000 / 01
Hardware version	: KaVo Radio Master / Slave
Serial number	: ---
Software release	: ---
Power used	: KaVo Radio Master: 110 VAC \ 50 60Hz, KaVo Radio Slave: 3.0 VDC
Frequency used	: 2.402 GHz to 2.410 GHz
Generated or used frequencies	: 6 MHz, 16 MHz
<b>FCC ID</b>	<b>: R7TF16200010</b>

### 4 Test schedule

Tests were carried out in accordance with the specifications detailed in chapter 7 “Summary“ of this report.

Tests were carried out at:

**- m. dudde hochfrequenz - technik, D-51429 Bergisch Gladbach**

The test sample was received on:

**- 2004-05-18**

The tests were carried out in the following period of time:

**- 2005-05-18 - 2005-05-22**

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 5 Product and measurement documentation

For issuing this report the following product documentation was used and the following annexes were created:

<b>Description:</b>	<b>Date:</b>	<b>Identifications:</b>
External photographs of the Equipment Under Test (EUT)		Annex no. 1
Internal photographs of the Equipment Under Test (EUT)		Annex no. 2
Occupied bandwidth plot		Annex no. 3
FCC ID label sample		Annex no. 4
Technical description		Annex no. 5
Test setup photos		Annex no. 6
Block diagram		Annex no. 7
Schematics		Annex no. 8

The above-mentioned documentation will be filed at m. dudde hochfrequenz - technik for a period of 10 years following the issue of this report.

## 6 Observations and comments

### **Additional equipment for all tests to carry on the KaVo Radio Master / Slave:**

**Sony Notebook,  
Type: PCG-F 807 K  
Serial No.: 1141611**

## 7 Summary

The product is intended for use in the following areas of application:  
Radio- Noise Emissions from Low- Voltage Electrical and Electronic Equipment  
in the frequency range 9 kHz to 40 GHz

The samples were tested according to the following specification:

47 CFR Part 15 – Intentional Radiators, ANSI C63.4 - 1992

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 8 Conclusions

Samples of the apparatus were found to **CONFORM WITH** the specifications stated in chapter 7 "Summary" of this report.

In the opinion of m. dudde hochfrequenz - technik, the samples satisfied all applicable requirements relating to the network interface types specified in chapter 7 "Summary".

The results of the type tests as stated in this report are exclusively applicable to the product item as identified in this report. m. dudde hochfrequenz - technik does not accept any responsibility for the results stated in this report, with respect to the properties of product items not involved in these tests.

This report consists of a main module, modules with test results and annexes listed in chapter 5: "Product documentation". All pages have been numbered consecutively and bear the m. dudde hochfrequenz - technik logo, the report number and sub numbers.  
The total number of pages in this report is **31**.

### Tester:

Date : 2005-05-23

Name : Ralf Trepper

Signature : 

### Technical responsibility for area of testing:

Date : 2005-05-23

Name : Manfred Dudde

Signature : 



---

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 9 Operation description

### 9.1 EUT details

The transceiver module KaVo Radio Slave will be used in order to establish a wireless radio connection between a computer and the video-system KaVo Radio Master. Further technical details are indicated in Annex no. 5 (technical description / user's manual).

### 9.2 EUT configuration

In order to initiate a radio transmission, the KaVo Radio Slave has to be connected to the serial port of a computer, and the device KaVo Radio Master has to be supplied with mains voltage. With the appropriate software there will be established a communication path.

### 9.3 EUT measurement description

#### **Radiated emission test**

The transceiver module F16200000 / 01 is inserted both in the KaVo Radio Slave and in the KaVo Radio Master and it is technically identical. Both devices will be tested. In order to establish the maximum radiation, firstly, there have been viewed all orthogonal adjustments of the test samples, secondly the test samples have been rotated at all adjustments around the own axis between 0° and 360°, and thirdly, the antenna polarization between horizontal and vertical had been varied.

#### **Conducted emission test**

The device KaVo Radio Master was connected directly with its supply mains to an artificial mains network. With a test receiver there have been viewed both L1 and N.

The KaVo Radio Slave was connected to a Sony Notebook and this to the artificial mains network. It has been tested in two runs: with inactive KaVo Radio Slave and with activated KaVo Radio Slave. L1 and N had been viewed too.

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 10.1 Antenna requirement

### 10.1.1 Regulation

15.203 An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31 (d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

### 10.1.2 Result

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	<del>yes</del>	<b>no</b>	page no:
-----------------------------------	----------------	-----------	----------

n.a <sup>x</sup> see page no. 23

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 10.2 Radiated emissions

### 10.2.1 Regulation

Test Requirement: FCC CFR47, Part 15C Section 15.249 Test Procedure: ANSI C63.4:1992

Fundamental frequency (MHz)	Field strength of fundamental (millivolts/meter)	Field strength of spurious emissions (microvolts/meter)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24.0-24.25 GHz	250	2500

(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this Section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in Section 15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of Section 15.205 shall be demonstrated using the measurement instrumentation specified in that section.

(3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in Section 15.209, whichever limit permits a higher field strength

Section 15.33 Frequency range of radiated measurements: (a) Unless otherwise noted in the specific rule section under which the equipment operates for an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph: (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

Test Requirement: FCC CFR47, Part 15C Section 15.209 Test Procedure: ANSI C63.4:1992

Section 15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

(b) In the emission table above, the tighter limit applies at the band edges.

(c) The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators which operate under the provisions of other sections within this part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emission and not the fundamental frequency. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.

(d) The emission limits shown in the above table are based on measurements employing a CISPR quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

(e) The provisions in §§ 15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

(f) In accordance with Section 15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in Section 15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in Section 15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit. Emissions which must be measured above the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator and which fall within the restricted bands shall comply with the general radiated emission limits in Section 15.109 that are applicable to the incorporated digital device.

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**10.2.2 Test equipment**

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration
Receiver (9 kHz –26.5 GHz)	Hewlett Packard Spectrum Analyzer 8593E (171)	3528U00990	2004/02	2006/02
Pre-amplifier (100kHz - 1.3GHz)	Hewlett Packard 8447 E (166a)	1726A00705	2002/04	2006/04
Loop antenna (0.009- 30 MHz)	Schwarzbeck			
Bilog antenna (30- 1000 MHz)	CHASE CBL611A (167)	1517	2002/04	2008/04
Horn antenna (0,86-8,5 GHz)	Schwarzbeck BBHA 9120 A (284)	236	1998/01	2008/01

**10.2.2 Test procedures**

The EUT and this peripheral (when additional equipment exist) are placed on a turn table which is 0.8m above the ground. The turn table would be allowed to rotate 360 degrees to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3 m. To find the maximum emission, the polarization of the receiving antenna are changed in horizontal and vertical polarization, the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4: 1992 Section 8 “Radiated Emissions Testing”

<b>Radiated emissions test characteristics</b>	
Frequency range	0.009 MHz - 10,000 MHz
Test distance	3 m*(for frequencies above 30 MHz)
Test instrumentation resolution bandwidth	9 kHz (0.009 – 30MHz)
	120 kHz (30 MHz - 1,000 MHz)
	1 MHz (1000 MHz - 10,000 MHz)
Receive antenna scan height	1 m (0.009 MHz - 30 MHz)
	1 m - 4 m (30 MHz - 10,000 MHz)
Receive antenna polarization / orientation	0 – 360°
	Vertical/horizontal (30 MHz - 1,000 MHz)

\* According to Section 15.31 (f)(1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

---

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

### 10.2.3 Calculation of field strength Section 15.209 below 30 MHz

The Receiver reading gives not directly the field strength result in (dB $\mu$ V/m). The antenna factors of the loop antenna and cable losses must be added to find the correct result.

For frequencies below 30 MHz and for an test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40 dB/decade (inverse linear distance for field strength measurements).

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of an Pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Loop Antenna factor + cable loss

$$FS = 40.7 - 40 = 0.7 \text{ [dB}\mu\text{V/m]}$$

Level in  $\mu$ V/m Common Antilogarithm  $(0.7/20) = 1.1$

### 10.2.3 Calculation of field strength Section 15.209 above 30 MHz

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of an Pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of an Pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f)(1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

### 10.2.4 Calculation of average correction factor

The average correction factor is computed by analyzing the "worst case" on time in any 100msec time period and using the formula: Corrections Factor +  $20 \cdot \log(\text{worst case on time}/100\text{msec})$  Analysis of the remote transmitter worst case on time in any 100msec time period is an on time of 50msec, there for the correction factor is  $20 \cdot \log(50/100) = -6$  dB. The maximum correction factor to be applied is 20 dB per section 15.35 of the FCC rules.

---

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

### 10.2.5 Calculation of the field strength Section 15.249

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of an Pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of an Pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB $\mu$ V. The antenna factor for the measured frequency is +2.5 dB(1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91dB $\mu$ V/m.

The 35.91dB $\mu$ V/m value can be mathematically converted to its corresponding level in  $\mu$ V/m.

Level in  $\mu$ V/m = Common Antilogarithm (35.91/20) = 39.8

For a test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f)(1), the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**10.2.6 Result**

*KaVo Radio Master*

<b>TRANSMITTER SPURIOUS RADIATION (Section 15.249 (a), (d))</b>											
f (GHz)	Bandwidth (kHz)/Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	AV Correction factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dB	Polaris. EUT / antenna	Antenna height cm
2.402	1000, AV	<b>51.90</b>	3	35.4	0	0	<b>87.30</b>	94	<b>6.70</b>	V/V	230
4.804	1000, AV	< 10	1	36.8	-19.1	0	27.7	54	26.3	H,V/H,V	100-400
7.206	1000, AV	< 14	1	39.4	-19.1	0	34.3	54	19.7	H,V/H,V	100-400
9.608	1000, AV	< 14	1	40.9	-19.1	0	35.8	54	18.2	H,V/H,V	100-400
12.010	1000, AV	< 14	1	44.7	-19.1	0	39.6	54	14.4	H,V/H,V	100-400
14.412	1000, AV	< 14	1	46.8	-19.1	0	41.7	54	12.3	H,V/H,V	100-400
16.814	1000, AV	< 18	1	43.2	-19.1	0	42.1	54	11.9	H,V/H,V	100-400
19.216	1000, AV	< 18	1	43.7	-19.1	0	42.6	54	11.4	H,V/H,V	100-400
21.618	1000, AV	< 18	1	43.4	-19.1	0	42.3	54	11.7	H,V/H,V	100-400
24.020	1000, AV	< 18	1	44.9	-19.1	0	43.8	54	10.2	H,V/H,V	100-400
26.422	1000, AV	< 18	1	45.7	-19.1	0	44.6	54	9.4	H,V/H,V	100-400
Measurement uncertainty			4 dB								

\* Bandwidth = the measuring receiver bandwidth

- Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
- Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument ≤ 4.5 dBμV @ 3m distance (1,000 – 2,000 MHz)
- Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument ≤ 10 dBμV @ 3m distance (2,000 – 5,500 MHz)
- Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument ≤ 14 dBμV @ 3m distance (5,500 – 14,500 MHz)
- Remark: \*<sup>5</sup> noise floor noise level of the measuring instrument ≤ 18 dBμV @ 3m distance (14,500 – 26,500 MHz)
- Remark: \*<sup>6</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
- Remark: \*<sup>7</sup> for using a pre-amplifier in the range between 4.0 GHz and 18.0 GHz

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	<b>yes</b>	<b>no</b>	page no:
-----------------------------------	------------	-----------	----------

n.a <sup>x</sup> see page no. 24



**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**10.2.6 Result**

*KaVo Radio Slave*

<b>TRANSMITTER SPURIOUS RADIATION (Section 15.249 (a), (d))</b>											
f (GHz)	Bandwidth (kHz)/Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	AV Correction factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dB	Polaris. EUT / antenna	Antenna height cm
2.402	1000, AV	<b>50.50</b>	3	35.4	0	0	<b>85.90</b>	94	<b>8.10</b>	V/V	250
4.804	1000, AV	< 10	1	36.8	-19.1	0	27.7	54	26.3	H,V/H,V	100-400
7.206	1000, AV	< 14	1	39.4	-19.1	0	34.3	54	19.7	H,V/H,V	100-400
9.608	1000, AV	< 14	1	40.9	-19.1	0	35.8	54	18.2	H,V/H,V	100-400
12.010	1000, AV	< 14	1	44.7	-19.1	0	39.6	54	14.4	H,V/H,V	100-400
14.412	1000, AV	< 14	1	46.8	-19.1	0	41.7	54	12.3	H,V/H,V	100-400
16.814	1000, AV	< 18	1	43.2	-19.1	0	42.1	54	11.9	H,V/H,V	100-400
19.216	1000, AV	< 18	1	43.7	-19.1	0	42.6	54	11.4	H,V/H,V	100-400
21.618	1000, AV	< 18	1	43.4	-19.1	0	42.3	54	11.7	H,V/H,V	100-400
24.020	1000, AV	< 18	1	44.9	-19.1	0	43.8	54	10.2	H,V/H,V	100-400
26.422	1000, AV	< 18	1	45.7	-19.1	0	44.6	54	9.4	H,V/H,V	100-400
Measurement uncertainty			4 dB								

\* Bandwidth = the measuring receiver bandwidth

- Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
- Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument ≤ 4.5 dBμV @ 3m distance (1,000 – 2,000 MHz)
- Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument ≤ 10 dBμV @ 3m distance (2,000 – 5,500 MHz)
- Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument ≤ 14 dBμV @ 3m distance (5,500 – 14,500 MHz)
- Remark: \*<sup>5</sup> noise floor noise level of the measuring instrument ≤ 18 dBμV @ 3m distance (14,500 – 26,500 MHz)
- Remark: \*<sup>6</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
- Remark: \*<sup>7</sup> for using a pre-amplifier in the range between 4.0 GHz and 18.0 GHz

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	<b>yes</b>	<b>no</b>	page no:
-----------------------------------	------------	-----------	----------

n.a<sup>x</sup> see page no. 24

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**10.2.6 Result**

*KaVo Radio Master*

<b>TRANSMITTER SPURIOUS RADIATION (Section 15.249 (a), (d))</b>											
f (GHz)	Bandwidth (kHz)/Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	AV Correction factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dB	Polaris. EUT / antenna	Antenna height cm
2.480	1000, AV	<b>52.83</b>	3	35.4	0	0	<b>88.23</b>	94	<b>5.77</b>	V/V	245
4.960	1000, AV	< 10	1	36.8	-19.1	0	27.7	54	26.3	H,V/H,V	100-400
7.440	1000, AV	< 14	1	39.4	-19.1	0	34.3	54	19.7	H,V/H,V	100-400
9.920	1000, AV	< 14	1	40.9	-19.1	0	35.8	54	18.2	H,V/H,V	100-400
12.400	1000, AV	< 14	1	44.7	-19.1	0	39.6	54	14.4	H,V/H,V	100-400
14.880	1000, AV	< 14	1	46.8	-19.1	0	41.7	54	12.3	H,V/H,V	100-400
17.360	1000, AV	< 18	1	43.2	-19.1	0	42.1	54	11.9	H,V/H,V	100-400
19.840	1000, AV	< 18	1	43.7	-19.1	0	42.6	54	11.4	H,V/H,V	100-400
22.320	1000, AV	< 18	1	43.4	-19.1	0	42.3	54	11.7	H,V/H,V	100-400
24.800	1000, AV	< 18	1	44.9	-19.1	0	43.8	54	10.2	H,V/H,V	100-400
27.480	1000, AV	< 18	1	45.7	-19.1	0	44.6	54	9.4	H,V/H,V	100-400
Measurement uncertainty			4 dB								

\* Bandwidth = the measuring receiver bandwidth

- Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
- Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument ≤ 4.5 dBμV @ 3m distance (1,000 – 2,000 MHz)
- Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument ≤ 10 dBμV @ 3m distance (2,000 – 5,500 MHz)
- Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument ≤ 14 dBμV @ 3m distance (5,500 – 14,500 MHz)
- Remark: \*<sup>5</sup> noise floor noise level of the measuring instrument ≤ 18 dBμV @ 3m distance (14,500 – 26,500 MHz)
- Remark: \*<sup>6</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
- Remark: \*<sup>7</sup> for using a pre-amplifier in the range between 4.0 GHz and 18.0 GHz

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	<b>yes</b>	<b>no</b>	page no:
-----------------------------------	------------	-----------	----------

n.a<sup>x</sup> see page no. 24

FCC ID: R7TF162000010

Issue date: 2005-05-23

**10.2.6 Result**

*KaVo Radio Slave*

TRANSMITTER SPURIOUS RADIATION (Section 15.249 (a), (d))											
f (GHz)	Bandwidth (kHz)/Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	AV Correction factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dB	Polaris. EUT / antenna	Antenna height cm
2.480	1000, AV	49.90	3	35.4	0	0	85.30	94	8.70	V/V	250
4.960	1000, AV	< 10	1	36.8	-19.1	0	27.7	54	26.3	H,V/H,V	100-400
7.440	1000, AV	< 14	1	39.4	-19.1	0	34.3	54	19.7	H,V/H,V	100-400
9.920	1000, AV	< 14	1	40.9	-19.1	0	35.8	54	18.2	H,V/H,V	100-400
12.400	1000, AV	< 14	1	44.7	-19.1	0	39.6	54	14.4	H,V/H,V	100-400
14.880	1000, AV	< 14	1	46.8	-19.1	0	41.7	54	12.3	H,V/H,V	100-400
17.360	1000, AV	< 18	1	43.2	-19.1	0	42.1	54	11.9	H,V/H,V	100-400
19.840	1000, AV	< 18	1	43.7	-19.1	0	42.6	54	11.4	H,V/H,V	100-400
22.320	1000, AV	< 18	1	43.4	-19.1	0	42.3	54	11.7	H,V/H,V	100-400
24.800	1000, AV	< 18	1	44.9	-19.1	0	43.8	54	10.2	H,V/H,V	100-400
27.480	1000, AV	< 18	1	45.7	-19.1	0	44.6	54	9.4	H,V/H,V	100-400
Measurement uncertainty			4 dB								

\* Bandwidth = the measuring receiver bandwidth

- Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
- Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument ≤ 4.5 dBμV @ 3m distance (1,000 – 2,000 MHz)
- Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument ≤ 10 dBμV @ 3m distance (2,000 – 5,500 MHz)
- Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument ≤ 14 dBμV @ 3m distance (5,500 – 14,500 MHz)
- Remark: \*<sup>5</sup> noise floor noise level of the measuring instrument ≤ 18 dBμV @ 3m distance (14,500 – 26,500 MHz)
- Remark: \*<sup>6</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
- Remark: \*<sup>7</sup> for using a pre-amplifier in the range between 4.0 GHz and 18.0 GHz

The equipment meets the requirements	yes	no	n.a.
--------------------------------------	-----	----	------

Further test results are attached	yes	no	page no:
-----------------------------------	-----	----	----------

n.a <sup>x</sup> see page no. 24

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

*KaVo Radio Master*

<b>TRANSMITTER SPURIOUS RADIATION BELOW 30 MHz (Section 15.205, 15.209)</b>									
f (MHz)	Bandwidth (kHz), Type of detector	Noted receiver level dBµV	Test distance m	Correction factor dB	Distance extrapol. factor dB	Level corrected dBµV/m	Limit dBµV/m	Margin dBµV/m	Polarisation EUT / antenna orientation
0.1200	PK/0.2kHz	< 4.0	10	20.2	-59.1	-34.90	Pk46.0- @ 300	80.90	V, H/0-360°
	AV/0.2kHz	< 4.0	10	20.2	-59.1	-34.90	AV26.0 @ 300	80.90	V, H/0-360°
0.5000	AV/0.2kHz	< 4.0	10	20.2	-19.1	5.10	AV33.6 @ 30	28.5	V, H/0-360°
1.5000	AV/0.2kHz	< 4.0	10	20.2	-19.1	5.10	AV24.1 @ 30	19.00	V, H/0-360°
3.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
5.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
8.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
10.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
20.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
30.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
<b>No emissions detected</b>									
Measurement uncertainty			4 dB						

Remark: \*<sup>1</sup> Noise level of the measuring instrument ≤ 4.0dBµV @ 10m distance (0.009 MHz –30 MHz)  
 Remark: \* Peak Limit according to Section 15.35 (b).

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	yes	<b>no</b>	page no:
-----------------------------------	-----	-----------	----------

n.a<sup>x</sup> see page no. 24

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

*KaVo Radio Slave*

<b>TRANSMITTER SPURIOUS RADIATION BELOW 30 MHz (Section 15.205, 15.209)</b>									
f (MHz)	Bandwidth (kHz), Type of detector	Noted receiver level dBµV	Test distance m	Correction factor dB	Distance extrapol. factor dB	Level corrected dBµV/m	Limit dBµV/m	Margin dBµV/m	Polarisation EUT / antenna orientation
0.1200	PK/0.2kHz	< 4.0	10	20.2	-59.1	-34.90	PK46.0- @ 300	80.90	V, H/0-360°
	AV/0.2kHz	< 4.0	10	20.2	-59.1	-34.90	AV26.0 @ 300	80.90	V, H/0-360°
0.5000	AV/0.2kHz	< 4.0	10	20.2	-19.1	5.10	AV33.6 @ 30	28.5	V, H/0-360°
1.5000	AV/0.2kHz	< 4.0	10	20.2	-19.1	5.10	AV24.1 @ 30	19.00	V, H/0-360°
3.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
5.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
8.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
10.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
20.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
30.0000	AV/9.0kHz	< 4.0	10	20.2	-19.1	5.10	AV29.5 @ 30	24.4	V, H/0-360°
<b>No emissions detected</b>									
Measurement uncertainty			4 dB						

Remark: \*<sup>1</sup> Noise level of the measuring instrument ≤ 4.0dBµV @ 10m distance (0.009 MHz –30 MHz)  
 Remark: \* Peak Limit according to Section 15.35 (b).

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	<b>yes</b>	<b>no</b>	page no:
-----------------------------------	------------	-----------	----------

n.a<sup>x</sup> see page no. 24

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

*KaVo Radio Master*

TRANSMITTER SPURIOUS RADIATION ABOVE 30 MHz (Section 15.205, 15.209)											
f (MHz)	Bandwidth (kHz)/Type of detector	Noted receiver level dB $\mu$ V	Test distance m	Correction factor dB	Distance extrapol. factor dB	AV Correction factor dB	Level corrected dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin dB $\mu$ V/m	Polaris. EUT / antenna	Antenna height cm
30.0000	100, AV	≤ 3.5	3	-2.60	0	0	0.90	40.00	39.10	H,V/H,V	100-400
88.0000	100, AV	≤ 3.5	3	-10.80	0	0	-7.30	40.00	47.30	H,V/H,V	100-400
216.0000	100, AV	≤ 3.5	3	-10.30	0	0	-6.80	43.50	50.30	H,V/H,V	100-400
960.0000	100, AV	≤ 3.5	3	8.50	0	0	12.00	43.50	31.50	H,V/H,V	100-400
1700.0000	1000, AV	≤ 4.5	3	3.80	0	0	8.30	54.00	45.70	H,V/H,V	100-400
2250.0000	1000, AV	≤ 10	3	8.00	0	0	18.00	54.00	36.00	H,V/H,V	100-400
4000.0000	1000, AV	≤ 10	3	8.40* <sup>6</sup>	0	0	18.40	54.00	35.60	H,V/H,V	100-400
5000.0000	1000, AV	≤ 10	3	9.10* <sup>6</sup>	0	0	19.40	54.00	34.60	H,V/H,V	100-400
7500.0000	1000, AV	≤ 14	3	12.9* <sup>6</sup> <sub>0</sub>	0	0	26.90	54.00	27.10	H,V/H,V	100-400
8300.0000	1000, AV	≤ 14	3	14.80* <sup>6</sup>	0	0	28.80	54.00	25.20	H,V/H,V	100-400
9400.0000	1000, AV	≤ 14	3	16.00* <sup>6</sup>	0	0	30.00	54.00	24.00	H,V/H,V	100-400
11000.0000	1000, AV	≤ 14	3	18.25* <sup>6</sup>	0	0	32.25	54.00	21.75	H,V/H,V	100-400
Measurement uncertainty			4 dB								

\* Bandwidth = the measuring receiver bandwidth

- Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument ≤ 3.5dB $\mu$ V @ 3m distance (30 – 1,000 MHz)
- Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument ≤ 4.5 dB $\mu$ V @ 3m distance (1,000 – 2,000 MHz)
- Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument ≤ 10 dB $\mu$ V @ 3m distance (2,000 – 5,500 MHz)
- Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument ≤ 14 dB $\mu$ V @ 3m distance (5,500 – 14,500 MHz)
- Remark: \*<sup>5</sup> noise floor noise level of the measuring instrument ≤ 18 dB $\mu$ V @ 3m distance (14,500 – 26,500 MHz)
- Remark: \*<sup>6</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
- Remark: \*<sup>7</sup> for using a pre-amplifier in the range between 4.0 GHz and 18.0 GHz

The equipment meets the requirements	yes	no	n.a.
--------------------------------------	-----	----	------

Further test results are attached	yes	no	page no:
-----------------------------------	-----	----	----------

n.a<sup>x</sup> see page no. 24

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

*KaVo Radio Slave*

TRANSMITTER SPURIOUS RADIATION ABOVE 30 MHz (Section 15.205, 15.209)											
f (MHz)	Bandwidth (kHz)/Type of detector	Noted receiver level dBμV	Test distance m	Correction factor dB	Distance extrapol. factor dB	AV Correction factor dB	Level corrected dBμV/m	Limit dBμV/m	Margin dBμV/m	Polaris. EUT / antenna	Antenna height cm
30.0000	100, AV	≤ 3.5	3	-2.60	0	0	0.90	40.00	39.10	H,V/H,V	100-400
88.0000	100, AV	≤ 3.5	3	-10.80	0	0	-7.30	40.00	47.30	H,V/H,V	100-400
216.0000	100, AV	≤ 3.5	3	-10.30	0	0	-6.80	43.50	50.30	H,V/H,V	100-400
960.0000	100, AV	≤ 3.5	3	8.50	0	0	12.00	43.50	31.50	H,V/H,V	100-400
1700.0000	1000, AV	≤ 4.5	3	3.80	0	0	8.30	54.00	45.70	H,V/H,V	100-400
2250.0000	1000, AV	≤ 10	3	8.00	0	0	18.00	54.00	36.00	H,V/H,V	100-400
4000.0000	1000, AV	≤ 10	3	8.40* <sup>6</sup>	0	0	18.40	54.00	35.60	H,V/H,V	100-400
5000.0000	1000, AV	≤ 10	3	9.10* <sup>6</sup>	0	0	19.40	54.00	34.60	H,V/H,V	100-400
7500.0000	1000, AV	≤ 14	3	12.9* <sup>6</sup> <sub>0</sub>	0	0	26.90	54.00	27.10	H,V/H,V	100-400
8300.0000	1000, AV	≤ 14	3	14.80* <sup>6</sup>	0	0	28.80	54.00	25.20	H,V/H,V	100-400
9400.0000	1000, AV	≤ 14	3	16.00* <sup>6</sup>	0	0	30.00	54.00	24.00	H,V/H,V	100-400
11000.0000	1000, AV	≤ 14	3	18.25* <sup>6</sup>	0	0	32.25	54.00	21.75	H,V/H,V	100-400
Measurement uncertainty			4 dB								

\* Bandwidth = the measuring receiver bandwidth

- Remark: \*<sup>1</sup> noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
- Remark: \*<sup>2</sup> noise floor noise level of the measuring instrument ≤ 4.5 dBμV @ 3m distance (1,000 – 2,000 MHz)
- Remark: \*<sup>3</sup> noise floor noise level of the measuring instrument ≤ 10 dBμV @ 3m distance (2,000 – 5,500 MHz)
- Remark: \*<sup>4</sup> noise floor noise level of the measuring instrument ≤ 14 dBμV @ 3m distance (5,500 – 14,500 MHz)
- Remark: \*<sup>5</sup> noise floor noise level of the measuring instrument ≤ 18 dBμV @ 3m distance (14,500 – 26,500 MHz)
- Remark: \*<sup>6</sup> for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
- Remark: \*<sup>7</sup> for using a pre-amplifier in the range between 4.0 GHz and 18.0 GHz

The equipment meets the requirements	yes	no	n.a.
--------------------------------------	-----	----	------

Further test results are attached	yes	no	page no:
-----------------------------------	-----	----	----------

n.a<sup>x</sup> see page no. 24

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 10.3 Conducted emissions

### 10.3.1 Regulation

Section 15.207 (a) For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50ohms line impedance stabilization network (LISN). Compliance with this provision of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission(MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.50	66 to 56*	56 to 46*
0.50-5.0	56	46
5.0-30.0	60	50

\* Decreases with the logarithm of the frequency.

Section 15.207 (c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which-do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or connected to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.



**FCC ID: R7TF162000010**

Issue date: 2005-05-23

### 10.3.2 Test equipment

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration	Remarks
Receiver (9 kHz - 30MHz)	Rhode & Schwarz ESH2 (22)	882902/007	01 / 04	01 / 06	---
Protector limiter 9 kHz - 30MHz, 10 dB	Rhode & Schwarz ESH 3Z2 (272)	357,881052	01 / 04	01 / 06	---
V-LISN 50 ohms/(50 uH+5 ohms)	RFT NNB 11 (72)	13835240	03 / 05	03 / 07	---
V-LISN 50 ohms/(50 uH+5 ohms)	Dudde (73)	---	03 / 05	03 / 07	---

### 10.3.3 Test procedures

The EUT and the additional equipment (if required) are connected to the main power through a line impedance stabilization network (LISN). The LISN must be appropriate to ANSI C63.4: 1992 Section 7. Additional equipment must also be connected to a second LISN with the same specifications described in the above sentence (if required).

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**10.3.4 Test results**

*KAVO Radio Master*

TRANSMITTER CONDUCTED EMISSIONS (Section 15.207)						
Tested line	Emission frequency [MHz]	Receiver bandwidth [kHz]	Result Quasi-peak [dBμV]	Spec Limit (Average) [dBμV]	Margin [dB]	Remarks
L1	0.176	10	<b>42</b>	55.8	<b>13.8</b>	*2
N	0.176	10	<b>40</b>	55.8	<b>15.8</b>	*2
L1	0.219	10	<b>36</b>	53.0	<b>17.0</b>	*2
N	0.219	10	<b>36</b>	53.0	<b>17.0</b>	*2
L1	0.475	10	<b>33.5</b>	51.0	<b>17.5</b>	*2
N	0.475	10	<b>35</b>	51.0	<b>16.0</b>	*2
L1	0.567	10	≤-2	46	<b>48</b>	*1
N	0.567	10	≤-2	46	<b>48</b>	*1
L1	0.725	10	≤-2	46	<b>48</b>	*1
N	0.725	10	≤-2	46	<b>48</b>	*1
L1	0.850	10	≤-2	46	<b>48</b>	*1
N	0.850	10	≤-2	46	<b>48</b>	*1
L1	1.000	10	≤-2	46	<b>48</b>	*1
N	1.000	10	≤-2	46	<b>48</b>	*1
L1	1.303	10	<b>39.0</b>	46	<b>7.0</b>	*2
N	1.303	10	<b>40.0</b>	46	<b>6.0</b>	*2
L1	2.000	10	≤-2	46	<b>48</b>	*1
N	2.000	10	≤-2	46	<b>48</b>	*1
L1	4.000	10	≤-2	46	<b>48</b>	*1
N	4.000	10	≤-2	46	<b>48</b>	*1
L1	6.7644	10	≤-2	50	<b>52</b>	*1
N	6.7644	10	≤-2	50	<b>52</b>	*1
L1	13.5288	10	≤-2	50	<b>52</b>	*1
N	13.5288	10	≤-2	50	<b>52</b>	*1
L1	20.2931	10	≤-2	50	<b>52</b>	*1
N	20.2931	10	≤-2	50	<b>52</b>	*1
L1	27.0575	10	≤-2	50	<b>52</b>	*1
N	27.0575	10	≤-2	50	<b>52</b>	*1

Remark: \*1 Noise level of the measuring instrument ≤ -2 dBμV (0.009 – 30MHz)

Remark: \*2 Quasi peak measurements lower than “Specified Average Limit”

The equipment meets the requirements	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--------------------------------------	-------------------------------------	--------------------------	--------------------------

Further test results are attached	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<b>Annex no: 6</b>
-----------------------------------	-------------------------------------	--------------------------	--------------------

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**10.3.4 Test results**

*KaVo Radio Slave*

TRANSMITTER CONDUCTED EMISSIONS (Section 15.207)						
Tested line	Emission frequency [MHz]	Receiver bandwidth [kHz]	Result Quasi-peak [dBμV]	Spec Limit (Average) [dBμV]	Margin [dB]	Remarks
L1	0.250	10	≤-2	53	55	* <sup>1</sup>
N	0.250	10	≤-2	53	55	* <sup>1</sup>
L1	0.375	10	≤-2	50	52	* <sup>1</sup>
N	0.375	10	≤-2	50	52	* <sup>1</sup>
L1	0.475	10	≤-2	47	49	* <sup>1</sup>
N	0.475	10	≤-2	47	49	* <sup>1</sup>
L1	0.600	10	≤-2	46	48	* <sup>1</sup>
N	0.600	10	≤-2	46	48	* <sup>1</sup>
L1	0.725	10	≤-2	46	48	* <sup>1</sup>
N	0.725	10	≤-2	46	48	* <sup>1</sup>
L1	0.850	10	≤-2	46	48	* <sup>1</sup>
N	0.850	10	≤-2	46	48	* <sup>1</sup>
L1	1.000	10	≤-2	46	48	* <sup>1</sup>
N	1.000	10	≤-2	46	48	* <sup>1</sup>
L1	1.125	10	≤-2	46	48	* <sup>1</sup>
N	1.125	10	≤-2	46	48	* <sup>1</sup>
L1	2.000	10	≤-2	46	48	* <sup>1</sup>
N	2.000	10	≤-2	46	48	* <sup>1</sup>
L1	4.000	10	≤-2	46	48	* <sup>1</sup>
N	4.000	10	≤-2	46	48	* <sup>1</sup>
L1	6.7644	10	≤-2	50	52	* <sup>1</sup>
N	6.7644	10	≤-2	50	52	* <sup>1</sup>
L1	13.5288	10	≤-2	50	52	* <sup>1</sup>
N	13.5288	10	≤-2	50	52	* <sup>1</sup>
L1	20.2931	10	≤-2	50	52	* <sup>1</sup>
N	20.2931	10	≤-2	50	52	* <sup>1</sup>
L1	27.0575	10	≤-2	50	52	* <sup>1</sup>
N	27.0575	10	≤-2	50	52	* <sup>1</sup>

Remark: \*<sup>1</sup> Noise level of the measuring instrument ≤ -2 dBμV (0.009 – 30MHz)

Remark: \*<sup>2</sup> Quasi peak measurements lower than “Specified Average Limit”

The equipment meets the requirements	yes	<del>no</del>	<del>na</del>
--------------------------------------	-----	---------------	---------------

Further test results are attached	yes	<del>no</del>	Annex no: 6
-----------------------------------	-----	---------------	-------------

***No emissions detected!***

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 10.4 Bandwidth

### 10.4.1 Regulation

15.231 (c) The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

### 10.4.2 Calculation of the 20 dB bandwidth limit

The 20 dB bandwidth limit =  $0.005 * 2.402 \text{ GHz} = 12.01 \text{ MHz}$

### 10.4.3 Test equipment

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration
Receiver (30MHz - 1GHz)	Hewlett Packard Spectrum Analyzer 8593 E (171)	3528U00990	02/2004	02/2006
Test fixture for relative measurement	Dudde	---	---	---
Power supply	Hewlett Packard (DC Power Supply) 6034L (226)		02/2004	02/2006

### 10.4.4 Test procedure

ANSI C63.4-1992 Section 13.1.7 Occupied Bandwidth Measurements. The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce worst-case (i.e., the widest) bandwidth. In order to measure the modulated signal properly, a resolution bandwidth that is small compared to the bandwidth required by the procuring or regulatory agency shall be used on the measuring instrument. However, the 6 dB resolution bandwidth of the measuring instrument shall be set to a value greater than 5% of the bandwidth requirements.

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**10.4.5 Test result**

*KaVo Radio Master*

The measured 20 dB bandwidth is: .....**880.0 kHz**

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	<b>yes</b>	<del>no</del>	<b>Annex no: 3</b>
-----------------------------------	------------	---------------	--------------------

*KaVo Radio Slave*

The measured 20 dB bandwidth is: .....**795.0 kHz**

The equipment meets the requirements	<b>yes</b>	<del>no</del>	<del>n.a.</del>
--------------------------------------	------------	---------------	-----------------

Further test results are attached	<b>yes</b>	<del>no</del>	<b>Annex no: 3</b>
-----------------------------------	------------	---------------	--------------------

---

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

## 11 Additional information to this test report

### Remarks

- n.a.<sup>1</sup>                    not applicable, because antenna is part of the PCB
- n.a.<sup>2</sup>                    not applicable, because EUT is directly battery powered

---

**FCC ID: R7TF162000010**

Issue date: 2005-05-23

**End of test report**