

FCC ID:R8HBTS-636

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)		Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	3.29	2.13	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	4.07	2.55	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	4.36	2.73	2±1	3.00	2.00	<5	0.62843	3.00	YES
Pi/4 DQPSK	2.402	3.99	2.51	3±1	4.00	2.51	<5	0.77860	3.00	YES
	2.441	4.74	2.98	3±1	4.00	2.51	<5	0.78490	3.00	YES
	2.480	5.05	3.20	3±1	4.00	2.51	<5	0.79114	3.00	YES

Conclusion:

For the max result: 0.79114W/Kg ≤ FCC Limit 3.0 for 1g SAR.