

FCC RF Test Report

:	Guangdong OPPO Mobile
	Telecommunications Corp., Ltd.
:	Mobile Phone
:	OPPO
:	CPH2065
:	R9C-CPH2065
:	47 CFR Part 2, and 90(S)
:	PCS Licensed Transmitter Held to Ear (PCE)
	::

The product was received on Jun. 01, 2020 and completely tested on Jun. 23, 2020. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Doque Chens

Reviewed by: Derreck Chen / Supervisor

File Shih

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc. 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China



TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAF	Y OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1 1.2	Applicant Manufacturer	5
	1.3 1.4	Feature of Equipment Under Test Product Specification of Equipment Under Test	5
	1.5 1.6 1.7 1.8	Modification of EUT Maximum Conducted Power, Frequency Tolerance and Emission Designator Testing Site Test Software	6 7
2	1.9 TEST	Applied Standards	
	2.1 2.2 2.3 2.4 2.5	Test Mode Connection Diagram of Test System Support Unit used in test configuration and system Measurement Results Explanation Example Frequency List of Low/Middle/High Channels	10 10 10
3	TEST	RESULT	12
4	3.1 3.2 3.3 3.4 3.5 3.6	Conducted Output Power Measurement 99% Occupied Bandwidth and 26dB Bandwidth Measurement Emissions Mask Measurement Emissions Mask – Out Of Band Emissions Measurement Field Strength of Spurious Radiation Measurement Frequency Stability Measurement	13 14 16 17 19
4 5	_	ERTAINTY OF EVALUATION	

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FW060110	Rev. 01	Initial issue of report	Jul. 30, 2020



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< 50+10log ₁₀ (P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 45.27 dB at 3259.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha village, Chang An Town, DongGuan City, Guangdong, China

1.2 Manufacturer

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha village, Chang An Town, DongGuan City, Guangdong, China

1.3 Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Phone
Brand Name	OPPO
Model Name	CPH2065
FCC ID	R9C-CPH2065
	GSM/WCDMA/LTE/5G NR
	WLAN 2.4GHz 802.11b/g/n HT20/HT40
EUT supports Radios application	WLAN 5GHz 802.11a/n HT20/HT40
EOT Supports Radios application	WLAN 5GHz 802.11ac VHT20/VHT40/VHT80
	Bluetooth BR / EDR / LE
	GNSS / NFC
	Conducted: 863597040018278/863597040018260
IMEI Code	Radiation: 863597040018435/863597040018427
HW Version	11
SW Version	ColorOS 7.1
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard						
Tx Frequency	814.7 ~ 823.3 MHz					
Rx Frequency	859.7 ~ 868.3 MHz					
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz					
Maximum Output Power to Antenna	23.47 dBm					
Antonno Coin	Top Antenna: -4.20 dBi					
Antenna Gain	Bottom Antenna: -3.90 dBi					
Type of Modulation	QPSK / 16QAM / 64QAM					




1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power, Frequency Tolerance and Emission Designator

FCC Rule	System	Type of Modulation	BW	Frequency Tolerance (ppm)	Emission Designator	Maximum Conducted power(W)
Part 90S	LTE Band 26	QPSK	1.4 MHz	-	1M10G7D	0.2218
Part 90S	LTE Band 26	16QAM	1.4 MHz	-	1M10W7D	0.1742
Part 90S	LTE Band 26	64QAM	1.4 MHz	-	1M09W7D	0.1439
Part 90S	LTE Band 26	QPSK	3 MHz	-	2M72G7D	0.2208
Part 90S	LTE Band 26	16QAM	3 MHz	-	2M72W7D	0.1734
Part 90S	LTE Band 26	64QAM	3 MHz	-	2M73W7D	0.1449
Part 90S	LTE Band 26	QPSK	5 MHz	-	4M52G7D	0.2223
Part 90S	LTE Band 26	16QAM	5 MHz	-	4M50W7D	0.1758
Part 90S	LTE Band 26	64QAM	5 MHz	-	4M50W7D	0.1449
Part 90S	LTE Band 26	QPSK	10 MHz	0.0035	9M03G7D	0.2218
Part 90S	LTE Band 26	16QAM	10 MHz	-	9M05W7D	0.1730
Part 90S	LTE Band 26	64QAM	10 MHz	-	9M09W7D	0.1435
Part 90S	LTE Band 26	QPSK	15 MHz		13M5G7D	0.2188
Part 90S	LTE Band 26	16QAM	15 MHz	-	13M5W7D	0.1730
Part 90S	LTE Band 26	64QAM	15 MHz	-	13M5W7D	0.1435





1.7 Testing Site

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.								
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595								
	Sporton Site No.	FCC Designation No.	FCC Test Firm						
Test Site No.			Registration No.						
	TH01-SZ	CN1256	421272						
Test Firm	Sporton International (Sh	nenzhen) Inc.							
Test Site Location	5	055 People's Republic of C	st, Fengzeyuan Warehouse, hina						
			FCC Test Firm						
	Sporton Site No	ECC Designation No	1 CC Test T IIII						
Test Site No.	Sporton Site No.	FCC Designation No.	Registration No.						



1.8 Test Software

ltem	Site	Manufacture	Name	Version	
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24	

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode


During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

	Bandwidth (MHz)				Modulation			RB #			Test Channel					
Test Items	Band	1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	м	н
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v	v			v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v	v			v	v	v
Frequency Stability	26				v	v	-	v					v		v	
Radiated Spurious Emission	26	v	v	v	v	v	-	v			v				v	
Note	2. The 3. LTE 15N	2. The mark "-" means that this bandwidth is not supported.														

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.



2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

lter	n Equipment	Trade Name	Model No.	FCC ID Data Cable		Power Cord	
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m	

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.00 dB and a 10dB attenuator.

Example : $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ $= 4.00 + 10 = 14.00 \ (dB)$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List									
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest					
15	Channel	26765	-	-					
15	Frequency	821.5	-	-					
10	Channel	-	26740	-					
10	Frequency	-	819	-					
5	Channel	26715	26740	26765					
5	Frequency	816.5	819	821.5					
3	Channel	26705	26740	26775					
5	Frequency	815.5	819	822.5					
1.4	Channel	26697	26740	26783					
1.4	Frequency	814.7	819	823.3					



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.



3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.



3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log₁₀(f/6.1) decibels or 50 + 10 Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The emissions mask of low and high channels for the highest RF powers were measured.
- The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
- 4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.



3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.



3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P) dB$. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10^{th} harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

Sporton International (Shenzhen) Inc. TEL: +86-755-86379589 FAX: +86-755-86379595 FCC ID: R9C-CPH2065

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[Watts])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.5.3 Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)




3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.



3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation


- 1. The EUT was set up in the thermal chamber and connected with the base station.
- 2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
- 2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
- 4. battery operating end point, which shall be specified by the manufacturer.
- 5. The variation in frequency was measured for the worst case.



3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



4 List of Measuring Equipment

Instrument	Manufacturer Model N		Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 16, 2020	Jun. 10, 2020	Apr. 15, 2021	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangrou p	LP-150U	H201408180 3	-40~+150°C	Dec. 26, 2019	Jun. 10, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY5226018 5	20Hz~26.5GHz	Jul. 22, 2019	Jun. 23, 2020	Jul. 21, 2020	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY5327010 4	0.5GHz~26.5Gh z	Dec. 27, 2019	Jun. 23, 2020	Dec. 26, 2020	Radiation (03CH01-SZ
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Jul. 19, 2019	Jun. 23, 2020	Jul. 18, 2020	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Aug. 27, 2019	Jun. 23, 2020	Aug. 26, 2020	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 17, 2020	Jun. 23, 2020	Apr. 16, 2021	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 17, 2020	Jun. 23, 2020	Apr. 16, 2021	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30- 10P-R	1943528	1GHz~18GHz	Oct. 18,2019	Jun. 23, 2020	Oct. 17, 2020	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 22. 2019	Jun. 23, 2020	Jul. 21, 2020	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	6160100019 85	N/A	NCR	Jun. 23, 2020	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 23, 2020	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 23, 2020	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	2.48dB
Confidence of 95% (U = 2Uc(y))	Liidab

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)


Measuring Uncertainty for a Level of	3.53dB
Confidence of 95% (U = 2Uc(y))	3.330B



Appendix A. Test Results of Conducted Test


Conducted Output Power (Average power)

	LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest					
15	1	0		23.33							
15	1	37		23.40							
15	1	74		23.30							
15	36	0	QPSK	22.09							
15	36	20		22.10							
15	36	39		22.05							
15	75	0		22.14							
15	1	0		22.26							
15	1	37		22.38							
15	1	74		22.25							
15	36	0	16-QAM	21.44	-	-					
15	36	20		21.40							
15	36	39		21.41							
15	75	0		21.41							
15	1	0		21.48							
15	1	37		21.57							
15	1	74		21.47							
15	36	0	64-QAM	20.43							
15	36	20		20.39							
15	36	39		20.40							
15	75	0		20.37							






LTE Band 26 Maximum Average Power [dBm]										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest				
10	1	0			23.30					
10	1	25	-		23.46					
10	1	49	-		23.40					
10	25	0	QPSK		22.07					
10	25	12			22.12					
10	25	25			22.03					
10	50	0			22.06					
10	1	0			22.29					
10	1	25	-		22.38					
10	1	49	-		22.32					
10	25	0	16-QAM	-	21.40	-				
10	25	12	-		21.41					
10	25	25			21.34					
10	50	0			21.36					
10	1	0			21.47					
10	1	25			21.57	1				
10	1	49			21.50	1				
10	25	0	64-QAM		20.39					
10	25	12			20.41					
10	25	25			20.32					
10	50	0			20.34					






LTE Band 26 Maximum Average Power [dBm]									
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest			
5	1	0		23.42	23.41	23.42			
5	1	12	-	23.46	<mark>23.47</mark>	23.41			
5	1	24	-	23.47	23.46	23.46			
5	12	0	QPSK	22.11	22.11	22.07			
5	12	7		22.13	22.12	22.09			
5	12	13	-	22.05	22.11	22.09			
5	25	0	-	22.10	22.12	22.10			
5	1	0		22.36	22.38	22.45			
5	1	12	-	22.37	22.43	22.39			
5	1	24		22.38	22.39	22.39			
5	12	0	16-QAM	21.39	21.42	21.42			
5	12	7		21.41	21.44	21.41			
5	12	13		21.34	21.39	21.37			
5	25	0	-	21.41	21.42	21.41			
5	1	0		21.55	21.56	21.60			
5	1	12		21.60	21.61	21.56			
5	1	24		21.59	21.56	21.59			
5	12	0	64-QAM	20.44	20.43	20.41			
5	12	7		20.44	20.45	20.41			
5	12	13		20.37	20.41	20.40			
5	25	0		20.36	20.40	20.38			





	LTE Band 26 Maximum Average Power [dBm]									
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest				
3	1	0		23.40	23.44	23.40				
3	1	8	-	23.39	23.43	23.40				
3	1	14	-	23.40	23.42	23.41				
3	8	0	QPSK	22.05	22.10	22.10				
3	8	4		22.08	22.09	22.09				
3	8	7		22.06	22.12	22.09				
3	15	0	-	22.07	22.13	22.12				
3	1	0		22.33	22.34	22.38				
3	1	8		22.30	22.33	22.39				
3	1	14		22.32	22.32	22.38				
3	8	0	16-QAM	21.44	21.49	21.46				
3	8	4		21.46	21.46	21.48				
3	8	7	-	21.43	21.49	21.45				
3	15	0		21.42	21.45	21.43				
3	1	0		21.52	21.61	21.55				
3	1	8		21.51	21.58	21.57				
3	1	14		21.54	21.59	21.56				
3	8	0	64-QAM	20.38	20.42	20.43				
3	8	4		20.41	20.42	20.43				
3	8	7		20.39	20.45	20.42				
3	15	0		20.36	20.42	20.39				






LTE Band 26 Maximum Average Power [dBm]									
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest			
1.4	1	0		23.38	23.45	23.43			
1.4	1	3		23.43	23.46	23.46			
1.4	1	5		23.41	23.46	23.45			
1.4	3	0	QPSK	23.43	23.45	23.46			
1.4	3	1		23.42	23.42	23.46			
1.4	3	3		23.45	23.44	23.45			
1.4	6	0		22.11	22.10	22.14			
1.4	1	0		22.36	22.38	22.41			
1.4	1	3		22.38	22.40	22.40			
1.4	1	5		22.37	22.38	22.39			
1.4	3	0	16-QAM	22.12	22.12	22.11			
1.4	3	1		22.13	22.13	22.10			
1.4	3	3		22.14	22.12	22.11			
1.4	6	0		21.48	21.48	21.52			
1.4	1	0		21.54	21.57	21.52			
1.4	1	3		21.58	21.56	21.48			
1.4	1	5		21.54	21.57	21.50			
1.4	3	0	64-QAM	21.51	21.53	21.52			
1.4	3	1		21.52	21.53	21.53			
1.4	3	3		21.54	21.51	21.54			
1.4	6	0		20.33	20.38	20.40			




Peak-to-Average Ratio

Mode						
Mod.	QP	SK	160	16QAM		
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	-	-	-	-		
Middle CH	5.30	6.06	6.23	6.67	PASS	
Highest CH	-	-	-	-		
Mode		LTE Band	26 / 10MHz			
Mod.	640	AM			Limit: 13dB	
RB Size	1RB	Full RB			Result	
Lowest CH	-	-	-	-		
Middle CH	5.88	6.64	-	-	PASS	
Highest CH	-	-	-	-		














26dB Bandwidth

Mode		LTE Band 26 : 26dB BW(MHz)										
BW	1.4	MHz	3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.26	1.27	3.00	2.99	4.85	4.88	-	-	14.30	14.30	-	-
Middle CH	1.29	1.30	3.02	2.97	4.95	4.91	9.83	9.71	-	-	-	-
Highest CH	1.30	1.24	2.99	2.99	4.89	4.97	-	-	-	-	-	-
Mode					LTE Ba	and 26 :	26dB BV	V(MHz)				
BW	1.4	MHz	3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.28	-	2.96	-	4.91	-	-	-	14.27	-	-	-
Middle CH	1.29	-	2.97	-	4.92	-	9.79	-	-	-	-	-
Highest CH	1.28	-	2.96	-	4.86	-	-	-	-	-	-	-
























































Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.10	2.70	2.69	4.49	4.49	-	-	13.46	13.46	-	-
Middle CH	1.10	1.10	2.72	2.72	4.52	4.50	9.03	9.05	-	-	-	-
Highest CH	1.10	1.09	2.70	2.72	4.49	4.50	-	-	-	-	-	-
Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.09	-	2.73	-	4.47	-	-	-	13.52	-	-	-
Middle CH	1.09	-	2.73	-	4.48	-	9.09	-	-	-	-	-
Highest CH	1.09	-	2.72	-	4.50	-	-	-	-	-	-	-


















































Conducted Band Edge

