

TEST REPORT

Applicant: Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address: NO.18 Haibin Road, Wusha Village, Chang'an Town, Dongguan City, Guangdong, China
Equipment Type: Mobile Phone
Model Name: CPH2387
Brand Name: OPPO
FCC ID: R9C-CPH2387
Test Standard: 47 CFR Part 15 Subpart B
Test Date: Feb. 18, 2022 - Feb. 22, 2022
Date of Issue: Apr. 18, 2022

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Zhang Guoxi

Zhang Guoxi

Checked by: Xia Long

Xia Long

Approved by: Liao Jianming

(Technical Director)

Liao Jianming

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Apr. 06, 2022</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Apr. 18, 2022</u>	<u>Update section 4.4 & 4.6.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Identification of the Testing Laboratory	4
1.2	Identification of the Responsible Testing Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	Factory Information	5
2.4	General Description for Equipment under Test (EUT)	5
2.5	Ancillary Equipment	6
2.6	Technical Information	9
3	SUMMARY OF TEST RESULTS.....	10
3.1	Test Standards.....	10
3.2	Verdict.....	10
3.3	Test Uncertainty	10
4	GENERAL TEST CONFIGURATIONS.....	11
4.1	Test Environments, Test Date and Test Engineer	11
4.2	Test Equipment List	11
4.3	Test Enclosure list.....	13
4.4	Test Configurations	14
4.5	Test Setups	15
4.6	Test Conditions	17
5	TEST ITEMS.....	18
5.1	Emission Tests.....	18
	ANNEX A TEST RESULTS.....	22
A.1	Radiated Emission	22

A.2	Conducted Emission	30
ANNEX B	TEST SETUP PHOTOS	34
ANNEX C	EUT EXTERNAL PHOTOS	34
ANNEX D	EUT INTERNAL PHOTOS	34

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 Haibin Road, Wusha Village, Chang'an Town, Dongguan City, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 Haibin Road, Wusha Village, Chang'an Town, Dongguan City, Guangdong, China

2.3 Factory Information

Factory	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 Haibin Road, Wusha Village, Chang'an Town, Dongguan City, Guangdong, China

2.4 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	CPH2387
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	11
Software Version	ColorOS V12.1
Dimensions (Approx.)	163.74x75.03x7.99mm
Weight (Approx.)	N/A

2.5 Ancillary Equipment

Ancillary Equipment 1	Li-Polymer Battery 1	
	Brand Name	SUPERVOOC
	Model No.	BLP923
	Serial No.	N/A
	Capacitance	Rated: 4880mAh/18.88Wh Typical: 5000mAh/19.35Wh
	Rated Voltage	3.87 V
	Limited Voltage	4.45 V
	Manufacturer	Dongguan NVT Technology Co., Ltd
Ancillary Equipment 2	Li-Polymer Battery 2	
	Brand Name	SUPERVOOC
	Model No.	BLP923
	Serial No.	N/A
	Capacitance	Rated: 4880mAh/18.88Wh Typical: 5000mAh/19.35Wh
	Rated Voltage	3.87V
	Limited Voltage	4.45 V
	Manufacturer	Chongqing CosMX Battery Co., Ltd.
Ancillary Equipment 3	Li-Polymer Battery 3	
	Brand Name	SUPERVOOC
	Model No.	BLP923
	Serial No.	N/A
	Capacitance	Rated: 4880mAh/18.88Wh Typical: 5000mAh/19.35Wh
	Rated Voltage	3.87V
	Limited Voltage	4.45 V
	Manufacturer	TWS Technology (Guangzhou) Limited
Ancillary Equipment 4	Li-Polymer Battery 4	
	Brand Name	SUPERVOOC
	Model No.	BLP923
	Serial No.	N/A
	Capacitance	Rated: 4880mAh/18.88Wh Typical: 5000mAh/19.35Wh
	Rated Voltage	3.87V
	Limited Voltage	4.45 V
	Manufacturer	PT. Battery Technology Indonesia
Ancillary Equipment 5	Power Supply Unit 1	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDYH (UK Plug)
	Serial No.	Huntkey

	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A 10W or 5-11VDC 3.0A Max
Ancillary Equipment 6	Power Supply Unit 2	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDEH (EU Plug)
	Serial No.	Huntkey
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A 10W or 5-11VDC 3.0A Max
Ancillary Equipment 7	Power Supply Unit 3	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDEH (EU Plug)
	Serial No.	GOLDEN LAKE
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A 10W or 5-11VDC 3.0A Max
Ancillary Equipment 8	Power Supply Unit 4	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDEH (EU Plug)
	Serial No.	Yohoo
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A 10W or 5-11VDC 3.0A Max
Ancillary Equipment 9	Power Supply Unit 5	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDUH (USA Plug)
	Serial No.	Huntkey
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A or 5-11VDC 3.0A Max
Ancillary Equipment 10	Power Supply Unit 6	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDUH (USA Plug)
	Serial No.	GOLDEN LAKE
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A or 5-11VDC 3.0A Max
Ancillary Equipment 11	Power Supply Unit 7	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDUH (USA Plug)
	Serial No.	Yohoo
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A 10W or 5-11VDC 3.0A Max
Ancillary Equipment 12	Power Supply Unit 8	
	Brand Name	SUPERVOOC
	Model No.	VCB3HDAH (AU Plug)

	Serial No.	Huntkey
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A 10W or 5-11VDC 3.0A Max
Ancillary Equipment 13	Power Supply Unit 9	
	Brand Name	SUPERVOOC
	Model No.	VCB3ACPH (EU Plug)
	Serial No.	Yohoo
	Rated Input	100-240VAC 50/60Hz 1.2A
	Rated Output	5VDC 2A 10W or 5-11VDC 3.0A Max
Ancillary Equipment 14	USB Cable 1	
	Model No.	DL143
	Length (Approx.)	1.0 m
Ancillary Equipment 15	USB Cable 2	
	Model No.	DL150
	Length (Approx.)	1.0 m
Ancillary Equipment 16	Headset	
	Model No.	MH156
	Length (Approx.)	1.2 m
<p>Note 1: Letter in () means plug type.</p> <p>Note 2: All adapters are tested, only the worst data of VCB3HDUH-Yohoo (USA Plug) shown in this report.</p> <p>Note 3: All USB Cable are tested, only the worst data of DL143 shown in this report.</p> <p>Note 4: All batteries are tested, only the worst data of BLP923 (PT. Battery Technology Indonesia) shown in this report.</p>		

2.6 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EGPRS 850/ 1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/ 4/ 5 4G Network FDD LTE Band 2/ 4/ 5/ 7/ 12/ 13/ 17/ 26/ 66 TDD LTE Band 38/ 41 2.4G WIFI 802.11b, 802.11g, 802.11n(20/40) and VHT20/40 5G WIFI 802.11a, 802.11n(20/40) and 802.11ac(VHT20/40) U-NII-1/2A/2C/3
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

The Highest Speed of Processor	2.3 GHz
--------------------------------	---------

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Result
1	Radiated Emission	15.109	Pass	Annex A .1
2	Conducted Emission, AC Ports	15.107	Pass	Annex A .2

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.22 dB
Radiated emissions (30 MHz-1 GHz)-10m	4.80 dB
Radiated emissions (30 MHz-1 GHz)-3m	4.76 dB
Radiated emissions (1 GHz-18 GHz)-3m	4.88 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments, Test Date and Test Engineer

Test items	Voltage	Temperature	Relative Humidity	Ambient Pressure	Test Date	Test Engineer
Radiated Emission	AC 120V/60Hz DC 3.87V(battery)	23.4℃	54%RH	101kPa	Feb. 18, 2022	Wu Yunan
Conducted Emission	AC 230V/50Hz AC 120V/60Hz DC 3.87V(battery)	21.5℃	55%RH	101kPa	Feb. 22, 2022	Ye Guangqi

4.2 Test Equipment List

Radiated Emission Test For Frequency Below 1 GHz (10 m)						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.10.10	2022.10.09	<input type="checkbox"/>
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2018054558	2021.10.10	2022.10.09	<input type="checkbox"/>
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2022.07.01	<input type="checkbox"/>
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2021.08.15	2024.08.14	<input type="checkbox"/>
Description	Manufacturer	Name		Version		Use
Test Software	BALUN	BL410-E		V19.918		<input type="checkbox"/>

Radiated Emission Test For Frequency Below 1 GHz (3m)						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	MY55330120	2021.10.20	2022.10.19	<input checked="" type="checkbox"/>
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2021.10.20	2022.10.19	<input checked="" type="checkbox"/>
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2022.07.01	<input checked="" type="checkbox"/>
Anechoic Chamber	YIHENG	9m*6m*6m	N/A	2021.09.04	2024.09.03	<input checked="" type="checkbox"/>
Description	Manufacturer	Name		Version		Use
Test Software	BALUN	BL410-E		V19.918		<input checked="" type="checkbox"/>

Radiated Emission Test For Frequency Above 1 GHz (3m)						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	Agilent	N9038A	MY55330120	2021.10.20	2022.10.19	<input checked="" type="checkbox"/>
Spectrum Analyzer	ROHDE & SCHWARZ	FSV40	101544	2022.01.04	2023.01.03	<input checked="" type="checkbox"/>
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2021.10.20	2022.10.19	<input checked="" type="checkbox"/>
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2021.10.20	2022.10.19	<input checked="" type="checkbox"/>
Amplifier (18-40GHz)	COM-MV	KA_LNA18-40G-01	18050001	2021.10.20	2022.10.19	<input checked="" type="checkbox"/>
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	1917	2019.07.02	2022.07.01	<input checked="" type="checkbox"/>
Test Antenna-Horn	A-INFOMW	LB-180400KF	J211060273	2021.07.02	2024.07.01	<input checked="" type="checkbox"/>
Anechoic Chamber	YIHENG	9m*6m*6m	N/A	2021.09.04	2024.09.03	<input checked="" type="checkbox"/>
Description	Manufacturer	Name		Version		Use
Test Software	BALUN	BL410-E		V19.918		<input checked="" type="checkbox"/>

Conducted disturbance Test						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2021.10.10	2022.10.09	<input checked="" type="checkbox"/>
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.08	2022.06.07	<input checked="" type="checkbox"/>
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	N/A	2022.02.19	2025.02.18	<input checked="" type="checkbox"/>
Description	Manufacturer	Name		Version		Use
Test Software	BALUN	BL410-E		V19.918		<input checked="" type="checkbox"/>

4.3 Test Enclosure list


Description	Manufacturer	Model	Serial No.	Length	Description	Use
Wireless Communications Test Set	R&S	CMW500	127801	N/A	Cal. Due 2023.01.03	<input checked="" type="checkbox"/>
Laptop	HONOR	N/A	N/A	N/A	N/A	<input checked="" type="checkbox"/>
TF Card	Kingston	N/A	N/A	N/A	N/A	<input checked="" type="checkbox"/>

4.4 Test Configurations

Test Configurations (TC) No.	Description
TC01	<u>The GSM 850 MHz RX Test Mode</u> GSM 850 MHz RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC02	<u>The EGPRS 850 MHz RX Test Mode</u> EGPRS 850 MHz RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC03	<u>The WCDMA Band 5 RX Test Mode</u> WCDMA Band 5 RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC04	<u>The FDD LTE Band 5 RX Test Mode</u> LTE Band 5 RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC05	<u>The FDD LTE Band 12 RX Test Mode</u> LTE Band 12 RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC06	<u>The FDD LTE Band 13 RX Test Mode</u> LTE Band 13 RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC07	<u>The FDD LTE Band 17 RX Test Mode</u> LTE Band 17 RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC08	<u>The FDD LTE Band 26 RX Test Mode</u> LTE Band 26 RX + EUT +Adapter + USB Cable + Battery + TF Card + Headset
TC09	<u>The Camera Test Mode</u> EUT + Adapter + USB Cable + Battery + TF Card + Headset
TC10	<u>The Video Play Test Mode</u> EUT + Adapter + USB Cable + Battery + TF Card + Headset
TC11	<u>The USB Test Mode</u> EUT + USB Cable + Battery + Laptop + TF Card + Headset


4.5 Test Setups

Test Setup 1




(For Radiated Emission Test (30 MHz-1 GHz))

Test Setup 2



(For Radiated Emission Test (above 1 GHz))

Test Setup 3



(For Conducted Emission, AC Ports Test)

4.6 Test Conditions

Test Case	Test Conditions	
Radiated Emission	Test Setup	Test Setup 1&2
	Test Configuration	TC01~TC11 ^{Note}
Conducted Emission, AC Ports	Test Setup	Test Setup 3
	Test Configuration	TC01~TC11 ^{Note}

Note: Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report. The Camera Test Mode is the worst mode in this report.

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class B (at 10 m)	Class A (at 10 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)
30 - 88	100	40	30	90	39
88 - 216	150	43.5	33.5	150	43.5
216 - 960	200	46	36	210	46.4
Above 960	500	54	44	300	49.5

NOTE:

- 1) Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log$ [Field Strength ($\mu\text{V/m}$)].
- 2) In the emission tables above, the tighter limit applies at the band edges.

5.1.1.2 Test Setup

Refer to 4.5 section (test setup 1 to test setup 2) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak for $f < 1$ GHz, peak & RMS Average for $f \geq 1$ GHz

Trace = max hold

5.1.1.4 Test Result

Please refer to ANNEX A.1.

NOTE:

1. Results (dBuV/m) = Reading (dBuV/m) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Over limit = Results – Limit.

5.1.2 Conducted Emission

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.5 section test (test setup 3) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 KHz

VBW \geq RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result

Please refer to ANNEX A.2.

NOTE:

1. Results (dBuV) = Reading (dBuV) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Over limit = Results – Limit.

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The Radiated Emission from 18G-40G is noise only, do not show on the report.

Note 4: All the configurations were pre tested, only the worst configuration has been reported in this report.

Test Data and Plots


The Camera Test Mode

A.1.1 Test Antenna Vertical, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	39.312	32.05	-26.92	40.0	-7.95	Peak	11.00	100	Vertical	Pass
2	100.276	32.53	-26.71	43.5	-10.97	Peak	76.00	100	Vertical	Pass
3	168.225	30.28	-29.24	43.5	-13.22	Peak	25.00	100	Vertical	Pass
4	272.064	24.36	-24.42	46.0	-21.64	Peak	360.00	100	Vertical	Pass
5	434.539	21.79	-20.12	46.0	-24.21	Peak	11.00	100	Vertical	Pass
6	985.547	30.20	-8.65	54.0	-23.80	Peak	360.00	200	Vertical	Pass

A.1.2 Test Antenna Horizontal, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	43.337	16.45	-25.75	40.0	-23.55	Peak	360.00	200	Horizontal	Pass
2	94.165	19.65	-27.67	43.5	-23.85	Peak	251.00	200	Horizontal	Pass
3	136.264	23.56	-30.10	43.5	-19.94	Peak	147.00	200	Horizontal	Pass
4	197.471	27.71	-26.64	43.5	-15.79	Peak	63.00	100	Horizontal	Pass
5	274.682	29.60	-24.38	46.0	-16.40	Peak	235.00	100	Horizontal	Pass
6	966.583	31.07	-9.06	54.0	-22.93	Peak	2.00	200	Horizontal	Pass

A.1.3 Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1543.900	38.43	-5.49	74.0	-35.57	Peak	71.00	150	Vertical	Pass
1**	1543.900	28.07	-5.49	54.0	-25.93	AV	71.00	150	Vertical	Pass
2	2915.800	46.33	6.22	74.0	-27.67	Peak	120.00	150	Vertical	Pass
2**	2915.800	37.64	6.22	54.0	-16.36	AV	120.00	150	Vertical	Pass
3	5627.250	53.05	-0.35	74.0	-20.95	Peak	77.00	150	Vertical	Pass
3**	5627.250	42.47	-0.35	54.0	-11.53	AV	77.00	150	Vertical	Pass
4	7348.000	55.26	0.82	74.0	-18.74	Peak	182.00	150	Vertical	Pass
4**	7348.000	44.07	0.82	54.0	-9.93	AV	182.00	150	Vertical	Pass
5	9434.500	51.96	-1.28	74.0	-22.04	Peak	183.00	150	Vertical	Pass
5**	9434.500	42.72	-1.28	54.0	-11.28	AV	183.00	150	Vertical	Pass
6	13359.500	53.61	1.66	74.0	-20.39	Peak	314.00	150	Vertical	Pass
6**	13359.500	45.14	1.66	54.0	-8.86	AV	314.00	150	Vertical	Pass

A.1.4 Test Antenna Horizontal, 1 GHz – 18 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2996.600	48.30	6.45	74.0	-25.70	Peak	360.00	150	Horizontal	Pass
1**	2996.600	37.95	6.45	54.0	-16.05	AV	360.00	150	Horizontal	Pass
2	3924.000	48.78	-3.82	74.0	-25.22	Peak	183.00	150	Horizontal	Pass
2**	3924.000	38.49	-3.82	54.0	-15.51	AV	183.00	150	Horizontal	Pass
3	5629.500	52.21	-0.26	74.0	-21.79	Peak	69.00	150	Horizontal	Pass
3**	5629.500	44.05	-0.26	54.0	-9.95	AV	69.00	150	Horizontal	Pass
4	7509.500	55.37	0.94	74.0	-18.63	Peak	171.00	150	Horizontal	Pass
4**	7509.500	45.23	0.94	54.0	-8.77	AV	171.00	150	Horizontal	Pass
5	10052.500	51.95	-0.50	74.0	-22.05	Peak	167.00	150	Horizontal	Pass
5**	10052.500	44.00	-0.50	54.0	-10.00	AV	167.00	150	Horizontal	Pass
6	13346.000	54.30	1.58	74.0	-19.70	Peak	299.00	150	Horizontal	Pass
6**	13346.000	45.97	1.58	54.0	-8.03	AV	299.00	150	Horizontal	Pass

Test Data and Plots


The USB Test Mode

A.1.5 Test Antenna Vertical, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.672	15.66	-25.35	40.0	-24.34	Peak	0.00	200	Vertical	Pass
2	93.535	33.74	-27.76	43.5	-9.76	Peak	155.00	100	Vertical	Pass
3	160.028	19.92	-29.57	43.5	-23.58	Peak	80.00	100	Vertical	Pass
4	277.447	35.63	-24.30	46.0	-10.37	Peak	46.00	200	Vertical	Pass
5	594.006	31.74	-16.07	46.0	-14.26	Peak	133.00	100	Vertical	Pass
6	988.990	30.34	-8.55	54.0	-23.66	Peak	0.00	200	Vertical	Pass

A.1.6 Test Antenna Horizontal, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	49.497	15.53	-25.52	40.0	-24.47	Peak	157.00	200	Horizontal	Pass
2	92.759	32.09	-27.93	43.5	-11.41	Peak	222.00	200	Horizontal	Pass
3	217.938	22.51	-26.33	46.0	-23.49	Peak	94.00	200	Horizontal	Pass
4	270.754	35.65	-24.40	46.0	-10.35	Peak	96.00	100	Horizontal	Pass
5	402.383	24.79	-20.89	46.0	-21.21	Peak	84.00	100	Horizontal	Pass
6	975.313	31.09	-8.70	54.0	-22.91	Peak	108.00	100	Horizontal	Pass

A.1.7 Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1789.200	38.37	-3.78	74.0	-35.63	Peak	301.00	150	Vertical	Pass
1**	1789.200	28.97	-3.78	54.0	-25.03	AV	301.00	150	Vertical	Pass
2	2992.700	46.81	6.26	74.0	-27.19	Peak	6.00	150	Vertical	Pass
2**	2992.700	37.48	6.26	54.0	-16.52	AV	6.00	150	Vertical	Pass
3	3875.750	48.86	-3.55	74.0	-25.14	Peak	330.00	150	Vertical	Pass
3**	3875.750	38.63	-3.55	54.0	-15.37	AV	330.00	150	Vertical	Pass
4	7903.750	54.21	1.15	74.0	-19.79	Peak	138.00	150	Vertical	Pass
4**	7903.750	44.79	1.15	54.0	-9.21	AV	138.00	150	Vertical	Pass
5	10052.000	52.62	-0.49	74.0	-21.38	Peak	251.00	150	Vertical	Pass
5**	10052.000	43.17	-0.49	54.0	-10.83	AV	251.00	150	Vertical	Pass
6	13349.500	54.59	1.70	74.0	-19.41	Peak	44.00	150	Vertical	Pass
6**	13349.500	45.46	1.70	54.0	-8.54	AV	44.00	150	Vertical	Pass

A.1.8 Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1546.000	37.41	-5.55	74.0	-36.59	Peak	0.00	150	Horizontal	Pass
1**	1546.000	29.00	-5.55	54.0	-25.00	AV	0.00	150	Horizontal	Pass
2	2797.500	46.04	4.62	74.0	-27.96	Peak	206.00	150	Horizontal	Pass
2**	2797.500	37.08	4.62	54.0	-16.92	AV	206.00	150	Horizontal	Pass
3	3636.750	47.94	-4.83	74.0	-26.06	Peak	316.00	150	Horizontal	Pass
3**	3636.750	38.74	-4.83	54.0	-15.26	AV	316.00	150	Horizontal	Pass
4	7965.000	55.06	1.66	74.0	-18.94	Peak	112.00	150	Horizontal	Pass
4**	7965.000	45.23	1.66	54.0	-8.77	AV	112.00	150	Horizontal	Pass
5	9500.000	52.52	-2.09	74.0	-21.48	Peak	233.00	150	Horizontal	Pass
5**	9500.000	42.68	-2.09	54.0	-11.32	AV	233.00	150	Horizontal	Pass
6	13355.500	54.54	1.68	74.0	-19.46	Peak	0.00	150	Horizontal	Pass
6**	13355.500	45.13	1.68	54.0	-8.87	AV	0.00	150	Horizontal	Pass


A.2 Conducted Emission

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Test Data and Plots


The Camera Test Mode

A.2.1 L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.210	40.38	10.09	63.21	-22.83	Peak	L	Pass
1**	0.210	28.09	10.09	53.21	-25.12	AV	L	Pass
2	0.388	45.14	10.09	58.11	-12.97	Peak	L	Pass
2**	0.388	30.88	10.09	48.11	-17.23	AV	L	Pass
3	0.688	36.74	10.08	56.00	-19.26	Peak	L	Pass
3**	0.688	22.88	10.08	46.00	-23.12	AV	L	Pass
4	1.734	35.87	9.91	56.00	-20.13	Peak	L	Pass
4**	1.734	25.01	9.91	46.00	-20.99	AV	L	Pass
5	4.800	37.11	9.96	56.00	-18.89	Peak	L	Pass
5**	4.800	26.32	9.96	46.00	-19.68	AV	L	Pass
6	10.116	41.56	10.10	60.00	-18.44	Peak	L	Pass
6**	10.116	33.62	10.10	50.00	-16.38	AV	L	Pass

A.2.2 N Phase




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	39.24	10.19	66.00	-26.76	Peak	N	Pass
1**	0.150	25.05	10.19	56.00	-30.95	AV	N	Pass
2	0.380	39.57	10.08	58.28	-18.71	Peak	N	Pass
2**	0.380	29.21	10.08	48.28	-19.07	AV	N	Pass
3	0.640	31.80	10.09	56.00	-24.20	Peak	N	Pass
3**	0.640	20.69	10.09	46.00	-25.31	AV	N	Pass
4	1.780	33.28	9.90	56.00	-22.72	Peak	N	Pass
4**	1.780	25.01	9.90	46.00	-20.99	AV	N	Pass
5	5.444	37.97	10.00	60.00	-22.03	Peak	N	Pass
5**	5.444	29.14	10.00	50.00	-20.86	AV	N	Pass
6	10.078	43.16	10.10	60.00	-16.84	Peak	N	Pass
6**	10.078	34.67	10.10	50.00	-15.33	AV	N	Pass

Test Data and Plots


The USB Test Mode

A.2.3 L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.152	53.30	10.19	65.89	-12.59	Peak	L	Pass
1**	0.152	37.44	10.19	55.89	-18.45	AV	L	Pass
2	0.320	41.28	10.07	59.71	-18.43	Peak	L	Pass
2**	0.320	18.62	10.07	49.71	-31.09	AV	L	Pass
3	0.420	43.12	10.09	57.45	-14.33	Peak	L	Pass
3**	0.420	29.80	10.09	47.45	-17.65	AV	L	Pass
4	1.184	32.88	10.00	56.00	-23.12	Peak	L	Pass
4**	1.184	18.58	10.00	46.00	-27.42	AV	L	Pass
5	4.784	35.37	9.96	56.00	-20.63	Peak	L	Pass
5**	4.784	24.07	9.96	46.00	-21.93	AV	L	Pass
6	19.060	34.02	10.22	60.00	-25.98	Peak	L	Pass
6**	19.060	21.18	10.22	50.00	-28.82	AV	L	Pass

A.2.4 N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.154	51.65	10.18	65.78	-14.13	Peak	N	Pass
1**	0.154	35.15	10.18	55.78	-20.63	AV	N	Pass
2	0.254	43.70	10.08	61.63	-17.93	Peak	N	Pass
2**	0.254	27.23	10.08	51.63	-24.40	AV	N	Pass
3	0.406	43.39	10.09	57.73	-14.34	Peak	N	Pass
3**	0.406	28.89	10.09	47.73	-18.84	AV	N	Pass
4	0.710	35.65	10.08	56.00	-20.35	Peak	N	Pass
4**	0.710	22.71	10.08	46.00	-23.29	AV	N	Pass
5	4.274	31.74	10.05	56.00	-24.26	Peak	N	Pass
5**	4.274	20.19	10.05	46.00	-25.81	AV	N	Pass
6	18.188	32.09	10.20	60.00	-27.91	Peak	N	Pass
6**	18.188	18.85	10.20	50.00	-31.15	AV	N	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2220363-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2220363-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2220363-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--