



FCC RF Test Report

APPLICANT : Guangdong OPPO Mobile Telecommunications Corp., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : OPPO
MODEL NAME : CPH2639
FCC ID : R9C-OP23302
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Mar. 29, 2024 ~ Apr. 10, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY3
SUMMARY OF TEST RESULT4
1 GENERAL DESCRIPTION5
1.1 Applicant5
1.2 Manufacturer5
1.3 Product Feature of Equipment Under Test5
1.4 Product Specification of Equipment Under Test5
1.5 Modification of EUT6
1.6 Maximum ERP/EIRP Power and Emission Designator7
1.7 Testing Location8
1.8 Test Software9
1.9 Applicable Standards9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST10
2.1 Test Mode10
2.2 Connection Diagram of Test System11
2.3 Support Unit used in test configuration and system11
2.4 Measurement Results Explanation Example11
2.5 Frequency List of Low/Middle/High Channels12
3 CONDUCTED TEST ITEMS14
3.1 Measuring Instruments14
3.2 Test Setup14
3.3 Test Result of Conducted Test14
3.4 Conducted Output Power and ERP/EIRP15
3.5 Peak-to-Average Ratio16
3.6 Occupied Bandwidth17
3.7 Conducted Band Edge18
3.8 Conducted Spurious Emission20
3.9 Frequency Stability21
4 RADIATED TEST ITEMS22
4.1 Measuring Instruments22
4.2 Test Setup22
4.3 Test Result of Radiated Test23
4.4 Radiated Spurious Emission24
5 LIST OF MEASURING EQUIPMENT25
6 MEASUREMENT UNCERTAINTY26
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power (Band 5) (Band 26)	ERP < 7 Watt	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	EIRP < 2Watt		-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4) (Band 66)	EIRP < 1Watt		-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	-	Report Only	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 26) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 26) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 26) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 42.30 dB at 2474.25 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

1.2 Manufacturer

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	OPPO
Model Name	CPH2639
FCC ID	R9C-OP23302
IMEI Code	Conducted: 860772070027431 Radiation: 860772070026672/860772070026664
HW Version	11
SW Version	ColorOS 14.0.1
EUT Stage	Production Unit

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 26 : 824 MHz ~ 849 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz
Rx Frequency	LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 26 : 869 MHz ~ 894 MHz LTE Band 66 : 2110 MHz~ 2180 MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 26 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz LTE Band 66 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	<ANT0> LTE Band 2 : 23.05 dBm LTE Band 4 : 24.05 dBm LTE Band 5 : 23.88 dBm LTE Band 26 : 24.03 dBm LTE Band 66 : 24.15 dBm



	<ANT1> LTE Band 2 : 23.01 dBm LTE Band 4 : 24.17 dBm LTE Band 5 : 23.85 dBm LTE Band 26 : 23.95 dBm LTE Band 66 : 24.22 dBm <ANT4> LTE Band 2 : 22.02 dBm LTE Band 4 : 23.60 dBm LTE Band 66 : 23.65 dBm
Antenna Gain	<ANT0> LTE Band 2 : -1.5 dBi LTE Band 4 : -1.9 dBi LTE Band 5 : -5.5 dBi LTE Band 26 : -5.5 dBi LTE Band 66 : -0.9 dBi <ANT1> LTE Band 2 : -1.9 dBi LTE Band 4 : -2.9 dBi LTE Band 5 : -4.2 dBi LTE Band 26 : -4.2 dBi LTE Band 66 : -2.3 dBi <ANT4> LTE Band 2 : -6.5 dBi LTE Band 4 : -8.1 dBi LTE Band 66 : -6.6 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

Note: The maximum ERP/EIRP is calculated from Output power and antenna gain, only the maximum ERP/EIRP of Ant.0 for LTE Band 2/4/66, and Ant.1 for LTE Band 5/26 are shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power and Emission Designator

LTE Band 2		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1850.7 ~ 1909.3	0.1390	1M09G7D	0.1107	1M09W7D
3	1851.5 ~ 1908.5	0.1396	2M73G7D	0.1175	2M72W7D
5	1852.5 ~ 1907.5	0.1400	4M49G7D	0.1183	4M49W7D
10	1855.0 ~ 1905.0	0.1384	9M05G7D	0.1175	9M01W7D
15	1857.5 ~ 1902.5	0.1400	13M5G7D	0.1167	13M4W7D
20	1860.0 ~ 1900.0	0.1429	17M9G7D	0.1202	17M9W7D
LTE Band 4		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1710.7 ~ 1754.3	0.1611	1M09G7D	0.1279	1M09W7D
3	1711.5 ~ 1753.5	0.1600	2M70G7D	0.1303	2M70W7D
5	1712.5 ~ 1752.5	0.1603	4M49G7D	0.1334	4M49W7D
10	1715.0 ~ 1750.0	0.1596	9M03G7D	0.1321	8M99W7D
15	1717.5 ~ 1747.5	0.1603	13M5G7D	0.1321	13M4W7D
20	1720.0 ~ 1745.0	0.1641	17M8G7D	0.1349	17M9W7D
LTE Band 5		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
1.4	824.7 ~ 848.3	0.0560	1M10G7D	0.0431	1M10W7D
3	825.5 ~ 847.5	0.0552	2M70G7D	0.0456	2M71W7D
5	826.5 ~ 846.5	0.0557	4M47G7D	0.0461	4M51W7D
10	829.0 ~ 844.0	0.0562	9M11G7D	0.0466	9M01W7D
LTE Band 26		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
1.4	824.7 ~ 848.3	0.0573	1M10G7D	0.0433	1M10W7D
3	825.5 ~ 847.5	0.0568	2M70G7D	0.0469	2M71W7D
5	826.5 ~ 846.5	0.0569	4M47G7D	0.0468	4M51W7D
10	829.0 ~ 844.0	0.0574	9M11G7D	0.0461	9M01W7D
15	831.5 ~ 841.5	0.0575	13M5G7D	0.0471	13M4W7D
CH26790	824.0	0.0547	13M4G7D	0.0459	13M4W7D



LTE Band 66		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1710.7 ~ 1779.3	0.2046	1M09G7D	0.1607	1M09W7D
3	1711.5 ~ 1778.5	0.2089	2M70G7D	0.1710	2M70W7D
5	1712.5 ~ 1777.5	0.2042	4M49G7D	0.1706	4M49W7D
10	1715.0 ~ 1775.0	0.2075	9M03G7D	0.1690	8M99W7D
15	1717.5 ~ 1772.5	0.2037	13M5G7D	0.1690	13M4W7D
20	1720.0 ~ 1770.0	0.2113	17M8G7D	0.1746	17M9W7D

Note:

1. LTE Band 26 overlaps the entire frequency range of LTE Band 5. Therefore, the test results provided in this report covers Band 5 and the portion of Band 26 subject to Part 22.
2. LTE Band 66 overlaps the entire frequency range of LTE Band 4. Therefore, the test results provided in this report covers Band 66 as well as Band 4.

1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-SZ	CN1256	421272



1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Y Plane)

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel			
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H	
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	
	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	
	66	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
Peak-to-Average Ratio	2						v	v	v	v			v		v		
	26					v	-	v	v	v			v		v		
	66						v	v	v	v			v		v		
26dB and 99% Bandwidth	2	v	v	v	v	v	v	v	v				v		v		
	26	v	v	v	v	v	-	v	v				v		v		
	66	v	v	v	v	v	v	v	v				v		v		
Conducted Band Edge	2	v	v	v	v	v	v	v	v	v	v		v	v		v	
	26	v	v	v	v	v	-	v	v	v	v		v	v		v	
	66	v	v	v	v	v	v	v	v	v	v		v	v		v	
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v				v	v		v	
	26	v	v	v	v	v	-	v	v				v	v		v	
	66	v	v	v	v	v	v	v	v				v	v		v	
Frequency Stability	2				v			v					v		v		
	26				v		-	v					v		v		
	66				v			v					v		v		
E.R.P / E.I.R.P	2	v	v	v	v	v	v	v	v	v	v			v	v	v	
	4	v	v	v	v	v	v	v	v	v	v			v	v	v	
	5	v	v	v	v	-	-	v	v	v	v			v	v	v	
	26	v	v	v	v	v	-	v	v	v	v			v	v	v	
	66	v	v	v	v	v	v	v	v	v	v			v	v	v	
Radiated Spurious Emission	2	Worst Case														v	
	26	Worst Case														v	
	66	Worst Case														v	
Note	1. The mark "v " means that this configuration is chosen for testing 2. The mark "- " means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.5 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.5 + 10 = 14.5 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26865	26915	26965
	Frequency	831.5	836.5	841.5
10	Channel	26840	26915	26990
	Frequency	829	836.5	844
5	Channel	26815	26915	27015
	Frequency	826.5	836.5	846.5
3	Channel	26805	26915	27025
	Frequency	825.5	836.5	847.5
1.4	Channel	26797	26915	27033
	Frequency	824.7	836.5	848.3

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3


3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5 and Band 26.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4 and Band 66.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.



3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

8. When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)] \text{ (dB)}$
= $[30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
= -13dBm.



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Apr. 08, 2024~ Apr. 10, 2024	Apr. 05, 2024	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 05, 2024		Apr. 04, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 16, 2023	Apr. 08, 2024~ Apr. 10, 2024	Oct. 15, 2024	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2023	Apr. 08, 2024~ Apr. 10, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 05, 2023	Apr. 08, 2024~ Apr. 10, 2024	Jul. 04, 2024	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 18, 2023	Mar. 29, 2024~ Apr. 07, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2023	Mar. 29, 2024~ Apr. 07, 2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	Mar. 29, 2024~ Apr. 07, 2024	Jun. 27, 2024	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May 14, 2023	Mar. 29, 2024~ Apr. 07, 2024	May 13, 2024	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	Jul. 07, 2023	Mar. 29, 2024~ Apr. 07, 2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 08, 2023	Mar. 29, 2024~ Apr. 07, 2024	Jul. 07, 2024	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 18, 2023	Mar. 29, 2024~ Apr. 07, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P-R	1943528	1GHz~18GHz	Oct. 18, 2023	Mar. 29, 2024~ Apr. 07, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 07, 2023	Mar. 29, 2024~ Apr. 07, 2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY57280136	500MHz~26.5GHz	Aug. 21, 2023	Mar. 29, 2024~ Apr. 07, 2024	Aug. 20, 2024	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F119050019	N/A	Oct. 18, 2023	Mar. 29, 2024~ Apr. 07, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 29, 2024~ Apr. 07, 2024	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 29, 2024~ Apr. 07, 2024	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required



6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8 dB
---------------------------------------------------------------------	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.1 dB
---------------------------------------------------------------------	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.9 dB
---------------------------------------------------------------------	--------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Lorenzo Liu	Temperature :	24~26°C
		Relative Humidity :	50~53%

Conducted Output Power(Average power) and ERP/EIRP

LTE Band 2_Ant.0:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				18700	18900	19100	EIRP(W)		
Frequency (MHz)				1860	1880	1900	L	M	H
20	QPSK	1	0	23.02	23.05	23.01	0.1419	0.1429	0.1416
20	QPSK	1	49	23.00	23.01	22.99	0.1413	0.1416	0.1409
20	QPSK	1	99	22.86	22.88	22.99	0.1368	0.1374	0.1409
20	QPSK	50	0	22.03	22.08	22.05	0.1130	0.1143	0.1135
20	QPSK	50	24	21.97	21.97	22.03	0.1114	0.1114	0.1130
20	QPSK	50	50	21.94	21.96	21.99	0.1107	0.1112	0.1119
20	QPSK	100	0	21.93	22.05	22.03	0.1104	0.1135	0.1130
20	16QAM	1	0	22.30	22.27	22.29	0.1202	0.1194	0.1199
20	64QAM	1	0	21.11	21.14	21.12	0.0914	0.0920	0.0916
Channel				18675	18900	19125	EIRP(W)		
Frequency (MHz)				1857.5	1880	1902.5	L	M	H
15	QPSK	1	0	22.87	22.96	22.90	0.1371	0.1400	0.1380
15	16QAM	1	0	22.17	22.15	22.15	0.1167	0.1161	0.1161
Channel				18650	18900	19150	EIRP(W)		
Frequency (MHz)				1855	1880	1905	L	M	H
10	QPSK	1	0	22.91	22.89	22.87	0.1384	0.1377	0.1371
10	16QAM	1	0	22.15	22.16	22.20	0.1161	0.1164	0.1175
Channel				18625	18900	19175	EIRP(W)		
Frequency (MHz)				1852.5	1880	1907.5	L	M	H
5	QPSK	1	0	22.89	22.94	22.96	0.1377	0.1393	0.1400
5	16QAM	1	0	22.23	22.18	22.17	0.1183	0.1169	0.1167
Channel				18615	18900	19185	EIRP(W)		
Frequency (MHz)				1851.5	1880	1908.5	L	M	H
3	QPSK	1	0	22.94	22.93	22.95	0.1393	0.1390	0.1396
3	16QAM	1	0	22.20	22.17	22.14	0.1175	0.1167	0.1159
Channel				18607	18900	19193	EIRP(W)		
Frequency (MHz)				1850.7	1880	1909.3	L	M	H
1.4	QPSK	1	0	22.92	22.93	22.86	0.1387	0.1390	0.1368
1.4	16QAM	1	0	21.84	21.82	21.94	0.1081	0.1076	0.1107



LTE Band 4_Ant.0:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				20050	20175	20300	EIRP(W)		
Frequency (MHz)				1720	1732.5	1745	L	M	H
20	QPSK	1	0	23.67	24.05	24.02	0.1503	0.1641	0.1629
20	QPSK	1	49	23.66	23.92	24.00	0.1500	0.1592	0.1622
20	QPSK	1	99	23.66	23.95	23.96	0.1500	0.1603	0.1607
20	QPSK	50	0	22.78	23.15	23.10	0.1225	0.1334	0.1318
20	QPSK	50	24	22.70	22.90	23.07	0.1202	0.1259	0.1309
20	QPSK	50	50	22.76	22.92	23.05	0.1219	0.1265	0.1303
20	QPSK	100	0	22.72	23.08	23.06	0.1208	0.1312	0.1306
20	16QAM	1	0	22.99	23.07	23.20	0.1285	0.1309	0.1349
20	64QAM	1	0	21.83	21.88	22.08	0.0984	0.0995	0.1042
Channel				20025	20175	20325	EIRP(W)		
Frequency (MHz)				1717.5	1732.5	1747.5	L	M	H
15	QPSK	1	0	23.54	23.95	23.88	0.1459	0.1603	0.1578
15	16QAM	1	0	22.92	22.91	23.11	0.1265	0.1262	0.1321
Channel				20000	20175	20350	EIRP(W)		
Frequency (MHz)				1715	1732.5	1750	L	M	H
10	QPSK	1	0	23.53	23.93	23.90	0.1455	0.1596	0.1585
10	16QAM	1	0	22.93	22.95	23.11	0.1268	0.1274	0.1321
Channel				19975	20175	20375	EIRP(W)		
Frequency (MHz)				1712.5	1732.5	1752.5	L	M	H
5	QPSK	1	0	23.59	23.95	23.90	0.1476	0.1603	0.1585
5	16QAM	1	0	22.83	23.02	23.15	0.1239	0.1294	0.1334
Channel				19965	20175	20385	EIRP(W)		
Frequency (MHz)				1711.5	1732.5	1753.5	L	M	H
3	QPSK	1	0	23.58	23.90	23.94	0.1472	0.1585	0.1600
3	16QAM	1	0	22.86	23.00	23.05	0.1247	0.1288	0.1303
Channel				19950	20175	20393	EIRP(W)		
Frequency (MHz)				1710	1732.5	1754.3	L	M	H
1.4	QPSK	1	0	23.55	23.97	23.88	0.1462	0.1611	0.1578
1.4	16QAM	1	0	22.62	22.75	22.97	0.1180	0.1216	0.1279



LTE Band 5_Ant.1:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				20450	20525	20600			
Frequency (MHz)				829	836.5	844	L	M	H
10	QPSK	1	0	23.83	23.85	23.81	0.0560	0.0562	0.0557
10	QPSK	1	25	23.77	23.71	23.76	0.0552	0.0545	0.0551
10	QPSK	1	49	23.78	23.76	23.76	0.0553	0.0551	0.0551
10	QPSK	25	0	22.76	22.78	22.75	0.0438	0.0440	0.0437
10	QPSK	25	12	22.72	22.75	22.73	0.0434	0.0437	0.0435
10	QPSK	25	25	22.75	22.73	22.74	0.0437	0.0435	0.0436
10	QPSK	50	0	22.74	22.75	22.74	0.0436	0.0437	0.0436
10	16QAM	1	0	22.84	23.03	23.01	0.0446	0.0466	0.0463
10	64QAM	1	0	21.75	21.94	21.87	0.0347	0.0362	0.0356
Channel				20425	20525	20625	ERP(W)		
Frequency (MHz)				826.5	836.5	846.5	L	M	H
5	QPSK	1	0	23.77	23.81	23.74	0.0552	0.0557	0.0548
5	16QAM	1	0	22.80	22.97	22.99	0.0442	0.0459	0.0461
Channel				20415	20525	20635	ERP(W)		
Frequency (MHz)				825.5	836.5	847.5	L	M	H
3	QPSK	1	0	23.69	23.77	23.69	0.0542	0.0552	0.0542
3	16QAM	1	0	22.81	22.94	22.93	0.0443	0.0456	0.0455
Channel				20407	20525	20643	ERP(W)		
Frequency (MHz)				824.7	836.5	848.3	L	M	H
1.4	QPSK	1	0	23.73	23.83	23.66	0.0547	0.0560	0.0538
1.4	16QAM	1	0	22.64	22.69	22.69	0.0426	0.0431	0.0431



LTE Band 26_Ant.1:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)			
Channel				26790	26865	26915	26965				
Frequency (MHz)				824	831.5	836.5	841.5	Straddle Ch	L	M	H
15	QPSK	1	0	23.73	23.93	23.95	23.92	0.0547	0.0573	0.0575	0.0571
15	QPSK	1	37	23.70	23.90	23.86	23.87	0.0543	0.0569	0.0564	0.0565
15	QPSK	1	74	23.60	23.84	23.82	23.76	0.0531	0.0561	0.0558	0.0551
15	QPSK	36	0	22.71	22.85	22.88	22.83	0.0433	0.0447	0.0450	0.0445
15	QPSK	36	20	22.51	22.81	22.76	22.72	0.0413	0.0443	0.0438	0.0434
15	QPSK	36	39	22.61	22.80	22.76	22.73	0.0423	0.0442	0.0438	0.0435
15	QPSK	75	0	22.55	22.80	22.85	22.74	0.0417	0.0442	0.0447	0.0436
15	16QAM	1	0	22.97	23.07	23.08	23.08	0.0459	0.0470	0.0471	0.0471
15	64QAM	1	0	21.75	22.00	21.91	21.97	0.0347	0.0367	0.0360	0.0365
Channel					26840	26915	26990	ERP(W)			
Frequency (MHz)					829	836.5	844		L	M	H
10	QPSK	1	0		23.84	23.94	23.78		0.0561	0.0574	0.0553
10	16QAM	1	0		22.97	22.97	22.99		0.0459	0.0459	0.0461
Channel					26815	26915	27015	ERP(W)			
Frequency (MHz)					826.5	836.5	846.5		L	M	H
5	QPSK	1	0		23.82	23.83	23.90		0.0558	0.0560	0.0569
5	16QAM	1	0		23.04	23.05	23.00		0.0467	0.0468	0.0462
Channel					26815	26915	27025	ERP(W)			
Frequency (MHz)					825.5	836.5	847.5		L	M	H
3	QPSK	1	0		23.84	23.84	23.89		0.0561	0.0561	0.0568
3	16QAM	1	0		23.06	23.03	22.98		0.0469	0.0466	0.0460
Channel					26797	26915	27033	ERP(W)			
Frequency (MHz)					824.7	836.5	848.3		L	M	H
1.4	QPSK	1	0		23.89	23.93	23.78		0.0568	0.0573	0.0553
1.4	16QAM	1	0		22.71	22.62	22.59		0.0433	0.0424	0.0421



LTE Band.66_Ant.0:


BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				132072	132322	132572	EIRP(W)		
Frequency (MHz)				1720	1745	1770	L	M	H
20	QPSK	1	0	23.85	24.15	24.04	0.1972	0.2113	0.2061
20	QPSK	1	49	23.66	24.10	23.85	0.1888	0.2089	0.1972
20	QPSK	1	99	23.72	24.00	23.68	0.1914	0.2042	0.1897
20	QPSK	50	0	22.80	23.08	23.01	0.1549	0.1652	0.1626
20	QPSK	50	24	22.70	23.07	22.91	0.1514	0.1648	0.1589
20	QPSK	50	50	22.76	23.03	22.79	0.1535	0.1633	0.1545
20	QPSK	100	0	22.71	23.04	22.90	0.1517	0.1637	0.1585
20	16QAM	1	0	22.99	23.24	23.32	0.1618	0.1714	0.1746
20	64QAM	1	0	21.82	22.05	22.13	0.1236	0.1303	0.1327
Channel				132047	132322	132597	EIRP(W)		
Frequency (MHz)				1717.5	1745	1772.5	L	M	H
15	QPSK	1	0	23.73	23.99	23.93	0.1919	0.2037	0.2009
15	16QAM	1	0	22.94	23.10	23.18	0.1600	0.1660	0.1690
Channel				132022	132322	132622	EIRP(W)		
Frequency (MHz)				1715	1745	1775	L	M	H
10	QPSK	1	0	23.78	24.07	23.97	0.1941	0.2075	0.2028
10	16QAM	1	0	22.91	23.18	23.16	0.1589	0.1690	0.1683
Channel				131997	132322	132647	EIRP(W)		
Frequency (MHz)				1712.5	1745	1777.5	L	M	H
5	QPSK	1	0	23.78	24.00	23.91	0.1941	0.2042	0.2000
5	16QAM	1	0	22.89	23.08	23.22	0.1581	0.1652	0.1706
Channel				131987	132322	132657	EIRP(W)		
Frequency (MHz)				1711.5	1745	1778.5	L	M	H
3	QPSK	1	0	23.70	24.10	23.98	0.1905	0.2089	0.2032
3	16QAM	1	0	22.92	23.18	23.23	0.1592	0.1690	0.1710
Channel				131979	132322	132665	EIRP(W)		
Frequency (MHz)				1710.7	1745	1779.3	L	M	H
1.4	QPSK	1	0	23.77	24.01	23.89	0.1936	0.2046	0.1991
1.4	16QAM	1	0	22.62	22.96	22.78	0.1486	0.1607	0.1542



LTE Band 2

Peak-to-Average Ratio

Mode	LTE Band 2 / 20MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	5.25	6.20	6.46	PASS






26dB Bandwidth

Mode	LTE Band 2 : 26dB BW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.28	1.27	2.99	2.99	4.88	4.89	9.83	9.87	14.33	14.27	18.86	18.78




LTE Band 2

Middle Channel / 1.4MHz / QPSK




Date: 8 APR 2024 16:46:14

Middle Channel / 1.4MHz / 16QAM




Date: 8 APR 2024 16:46:54

Middle Channel / 3MHz / QPSK




Date: 8 APR 2024 16:59:54

Middle Channel / 3MHz / 16QAM




Date: 8 APR 2024 17:00:34

Middle Channel / 5MHz / QPSK



Date: 8 APR 2024 17:13:34

Middle Channel / 5MHz / 16QAM




Date: 8 APR 2024 17:14:13




LTE Band 2

Middle Channel / 10MHz / QPSK




Date: 8 APR 2024 17:27:13

Middle Channel / 10MHz / 16QAM




Date: 8 APR 2024 17:27:52

Middle Channel / 15MHz / QPSK




Date: 8 APR 2024 17:40:51

Middle Channel / 15MHz / 16QAM




Date: 8 APR 2024 17:41:31

Middle Channel / 20MHz / QPSK



Date: 8 APR 2024 17:54:30

Middle Channel / 20MHz / 16QAM



Date: 8 APR 2024 17:55:10




Occupied Bandwidth

Mode	LTE Band 2 : 99%OBW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.09	1.09	2.73	2.72	4.49	4.49	9.05	9.01	13.46	13.40	17.94	17.90




LTE Band 2

Middle Channel / 1.4MHz / QPSK




Date: 8 APR 2024 16:46:00

Middle Channel / 1.4MHz / 16QAM




Date: 8 APR 2024 16:46:40

Middle Channel / 3MHz / QPSK




Date: 8 APR 2024 16:59:40

Middle Channel / 3MHz / 16QAM




Date: 8 APR 2024 17:00:20

Middle Channel / 5MHz / QPSK



Date: 8 APR 2024 17:13:20

Middle Channel / 5MHz / 16QAM




Date: 8 APR 2024 17:13:59




LTE Band 2

Middle Channel / 10MHz / QPSK




Date: 8 APR 2024 17:26:59

Middle Channel / 10MHz / 16QAM




Date: 8 APR 2024 17:27:38

Middle Channel / 15MHz / QPSK




Date: 8 APR 2024 17:40:37

Middle Channel / 15MHz / 16QAM




Date: 8 APR 2024 17:41:17

Middle Channel / 20MHz / QPSK



Date: 8 APR 2024 17:54:16

Middle Channel / 20MHz / 16QAM




Date: 8 APR 2024 17:54:56



Conducted Band Edge


LTE Band 2 / 1.4MHz / QPSK

Lowest Band Edge / 1RB




Date: 8 APR 2024 16:39:54

Highest Band Edge / 1RB




Date: 8 APR 2024 16:47:29

Lowest Band Edge / Full RB



Date: 8 APR 2024 16:43:02

Highest Band Edge / Full RB




Date: 8 APR 2024 16:50:37




LTE Band 2 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 16:40:30

Highest Band Edge / 1 RB




Date: 8 APR 2024 16:48:05

Lowest Band Edge / Full RB



Date: 8 APR 2024 16:43:38

Highest Band Edge / Full RB




Date: 8 APR 2024 16:51:13




LTE Band 2 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 16:41:06

Highest Band Edge / 1 RB




Date: 8 APR 2024 16:48:41

Lowest Band Edge / Full RB



Date: 8 APR 2024 16:44:14

Highest Band Edge / Full RB




Date: 8 APR 2024 16:51:49




LTE Band 2 / 3MHz / QPSK

Lowest Band Edge / 1RB




Date: 8 APR 2024 16:53:33

Highest Band Edge / 1RB




Date: 8 APR 2024 17:01:08

Lowest Band Edge / Full RB



Date: 8 APR 2024 16:56:41

Highest Band Edge / Full RB




Date: 8 APR 2024 17:02:57




LTE Band 2 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 16:54:09

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:01:44

Lowest Band Edge / Full RB



Date: 8 APR 2024 16:57:17

Highest Band Edge / Full RB




Date: 8 APR 2024 17:03:33




LTE Band 2 / 3MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 16:54:45

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:02:20

Lowest Band Edge / Full RB



Date: 8 APR 2024 16:57:53

Highest Band Edge / Full RB




Date: 8 APR 2024 17:04:09




LTE Band 2 / 5MHz / QPSK

Lowest Band Edge / 1RB




Date: 8 APR 2024 17:07:13

Highest Band Edge / 1RB




Date: 8 APR 2024 17:14:48

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:10:21

Highest Band Edge / Full RB




Date: 8 APR 2024 17:16:36




LTE Band 2 / 5MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 17:07:49

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:15:24

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:10:57

Highest Band Edge / Full RB




Date: 8 APR 2024 17:17:12




LTE Band 2 / 5MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 17:08:25

Highest Band Edge / 1 RB



Date: 8 APR 2024 17:16:00

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:11:33

Highest Band Edge / Full RB




Date: 8 APR 2024 17:17:48




LTE Band 2 / 10MHz / QPSK

Lowest Band Edge / 1RB




Date: 8 APR 2024 17:20:53

Highest Band Edge / 1RB




Date: 8 APR 2024 17:28:27

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:22:41

Highest Band Edge / Full RB




Date: 8 APR 2024 17:30:15




LTE Band 2 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 17:21:28

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:29:03

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:23:17

Highest Band Edge / Full RB




Date: 8 APR 2024 17:30:51




LTE Band 2 / 10MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 17:22:04

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:29:39

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:23:52

Highest Band Edge / Full RB




Date: 8 APR 2024 17:31:27




LTE Band 2 / 15MHz / QPSK

Lowest Band Edge / 1RB




Date: 8 APR 2024 17:34:31

Highest Band Edge / 1RB




Date: 8 APR 2024 17:42:05

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:36:19

Highest Band Edge / Full RB




Date: 8 APR 2024 17:43:53




LTE Band 2 / 15MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 17:35:07

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:42:41

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:36:55

Highest Band Edge / Full RB




Date: 8 APR 2024 17:44:29




LTE Band 2 / 15MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 17:35:43

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:43:17

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:37:31

Highest Band Edge / Full RB




Date: 8 APR 2024 17:45:05




LTE Band 2 / 20MHz / QPSK

Lowest Band Edge / 1RB




Date: 8 APR 2024 17:48:10

Highest Band Edge / 1RB




Date: 8 APR 2024 17:55:44

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:49:58

Highest Band Edge / Full RB




Date: 8 APR 2024 17:57:33




LTE Band 2 / 20MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 8 APR 2024 17:48:46

Highest Band Edge / 1 RB




Date: 8 APR 2024 17:56:20

Lowest Band Edge / Full RB



Date: 8 APR 2024 17:50:34

Highest Band Edge / Full RB



Date: 8 APR 2024 17:58:08