



FCC RF Test Report

APPLICANT : Guangdong OPPO Mobile Telecommunications Corp., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : OPPO
MODEL NAME : CPH2689
FCC ID : R9C-OP24222
STANDARD : 47 CFR Part 27(H), 27(M), 27(F)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Sep. 20, 2024 ~ Oct. 17, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	7
1.6 Maximum ERP/EIRP Power and Emission Designator	7
1.7 Testing Location	9
1.8 Test Software	9
1.9 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	11
2.1 Test Mode	11
2.2 Connection Diagram of Test System	13
2.3 Support Unit used in test configuration and system	13
2.4 Measurement Results Explanation Example	13
2.5 Frequency List of Low/Middle/High Channels	14
3 CONDUCTED TEST ITEMS	18
3.1 Measuring Instruments	18
3.2 Test Setup	18
3.3 Test Result of Conducted Test	18
3.4 Conducted Output Power and ERP/EIRP	19
3.5 Peak-to-Average Ratio	21
3.6 Occupied Bandwidth	22
3.7 Conducted Band Edge	23
3.8 Conducted Spurious Emission	25
3.9 Frequency Stability	26
4 RADIATED TEST ITEMS	27
4.1 Measuring Instruments	27
4.2 Test Setup	27
4.3 Test Result of Radiated Test	28
4.4 Radiated Spurious Emission	29
5 LIST OF MEASURING EQUIPMENT	30
6 MEASUREMENT UNCERTAINTY	31
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG491807C	Rev. 01	Initial issue of report	Nov. 12, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§27.50(b)(10) §27.50(c)(10)	Effective Radiated Power (Band 12) (Band 13) (Band 17)	ERP < 3 Watt	PASS	-
	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 7) (Band 38) (Band 41)	EIRP < 2Watt		-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	-	Report Only	-
3.7	§2.1051 §27.53(c)(2)(4) §27.53(g)	Conducted Band Edge Measurement (Band 12) (Band 13) (Band 17)	< 43+10log ₁₀ (P[Watts])	PASS	-
	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7) (Band 38) (Band 41)	§27.53(m)(4)		
3.8	§2.1051 §27.53(c)(2) §27.53(g)	Conducted Spurious Emission (Band 12) (Band 13) (Band 17)	< 43+10log ₁₀ (P[Watts])	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7) (Band 38) (Band 41)	< 55+10log ₁₀ (P[Watts])		
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§27.53(c)(2) §27.53(g)	Radiated Spurious Emission (Band 12) (Band 13) (Band 17)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 22.05 dB at 1559.50 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7) (Band 38) (Band 41)	< 55+10log ₁₀ (P[Watts])		

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

1.2 Manufacturer

Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	OPPO
Model Name	CPH2689
FCC ID	R9C-OP24222
IMEI Code	Conducted: 863233070025799/863233070025781 Radiation: 863233070022457/863233070022440
HW Version	11
SW Version	ColorOS 15.0
EUT Stage	Production Unit

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 7 : 2500 MHz ~ 2570 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 17 : 704 MHz ~ 716 MHz LTE Band 38 : 2570 MHz ~ 2620 MHz LTE Band 41 : 2496 MHz ~ 2690 MHz
Rx Frequency	LTE Band 7 : 2620 MHz ~ 2690 MHz LTE Band 12 : 729 MHz ~ 746 MHz LTE Band 13 : 746 MHz ~ 756 MHz LTE Band 17 : 734 MHz ~ 746 MHz LTE Band 38 : 2570 MHz ~ 2620 MHz LTE Band 41 : 2496 MHz ~ 2690 MHz
Bandwidth	LTE Band 7 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 12 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 13 : 5MHz / 10MHz LTE Band 17 : 5MHz / 10MHz LTE Band 38 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 41 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to	<Ant.0>



Antenna	LTE Band 12 : 22.81 dBm LTE Band 13 : 22.73 dBm LTE Band 17 : 22.77 dBm <Ant.1> LTE Band 12 : 23.11 dBm LTE Band 13 : 23.00 dBm LTE Band 17 : 23.10 dBm <Ant.5> LTE Band 7 : 24.48 dBm LTE CA_7C : 24.16 dBm LTE Band 38 : 24.62 dBm LTE CA_38C : 24.39 dBm LTE Band 41 : 25.54 dBm <Ant.6> LTE Band 7 : 23.71 dBm LTE CA_7C : 23.56 dBm LTE Band 38 : 23.85 dBm LTE CA_38C : 23.80 dBm LTE Band 41 : 24.72 dBm <Ant.7> LTE Band 7 : 20.36 dBm LTE CA_7C : 20.15 dBm LTE Band 38 : 20.93 dBm LTE CA_38C : 20.75 dBm LTE Band 41 : 21.80 dBm <Ant.11> LTE Band 7 : 23.84 dBm LTE CA_7C : 23.51 dBm LTE Band 38 : 24.01 dBm LTE CA_38C : 23.82 dBm LTE Band 41 : 24.86 dBm
Antenna Gain	<Ant.0> LTE Band 12/17 : -6.1 dBi LTE Band 13 : -5.6 dBi <Ant.1> LTE Band 12/17 : -4.7 dBi LTE Band 13 : -3.2 dBi <Ant.5> LTE Band 7 : 0.67 dBi LTE Band 38 : 0.6 dBi LTE Band 41 : 0.7 dBi <Ant.6> LTE Band 7 : -0.7 dBi LTE Band 38 : -0.8 dBi LTE Band 41 : -0.2 dBi <Ant.7> LTE Band 7/38/41 : 0.5 dBi <Ant.11> LTE Band 7/38/41 : -0.3 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

Note:

1. The maximum ERP/EIRP is calculated from max output power and max antenna gain, so only the maximum ERP/EIRP of Antenna 5 for LTE Band7/7C/38/38C/41 and Antenna 1 for LTE Band 12/13/17 are shown in the report.



2. LTE B41 support power class 2 mode.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power and Emission Designator

LTE Band 7		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	2502.5 ~ 2567.5	0.3251	4M49G7D	0.2958	4M50W7D
10	2505.0 ~ 2565.0	0.3206	9M03G7D	0.2958	9M05W7D
15	2507.5 ~ 2562.5	0.3243	13M4G7D	0.2904	13M4W7D
20	2510.0 ~ 2560.0	0.3273	17M8G7D	0.3006	17M9W7D
LTE Band 12		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
1.4	699.7 ~ 715.3	0.0410	1M09G7D	0.0397	1M09W7D
3	700.5 ~ 714.5	0.0417	2M72G7D	0.0404	2M72W7D
5	701.5 ~ 713.5	0.0422	4M49G7D	0.0406	4M48W7D
10	704.0 ~ 711.0	0.0423	9M01G7D	0.0408	9M03W7D
LTE Band 13		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	779.5 ~ 784.5	0.0573	4M50G7D	0.0558	4M49W7D
10	782.0	0.0582	9M11G7D	0.0566	9M05W7D
LTE Band 17		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	706.5 ~ 713.5	0.0416	4M49G7D	0.0410	4M48W7D
10	709.0 ~ 711.0	0.0422	9M01G7D	0.0417	9M03W7D



LTE Band 38		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	2572.5 ~ 2617.5	0.3289	4M49G7D	0.2904	4M49W7D
10	2575.0 ~ 2615.0	0.3273	8M99G7D	0.2951	9M03W7D
15	2577.5 ~ 2612.5	0.3251	13M4G7D	0.2972	13M4W7D
20	2580.0 ~ 2610.0	0.3327	17M8G7D	0.2985	17M9W7D
LTE Band 41		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	2498.5 ~ 2687.5	0.4140	4M49G7D	0.3793	4M49W7D
10	2501.0 ~ 2685.0	0.4093	8M99G7D	0.3828	9M03W7D
15	2503.5 ~ 2682.5	0.4102	13M4G7D	0.3846	13M4W7D
20	2506.0 ~ 2680.0	0.4207	17M8G7D	0.3864	17M9W7D
LTE Band 7 CA		QPSK		16QAM/64QAM/256QAM	
BW (MHz)		Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
10MHz+20MHz		0.2972	28M1G7D	0.2661	28M2W7D
15MHz+15MHz		0.2985	28M8G7D	0.2618	28M7W7D
15MHz+20MHz		0.3020	32M7G7D	0.2679	32M9W7D
15MHz+10MHz		0.3006	23M4G7D	0.2692	23M5W7D
20MHz+10MHz		0.2965	27M9G7D	0.2667	28M1W7D
20MHz+15MHz		0.2979	32M7G7D	0.2649	32M7W7D
20MHz+20MHz		0.3041	37M8G7D	0.2704	37M6W7D
LTE Band 38 CA		QPSK		16QAM/64QAM/256QAM	
BW (MHz)		Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
15MHz+15MHz		0.3112	28M7G7D	0.2438	28M7W7D
20MHz+20MHz		0.3155	37M8G7D	0.2506	37M6W7D

Note:

1. LTE Band 12 overlaps the entire frequency range of LTE Band 17. Therefore, the test results provided in this report covers Band 12 as well as Band 17.
2. LTE Band 41 overlaps the entire frequency range of LTE Band 38. Therefore, the test results provided in this report covers Band 41 as well as Band 38.

1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH03SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 27(H), 27(M), 27(F)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation



during the test.

2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Y Plane)


Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256 QAM	1	Half	Full	L	M	H
Max. Output Power	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	12	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	13	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	17	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	41	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	7	-	-				v	v	v	v		v		v		v	
	12				v	-	-	v	v	v		v		v		v	
	13	-	-		v	-	-	v	v	v		v		v		v	
	41	-	-				v	v	v	v		v		v		v	
26dB and 99% Bandwidth	7	-	-	v	v	v	v	v	v					v		v	
	12	v	v		v	-	-	v	v					v		v	
	13	-	-		v	-	-	v	v					v		v	
	41	-	-	v	v	v	v	v	v					v		v	
Conducted Band Edge	7	-	-	v	v	v	v	v	v	v		v		v	v		v
	12	v	v		v	-	-	v	v	v		v		v	v		v
	13	-	-		v	-	-	v	v	v		v		v	v		v
	41	-	-	v	v	v	v	v	v	v		v		v	v		v
Conducted Spurious Emission	7	-	-	v	v	v	v	v				v			v	v	v
	12	v	v		v	-	-	v				v			v	v	v
	13	-	-		v	-	-	v				v			v	v	v
	41	-	-	v	v	v	v	v				v			v	v	v
Frequency Stability	7	-	-		v			v						v		v	
	12				v	-	-	v						v		v	
	13	-	-		v	-	-	v						v		v	
	41	-	-		v			v						v		v	



E.I.R.P.	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	12	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	13	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	17	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	41	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	7	Worst Case														v	
	12	Worst Case														v	
	13	Worst Case														v	
	41	Worst Case														v	
Note	1. The mark “v ” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																

Test Items	Band	Bandwidth (MHz)										Modulation			RB #			Test Channel				
		20+20	20+15	15+20	20+10	10+20	20+5	5+20	15+15	15+10	10+15	QPSK	16QAM	64QAM	1	Half	Full	L	M	H		
Max. Output Power	7C_CA	v	v	v	v	v	-	-	v	v	-	v	v	v	v	v	v	v	v	v		
	38C_CA	v	-	-	-	-	-	-	v	-	-	v	v	v	v	v	v	v	v	v		
26dB and 99% Bandwidth	7C_CA	v	v	v	v	v	-	-	v	v	-	v	v				v		v			
	38C_CA	v	-	-	-	-	-	-	v	-	-	v	v				v		v			
Conducted Band Edge	7C_CA	v	v	v	v	v	-	-	v	v	-	v	v	v	v		v	v		v		
	38C_CA	v	-	-	-	-	-	-	v	-	-	v	v	v	v		v	v		v		
Conducted Spurious Emission	7C_CA	v	v	v	v	v	-	-	v	v	-	v			v			v	v	v		
	38C_CA	v	-	-	-	-	-	-	v	-	-	v			v			v	v	v		
E.I.R.P.	7C_CA	v	v	v	v	v	-	-	v	v	-	v	v	v	v	v	v	v	v	v		
	38C_CA	v	-	-	-	-	-	-	v	-	-	v	v	v	v	v	v	v	v	v		
Radiated Spurious Emission	7C_CA	Worst Case																			v	
	38C_CA	Worst Case																			v	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																					

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 5.0 + 10 = 15.0 \text{ (dB)}
 \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3

LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5



LTE Band 17 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23780	23790	23800
	Frequency	709	710	711
5	Channel	23755	23790	23825
	Frequency	706.5	710	713.5

LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5

LTE Band 41 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	39750	40620	41490
	Frequency	2506	2593	2680
15	Channel	39725	40620	41515
	Frequency	2503.5	2593	2682.5
10	Channel	39700	40620	41540
	Frequency	2501	2593	2685
5	Channel	39675	40620	41565
	Frequency	2498.5	2593	2687.5



LTE Band 7C_CA Channel and Frequency List					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
20 + 20	PCC	Channel	20850	21001	21152
		Frequency	2510.0	2525.1	2540.2
	SCC	Channel	21048	21199	21350
		Frequency	2529.8	2544.9	2560.0
20 + 15	PCC	Channel	20850	21026	21201
		Frequency	2510.0	2527.6	2545.1
	SCC	Channel	21021	21197	21372
		Frequency	2527.1	2544.7	2562.2
15 + 20	PCC	Channel	20828	21003	21179
		Frequency	2507.8	2525.3	2542.9
	SCC	Channel	20999	21174	21350
		Frequency	2524.9	2542.4	2560.0
20 + 10	PCC	Channel	20850	21051	21251
		Frequency	2510.0	2530.1	2550.1
	SCC	Channel	20994	21195	21395
		Frequency	2524.4	2544.5	2564.5
10 + 20	PCC	Channel	20805	21006	21206
		Frequency	2505.5	2525.6	2545.6
	SCC	Channel	20949	21150	21350
		Frequency	2519.9	2540.0	2560.0
15 + 15	PCC	Channel	20825	21025	21225
		Frequency	2507.5	2527.5	2547.5
	SCC	Channel	20975	21175	21375
		Frequency	2522.5	2542.5	2562.5
15 + 10	PCC	Channel	20825	21051	21277
		Frequency	2507.5	2530.1	2552.7
	SCC	Channel	20945	21171	21397
		Frequency	2519.5	2542.1	2564.7



LTE Band 38C_CA Channel and Frequency List					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
20 + 20	PCC	Channel	37850	37901	37952
		Frequency	2580.0	2585.1	2590.2
	SCC	Channel	38048	38099	38150
		Frequency	2599.8	2604.9	2610.0
15+ 15	PCC	Channel	37825	37925	38025
		Frequency	2577.5	2587.5	2597.5
	SCC	Channel	37975	38075	38175
		Frequency	2592.5	2602.5	2612.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 12, Band 13 and Band 17.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 7 and Band 38 and Band 41.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB


3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.


3.4.3 Test Procedures for LTE ULCA

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter PCC & SCC output ports were connected to the system simulator.
3. Set EUT at maximum power, set the PCC/SCC CA band, channel, bandwidth and RB config.


PCC config_(Channel Bandwidth / Channel / Band)




SCC config_(Channel Bandwidth / Channel / Band)



PCC config_(Number of RB / Starting RB)




SCC config_(Number of RB / Starting RB)




4. Select lowest, middle, and highest channels for each ULCA band and different modulation.
5. Check the ULCA spectrum and record the total power from the system simulator.

Check the ULCA spectrum (eg. 20M+20M)



Read the Total UL CA output power (PCC+SCC)



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

27.53 (c)

For operations in the 776-788 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least $65 + 10 \log_{10} p(\text{watts})$, dB, for mobile and portable equipment.

27.53 (g)

For operations in the 600MHz band and 698 -746 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.

5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

9. For LTE Band 7, 38, 41, the other 40 dB, and 55 dB have additionally applied same calculation above.
10. When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7,38,41:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.
11. For Band 7, 38, 41
The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [55 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[55 + 10\log(P)]$ (dB)
 $= -25\text{dBm}$.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7, 38, 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)} = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$
13. For Band 7, 38, 41:
The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Sep. 20, 2024~ Oct. 17, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 16, 2023	Sep. 20, 2024~ Oct. 17, 2024	Oct. 15, 2024	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 16, 2024		Oct. 15, 2025	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2023	Sep. 20, 2024~ Oct. 17, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 03, 2024	Sep. 20, 2024~ Oct. 17, 2024	Jul. 02, 2025	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 09, 2024	Sep. 29, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 09, 2024	Sep. 29, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 29, 2023	Sep. 29, 2024	Dec. 28, 2024	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Aug. 20, 2023	Sep. 29, 2024	Aug. 19, 2025	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 09, 2024	Sep. 29, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 18, 2023	Sep. 29, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2024	Sep. 29, 2024	Jul. 02, 2025	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 09, 2024	Sep. 29, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 27, 2023	Sep. 29, 2024	Dec. 26, 2024	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	61601000272 9	N/A	Oct. 18, 2023	Sep. 29, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Sep. 29, 2024	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Sep. 29, 2024	NCR	Radiation (03CH03-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 09, 2024	Sep. 29, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 29, 2023	Sep. 29, 2024	Dec. 28, 2024	Radiation (03CH03-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Peak to Average Ratio	± 1.34 dB
Frequency Stability	± 1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.8 dB
---	--------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Sky	Temperature :	24~26°C
		Relative Humidity :	50~53%

Conducted Output Power(Average power) and ERP/EIRP

LTE_B7_Ant.5:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				20850	20850	21350			
Frequency (MHz)				2510	2535	2560	L	M	H
20	QPSK	1	0	24.43	24.48	24.40	0.3236	0.3273	0.3214
20	QPSK	1	49	24.32	24.39	24.38	0.3155	0.3206	0.3199
20	QPSK	1	99	24.34	24.47	24.36	0.3170	0.3266	0.3184
20	QPSK	50	0	24.02	24.12	24.00	0.2944	0.3013	0.2931
20	QPSK	50	24	23.67	23.82	23.75	0.2716	0.2812	0.2767
20	QPSK	50	50	23.84	23.88	23.79	0.2825	0.2851	0.2793
20	QPSK	100	0	23.86	23.95	23.94	0.2838	0.2897	0.2891
20	16QAM	1	0	23.96	24.11	23.98	0.2904	0.3006	0.2917
20	64QAM	1	0	22.95	22.98	22.87	0.2301	0.2317	0.2259
20	256QAM	1	0	19.40	19.55	19.52	0.1016	0.1052	0.1045
Channel				20825	21100	21375	EIRP(W)		
Frequency (MHz)				2507.5	2535	2562.5	L	M	H
15	QPSK	1	0	24.42	24.44	24.39	0.3228	0.3243	0.3206
15	16QAM	1	0	23.82	23.96	23.94	0.2812	0.2904	0.2891
Channel				20800	21100	21400	EIRP(W)		
Frequency (MHz)				2505	2535	2565	L	M	H
10	QPSK	1	0	24.39	24.35	24.35	0.3206	0.3177	0.3177
10	16QAM	1	0	23.85	24.04	23.94	0.2831	0.2958	0.2891
Channel				20775	21100	21425	EIRP(W)		
Frequency (MHz)				2502.5	2535	2567.5	L	M	H
5	QPSK	1	0	24.33	24.45	24.35	0.3162	0.3251	0.3177
5	16QAM	1	0	23.88	24.04	23.91	0.2851	0.2958	0.2871



LTE_B12_Ant.1:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23060	23095	23130			
Frequency (MHz)				704	707.5	711	L	M	H
10	QPSK	1	0	23.04	23.11	23.01	0.0416	0.0423	0.0413
10	QPSK	1	25	22.96	23.06	22.92	0.0408	0.0418	0.0405
10	QPSK	1	49	23.01	23.06	23.00	0.0413	0.0418	0.0412
10	QPSK	25	0	22.83	22.90	22.79	0.0396	0.0403	0.0393
10	QPSK	25	12	22.49	22.60	22.49	0.0366	0.0376	0.0366
10	QPSK	25	25	22.57	22.65	22.60	0.0373	0.0380	0.0376
10	QPSK	50	0	22.77	22.85	22.76	0.0391	0.0398	0.0390
10	16QAM	1	0	22.84	22.96	22.87	0.0397	0.0408	0.0400
10	64QAM	1	0	21.71	21.74	21.64	0.0306	0.0308	0.0301
10	256QAM	1	0	18.09	18.10	17.99	0.0133	0.0133	0.0130
Channel				23035	23095	23155	ERP(W)		
Frequency (MHz)				701.5	707.5	713.5	L	M	H
5	QPSK	1	0	23.01	23.10	22.88	0.0413	0.0422	0.0401
5	16QAM	1	0	22.72	22.93	22.85	0.0386	0.0406	0.0398
Channel				23025	23095	23165	ERP(W)		
Frequency (MHz)				700.5	707.5	714.5	L	M	H
3	QPSK	1	0	22.94	23.05	22.90	0.0406	0.0417	0.0403
3	16QAM	1	0	22.72	22.91	22.78	0.0386	0.0404	0.0392
Channel				23017	23095	23173	ERP(W)		
Frequency (MHz)				699.7	707.5	715.3	L	M	H
1.4	QPSK	1	0	22.91	22.98	22.97	0.0404	0.0410	0.0409
1.4	16QAM	1	0	22.73	22.84	22.72	0.0387	0.0397	0.0386



LTE_B13_Ant.1:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23230					
Frequency (MHz)				782				M	
10	QPSK	1	0		23.00			0.0582	
10	QPSK	1	25		22.94			0.0574	
10	QPSK	1	49		22.92			0.0571	
10	QPSK	25	0		22.93			0.0573	
10	QPSK	25	12		22.73			0.0547	
10	QPSK	25	25		22.72			0.0546	
10	QPSK	50	0		22.85			0.0562	
10	16QAM	1	0		22.88			0.0566	
10	64QAM	1	0		21.74			0.0436	
10	256QAM	1	0		18.10			0.0188	
Channel				23205	23230	23255	ERP(W)		
Frequency (MHz)				779.5	782	784.5	L	M	H
5	QPSK	1	0	22.84	22.92	22.93	0.0561	0.0571	0.0573
5	16QAM	1	0	22.80	22.79	22.82	0.0556	0.0555	0.0558

**LTE_B17_Ant.1:**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23780	23790	23800			
Frequency (MHz)				709	710	711	L	M	H
10	QPSK	1	0	23.09	23.10	23.09	0.0421	0.0422	0.0421
10	QPSK	1	25	23.07	23.05	23.04	0.0419	0.0417	0.0416
10	QPSK	1	49	22.99	23.03	22.96	0.0411	0.0415	0.0408
10	QPSK	25	0	22.58	22.64	22.63	0.0374	0.0379	0.0378
10	QPSK	25	12	22.48	22.51	22.56	0.0366	0.0368	0.0372
10	QPSK	25	25	22.55	22.54	22.51	0.0372	0.0371	0.0368
10	QPSK	50	0	22.48	22.62	22.55	0.0366	0.0378	0.0372
10	16QAM	1	0	22.95	23.05	22.90	0.0407	0.0417	0.0403
10	64QAM	1	0	21.76	21.77	21.64	0.0310	0.0310	0.0301
10	256QAM	1	0	17.89	18.04	17.89	0.0127	0.0132	0.0127
Channel				23755	23790	23825	ERP(W)		
Frequency (MHz)				706.5	710	713.5	L	M	H
5	QPSK	1	0	22.97	23.04	23.00	0.0409	0.0416	0.0412
5	16QAM	1	0	22.91	22.98	22.79	0.0404	0.0410	0.0393



LTE_B38_Ant.5:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				37850	38000	38150			
Frequency (MHz)				2580	2595	2610	L	M	H
20	QPSK	1	0	24.57	24.62	24.57	0.3289	0.3327	0.3289
20	QPSK	1	49	24.44	24.58	24.48	0.3192	0.3296	0.3221
20	QPSK	1	99	24.42	24.53	24.45	0.3177	0.3258	0.3199
20	QPSK	50	0	24.17	24.27	24.18	0.2999	0.3069	0.3006
20	QPSK	50	24	24.09	24.11	23.96	0.2944	0.2958	0.2858
20	QPSK	50	50	23.96	24.09	24.00	0.2858	0.2944	0.2884
20	QPSK	100	0	24.12	24.17	24.02	0.2965	0.2999	0.2897
20	16QAM	1	0	24.08	24.15	24.08	0.2938	0.2985	0.2938
20	64QAM	1	0	22.80	22.84	22.71	0.2188	0.2208	0.2143
20	256QAM	1	0	19.41	19.46	19.41	0.1002	0.1014	0.1002
Channel				37825	38000	38175	EIRP(W)		
Frequency (MHz)				2577.5	2595	2612.5	L	M	H
15	QPSK	1	0	24.50	24.52	24.50	0.3236	0.3251	0.3236
15	16QAM	1	0	23.95	24.13	24.07	0.2851	0.2972	0.2931
Channel				37800	38000	38200	EIRP(W)		
Frequency (MHz)				2575	2595	2615	L	M	H
10	QPSK	1	0	24.43	24.55	24.54	0.3184	0.3273	0.3266
10	16QAM	1	0	23.94	24.10	24.06	0.2844	0.2951	0.2924
Channel				37775	38000	38225	EIRP(W)		
Frequency (MHz)				2572.5	2595	2617.5	L	M	H
5	QPSK	1	0	24.47	24.57	24.48	0.3214	0.3289	0.3221
5	16QAM	1	0	24.00	24.03	24.00	0.2884	0.2904	0.2884



LTE_B41_Ant.5:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				39750	40620	41490			
Frequency (MHz)				2506	2593	2680	L	M	H
20	QPSK	1	0	25.41	25.54	25.48	0.4083	0.4207	0.4150
20	QPSK	1	49	25.28	25.43	25.31	0.3963	0.4102	0.3990
20	QPSK	1	99	25.34	25.49	25.36	0.4018	0.4159	0.4036
20	QPSK	50	0	25.07	25.10	25.09	0.3776	0.3802	0.3793
20	QPSK	50	24	24.77	24.93	24.82	0.3524	0.3656	0.3565
20	QPSK	50	50	24.62	24.85	24.72	0.3404	0.3589	0.3483
20	QPSK	100	0	24.91	25.01	24.93	0.3639	0.3724	0.3656
20	16QAM	1	0	25.03	25.17	25.16	0.3741	0.3864	0.3855
20	64QAM	1	0	23.74	23.94	23.85	0.2780	0.2911	0.2851
20	256QAM	1	0	20.28	20.34	20.30	0.1253	0.1271	0.1259
Channel				39725	40620	41515	EIRP(W)		
Frequency (MHz)				2503.5	2593	2682.5	L	M	H
15	QPSK	1	0	25.27	25.43	25.33	0.3954	0.4102	0.4009
15	16QAM	1	0	24.94	25.14	25.15	0.3664	0.3837	0.3846
Channel				39700	40620	41540	EIRP(W)		
Frequency (MHz)				2501	2593	2685	L	M	H
10	QPSK	1	0	25.39	25.42	25.37	0.4064	0.4093	0.4046
10	16QAM	1	0	25.00	25.04	25.13	0.3715	0.3750	0.3828
Channel				39675	40620	41565	EIRP(W)		
Frequency (MHz)				2498.5	2593	2687.5	L	M	H
5	QPSK	1	0	25.28	25.47	25.41	0.3963	0.4140	0.4083
5	16QAM	1	0	25.02	25.09	25.03	0.3733	0.3793	0.3741



LTE_7C_Ant.5:

Combination 20MHz+20MHz (100RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.16	0.3041
M	QPSK	1	Max	1	0	24.02	0.2944
H	QPSK	1	Max	1	0	24.07	0.2979
L	16QAM	1	Max	1	0	23.65	0.2704
M	16QAM	1	Max	1	0	23.60	0.2673
H	16QAM	1	Max	1	0	23.60	0.2673
L	64QAM	1	Max	1	0	22.56	0.2104
M	64QAM	1	Max	1	0	22.43	0.2042
H	64QAM	1	Max	1	0	22.49	0.2070
L	256QAM	1	Max	1	0	19.43	0.1023
M	256QAM	1	Max	1	0	19.40	0.1016
H	256QAM	1	Max	1	0	19.38	0.1012
Combination 20MHz+15MHz (100RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.07	0.2979
L	16QAM	1	Max	1	0	23.56	0.2649
Combination 15MHz+20MHz (75RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.13	0.3020
L	16QAM	1	Max	1	0	23.61	0.2679
Combination 15MHz+15MHz (75RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.08	0.2985
L	16QAM	1	Max	1	0	23.51	0.2618
Combination 20MHz+10MHz (100RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.05	0.2965
L	16QAM	1	Max	1	0	23.59	0.2667



Combination 10MHz+20MHz (50RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.06	0.2972
L	16QAM	1	Max	1	0	23.58	0.2661
Combination 15MHz+10MHz (75RB+50RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.11	0.3006
L	16QAM	1	Max	1	0	23.63	0.2692

LTE_38C_Ant.5:


Combination 20MHz+20MHz (100RB+100RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.39	0.3155
M	QPSK	1	Max	1	0	24.26	0.3062
H	QPSK	1	Max	1	0	24.35	0.3126
L	16QAM	1	Max	1	0	23.39	0.2506
M	16QAM	1	Max	1	0	23.26	0.2432
H	16QAM	1	Max	1	0	23.30	0.2455
L	64QAM	1	Max	1	0	21.98	0.1811
M	64QAM	1	Max	1	0	21.90	0.1778
H	64QAM	1	Max	1	0	21.93	0.1791
L	256QAM	1	Max	1	0	19.11	0.0935
M	256QAM	1	Max	1	0	19.03	0.0918
H	256QAM	1	Max	1	0	19.02	0.0916
Combination 15MHz+15MHz (75RB+75RB)							
Channel	Modulation	PCC		SCC		Measured Power	EIRP(W)
		RB Size	RB offset	RB Size	RB offset		
L	QPSK	1	Max	1	0	24.33	0.3112
L	16QAM	1	Max	1	0	23.27	0.2438



LTE Band 7

Peak-to-Average Ratio


Mode	LTE Band 7 / 20MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	5.48	6.17	6.41	PASS






26dB Bandwidth

Mode	LTE Band 7 : 26dB BW(MHz)							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	4.96	4.99	9.71	9.79	14.42	14.36	18.62	18.86






Middle Channel / 15MHz / QPSK



Date: 20 SEP 2024 18:23:51


Middle Channel / 15MHz / 16QAM



Date: 20 SEP 2024 18:24:30


LTE Band 7

Middle Channel / 20MHz / QPSK



Date: 20 SEP 2024 18:42:38

Middle Channel / 20MHz / 16QAM




Date: 20 SEP 2024 18:43:18




Occupied Bandwidth

Mode	LTE Band 7 : 99%OBW(MHz)							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	4.49	4.50	9.03	9.05	13.43	13.40	17.78	17.86






Middle Channel / 15MHz / QPSK



Date: 20 SEP 2024 18:23:17


Middle Channel / 15MHz / 16QAM



Date: 20 SEP 2024 18:24:17


LTE Band 7

Middle Channel / 20MHz / QPSK



Date: 20 SEP 2024 18:42:25

Middle Channel / 20MHz / 16QAM




Date: 20 SEP 2024 18:43:04



Conducted Band Edge


LTE Band 7 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 23 SEP 2024 16:54:11

Highest Band Edge / 1 RB




Date: 25 SEP 2024 09:08:38

Lowest Band Edge / Full RB



Date: 23 SEP 2024 16:38:38

Highest Band Edge / Full RB




Date: 23 SEP 2024 16:48:29




LTE Band 7 / 5MHz / 16QAM

Lowest Band Edge / 1RB




Date: 23 SEP 2024 17:12:57

Highest Band Edge / 1 RB




Date: 25 SEP 2024 09:06:43

Lowest Band Edge / Full RB



Date: 23 SEP 2024 16:39:39

Highest Band Edge / Full RB




Date: 23 SEP 2024 16:49:29




LTE Band 7 / 5MHz / 64QAM

Lowest Band Edge / 1RB




Date: 25 SEP 2024 09:05:07

Highest Band Edge / 1 RB




Date: 25 SEP 2024 09:07:29

Lowest Band Edge / Full RB



Date: 23 SEP 2024 16:40:40

Highest Band Edge / Full RB




Date: 23 SEP 2024 16:50:30




LTE Band 7 / 10MHz / QPSK

Lowest Band Edge / 1 RB




Date: 20 SEP 2024 17:54:27

Highest Band Edge / 1 RB




Date: 25 SEP 2024 09:16:25

Lowest Band Edge / Full RB



Date: 20 SEP 2024 17:57:33

Highest Band Edge / Full RB




Date: 20 SEP 2024 18:07:32




LTE Band 7 / 10MHz / 16QAM

Lowest Band Edge / 1RB




Date: 25 SEP 2024 09:11:56

Highest Band Edge / 1 RB




Date: 25 SEP 2024 09:15:45

Lowest Band Edge / Full RB



Date: 20 SEP 2024 17:58:34

Highest Band Edge / Full RB




Date: 20 SEP 2024 18:08:34




LTE Band 7 / 10MHz / 64QAM


Lowest Band Edge / 1RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 7 / 15MHz / QPSK


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 7 / 15MHz / 16QAM


Lowest Band Edge / 1RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 7 / 15MHz / 64QAM


Lowest Band Edge / 1RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 7 / 20MHz / QPSK


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 7 / 20MHz / 16QAM

Lowest Band Edge / 1RB




Date: 20 SEP 2024 18:35:18

Highest Band Edge / 1 RB




Date: 25 SEP 2024 09:25:35

Lowest Band Edge / Full RB



Date: 20 SEP 2024 18:38:25

Highest Band Edge / Full RB




Date: 20 SEP 2024 18:49:49




LTE Band 7 / 20MHz / 64QAM


Lowest Band Edge / 1RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB



Highest Band Edge / Full RB






Conducted Spurious Emission


LTE Band 7 / 5MHz

Lowest Channel / QPSK




Date: 23 SEP 2024 16:41:54

Middle Channel / QPSK



Date: 23 SEP 2024 16:43:08

Highest Channel / QPSK




Date: 23 SEP 2024 16:51:44




LTE Band 7 / 10MHz

Lowest Channel / QPSK




Date: 20 SEP 2024 18:00:51

Middle Channel / QPSK



Date: 20 SEP 2024 18:02:06

Highest Channel / QPSK




Date: 20 SEP 2024 18:10:52




LTE Band 7 / 15MHz

Lowest Channel / QPSK




Date: 20 SEP 2024 18:21:55

Middle Channel / QPSK



Date: 20 SEP 2024 18:23:10

Highest Channel / QPSK




Date: 20 SEP 2024 18:31:55




LTE Band 7 / 20MHz

Lowest Channel / QPSK




Date: 20 SEP 2024 18:40:43

Middle Channel / QPSK



Date: 20 SEP 2024 18:41:58

Highest Channel / QPSK



Date: 20 SEP 2024 18:53:47

**Frequency Stability**

Test Conditions		LTE Band 7 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0025	PASS
40	Normal Voltage	0.0022	
30	Normal Voltage	0.0012	
20(Ref.)	Normal Voltage	0.0003	
10	Normal Voltage	0.0004	
0	Normal Voltage	0.00012	
-10	Normal Voltage	0.0026	
-20	Normal Voltage	0.0019	
-30	Normal Voltage	0.0000	
20	Maximum Voltage	0.0025	
20	Normal Voltage	0.0003	
20	Battery End Point	0.0012	

Note:

1. Normal Voltage = 4V. ; Battery End Point (BEP) =3.6 V. ; Maximum Voltage = 4.53V
2. The frequency fundamental emissions stay within the authorized frequency block.