



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Bluetooth Mono Headset

Model: BH600N

Brand: N/A

Test Report Number:

SZ120412B12-RP

Prepared for

Sunitec Enterprise Co.,Ltd

10F.-1, No.200, Jingping Rd., Jhonghe City, Taipei County, 23581, Taiwan

Prepared by

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.

**No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd.,
Guan Lan Town, Baoan District, Shenzhen, China**

TEL: 86-755-28055000

FAX: 86-755-28055221

Issued Date: April 30, 2012



TESTING CERT #2861.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test result of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue No.	Revisions	Effect Page	Revised By
00	SZ120412B12-RP	Initial Issue	ALL	Nancy Fu



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION4

2. EUT DESCRIPTION.....5

3. TEST METHODOLOGY6

 3.1. DESCRIPTION OF TEST MODES6

4. FACILITIES AND ACCREDITATIONS7

 4.1. FACILITIES.....7

 4.2. ACCREDITATIONS7

 4.3. MEASUREMENT UNCERTAINTY7

5. SETUP OF EQUIPMENT UNDER TEST8

 5.1. SETUP CONFIGURATION OF EUT8

 5.2. SUPPORT EQUIPMENT8

6. FCC PART 15.247 REQUIREMENTS9

 6.1. 20DB BANDWIDTH9

 6.2. PEAK POWER.....14

 6.3. PEAK POWER SPECTRAL DENSITY16

 6.4. BAND EDGES MEASUREMENT17

 6.5. FREQUENCY SEPARATION27

 6.6. NUMBER OF HOPPING FREQUENCY30

 6.7. TIME OF OCCUPANCY (DWELL TIME).....33

 6.8. SPURIOUS EMISSIONS40

 6.9. POWERLINE CONDUCTED EMISSIONS58



1. TEST RESULT CERTIFICATION

Product:	Bluetooth Mono Headset
Model:	BH600N
Brand:	N/A
Tested:	April 12~ April 29, 2012
Applicant:	Sunitec Enterprise Co.,Ltd 10F.-1, No.200, Jingping Rd., Jhonghe City, Taipei County, 23581, Taiwan
Manufacturer:	Sunitec Enterprise Co.,Ltd No.2, Qilin Road 2, RunTang Ind, Dan-Keng Village Fu Ming Community, Guan-Lan Town, BaoAn District, Shenzhen Guangdong China

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.207, 15.209 and 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Tom Gan
Supervisor of EMC Dept.
Compliance Certification Service Inc.

Reviewed by:

Aven Zhou
Supervisor of Report Dept.
Compliance Certification Service Inc.



2. EUT DESCRIPTION

Product	Bluetooth Mono Headset
Model Number	BH600N
Brand	N/A
Model Discrepancy	N/A
Identify Number	SZ120412B12-RP
Power Supply	DC 5V supplied by the notebook or DC3.7V supplied by the battery
Received Date	April 12, 2012
Frequency Range	2402 ~ 2480 MHz
Transmit Power	GFSK: 6.75dBm 8DPSK: 5.75dBm
Modulation Technique	FHSS (GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8DPSK for 3Mbps)
Number of Channels	79 Channels
Antenna Specification	Meander Line Antenna with 0dBi gain(Max)
Temperature Range	-20°C ~ +70°C

Note: This submittal(s) (test report) is intended for FCC ID: RA8-BH004 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

3.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

The following test mode(s) were scanned during the preliminary test below 1G:

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: Normal Link	<input checked="" type="checkbox"/>
Radiated Emission	Mode 1: TX	<input checked="" type="checkbox"/>

Above 1G, Channel Low (2402MHz) · Mid (2441MHz) and High (2480MHz) were chosen for full testing for GFSK.



4. FACILITIES AND ACCREDITATIONS

4.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.4:2009, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

4.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
Taiwan	TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	FCC
Japan	VCCI(C-3478, R-3135, T-652)
Canada	INDUSTRY CANADA
Taiwan	BSMI
Norway	Nemko

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	+/- 3.18dB
Radiated emissions	30MHz ~ 200MHz	+/- 3.79dB
	200MHz ~1000MHz	+/- 3.62dB
	Above 1000MHz	+/- 5.04dB
Band Edges	+/-0.182 dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



5. SETUP OF EQUIPMENT UNDER TEST

5.1. SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

5.2. SUPPORT EQUIPMENT

No	Equipment	Model	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1. 1	Notebook1	992F2VG	62P7043	N/A	IBM	Shielded 1.20m	Unshielded 1.80m
2. 2	Notebook1	Studio 1435	5315448686549	N/A	DELL	Shielded 1.20m	Unshielded 1.80m

Notes:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



6. FCC PART 15.247 REQUIREMENTS

6.1. 20DB BANDWIDTH


None; for reporting purpose only.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT, then connect a low loss RF cable from antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=30kHz, VBW=100kHz, Span=3MHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the test channels are investigated.

TEST RESULTS

No non-compliance noted




Test plot (GFSK)

20dB Bandwidth (CH Low)

Agilent 03:47:49 Apr 27, 2012

R T



Occupied Bandwidth 845.8624 kHz


Occ BW % Pwr 99.00 %
x dB -20.00 dB

Transmit Freq Error 19.180 kHz
x dB Bandwidth 870.179 kHz

20dB Bandwidth (CH Mid)

Agilent 03:47:06 Apr 27, 2012

R T



Occupied Bandwidth 845.3776 kHz

Occ BW % Pwr 99.00 %
x dB -20.00 dB


Transmit Freq Error 20.009 kHz
x dB Bandwidth 860.956 kHz



20dB Bandwidth (CH High)

Agilent 03:46:14 Apr 27, 2012

R T



Occupied Bandwidth
841.3874 kHz

Occ BW % Pwr 99.00 %
x dB -20.00 dB

Transmit Freq Error 20.900 kHz
x dB Bandwidth 860.798 kHz




Test plot (8DPSK)

20dB Bandwidth (CH Low)

Agilent 03:44:19 Apr 27, 2012

R T



Occupied Bandwidth 1.1965 MHz


Occ BW % Pwr 99.00 % x dB -20.00 dB

Transmit Freq Error 35.628 kHz x dB Bandwidth 1.210 MHz

20dB Bandwidth (CH Mid)

Agilent 03:44:54 Apr 27, 2012

R T



Occupied Bandwidth 1.1718 MHz

Occ BW % Pwr 99.00 % x dB -20.00 dB


Transmit Freq Error 37.957 kHz x dB Bandwidth 1.214 MHz



20dB Bandwidth (CH High)

Agilent 03:45:26 Apr 27, 2012

R T



Occupied Bandwidth
1.1578 MHz

Occ BW % Pwr 99.00 %
x dB -20.00 dB

Transmit Freq Error 38.121 kHz
x dB Bandwidth 1.209 MHz



6.2. PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:


1. For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.
3. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Power Meter	Anritsu	ML2487A	6K00001491	03/19/2012	03/19/2013
Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.



TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	2.67	3.50	6.17	0.00414	1	PASS
Mid	2441	3.24	3.50	6.74	0.00472		PASS
High	2480	3.25	3.50	6.75	0.00473		PASS

8DPSK

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	1.88	3.50	5.38	0.00345	1	PASS
Mid	2441	2.25	3.50	5.75	0.00376		PASS
High	2480	2.11	3.50	5.61	0.00364		PASS



6.3. PEAK POWER SPECTRAL DENSITY

LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5MHz, Sweep=500s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

Not applicable. Since EUT is the Bluetooth device.



6.4. BAND EDGES MEASUREMENT


LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

MEASUREMENT EQUIPMENT USED

Radiated Emission Test Site 966(2)						
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration	
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013	
Amplifier	MITEQ	AM-1604-3000	1411843	03/18/2012	03/18/2013	
Turn Table	EMCO	2081-1.21	N/A	N.C.R	N.C.R	
Controller	CT	N/A	N/A	N.C.R	N.C.R	
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2012	03/18/2013	
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/17/2012	03/17/2013	
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/17/2012	03/17/2013	
Loop Antenna	A. R. A	PLA-1030/B	1029	03/19/2012	03/19/2013	
Temp. / Humidity Meter	VICTOR	VC230	N/A	03/31/2012	03/31/2013	
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R	
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2				

Test Configuration





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=510Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

Refer to attach spectrum analyzer data chart.



Test Data (GFSK)

Band Edges (CH-Low)


Detector mode: Peak

Polarity: Vertical

Agilent 21:20:16 Apr 27, 2012

R T

Mkr1 2.402 12 GHz
91.25 dBµV




Detector mode: Average

Polarity: Vertical

Agilent 21:20:42 Apr 27, 2012

R T

Mkr1 2.402 12 GHz
75.45 dBµV






Detector mode: Peak

Polarity: Horizontal

Agilent 21:33:27 Apr 27, 2012

R T

Mkr1 2.402 12 GHz
82.41 dBµV




Detector mode: Average

Polarity: Horizontal

Agilent 21:34:09 Apr 27, 2012

R T

Mkr1 2.401 96 GHz
68.40 dBµV





Band Edges (CH-High)

Detector mode: Peak

Polarity: Vertical

Agilent 21:55:02 Apr 27, 2012

R T

Mkr1 2.479 96 GHz
89.93 dBµV



Start 2.475 00 GHz Stop 2.500 00 GHz
#Res BW 1 MHz VBW 1 MHz Sweep 1 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 96 GHz	89.93 dBµV
2	(1)	Freq	2.483 50 GHz	58.78 dBµV

Detector mode: Average

Polarity: Vertical

Agilent 21:55:32 Apr 27, 2012

R T

Mkr1 2.480 00 GHz
72.91 dBµV



Start 2.475 00 GHz Stop 2.500 00 GHz
#Res BW 1 MHz #VBW 510 Hz Sweep 38.24 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.480 00 GHz	72.91 dBµV
2	(1)	Freq	2.483 50 GHz	36.90 dBµV




Detector mode: Peak

Polarity: Horizontal

Agilent 21:41:50 Apr 27, 2012

R T

Mkr1 2.480 17 GHz
82.41 dBµV




Detector mode: Average

Polarity: Horizontal

Agilent 21:42:34 Apr 27, 2012

R T

Mkr1 2.480 00 GHz
68.33 dBµV





Test Data (8DPSK)

Band Edges (CH-Low)


Detector mode: Peak

Polarity: Vertical

Agilent 21:23:11 Apr 27, 2012

R T

Mkr1 2.401 96 GHz
89.99 dBµV




Detector mode: Average

Polarity: Vertical

Agilent 21:23:46 Apr 27, 2012

R T

Mkr1 2.402 12 GHz
73.53 dBµV






Detector mode: Peak

Polarity: Horizontal

Agilent 21:28:45 Apr 27, 2012

R T

Mkr1 2.401 96 GHz
80.73 dBµV




Detector mode: Average

Polarity: Horizontal

Agilent 21:29:12 Apr 27, 2012

R T

Mkr1 2.401 96 GHz
66.22 dBµV





Band Edges (CH-High)


Detector mode: Peak

Polarity: Vertical

Agilent

R T

Mkr1 2.480 04 GHz
88.39 dBµV



Ref 107 dBµV #Atten 20 dB
Start 2.475 00 GHz Stop 2.500 00 GHz
#Res BW 1 MHz #VBW 1 MHz Sweep 1 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.480 04 GHz	88.39 dBµV
2	(1)	Freq	2.483 50 GHz	41.77 dBµV

Detector mode: Average

Polarity: Vertical

Agilent

R T

Mkr1 2.479 88 GHz
72.10 dBµV



Ref 107 dBµV #Atten 20 dB
Start 2.475 00 GHz Stop 2.500 00 GHz
#Res BW 1 MHz #VBW 510 Hz Sweep 38.24 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 88 GHz	72.10 dBµV
2	(1)	Freq	2.483 50 GHz	29.87 dBµV




Detector mode: Peak

Polarity: Horizontal

Agilent 21:47:18 Apr 27, 2012

R T

Mkr1 2.480 04 GHz
80.13 dBµV




Detector mode: Average

Polarity: Horizontal

Agilent 21:45:46 Apr 27, 2012

R T

Mkr1 2.480 08 GHz
65.71 dBµV





6.5. FREQUENCY SEPARATION

LIMIT


According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW=30kHz, VBW=30kHz, Adjust Span to 4 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	580.119	> Two-thirds of the 20 dB Bandwidth	Pass

8DPSK

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	809.333	> Two-thirds of the 20 dB Bandwidth	Pass




GFSK

Test Plot

Measurement of Channel Separation

Agilent 04:29:58 Apr 27, 2012


R T



20 dB bandwidth(CH Low)

Agilent 03:47:49 Apr 27, 2012

R T



Occupied Bandwidth
845.8624 kHz

Occ BW % Pwr 99.00 %
x dB -20.00 dB

Transmit Freq Error 19.180 kHz
x dB Bandwidth 870.179 kHz




8DPSK

Test Plot

Measurement of Channel Separation

Agilent 04:25:41 Apr 27, 2012


R T



20 dB bandwidth(CH Mid)

Agilent 03:44:54 Apr 27, 2012

R T





6.6. NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = 1ms and Start=2441.5MHz, Stop = 2483MHz, Sweep = 1ms.
4. Set the spectrum analyzer as RBW, VBW=300kHz,
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

Test Data

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS




Test Plot (GFSK)

Channel Number

2.400 GHz – 2.4415 GHz

Agilent 04:04:51 Apr 27, 2012


R T



2.4415 GHz –2.483 GHz

Agilent 04:06:05 Apr 27, 2012

R T






Test Plot (8DPSK)

Channel Number

2.400 GHz – 2.4415 GHz

Agilent 04:03:13 Apr 27, 2012


R T



2.4415 GHz –2.483 GHz

Agilent 04:09:04 Apr 27, 2012

R T





6.7. TIME OF OCCUPANCY (DWELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

No non-compliance noted

Test Data

GFSK

DH 1

CH Mid: $0.513 * (1600/2)/79 * 31.6 = 164.160$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.513	164.160	31.60	400.00	PASS

DH 3

CH Mid: $1.770 * (1600/4)/79 * 31.6 = 283.200$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.770	283.200	31.60	400.00	PASS

DH 5

CH Mid: $3.020 * (1600/6)/79 * 31.6 = 322.133$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	3.020	322.133	31.60	400.00	PASS



Test Data

8DPSK

DH 1

CH Mid: $0.525 * (1600/2)/79 * 31.6 = 168.000$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.525	168.000	31.60	400.00	PASS

DH 3

CH Mid: $1.775 * (1600/4)/79 * 31.6 = 284.000$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.775	284.000	31.60	400.00	PASS

DH 5

CH Mid: $3.027 * (1600/6)/79 * 31.6 = 322.880$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	3.027	322.880	31.60	400.00	PASS



Test Plot

GFSK


DH 1

(CH Mid)

Agilent 04:15:08 Apr 27, 2012

R T

▲ Mkr1 513.3 μ s
54.47 dB



Center 2.441 000 GHz Span 0 Hz
Res BW 1 MHz VBW 1 MHz Sweep 1 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1R	(1)	Time	101.7 μ s	-50.55 dBm
1a	(1)	Time	513.3 μ s	54.47 dB


DH 3

(CH Mid)

Agilent 04:14:23 Apr 27, 2012

R T

▲ Mkr1 1.77 ms
55.77 dB



Center 2.441 000 GHz Span 0 Hz
Res BW 1 MHz VBW 1 MHz Sweep 3 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1R	(1)	Time	490 μ s	-49.67 dBm
1a	(1)	Time	1.77 ms	55.77 dB




DH 5

(CH Mid)

Agilent 04:13:26 Apr 27, 2012

R T

Mkr1 -3.02 ms
-56.87 dB



Marker	Trace	Type	X Axis	Amplitude
1R	(1)	Time	3.813 ms	6.14 dBm
1a	(1)	Time	-3.02 ms	-56.87 dB



Test Plot
8DPSK


DH 1

(CH Mid)

Agilent 04:10:57 Apr 27, 2012

R T

▲ Mkr1 525 μ s
56.27 dB




DH 3

(CH Mid)

Agilent 04:11:47 Apr 27, 2012

R T

▲ Mkr1 -1.775 ms
-55.79 dB






DH 5

(CH Mid)

Agilent 04:12:35 Apr 27, 2012

R T

Mkr1 3.027 ms
56.23 dB



Marker	Trace	Type	X Axis	Amplitude
1R	(1)	Time	426.7 μs	-51.32 dBm
1Δ	(1)	Time	3.027 ms	56.23 dB



6.8. SPURIOUS EMISSIONS

6.8.1. Conducted Measurement

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted




Test Plot (GFSK)

CH Low

30MHz ~2.9GHz

Agilent 03:51:48 Apr 27, 2012


R T



2.9MHz ~26.5GHz

Agilent 03:50:39 Apr 27, 2012

R T






CH Mid

30MHz ~ 2.9GHz

Agilent 03:52:30 Apr 27, 2012


R T



2.9GHz ~ 26.5GHz

Agilent 03:52:59 Apr 27, 2012

R T






CH High

30MHz ~ 2.9GHz

Agilent 03:53:57 Apr 27, 2012


R T



2.9GHz ~ 26.5GHz

Agilent 03:54:32 Apr 27, 2012

R T






Test Plot (8DPSK)

CH Low

30MHz ~2.9GHz

Agilent 03:59:40 Apr 27, 2012


R T



2.9MHz ~26.5GHz

Agilent 04:00:33 Apr 27, 2012

R T






CH Mid

30MHz ~ 2.9GHz

Agilent 03:57:46 Apr 27, 2012


R T



2.9GHz ~ 26.5GHz

Agilent 03:58:43 Apr 27, 2012

R T






CH High

30MHz ~ 2.9GHz

Agilent 03:55:50 Apr 27, 2012


R T



2.9GHz ~ 26.5GHz

Agilent 03:56:54 Apr 27, 2012

R T





6.8.2. Radiated Emissions

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54



MEASUREMENT EQUIPMENT USED


Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/19/2012	03/19/2013
Amplifier	MITEQ	AM-1604-3000	1411843	03/18/2012	03/18/2013
Turn Table	EMCO	2081-1.21	N/A	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2012	03/18/2013
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/17/2012	03/17/2013
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/17/2012	03/17/2013
Loop Antenna	A. R. A	PLA-1030/B	1029	03/19/2012	03/19/2013
Temp. / Humidity Meter	VICTOR	VC230	N/A	03/31/2012	03/31/2013
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

Remark: Each piece of equipment is scheduled for calibration once a year.




Test Configuration

Below 1 GHz



Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Link

Test Date: April 29, 2012

Temperature: 24°C

Tested by: Sunday Hu

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
398.6000	32.76	-15.46	17.30	46.00	-28.70	V	QP
482.6667	32.79	-13.91	18.88	46.00	-27.12	V	QP
579.6667	33.79	-12.44	21.35	46.00	-24.65	V	QP
713.8500	33.53	-11.45	22.08	46.00	-23.92	V	QP
788.2167	32.39	-10.27	22.12	46.00	-23.88	V	QP
867.4333	33.53	-9.38	24.15	46.00	-21.85	V	QP
372.7333	37.08	-16.45	20.63	46.00	-25.37	H	QP
474.5833	35.89	-14.15	21.74	46.00	-24.26	H	QP
539.2500	39.50	-13.17	26.33	46.00	-19.67	H	QP
576.4333	41.53	-12.48	29.05	46.00	-16.95	H	QP
778.5167	36.25	-10.25	26.00	46.00	-20.00	H	QP
823.7833	35.86	-9.76	26.10	46.00	-19.90	H	QP

****Remark:** No emission found between lowest internal used/generated frequency to 30MHz.

Notes:

- Measuring frequencies from 9kHz to the 1GHz.
- Radiated emissions measured in frequency range from 30MHz to 1GHz were made with an instrument using Quasi-peak detector mode.
- Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.
- | | |
|-------------------------|--|
| Frequency (MHz). | = Emission frequency in MHz |
| Reading (dBuV) | = Receiver reading |
| Correction Factor(dB/m) | = Antenna factor + Cable loss – Amplifier gain |
| Actual FS (dBuV/m) | = Reading (dBuV) + Corr. Factor (dB/m) |
| Limit (dBuV/m) | = Limit stated in standard |
| Margin(dB) | = Measured (dBuV/m) – Limits (dBuV/m) |
| Antenna Pole(V/H) | = Current carrying line of reading |



Above 1 GHz
GFSK

Operation Mode: TX(CH Low)
Temperature: 24°C
Humidity: 52% RH

Test Date: April 28, 2012
Tested by: Sunday Hu
Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1360.0000	48.27	-10.51	37.76	74.00	-36.24	V	peak
3220.0000	47.51	-5.45	42.06	74.00	-31.94	V	peak
4135.0000	45.68	-3.14	42.54	74.00	-31.46	V	peak
4810.0000	46.54	-0.62	45.92	74.00	-28.08	V	peak
6145.0000	43.91	3.58	47.49	74.00	-26.51	V	peak
7210.0000	45.25	5.00	50.25	74.00	-23.75	V	peak
1285.0000	48.95	-10.97	37.98	74.00	-36.02	H	peak
3040.0000	47.78	-5.87	41.91	74.00	-32.09	H	peak
4810.0000	47.35	-0.62	46.73	74.00	-27.27	H	peak
5785.0000	44.68	2.51	47.19	74.00	-26.81	H	peak
6025.0000	45.42	3.04	48.46	74.00	-25.54	H	peak
6805.0000	45.39	4.30	49.69	74.00	-24.31	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
 Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dBµV/m) = Limit stated in standard
 Margin (dB) = Result (dBµV/m)- Limit (dBµV/m)
 Pk = Peak Reading
 AV. = Average Reading
 Remark = Mark Peak Reading or Average Reading



Operation Mode: TX(CH Mid)

Test Date: April 28, 2012

Temperature: 24°C

Tested by: Sunday Hu

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1660.0000	48.35	-10.26	38.09	74.00	-35.91	V	peak
3820.0000	46.67	-3.85	42.82	74.00	-31.18	V	peak
4315.0000	45.67	-2.54	43.13	74.00	-30.87	V	peak
4885.0000	47.08	-0.38	46.70	74.00	-27.30	V	peak
6235.0000	44.49	3.80	48.29	74.00	-25.71	V	peak
6940.0000	44.87	4.37	49.24	74.00	-24.76	V	peak
1435.0000	48.07	-10.27	37.80	74.00	-36.20	H	peak
3715.0000	46.08	-3.85	42.23	74.00	-31.77	H	peak
4420.0000	45.22	-2.21	43.01	74.00	-30.99	H	peak
4795.0000	44.84	-0.68	44.16	74.00	-29.84	H	peak
6265.0000	44.57	3.77	48.34	74.00	-25.66	H	peak
7615.0000	45.09	5.82	50.91	74.00	-23.09	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
 Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dBµV/m) = Limit stated in standard
 Margin (dB) = Result (dBµV/m)- Limit (dBµV/m)
 Pk = Peak Reading
 AV = Average Reading
 Remark = Mark Peak Reading or Average Reading



Operation Mode: TX(CH High)

Test Date: April 28, 2012

Temperature: 24 °C

Tested by: Sunday Hu

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3535.0000	45.77	-4.21	41.56	74.00	-32.44	V	peak
4405.0000	45.34	-2.25	43.09	74.00	-30.91	V	peak
5740.0000	45.08	2.26	47.34	74.00	-26.66	V	peak
6220.0000	45.08	3.81	48.89	74.00	-25.11	V	peak
6925.0000	45.25	4.36	49.61	74.00	-24.39	V	peak
7990.0000	44.87	7.35	52.22	74.00	-21.78	V	peak
1600.0000	48.94	-10.31	38.63	74.00	-35.37	H	peak
3235.0000	47.55	-5.42	42.13	74.00	-31.87	H	peak
3895.0000	46.60	-3.73	42.87	74.00	-31.13	H	peak
4975.0000	45.16	-0.09	45.07	74.00	-28.93	H	peak
6400.0000	44.39	3.68	48.07	74.00	-25.93	H	peak
6940.0000	45.55	4.37	49.92	74.00	-24.08	H	peak

Notes:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Spectrum setting:
 - Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
- Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading

Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

Limit (dBµV/m) = Limit stated in standard

Margin (dB) = Result (dBµV/m)- Limit (dBµV/m)

Pk = Peak Reading

AV. = Average Reading

Remark = Mark Peak Reading or Average Reading



8DPSK

Operation Mode: TX(CH Low)

Test Date: April 28, 2012

Temperature: 24°C

Tested by: Sunday Hu

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1495.0000	48.69	-10.31	38.38	74.00	-35.62	V	peak
3415.0000	46.42	-4.97	41.45	74.00	-32.55	V	peak
4975.0000	45.32	-0.09	45.23	74.00	-28.77	V	peak
5830.0000	44.44	2.64	47.08	74.00	-26.92	V	peak
6115.0000	43.66	3.44	47.10	74.00	-26.90	V	peak
6670.0000	45.80	4.23	50.03	74.00	-23.97	V	peak
1390.0000	48.54	-10.31	38.23	74.00	-35.77	H	peak
3430.0000	46.54	-4.88	41.66	74.00	-32.34	H	peak
4225.0000	46.67	-2.85	43.82	74.00	-30.18	H	peak
5170.0000	44.64	0.50	45.14	74.00	-28.86	H	peak
5755.0000	45.73	2.34	48.07	74.00	-25.93	H	peak
6895.0000	45.05	4.35	49.40	74.00	-24.60	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
 Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dBµV/m) = Limit stated in standard
 Margin (dB) = Result (dBµV/m)- Limit (dBµV/m) ss
 Pk = Peak Reading
 AV. = Average Reading
 Remark = Mark Peak Reading or Average Reading



Operation Mode: TX(CH Mid)

Test Date: April 28, 2012

Temperature: 24°C

Tested by: Sunday Hu

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1375.0000	48.34	-10.41	37.93	74.00	-36.07	V	peak
3400.0000	46.86	-5.07	41.79	74.00	-32.21	V	peak
4240.0000	45.66	-2.80	42.86	74.00	-31.14	V	peak
4930.0000	45.15	-0.23	44.92	74.00	-29.08	V	peak
6055.0000	45.38	3.17	48.55	74.00	-25.45	V	peak
7210.0000	44.47	5.00	49.47	74.00	-24.53	V	peak
1570.0000	48.59	-10.31	38.28	74.00	-35.72	H	peak
4135.0000	46.14	-3.14	43.00	74.00	-31.00	H	peak
4975.0000	45.32	-0.09	45.23	74.00	-28.77	H	peak
5215.0000	45.72	0.62	46.34	74.00	-27.66	H	peak
6580.0000	44.41	4.14	48.55	74.00	-25.45	H	peak
6775.0000	45.17	4.29	49.46	74.00	-24.54	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
 Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dBµV/m) = Limit stated in standard
 Margin (dB) = Result (dBµV/m)- Limit (dBµV/m)
 Pk = Peak Reading
 AV. = Average Reading
 Remark = Mark Peak Reading or Average Reading



Operation Mode: TX(CH High)

Test Date: April 28, 2012

Temperature: 24 °C

Tested by: Sunday Hu

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2020.0000	47.79	-9.27	38.52	74.00	-35.48	V	peak
2980.0000	47.19	-6.10	41.09	74.00	-32.91	V	peak
4090.0000	46.65	-3.28	43.37	74.00	-30.63	V	peak
4765.0000	45.94	-0.84	45.10	74.00	-28.90	V	peak
5920.0000	44.11	2.79	46.90	74.00	-27.10	V	peak
6925.0000	44.97	4.36	49.33	74.00	-24.67	V	peak
1435.0000	48.34	-10.27	38.07	74.00	-35.93	H	peak
3655.0000	46.30	-3.82	42.48	74.00	-31.52	H	peak
4255.0000	45.79	-2.75	43.04	74.00	-30.96	H	peak
5860.0000	43.88	2.69	46.57	74.00	-27.43	H	peak
6415.0000	44.84	3.72	48.56	74.00	-25.44	H	peak
6895.0000	44.91	4.35	49.26	74.00	-24.74	H	peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.
5. Frequency (MHz) = Emission frequency in MHz
 Reading (dBµV/m) = Uncorrected Analyzer / Receiver Reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dBµV/m) = Limit stated in standard
 Margin (dB) = Result (dBµV/m)- Limit (dBµV/m)
 Pk = Peak Reading
 AV. = Average Reading
 Remark = Mark Peak Reading or Average Reading



6.9. POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.


MEASUREMENT EQUIPMENT USED

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
ESCI EMI TEST RECEIVE.ESCI	ROHDE&SCHWARZ	ESCI	100783	03/19/2012	03/19/2013
LISN	SCHAFFNER	NNB42	2001/001	05/26/2011	05/26/2012
LISN	EMCO	3825/2	8901-1459	03/19/2012	03/19/2013
Temp. / Humidity Meter	VICTOR	HTC-1	2	03/20/2012	03/20/2013
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

Remark: Each piece of equipment is scheduled for calibration once a year.



Test Configuration



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.



Test Data

Operation Mode: Normal Link Test Date: April 24,2012
Temperature: 22°C Humidity: 45% RH
Tested by: Mack Li

Table with 11 columns: Frequency (MHz), QuasiPeak Reading (dBuV), Average Reading (dBuV), Correction Factor (dB), QuasiPeak Result (dBuV), Average Result (dBuV), QuasiPeak Limit (dBuV), Average Limit (dBuV), QuasiPeak Margin (dB), Average Margin (dB), Line (L1/L2). It contains two groups of data rows for L1 and L2 lines.

Note:

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Peak detector, Quasi-peak detector and average detector.
3. "---" denotes the emission level was or more than 2dB below the Average limit.
4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
5. L1= Line One (Live Line)/ L2= Line Two (Neutral Line)