

# CFR 47 FCC Part 15.249

## TEST REPORT

Product : **RF 2.4G Wireless Keyboard**

Trade Name : N/A

Model Number : PSK-4571; ASK-4571; KSK-5211RFM

FCC ID : RAC4571A01

Prepared for

**PRECISION SQUARED TECHNOLOGY CORPORATION**  
5F-7, NO.2 JIAN BA ROAD, CHUNG HO CITY, TAIPEI HSIENG,  
TAIWAN, R.O.C.

TEL. : +886 2 8228 0125

FAX. : +886 2 8228 0105

Prepared by

**Interocean EMC Technology Corp.**  
244 No.5-2, Lin 1, Tin-Fu Tsun, Lin-Kou Hsiang,  
Taipei County, Taiwan, R.O.C.  
TEL.: +886 2 2600 6861  
FAX.: +886 2 2600 6859

**Remark :**

The test report consists of **37** pages in total. It shall not be reproduced except in full, without the written approval of IETC. This document may be altered or revised by IETC only, and shall be noted in the revision section of the document.  
The test results in the report only to the tested sample.

# Table of Contents

<b>1</b>	<b>General Information</b>	<b>4</b>
1.1	Description of Equipment Under Test	4
1.2	Table for Carrier Frequencies	5
1.3	Details of Tested Supporting System	6
1.4	Test Facility	8
1.5	Test Equipment	9
1.6	Summary of Measurement	10
1.7	Justification	11
<b>2</b>	<b>20dB Bandwidth test</b>	<b>12</b>
2.1	Limit	12
2.2	Configuration of Measurement	12
2.3	Test Procedure	12
2.4	Test Result	12
<b>3</b>	<b>RF Radiated spurious emission test</b>	<b>15</b>
3.1	Limit	15
3.2	Configuration of Measurement	15
3.3	Test Procedure	16
3.4	The description of operation mode	16
3.5	Test Result	16
<b>4</b>	<b>Emission on the Band Edge test</b>	<b>20</b>
4.1	Limit	20
4.2	Configuration of Measurement	20
4.3	Test Procedure	20
4.4	Test Result	20
<b>5</b>	<b>AC Power Line Conducted Emission test</b>	<b>23</b>
5.1	Limits	23
5.2	Configuration of Measurement	23
5.3	Test Procedures	23
5.4	Test Result	24
<b>6</b>	<b>Photographs of Test</b>	<b>27</b>
6.1	Radiated Emission Measurement	27
6.2	Power Line Conducted Emission Measurement	29
<b>7</b>	<b>Photographs of EUT</b>	<b>30</b>
7.1	Keyboard	30

# Statement of Compliance


**Applicant:** PRECISION SQUARED TECHNOLOGY CORPORATION  
**Manufacturer:** JING MOLD ELECTRONIC TECHNOLOGY (SHEN ZHEN) CO., LTD.  
**Product:** RF 2.4G Wireless Keyboard  
**Model No.:** PSK-4571; ASK-4571; KSK-5211RFM  
**Tested Power Supply:** DC 3V  
**Date of Final Test:** Apr. 25, 2011  
**Revision of Report:** Rev. 00  
**Configuration of Measurements and Standards Used :**  
FCC Rules and Regulations Part 15 Subpart C

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

- Note:** 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of IETC

Report Issued: 2011/06/13

Project Engineer:   
Elli Chang

Approved:   
Jerry Liu

# 1 General Information

## 1.1 Description of Equipment Under Test

<b>Product</b>	: RF 2.4G Wireless Keyboard
<b>Model Number</b>	: PSK-4571; ASK-4571; KSK-5211RFM
<b>Applicant</b>	: <b>PRECISION SQUARED TECHNOLOGY CORPORATION</b> 5F-7, NO.2 JIAN BA ROAD, CHUNG HO CITY, TAIPEI HSIENG, TAIWAN, R.O.C.
<b>Manufacturer</b>	: <b>JING MOLD ELECTRONIC TECHNOLOGY (SHEN ZHEN) CO., LTD.</b> Xinqiao, 3rd Industrial Zone, Shajing Town, Paoan District, Shenzhen City, Guangdong Province. China, Shenzhen, Guangdong, China.
<b>Operating Frequency</b>	: 2405MHz ~ 2477MHz
<b>Channel Number</b>	: Refer to section 1.2
<b>Type of Modulation</b>	: GFSK
<b>Antenna description</b>	: This device uses PCB Print antenna. The antenna is integral to the device, thereby meeting the requirement of FCC 15.203.
<b>Date of Test</b>	: Apr. 14 ~ 25, 2011
<b>Additional Description</b>	: 1. The model <b>PSK-4571</b> is representative selected in the test and included in this report. 2. All model included in this report, the difference is for different market; the rest parts are identical. 3. For more detail specification about EUT, please refer to the user's manual.

## 1.2 Table for Carrier Frequencies

CH No.	1	2	3	4	5	6	7	8	9	10	11
CF (MHz)	2405	2409	2413	2417	2421	2425	2429	2433	2437	2441	2445

CH No.	12	13	14	15	16	17	18	19
CF (MHz)	2449	2453	2457	2461	2465	2469	2473	2477

### 1.3 Details of Tested Supporting System

#### 1.3.1 Personal Computer

##### PC25

Model Number : ASUS-BM5320  
CPU Speed : Intel Core2 Duo E5200  
EMC Compliance : BSMI R31018  
Manufacturer : ASUS  
RAM : Anya 1G DDR2 800  
Hard Disk Driver : Seagate ST32500310AS 250G  
Switching Power Supply : Detal GPS-300AB C 300W  
USB 3.0 Card : Manufacturer: BUFFALO, Model: IFC-PCIE2U3-AP,  
SN: 15542291202517  
FCC, CE, VCCI, BSMI D33093  
Power Cord : Non-shielded, Detachable, 1.8m, w/o core

#### 1.3.2 Monitor

##### MT30

Model Number : CMV 92GH 19"  
Serial Number : 92GHAGCN9120289  
EMC Compliance : FCC, CE, BSMI: R31374, UL, TUV  
Manufacturer : CHIMEI  
Power Cord : Non-shielded, Detachable, 1.8m, w/o core  
D-Sub Cable : Non-shielded, Detachable, 1.8m, with core

#### 1.3.3 Modem

##### MD03

Model Number : 199450042  
Serial Number : 211-28E1-1100-3  
EMC Compliance : N/A  
Manufacturer : DATATRONICS  
Data Cable : Shielded, Detachable, 1.5m  
Power Adapter : Amigo, Model AM-12830A  
Non-Shielded, Detachable, 1.8m

1.3.4 Printer

PR06

Model Number : C20SX  
Serial Number : DW4E085945  
EMC Compliance : BSMI 3902E004  
Manufacturer : EPSON  
Data Cable : Shielded, Detachable, 1.8m  
Power Cord : Non-shielded, Un-detachable, 1.8m

1.3.5 Mouse

USB58

Model Number : CMS-721  
Serial Number : 02904439NF  
EMC Compliance : CE, FCC, C-Tick, BSMI  
Manufacturer : Aopen  
Data Cable : Non-shielded, detachable, 1.0m

1.3.6 Dongle

Model Number : PSX-2302  
Manufacturer : PERCISION

## 1.4 Test Facility

- Site Description** : ☑Conduction 2 ☑OATS 2
- Name of Firm** : Interocean EMC Technology Corp.
- Company web** : <http://www.ietc.com.tw>
- Site 1, 2, 3 Location** : No.5-2, Lin 1, Tin-Fu Tsun, Lin-Kou Hsiang,  
Taipei County, Taiwan, R.O.C.
- Site Filing** :
- Federal Communication Commissions – USA  
Registration No.: 96399 (OATS 1 & 2)  
Registration No.: 518958 (OATS 3)  
Designation No.: TW1020
  - Voluntary Control Council for Interference by Information  
Technology Equipment (VCCI) – Japan  
Member No.: 1349  
Registration No. (Conducted Room): C-1094  
Registration No. (Conducted Room): T-1562  
Registration No. (OATS 1): R-1040; G-274  
Registration No. (OATS 2): R-1041
  - Industry Canada (IC)  
OUR FILE: 46405-4437 Submission: 145171  
Registration No. (OATS 1): Site# 4437A-1  
Registration No. (OATS 2): Site# 4437A-2  
Registration No. (OATS 3): Site# 4437A-3
- Site Accreditation** :
- Bureau of Standards and Metrology and Inspection (BSMI) –  
Taiwan, R.O.C.  
Accreditation No.:  
SL2-IN-E-0026 for CNS13438 / CISPR22  
SL2-R1-E-0026 for CNS13439 / CISPR13  
SL2-R2-E-0026 for CNS13439 / CISPR13  
SL2-A1-E-0026 for CNS13783-1 / CISPR14-1  
SL2-L1-E-0026 for CNS 14115 / CISPR 15
  - Taiwan Accreditation Foundation (TAF)  
Accrditation No.: 1113
  - TÜV NORD  
Certificate No: TNTW0801R-03





## 1.5 Test Equipment

Instrument	Manufacturer	Model	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSP30	100002	2012/01/02
Biconical Antenna	Schwarzbeck	VHA 9103	2484	2011/10/08
Log Antenna	Schwarzbeck	UHALP 9108	A 0765	2011/10/08
Preamplifier	Agilent	8449B	3008A01434	2012/04/28
Preamplifier	Agilent	83050A	3950A00225	2012/09/07
Preamplifier	SCHAFFNER	CA30100	2	2011/10/28
Horn Antenna	COM-POWER	AH-118	10081	2012/05/19
Horn Antenna	Schwarzbeck	BBHA 9170	213	2012/07/19
Temp & Humidity chamber	GIAN FORCE	GTH-150-40-2P-U	MAA0305-012	2011/05/07
EMI Test Receiver	R&S	ESCS30	100134	2011/07/20
RF Cable	HARBOUR	M71/128-RG400	MILC17-1	2011/07/23
L.I.S.N.	Schaffner	MN2050D	1597	2011/06/10
L.I.S.N.	R&S	ESH3-Z5	829996/016	2011/01/09

Note: The above equipments are within the valid calibration period.

## 1.6 Summary of Measurement

Report Clause	Test Parameter	Reference Document CFR47 Part15	Results
2	20dB Bandwidth test	§15.215	Pass
3	RF Radiated spurious emission test	§15.249(a)(c)(d)	Pass
4	Emission on the Band Edge	§15.249(d)	Pass
5	AC Power Line Conducted Emission test	§15.207	Pass

## **1.7 Justification**


The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of the frequency band were all arrive limit requirement, thus we evaluate the EUT pass the specified test.

## 2 20dB Bandwidth test

### 2.1 Limit

According to FCC 15.215 requirement, there was no regulation limit and for reference purpose.

### 2.2 Configuration of Measurement



### 2.3 Test Procedure

The 20dB bandwidth per FCC §15.215 was measured using spectrum analyzer with the resolutions bandwidth set at 100 kHz, the video bandwidth  $\geq$  RBW, and the SPAN may equal to approximately 2 to 3 time the 20dB bandwidth.


### 2.4 Test Result

**PASS.**


The final test data is shown as following pages.

Test CH		20dB Bandwidth (MHz)
Modulation	Frq. (MHz)	
GFSK	2405	1.144
	2441	1.148
	2477	1.136

## 2405MHz 20dB BW




2441MHz 20dB BW



D.

2477MHz 20dB BW



### 3 RF Radiated spurious emission test

#### 3.1 Limit

According to §15.249 (a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

For intentional radiator, the radiated emission shall comply with §15.209(a).


Frequency (MHz)	Field strength dB( $\mu$ V/m)	Measurement distance (meters)
1.705~30.0	29.5	30
30 ~ 88	40	3
88~216	43.5	3
216~960	46	3
Above 960	54	3

#### 3.2 Configuration of Measurement

Measurement Frequency under 1GHz



### Measurement Frequency above 1GHz



### 3.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003.

Radiated emission measurements were performed from 30MHz to 25GHz. Spectrum Analyzer set as below: For frequency range from 30MHz to 1GHz: RBW=100kHz or greater. For frequencies above 1GHz: set RBW=VBW=1MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.

The EUT for testing is arranged on a wooden turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meter and down to 1 meter.

### 3.4 The description of operation mode

Setup EUT to continuously transmit signal with 100% duty cycle during the test period.

### 3.5 Test Result

**PASS.**

The final test data is shown on as following pages.



## Radiated spurious emission

### Fundamental Emissions

Low channel								
Frequency (MHz)	Antenna Polarization	Reading (dB $\mu$ V)	Preamplifier (dB)	Correction Factor (dB/m)	Corrected Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Det. Mode
2405	H	59.86	26.28	31.03	64.61	94	-29.39	PK
2405	V	59.02	26.28	31.03	63.77	94	-30.23	PK

Middle channel								
Frequency (MHz)	Antenna Polarization	Reading (dB $\mu$ V)	Preamplifier (dB)	Correction Factor (dB/m)	Corrected Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Det. Mode
2441	H	61.52	26.29	31.09	66.32	94	-27.68	PK
2441	V	59.46	26.29	31.09	64.26	94	-29.74	PK

High channel								
Frequency (MHz)	Antenna Polarization	Reading (dB $\mu$ V)	Preamplifier (dB)	Correction Factor (dB/m)	Corrected Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Det. Mode
2477	H	62.86	26.30	31.16	67.72	94	-26.28	PK
2477	V	60.35	26.30	31.16	65.21	94	-28.79	PK

Remark :

1. Corrected Level = Reading – Preamplifier + Correction Factor
2. Correction Factor = Antenna Factor + Cable Loss

## Radiated spurious emission

### Test Environment

Ambient temperature : 25.2°C

Relative humidity : 54%

### Radiated Emission below 1GHz

After verifying low, middle and high channel (2405MHz, 2441MHz and 2477MHz), the worse case was found at high channel, the data will present on report.

Worst case: High channel								
Frequency (MHz)	Antenna Polarization	Reading (dB $\mu$ V)	Preamplifier (dB)	Correction Factor (dB/m)	Corrected Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Det. Mode
120.000	H	48.63	33.00	13.83	29.46	43.52	-14.06	QP
166.320	H	44.70	33.36	16.80	28.14	43.52	-15.38	QP
240.000	H	49.68	33.40	19.65	35.93	46.02	-10.09	QP
336.000	H	48.96	33.56	17.30	32.70	46.02	-13.32	QP
433.230	H	49.88	34.20	20.15	35.83	46.02	-10.19	QP
480.000	H	47.00	33.90	21.22	34.32	46.02	-11.70	QP
65.600	V	52.56	33.30	7.42	26.68	40.00	-13.32	QP
115.630	V	48.52	33.00	13.89	29.41	43.52	-14.11	QP
165.320	V	44.62	33.35	17.67	28.94	43.52	-14.58	QP
240.000	V	47.62	33.40	21.05	35.27	46.02	-10.75	QP
336.000	V	48.85	33.56	17.24	32.53	46.02	-13.49	QP
480.000	V	46.56	33.90	20.92	33.58	46.02	-12.44	QP

Remark : Corrected Level = Reading + Correction Factor – Preamplifier

Correction Factor = Antenna Factor + Cable Loss

The present spurious only show those points are above noise level and the frequency range test from 30MHz to 1GHz.

## Radiated spurious emission

### Radiated Emission above 1GHz

Low Channel								
Frequency (MHz)	Antenna Polarization	Reading (dB $\mu$ V)	Preamp (dB)	Correction Factor (dB/m)	Corrected Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Det. Mode
4810	H	40.26	26.04	36.83	51.05	54	-2.95	PK
*7215	H	34.26	25.77	42.20	50.69	54	-3.31	PK
4810	V	40.85	26.04	36.83	51.64	54	-2.36	PK
*7215	V	33.63	25.77	42.20	50.06	54	-3.94	PK

Middle Channel								
Frequency (MHz)	Antenna Polarization	Reading (dB $\mu$ V)	Preamp (dB)	Correction Factor (dB/m)	Corrected Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Det. Mode
4882	H	39.69	26.02	37.04	50.71	54	-3.29	PK
*7323	H	33.62	25.71	42.51	50.42	54	-3.58	PK
4882	V	38.20	26.02	37.04	49.22	54	-4.78	PK
*7323	V	33.58	25.71	42.51	50.38	54	-3.62	PK

High Channel								
Frequency (MHz)	Antenna Polarization	Reading (dB $\mu$ V)	Preamp (dB)	Correction Factor (dB/m)	Corrected Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Det. Mode
4954	H	40.56	26.01	37.26	51.81	54	-2.19	PK
*7431	H	33.86	25.64	42.80	51.02	54	-2.98	PK
4954	V	38.21	26.01	37.26	49.46	54	-4.54	PK
*7431	V	34.00	25.64	42.80	51.16	54	-2.84	PK

Remark : Corrected Level = Reading + Correction Factor – Preamp

Correction Factor = Antenna Factor + Cable Loss

\* Mark indicated background noise level.


## 4 Emission on the Band Edge test

### 4.1 Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### 4.2 Configuration of Measurement

Measurement Frequency above 1GHz



### 4.3 Test Procedure

The EUT was setup to ANSI C63.4, 2003.

Set RBW =1M, VBW= RBW for peak, and VBW=10Hz for average.

The EUT for testing is arranged on a wooden turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meter and down to 1 meter.

### 4.4 Test Result


**PASS.**

The final test data is shown on as following pages.

## Band edge


Frequency	Restrict Freq. Band (MHz)	Detector Mode	Maximum level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2405	2310~2400	PK	48.86	54	-5.14
2477	2483.5~2500	PK	48.00	54	-6

## 2405MHz PK



2405MHz PK

## 2477MHz PK



2477MHz PK


## 5 AC Power Line Conducted Emission test

### 5.1 Limits

Frequency (MHz)	Quasi-Peak (dB $\mu$ V)	Average (dB $\mu$ V)
0.15 to 0.5	66 to 56	56 to 46
> 0.5 to 5	56	46
> 5 to 30	60	50

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 5.2 Configuration of Measurement



### 5.3 Test Procedures

- 1) The EUT was placed 80cm height above ground on a non-conductive table and vertical conducting plane located 40cm to the rear of the EUT.
- 2) The EUT was connected to the main power through Line Impedance Stabilization Networks (LISN). This setup provided a 50ohm/50mH coupling impedance for the measuring equipment. The auxiliary equipment will place in secondary LISN.
- 3) Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4/2003 on conducted measurement.

## **5.4 Test Result**

**PASS.**

The final test data is shown as following pages.



## Power Line Conducted Test Data


EUT: RF 2.4G Wireless Keyboard  
CLIENT: PRECISION  
MODEL: PSK-4571  
RATING: DC 3V  
Temperature: 26.0 °C  
Humidity: 54 %

POLARITY: Line  
DISTANCE:  
Serial No.:  
FILE/DATA#: PRECISION.emi/14  
OPERATOR: Fox  
TEST SITE: Conduction 2

Frequency (MHz)	Factor (dB)	Meter Reading (dBμV)		Emission Level (dBμV)		Limits (dBμV)		Margin (dB)	
		Quasi-Peak	Average	Quasi-Peak	Average	Quasi-Peak	Average	Quasi-Peak	Average
0.154	0.21	42.00	33.54	42.21	33.75	65.78	55.78	-23.57	-22.03
0.302	0.18	35.13	27.67	35.31	27.85	60.19	50.19	-24.88	-22.34
0.662	0.18	29.54	29.42	29.72	29.60	56.00	46.00	-26.28	-16.40
1.318	0.18	28.78	27.43	28.96	27.61	56.00	46.00	-27.04	-18.39
8.287	0.46	30.45	26.40	30.91	26.86	60.00	50.00	-29.09	-23.14
15.420	0.86	35.83	29.34	36.69	30.20	60.00	50.00	-23.31	-19.80

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



Test Mode: Working Mode

## Power Line Conducted Test Data

EUT: RF 2.4G Wireless Keyboard				POLARITY: Neutral					
CLIENT: PRECISION				DISTANCE:					
MODEL: PSK-4571				Serial No.:					
RATING: DC 3V				FILE/DATA#: PRECISION.emi/15					
Temperature: 26.0 °C				OPERATOR: Fox					
Humidity: 54 %				TEST SITE: Conduction2					
Frequency (MHz)	Factor (dB)	Meter Reading (dBμV)		Emission Level (dBμV)		Limits (dBμV)		Margin (dB)	
		Quasi-Peak	Average	Quasi-Peak	Average	Quasi-Peak	Average	Quasi-Peak	Average
0.150	0.22	43.64	41.51	43.86	41.73	66.00	56.00	-22.14	-14.27
0.295	0.19	29.90	29.41	30.09	29.60	60.38	50.38	-30.29	-20.78
0.662	0.18	31.53	30.06	31.71	30.24	56.00	46.00	-24.29	-15.76
1.322	0.18	28.54	28.15	28.72	28.33	56.00	46.00	-27.28	-17.67
7.978	0.40	35.22	35.00	35.62	35.40	60.00	50.00	-24.38	-14.60
19.673	0.89	37.94	32.17	38.83	33.06	60.00	50.00	-21.17	-16.94
Remark: 1. All readings are Quasi-Peak and Average values. 2. Factor = Insertion Loss + Cable Loss.									
Test Mode: Working Mode									