
Appendix for the Report

Dosimetric Assessment of the Alcatel OT-S853 (FCC ID: RAD026)

According to the FCC Requirements

SAR Distribution Plots

August 19, 2005
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
TCL&Alcatel mobile phones
32, avenue Kléber
F-92707 Colombes Cedex

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1 SAR DISTRIBUTION PLOTS, PCS 1900 HEAD 3

2 SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITH BLUETOOTH ACTIVATED 7

3 SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH HEADSET IN GSM MODE 8

4 SAR DISTRIBUTION PLOTS, GPRS 1900 BODY 9

5 SAR Z-AXIS SCANS (VALIDATION) 10

6 SAR Z-AXIS SCANS (MEASUREMENTS)..... 11

1 SAR Distribution Plots, PCS 1900 Head

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [xxxbp1m_1.da4](#)

DUT: Alcatel; Type: OT-S853; Serial: N/A

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³
 Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.144 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.39 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 0.198 W/kg

SAR(1 g) = 0.141 mW/g; SAR(10 g) = 0.088 mW/g

Maximum value of SAR (measured) = 0.154 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.39 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 0.219 W/kg

SAR(1 g) = 0.134 mW/g; SAR(10 g) = 0.080 mW/g

Maximum value of SAR (measured) = 0.146 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (August 15, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.8° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [xxxbp1m_2.da4](#)

DUT: Alcatel; Type: OT-S853;
Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.152 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.52 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 0.271 W/kg

SAR(1 g) = 0.160 mW/g; SAR(10 g) = 0.092 mW/g

Maximum value of SAR (measured) = 0.177 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (August 15, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.8° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [xxxbprm_1.da4](#)

DUT: Alcatel; Type: OT-S853; Serial: N/A
Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.167 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = 0.2 dB

Peak SAR (extrapolated) = 0.217 W/kg

SAR(1 g) = 0.158 mW/g; SAR(10 g) = 0.101 mW/g

Maximum value of SAR (measured) = 0.172 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = 0.2 dB

Peak SAR (extrapolated) = 0.277 W/kg

SAR(1 g) = 0.166 mW/g; SAR(10 g) = 0.098 mW/g

Maximum value of SAR (measured) = 0.181 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (August 15, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.8° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [xxxbprrm_2.da4](#)

DUT: Alcatel; Type: OT-S853;

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 17.03.2005

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.199 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.013 dB

Peak SAR (extrapolated) = 0.318 W/kg

SAR(1 g) = 0.190 mW/g; SAR(10 g) = 0.109 mW/g

Maximum value of SAR (measured) = 0.207 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (August 15, 2005; Ambient Temperature: 22.0 °C; Liquid Temperature : 21.8° C)

2 SAR Distribution Plots, PCS 1900 Head with Bluetooth activated

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [xxxbprm_2_BT.da4](#)

DUT: Alcatel; Type: OT-S853; Serial: N/A

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 17.03.2005

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.202 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.1 V/m; Power Drift = -0.080 dB

Peak SAR (extrapolated) = 0.324 W/kg

SAR(1 g) = 0.192 mW/g; SAR(10 g) = 0.109 mW/g

Maximum value of SAR (measured) = 0.212 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (August 15, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.8° C).

3 SAR Distribution Plots, PCS 1900 Body with headset in GSM mode

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [xxx**bphm**_3.da4](#)

DUT: Alcatel; Type: OT-S853; Serial: N/A

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.164 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.39 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 0.230 W/kg

SAR(1 g) = 0.151 mW/g; SAR(10 g) = 0.094 mW/g

Maximum value of SAR (measured) = 0.163 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, with headset and 20 mm distance (August 16, 2005; Ambient Temperature: 22.1° C; Liquid Temperature: 21.0° C).

4 SAR Distribution Plots, GPRS 1900 Body

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: xxx**bphm_1.da4**

DUT: Alcatel; Type: OT-S853; Serial: N/A

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.310 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.5 V/m; Power Drift = 0.069 dB

Peak SAR (extrapolated) = 0.951 W/kg

SAR(1 g) = 0.331 mW/g; SAR(10 g) = 0.118 mW/g

Maximum value of SAR (measured) = 0.320 mW/g




Fig. 7: SAR distribution for GPRS 1900 (Class 10), channel 661, body worn configuration, antenna towards the phantom, with 20 mm distance (August 16, 2005; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).

5 SAR z-axis scans (Validation)




Fig. 8: SAR versus liquid depth, 1900 MHz, head (August 15, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).




Fig. 9: SAR versus liquid depth, 1900 MHz, body (August 16, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).

6 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 10: SAR versus liquid depth, head: PCS 1900, channel 661, tilted position, right side of head, with BT (August 15, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.8° C).




Fig. 11: SAR versus liquid depth, body: GPRS 1900 (Class 10), channel 661, (August 16, 2005; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).