



47 CFR PART 15 C - BLUETOOTH

TEST REPORT

of

GSM/GPRS Dual-band Mobile Phone

Brand Name: ALCATEL
Model Name: B10CA
Report No.: SZ10060137E02
FCC ID.: RAD143

prepared for

TCT Mobile Limited

4/F, South Building, No.2966, Jinke Road, Zhangjiang High-Tech Park, Pudong, Shanghai, 201203,
P.R. China

prepared by

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory

3/F, Electronic Testing Building, Shahe Road, Xili,
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



Bluetooth®

CTIA Authorized Test Lab
LAB CODE 20081223-00

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

TABLE OF CONTENTS

1.	TEST CERTIFICATION.....	4
2.	GENERAL INFORMATION	5
2.1	EUT Description	5
2.2	Test Standards and Results	6
2.3	Facilities and Accreditations	7
2.3.1	Facilities	7
2.3.2	Test Environment Conditions.....	7
3.	47 CFR PART 15C REQUIREMENTS.....	8
3.1	Number of Hopping Frequency	8
3.1.1	Requirement	8
3.1.2	Test Description	8
3.1.3	Test Result.....	9
3.2	Peak Output Power	10
3.2.1	Requirement	10
3.2.2	Test Description	10
3.2.3	Test Result.....	10
3.3	20dB Bandwidth	13
3.3.1	Definition	13
3.3.2	Test Description	13
3.3.3	Test Result.....	13
3.4	Carried Frequency Separation.....	16
3.4.1	Definition	16
3.4.2	Test Description	16
3.4.3	Test Result.....	16
3.5	Time of Occupancy (Dwell time)	18
3.5.1	Requirement	18
3.5.2	Test Description	18
3.5.3	Test Result.....	18
3.6	Conducted Spurious Emissions	21
3.6.1	Requirement	21
3.6.2	Test Description	21

3.6.3	Test Result	21
3.7	Band Edge	25
3.7.1	Requirement	25
3.7.2	Test Description	25
3.7.3	Test Result	26
3.8	Conducted Emission	29
3.8.1	Requirement	29
3.8.2	Test Description	29
3.8.3	Test Result	30
3.9	Radiated Emission	32
3.9.1	Requirement	32
3.9.2	Test Description	32
3.9.3	Test Result	33
ANNEX A	PHOTOS OF TEST SETUP	41

Change History		
Issue	Date	Reason for change
1.0	July 16, 2010	First edition
2.0	July 22, 2010	Second edition: corrected the test data
3.0	July 31, 2010	Third edition: corrected the test data

1. TEST CERTIFICATION

Equipment under Test: GSM/GPRS Dual-band Mobile Phone

Brand Name: ALCATEL

Model Name: B10CA

FCC ID: RAD143

Applicant: TCT Mobile Limited

4/F, South Building, No. 2966, Jinke Road, Zhangjiang High-Tech Park,
Pudong, Shanghai, 201203, P.R. China

Manufacturer: TCT Mobile Limited

4/F, South Building, No. 2966, Jinke Road, Zhangjiang High-Tech Park,
Pudong, Shanghai, 201203, P.R. China

Test Standards: 47 CFR Part 15 Subpart C

Test Date(s): July 08, 2010 – July 12, 2010

Test Result: PASS

* We Hereby Certify That:

The equipment under test was tested by Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by: Mo Huina Dated: 2010.08.02
Mo Huina

Reviewed by: Luo Biao Dated: 2010.08.02
Luo Biao

Approved by: Shu Luan Dated: 2010.08.02
Shu Luan



2. GENERAL INFORMATION

2.1 EUT Description

EUT Type: GSM/GPRS Dual-band Mobile Phone
Serial No.....: (n.a, marked #1 by test site)
Hardware Version: PIO
Software Version: D12
Modulation Type.....: Frequency Hopping Spread Spectrum (FHSS)
Frequency: The frequency range used is 2402MHz - 2480MHz (79 channels, at intervals of 1MHz)
Battery: Accessory PN.: CAB30M0000C1
AC Adapter1: Accessory PN.: CBA30Y0AG0C1
AC Adapter2.....: Accessory PN.: CBA30Y0AG0C2
Earphone 1.....: Accessory PN.: CCA30B4000C0
Earphone 2.....: Accessory PN.: CCA30B4000C3
Earphone 3.....: Accessory PN.: CCA30B4000C2
Bluetooth earphone.....: MODEL:OT-BM82

Note 1: The EUT is a Mobile Phone, it contains Bluetooth Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth Module is $F(\text{MHz})=2402+1*n$ ($0 \leq n \leq 78$). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 39 (2441MHz) and 78 (2480MHz).

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-09 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.247(a)	Number of Hopping Frequency	PASS
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	20dB Bandwidth	PASS
4	15.247(a)	Carrier Frequency Separation	PASS
5	15.247(a)	Time of Occupancy (Dwell time)	PASS
6	15.247(c)	Conducted Spurious Emission	PASS
7	15.247(d)	Band Edge	PASS
8	15.207	Conducted Emission	PASS
9	15.209 15.247(c)	Radiated Emission	PASS

2.3 Facilities and Accreditations

2.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	86 - 106

3. 47 CFR PART 15C REQUIREMENTS


3.1 Number of Hopping Frequency

3.1.1 Requirement

According to FCC section 15.247(a)(1)(ii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 75 hopping frequencies.

3.1.2 Test Description

A. Connect Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. EUT and Equipment setup:

The EUT has its hopping function enable, and the spectrum analyzer settings are displayed below:

Span = 80MHz, RBW = 1MHz, VBW>=RBW, Sweep Time = auto, Detector function = peak, trace = max hold.

C. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Service Simulator	Agilent	E5515C	GB43130131	2009.09	1year
Spectrum Analyzer	Agilent	E7405A	US44210471	2009.09	1year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)	(n.a.)


3.1.3 Test Result

The Bluetooth Module operates at hopping-on test mode; the frequencies number employed is counted to verify the Module's using the number of hopping frequency.

A. Test Verdict:

Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Refer to Plot	Verdict
2400 - 2483.5	79	75	Plot A	PASS

B. Test Plot:



(Plot A: 2402MHz to 2480MHz)

3.2 Peak Output Power

3.2.1 Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.2.2 Test Description

A. Connect Setup

See section 3.1.2 A of this report.

B. EUT and Equipment setup:

The EUT was fixed in single channel, and the spectrum analyzer settings are displayed below:

Span = 5MHz, RBW = 1MHz, VBW>=RBW, Sweep Time = auto, Detector function = peak, trace = max hold.


3.2.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.


A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power			Limit		Verdict
		dBm	W	Refer to Plot	dBm	W	
0	2402	-2.29	0.59E-3	Plot A	30	1	PASS
39	2441	-2.19	0.60E-3	Plot B			PASS
78	2480	-0.79	0.83E-3	Plot C			PASS


B. Test Plot:



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)

3.3 20dB Bandwidth

3.3.1 Definition

The 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth ($10 \cdot \log 1\% = 20\text{dB}$) taking the total RF output power.

3.3.2 Test Description

A. Connect Setup

See section 3.1.2 A of this report.

B. EUT and Equipment setup:

The EUT was fixed in single channel, and the spectrum analyzer settings are displayed below:

Span = 2MHz, RBW = 10KHz, VBW \geq RBW, Sweep Time = auto, Detector function = peak, trace = max hold.

3.3.3 Test Result


The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.

A. Test Verdict:


The maximum 20dB bandwidth measured is 877.5KHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (KHz)	Refer to Plot
0	2402	791.25	Plot A
39	2441	787.5	Plot B
78	2480	877.5	Plot C


B. Test Plot:



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)

3.4 Carried Frequency Separation

3.4.1 Definition

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

3.4.2 Test Description

A. Connect Setup

See section 3.1.2 A of this report.

B. EUT and Equipment setup:


The EUT has its hopping function enable, and the spectrum analyzer settings are displayed below:

Span = 3MHz, RBW = 100KHz, VBW \geq RBW, Sweep Time = auto, Detector function = peak, trace = max hold.

3.4.3 Test Result

The Bluetooth Module operates at hopping-on test mode.

For any adjacent channels (e.g. the channel 39 and 40 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (877.5KHz, refer to section A), whichever is greater. So, the verdict is PASS.



(Plot A: Carried Frequency Separation)

3.5 Time of Occupancy (Dwell time)

3.5.1 Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.5.2 Test Description

A. Connect Setup

See section 3.1.2 A of this report.

B. EUT and Equipment setup:

The EUT was fixed in single channel, and the spectrum analyzer settings are displayed below:

Span = 0Hz, RBW = 1MHz, VBW>=RBW, Sweep Time = 10ms, Detector function = peak, trace = max hold.

3.5.3 Test Result

The average time of occupancy on any channel within the Period can be calculated with formulas (for DH5 package type):

$$\begin{aligned} \{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4s * \{\text{Number of Hopping Frequency}\} \end{aligned}$$


The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

A. Test Verdict:


Channel	Frequency (MHz)	Pulse Time		Total of Dwell (ms)	Limit (ms)	Verdict
		ms	Refer to Plot			
0	2402	2.95	Plot A	314.67	400	PASS
39	2441	2.975	Plot B	317.33		PASS
78	2480	2.95	Plot C	314.67		PASS

B. Test Plot:


Note: the following plots record the Pulse Time of the Module carrier.



(Plot A: Channel = 2402)



(Plot B: Channel = 2441)



(Plot C: Channel = 2480)

3.6 Conducted Spurious Emissions

3.6.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2 Test Description

A. Connect Setup

See section 3.1.2 A of this report.

B. EUT and Equipment setup:

The EUT was fixed in single channel, and the spectrum analyzer settings are displayed below:

RBW = 100KHz, VBW>=RBW, Sweep Time = auto, Detector function = peak, trace = max hold.

3.6.3 Test Result


The Bluetooth Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-50.01	Plot A.1/A.2	-6.59	-26.6	PASS
39	2441	-51.93	Plot B.1/B.2	-4.41	-24.4	PASS
78	2480	-52.43	Plot C.1/C.2	-3.83	-23.8	PASS

B. Test Plot:


Note: the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 0, 30MHz to 4GHz)




(Plot A.2: Channel = 0, 4GHz to 25GHz)




(Plot B.1: Channel = 39, 30MHz to 4GHz)



(Plot B.2: Channel = 39, 4GHz to 25GHz)



(Plot C.1: Channel = 78, 30MHz to 4GHz)



(Plot C.2: Channel = 78, 4GHz to 25GHz)


3.7 Band Edge

3.7.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.7.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength..

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2009.9	1year
Receiver	Agilent	E7405A	US44210471	2009.9	1year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2009.9	2year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2009.9	1year

3.7.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

The antenna factor at 2440M is 32.5dB.


The cable loss plus the amplifier at 2440M is -29.7dB.

So the offset added here is 2.8dB.


A. Test Verdict:.

Channel	Frequency (MHz)	Max. Emission in the Restricted Bands (dB μ V/m)		Limit (dB μ V/m)		Verdict
		PK	AV	PK	AV	
0	2402	40.25	38.43	74	54	PASS
78	2480	38.51	37.31	74	54	PASS


B. Test Plot:




(Plot A1: Channel = 0 PEAK)



(Plot A2: Channel = 0 AVERAGE)



(Plot B1: Channel = 78 PEAK)



(Plot B2: Channel = 78 AVERAGE)

3.8 Conducted Emission

3.8.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2 Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2003

The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The factors of the site are calibrated to correct the reading.


During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:


Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2009.09	1year
LISN	Schwarzbeck	NSLK 8127	812744	2009.09	1year
Service Supplier	R&S	CMU200	100448	2009.09	1year
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)

3.8.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.



(Plot A: L Phase)



(Plot B: N Phase)

3.9 Radiated Emission

3.9.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)	Detector
30 - 88	100	3	QP
88 - 216	150	3	QP
216 - 960	200	3	QP
960 - 1000	500	3	QP
Above 1000	500	3	AV

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

3.9.2 Test Description

A. Test Setup:



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2003). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna: In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength, the azimuth range of turntable was 0° to 360°, the receive antenna has two polarizations horizontal and vertical. When doing measurements above 1GHz, the EUT was placed within the 3dB beam width range of the horn antenna.

The EUT operates at hopping-off test mode, and was tested in 3 orthogonal positions as recommended in ANSI C63.4 for Radiated Emissions and the worst-case data was presented below.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2009.9	1year
Receiver	Agilent	E7405A	US44210471	2009.9	1year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2009.9	2year
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2009.9	1year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2009.9	1year
Test Antenna - circular	R&S	AC004R1	0749.3000.03	2009.9	1year

3.9.3 Test Result

A. Test Verdict for Harmonics:

The Fundamental Emissions

The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dB μ V/m)		Antenna Polarization	Refer to Plot
		PK	AV		
0	2402	75.36	71.08	Horizontal	Plot A.1
		86.9	79.87	Vertical	Plot A.2
39	2441	80.13	74.96	Horizontal	Plot B.1
		94.35	86.24	Vertical	Plot B.2

Channel	Frequency (MHz)	Fundamental Emission (dB μ V/m)		Antenna Polarization	Refer to Plot
		PK	AV		
78	2480	82.95	77.63	Horizontal	Plot C.1
		92.29	83.06	Vertical	Plot C.2

The un-wanted Emissions:

Test result of channel: 0 (2402MHz)

Frequency (MHz)	PK Level (dB μ V/m)	Limits (dB μ)	Margin (dB)	Ant Factor	cable loss	Azimuth (deg)	Hght (cm)	Ant Pol
720.6 M	35.3	46	-10.7	20.2	-31.7	206	100	H
912.7 M	34.79	46	-11.21	22.3	-31.88	70	100	H
2503.2M	46.32	54	-7.68	37.4	-29.6	106	100	H
2763.5M	46.25	54	-7.75	35.9	-30.76	205	100	H
3163.7M	47.03	54	-6.97	34.5	-26.7	190	100	H
37.8 M	30.03	40	-9.97	11.76	-35.6	357	100	V
720.6 M	35.21	46	-10.79	20.2	-31.7	186	100	V
2503.1	46.28	54	-7.72	37.04	-29.6	56	100	V
2763.5	46.15	54	-7.85	35.9	-30.76	307	100	V
3163.3	46.86	54	-7.14	34.5	-26.7	72	100	V

Test result of channel: 39 (2442MHz)

Frequency (MHz)	PK Level	Limits (dB μ)	Margin (dB)	Ant Factor	cable loss	Azimuth (deg)	Hght (cm)	Ant Pol
720.6 M	34.93	46	-11.07	20.2	-31.7	108	100	H
912.7 M	34.68	46	-11.32	22.3	-31.88	5	100	H
2503.2M	45.36	54	-8.64	37.4	-29.6	47	100	H
2763.5M	44.9	54	-9.1	35.9	-27.76	153	100	H
3163.7M	45.27	54	-8.73	34.5	-26.7	7	100	H
37.8 M	29.88	40	-10.12	11.76	-35.6	66	100	V
720.6 M	35.64	46	-10.36	20.2	-31.7	344	100	V
2513.4	45.87	54	-8.13	37.03	-29.6	260	100	V
2763.5	44.65	54	-9.35	35.9	-27.76	359	100	V
3163.3	45.37	54	-8.63	34.5	-26.7	25	100	V


Test result of channel: 78 (2480MHz)

Frequency (MHz)	PK Level (dB μ)	Limits (dB μ)	Margin (dB)	Ant Factor	cable loss	Azimuth (deg)	Hght (cm)	Ant Pol
37.8 M	25.56	40	-14.44	11.76	-35.6	343	100	H
720.6 M	34.65	46	-11.35	20.2	-31.7	106	100	H
912.7 M	35.1	46	-10.9	22.3	-31.9	135	100	H
2521.7M	45.86	54	-8.14	37.03	-29.7	160	100	H
3803.5M	45.03	54	-8.97	32.2	-25.4	190	100	H
3905.2M	45.2	54	-8.8	32	-23.4	80	100	H
34.9 M	34.6	40	-5.4	11.05	-35.6	0	100	V
65.9 M	33.85	40	-6.15	7.41	-36.1	0	100	V
2521.7M	45.98	54	-8.02	37.03	-29.8	350	100	V
3803.5M	45.01	54	-8.99	32.2	-25.4	341	100	V
3905.2M	45.24	54	-8.76	32	-23.4	284	100	V


Please note the cable loss contains the gain of the amplifier.

Test Plots for the Whole Measurement Frequency Range:


Plots for Channel = 0



(Plot A.0: 9kHz to 30MHz)




(Plot A.1: Antenna Horizontal)




(Plot A.2: Antenna Vertical)


Plot for Channel = 39



(Plot B.0: 9kHz to 30MHz)




(Plot B.1: Antenna Horizontal)




(Plot B.2: Antenna Vertical)


Plot for Channel = 78



(Plot C.0: 9kHz to 30MHz)




(Plot C.1: Antenna Horizontal)




(Plot C.2: Antenna Vertical)

Annex A Photos of Test Setup

1. Conducted Emission



2. Band Edge Setup



3. Radiated Measurement Setup



4. Conducted Measurement Setup



**** END OF REPORT ****