



FCC PART 15C TEST REPORT

No. 2011TAR152

for

TCT Mobile Limited

GSM/GPRS Dual bands mobile phone

Model Name: B11C US

Marketing Name: one touch 665A

FCC ID: RAD155

With

Hardware Version: PIO

Software Version: V721

Issued Date: 2011-04-21



No. DGA-PL-114/01-02

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

Shouxiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China 100191

Tel:+86(0)10-62304633-2678, Fax:+86(0)10-62304793 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

CONTENTS

CONTENTS	2
1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT.....	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION.....	6
4. REFERENCE DOCUMENTS.....	7
4.1. DOCUMENTS SUPPLIED BY APPLICANT	7
4.2. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS	9
6.1. SUMMARY OF TEST RESULTS.....	9
6.2. STATEMENTS.....	9
7. TEST EQUIPMENTS UTILIZED	10
ANNEX A: MEASUREMENT RESULTS.....	11
A.1. MEASUREMENT METHOD	11
A.2. PEAK OUTPUT POWER - CONDUCTED	12
A.3. FREQUENCY BAND EDGES - CONDUCTED.....	13
A.4. CONDUCTED EMISSION.....	20
A.5. RADIATED EMISSION.....	44
A.6. TIME OF OCCUPANCY (DWELL TIME)	66
A.7. 20dB BANDWIDTH.....	76
A.8. CARRIER FREQUENCY SEPARATION	82
A.9. NUMBER OF HOPPING CHANNELS.....	84
A.10. AC POWERLINE CONDUCTED EMISSION.....	88

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: Shouxiang Science Building, No 51, Xueyuan Road, Haidian District,
Beijing, P.R.China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793

1.2. Testing Environment

Normal Temperature: 15-35°C
Extreme Temperature: -20/+55°C
Relative Humidity: 20-75%

1.3. Project data

Project Leader: Zi Xiaogang
Testing Start Date: Mar 27, 2011
Testing End Date: Apr 21, 2011

1.4. Signature

Zi Xiaogang

(Prepared this test report)

Sun Xiangqian

(Reviewed this test report)

Lu Bingsong

Deputy Director of the laboratory

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Country: China
Telephone: 0086 21 68897541
Fax: 0086 21 50801070

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/GPRS Dual bands mobile phone
Model Name	B11C US
Marketing Name	one touch 665A
FCC ID	RAD155
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	GFSK/ $\pi/4$ DQPSK/8DPSK
Number of Channels	79
Power Supply	3.8V DC by Battery

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N11	012584000001445	PIO	V721
N12	012584000002062	PIO	V721

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	
AE2	Battery	
AE3	Battery	
AE4	Charger	
AE5	Charger	

AE1

Model	CAB22D0000C1
Manufacturer	BYD
Capacitance	650mAh
Nominal Voltage	3.8V

AE2

Model	CAB22B0000C1
Manufacturer	BYD
Capacitance	750mAh
Nominal Voltage	3.8V

AE3

Model	CAB22B0010C1
Manufacturer	BYD
Capacitance	850mAh
Nominal Voltage	3.8V

AE4

Model	CBA3120AG0C2
Manufacturer	Tenbao
Length of DC line	120cm

AE5

Model	CBA3120AG0C1
Manufacturer	BYD
Length of DC line	120cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/GPRS Dual bands mobile phone with integrated antenna. It consists of normal options: lithium battery, charger Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz. Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	July 10, 2008 Edition
ANSI C63.4		2003
FCC Public Notice DA 00-705	Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems	March 2000

5. LABORATORY ENVIRONMENT

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

Abbreviations used in this clause:

- P** Pass, The EUT complies with the essential requirements in the standard.
F Fail, The EUT does not comply with the essential requirements in the standard
NA Not Applicable, The test was not applicable
NP Not Performed, The test was not performed by TMC

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
Peak Output Power - Conducted	15.247 (b)(1)	P
Frequency Band Edges	15.247 (d)	P
Conducted Emission	15.247 (d)	P
Radiated Emission	15.247, 15.205, 15.209	P
Time of Occupancy (Dwell Time)	15.247 (a) (1)(iii)	P
20dB Bandwidth	15.247 (a)(1)	NA
Carrier Frequency Separation	15.247 (a)(1)	P
Number of hopping channels	15.247 (a)(b)(iii)	P
AC Powerline Conducted Emission	15.107, 15.207	P

Please refer to **ANNEX A** for detail.

The measurement is made according to Public notice DA 00-705 and ANSI C63.4.

6.2. Statements

TMC has evaluated the test cases requested by the applicant /manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

7. Test Equipments Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Vector Signal Analyzer	FSU26	200030	Rohde & Schwarz	2011-06-18
2	Bluetooth Tester	CBT32	100649	Rohde & Schwarz	2011-08-03

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Test Receiver	ESI40	831564/002	Rohde & Schwarz	2011-08-11
2	EMI Antenna	VULB 9163	9163 301	Schwarzbeck	2011-08-29
3	EMI Antenna	3117	00034610	EMCO	2011-08-30
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2011-08-01
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2011-08-01
6	Universal Radio Communication Tester	CMU200	105948	Rohde & Schwarz	2011-08-13
7	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	2011-08-12
8	Pre-amplifier(18GHz)	/	1005277	Rohde & Schwarz	/
9	Pre-amplifier(26.5GHz)	/	1005277	Rohde & Schwarz	/

Anechoic chamber

Fully anechoic chamber by Frankonia German.


ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

The measurement is made according to Public notice DA 00-705 and ANSI C63.4.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements


The measurement is made according to Public notice DA 00-705 and ANSI C63.4

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;



A.2. Peak Output Power - Conducted

Measurement Limit:

Standard	Limit (dBm)
FCC Part 15.247(b)(1)	< 30

The measurement is made according to Public notice DA 00-705 and ANSI C63.4.

Test Condition

Hopping Mode	RBW	VBW	Span	Sweeptime
Hopping OFF	1MHz	1MHz	5MHz	2.5ms

Measurement Results:

For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	6.82	6.14	6.87	P

For π/4 DQPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	6.20	5.57	6.56	P

For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	6.36	5.69	6.74	P

Conclusion: PASS

A.3. Frequency Band Edges - Conducted Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

The measurement is made according to Public notice DA 00-705 and ANSI C63.4.

Measurement Result:**For GFSK**

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.1	-44.37	P
	Hopping ON	Fig.2	-53.88	P
78	Hopping OFF	Fig.3	-59.10	P
	Hopping ON	Fig.4	-59.44	P

For π/4 DQPSK


Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.5	-54.31	P
	Hopping ON	Fig.6	-54.85	P
78	Hopping OFF	Fig.7	-60.85	P
	Hopping ON	Fig.8	-58.84	P

For 8DPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.9	-53.29	P
	Hopping ON	Fig.10	-55.43	P
78	Hopping OFF	Fig.11	-60.58	P
	Hopping ON	Fig.12	-58.09	P


Conclusion: PASS

Test graphs as below




Date: 15.APR.2011 08:51:38

Fig.1. Frequency Band Edges: GFSK, Channel 0, Hopping Off




Date: 15.APR.2011 08:53:58

Fig.2. Frequency Band Edges: GFSK, Channel 0, Hopping On




Date: 15.APR.2011 08:51:56

Fig.3. Frequency Band Edges: GFSK, Channel 78, Hopping Off




Date: 15.APR.2011 08:56:01

Fig.4. Frequency Band Edges: GFSK, Channel 78, Hopping On




Date: 15.APR.2011 09:13:51


 Fig.5. Frequency Band Edges: $\pi/4$ DQPSK, Channel 0, Hopping Off


Date: 15.APR.2011 09:16:11

 Fig.6. Frequency Band Edges: $\pi/4$ DQPSK, Channel 0, Hopping On




Date: 15.APR.2011 09:14:09

 Fig.7. Frequency Band Edges: $\pi/4$ DQPSK, Channel 78, Hopping Off



Date: 15.APR.2011 09:18:14

 Fig.8. Frequency Band Edges: $\pi/4$ DQPSK, Channel 78, Hopping On




Date: 15.APR.2011 09:36:00

Fig.9. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off




Date: 15.APR.2011 09:38:20

Fig.10. Frequency Band Edges: 8DPSK, Channel 0, Hopping On



Date: 15.APR.2011 09:36:17

Fig.11. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off



Date: 15.APR.2011 09:40:23

Fig.12. Frequency Band Edges: 8DPSK, Channel 78, Hopping On

A.4. Conducted Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

The measurement is made according to Public notice DA 00-705 and ANSI C63.4

Measurement Results:

Measurement Results:

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.13	P
	30 MHz ~ 1 GHz	Fig.14	P
	1 GHz ~ 3 GHz	Fig.15	P
	3 GHz ~ 10 GHz	Fig.16	P
	10 GHz ~ 26 GHz	Fig.17	P
Ch 39 2441 MHz	Center Frequency	Fig.18	P
	30 MHz ~ 1 GHz	Fig.19	P
	1 GHz ~ 3 GHz	Fig.20	P
	3 GHz ~ 10 GHz	Fig.21	P
	10 GHz ~ 26 GHz	Fig.22	P
Ch 78 2480 MHz	Center Frequency	Fig.23	P
	30 MHz ~ 1 GHz	Fig.24	P
	1 GHz ~ 3 GHz	Fig.25	P
	3 GHz ~ 10 GHz	Fig.26	P
	10 GHz ~ 26 GHz	Fig.27	P


For π/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.28	P
	30 MHz ~ 1 GHz	Fig.29	P
	1 GHz ~ 3 GHz	Fig.30	P
	3 GHz ~ 10 GHz	Fig.31	P
	10 GHz ~ 26 GHz	Fig.32	P
Ch 39 2441 MHz	Center Frequency	Fig.33	P
	30 MHz ~ 1 GHz	Fig.34	P
	1 GHz ~ 3 GHz	Fig.35	P
	3 GHz ~ 10 GHz	Fig.36	P
	10 GHz ~ 26 GHz	Fig.37	P
Ch 78 2480 MHz	Center Frequency	Fig.38	P
	30 MHz ~ 1 GHz	Fig.39	P

	1 GHz ~ 3 GHz	Fig.40	P
	3 GHz ~ 10 GHz	Fig.41	P
	10 GHz ~ 26 GHz	Fig.42	P


For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.43	P
	30 MHz ~ 1 GHz	Fig.44	P
	1 GHz ~ 3 GHz	Fig.45	P
	3 GHz ~ 10 GHz	Fig.46	P
	10 GHz ~ 26 GHz	Fig.47	P
Ch 39 2441 MHz	Center Frequency	Fig.48	P
	30 MHz ~ 1 GHz	Fig.49	P
	1 GHz ~ 3 GHz	Fig.50	P
	3 GHz ~ 10 GHz	Fig.51	P
	10 GHz ~ 26 GHz	Fig.52	P
Ch 78 2480 MHz	Center Frequency	Fig.53	P
	30 MHz ~ 1 GHz	Fig.54	P
	1 GHz ~ 3 GHz	Fig.55	P
	3 GHz ~ 10 GHz	Fig.56	P
	10 GHz ~ 26 GHz	Fig.57	P

Conclusion: PASS
Test graphs as below



Date: 15.APR.2011 08:56:20

Fig.13. Conducted spurious emission: GFSK, Channel 0,2402MHz




Date: 15.APR.2011 08:56:36

Fig.14. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz




Date: 15.APR.2011 08:57:08

Fig.15. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz




Date: 15.APR.2011 08:57:24

Fig.16. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz




Date: 15.APR.2011 08:57:40

Fig.17. Conducted spurious emission: GFSK, Channel 0, 10GHz - 26GHz




Date: 15.APR.2011 08:57:56

Fig.18. Conducted spurious emission: GFSK, Channel 39, 2441MHz




Date: 15.APR.2011 08:58:12

Fig.19. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz




Date: 15.APR.2011 08:58:43

Fig.20. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz




Date: 15.APR.2011 08:59:00

Fig.21. Conducted spurious emission: GFSK, Channel 39, 3GHz – 10GHz




Date: 15.APR.2011 08:59:16

Fig.22. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz




Date: 15.APR.2011 08:59:32

Fig.23. Conducted spurious emission: GFSK, Channel 78, 2480MHz




Date: 15.APR.2011 08:59:48

Fig.24. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz




Date: 15.APR.2011 09:00:19

Fig.25. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz




Date: 15.APR.2011 09:00:35

Fig.26. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz




Date: 15.APR.2011 09:00:52

Fig.27. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz



Date: 15.APR.2011 09:18:32

 Fig.28. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 2402MHz


Date: 15.APR.2011 09:18:49

 Fig.29. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 30MHz - 1GHz




Fig.30. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 1GHz - 3GHz






Fig.31. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 3GHz - 10GHz




Date: 15.APR.2011 09:19:54

 Fig.32. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 10GHz - 26GHz



Date: 15.APR.2011 09:20:10

 Fig.33. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 2441MHz




Date: 15.APR.2011 09:20:27

Fig.34. Conducted spurious emission: π/4 DQPSK, Channel 39, 30MHz - 1GHz




Date: 15.APR.2011 09:20:59

Fig.35. Conducted spurious emission: π/4 DQPSK, Channel 39, 1GHz - 3GHz




Date: 15.APR.2011 09:21:15


 Fig.36. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 3GHz - 10GHz


Date: 15.APR.2011 09:21:32

 Fig.37. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 10GHz – 26GHz




Date: 15.APR.2011 09:21:49


 Fig.38. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 2480MHz


Date: 15.APR.2011 09:22:05

 Fig.39. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 30MHz - 1GHz




Date: 15.APR.2011 09:22:37


 Fig.40. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 1GHz - 3GHz


Date: 15.APR.2011 09:22:53

 Fig.41. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 3GHz - 10GHz




Date: 15.APR.2011 09:23:10

 Fig.42. Fig.30 Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 10GHz - 26GHz



Date: 15.APR.2011 09:40:41

Fig.43. Conducted spurious emission: 8DPSK, Channel 0,2402MHz




Date: 15.APR.2011 09:40:58

Fig.44. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz




Date: 15.APR.2011 09:41:30

Fig.45. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz



Date: 15.APR.2011 09:41:46

Fig.46. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz



Date: 15.APR.2011 09:42:03

Fig.47. Conducted spurious emission: 8DPSK, Channel 0,10GHz - 26GHz




Fig.48. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz






Fig.49. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz




Date: 15.APR.2011 09:43:08

Fig.50. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz




Date: 15.APR.2011 09:43:24

Fig.51. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz




Date: 15.APR.2011 09:43:41

Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Date: 15.APR.2011 09:43:58

Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz




Date: 15.APR.2011 09:44:14

Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Date: 15.APR.2011 09:44:46

Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz



Date: 15.APR.2011 09:45:02

Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz



Date: 15.APR.2011 09:45:19

Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 26GHz

A.5. Radiated Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to Public notice DA 00-705 and ANSI C63.4

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

Measurement Results:

A "reference path loss" is established and the A_{RPL} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable los.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{RPL}}$$

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	30 MHz ~ 1 GHz	Fig.58	P
	1 GHz ~ 4 GHz	Fig.59	P
	4 GHz ~ 18 GHz	Fig.60	P
Ch 39 2441 MHz	30 MHz ~ 1 GHz	Fig.61	P
	1 GHz ~ 4 GHz	Fig.62	P
	4 GHz ~ 18 GHz	Fig.63	P

Ch 78 2480 MHz	30 MHz ~ 1 GHz	Fig.64	P
	1 GHz ~ 4 GHz	Fig.65	P
	4 GHz ~ 18 GHz	Fig.66	P
Power	2.38GHz~2.4GHz---L	Fig.67	P
Power	2.45GHz~2.5GHz---H	Fig.68	P
For all channels	18 GHz ~ 26 GHz	Fig.69	P

Forπ/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	30 MHz ~ 1 GHz	Fig.70	P
	1 GHz ~ 4 GHz	Fig.71	P
	4 GHz ~ 18 GHz	Fig.72	P
Ch 39 2441 MHz	30 MHz ~ 1 GHz	Fig.73	P
	1 GHz ~ 4 GHz	Fig.74	P
	4 GHz ~ 18 GHz	Fig.75	P
Ch 78 2480 MHz	30 MHz ~ 1 GHz	Fig.76	P
	1 GHz ~ 4 GHz	Fig.77	P
	4 GHz ~ 18 GHz	Fig.78	P
Power	2.38GHz~2.4GHz---L	Fig.79	P
Power	2.45GHz~2.5GHz---H	Fig.80	P
For all channels	18 GHz ~ 26 GHz	Fig.81	P

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	30 MHz ~ 1 GHz	Fig.82	P
	1 GHz ~ 4 GHz	Fig.83	P
	4 GHz ~ 18 GHz	Fig.84	P
Ch 39 2441 MHz	30 MHz ~ 1 GHz	Fig.85	P
	1 GHz ~ 4 GHz	Fig.86	P
	4 GHz ~ 18 GHz	Fig.87	P
Ch 78 2480 MHz	30 MHz ~ 1 GHz	Fig.88	P
	1 GHz ~ 4 GHz	Fig.89	P
	4 GHz ~ 18 GHz	Fig.90	P
Power	2.38GHz~2.4GHz---L	Fig.91	P
Power	2.45GHz~2.5GHz---H	Fig.92	P
For all channels	18 GHz ~ 26 GHz	Fig.93	P

GFSK Ch 0

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2398.798	49.7	8.7	41	HORIZONTAL
3713.427	48.88	14.5	34.38	VERTICAL
3705.411	48.87	14.3	34.57	VERTICAL
3715.431	48.86	14.5	34.36	HORIZONTAL
3707.415	48.85	14.3	34.55	VERTICAL
3699.399	48.83	14.2	34.63	VERTICAL

GFSK Ch 39

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3699.399	41.28	14.2	27.08	VERTICAL
3713.427	41.28	14.5	26.78	VERTICAL
3701.403	41.27	14.3	26.97	VERTICAL
3707.415	41.27	14.3	26.97	VERTICAL
3697.395	41.26	14.2	27.06	VERTICAL
3709.419	41.25	14.3	26.95	VERTICAL

GFSK Ch 78

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3713.427	48.88	14.5	34.38	VERTICAL
3715.431	48.86	14.5	34.36	VERTICAL
3707.415	48.85	14.3	34.55	VERTICAL
3699.399	48.83	14.2	34.63	VERTICAL
3709.419	48.83	14.3	34.53	VERTICAL
3717.435	48.83	14.5	34.33	VERTICAL

 $\pi/4$ DQPSK Ch 0

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3713.427	48.88	14.5	34.38	VERTICAL
3705.411	48.87	14.3	34.57	VERTICAL
3715.431	48.86	14.5	34.36	VERTICAL
3707.415	48.85	14.3	34.55	VERTICAL
3699.399	48.83	14.2	34.63	VERTICAL
3709.419	48.83	14.3	34.53	VERTICAL

 $\pi/4$ DQPSK Ch 39

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3709.419	48.93	14.3	34.63	VERTICAL
3713.427	48.88	14.5	34.38	VERTICAL
3705.411	48.87	14.3	34.57	VERTICAL
3715.431	48.86	14.5	34.36	VERTICAL
3707.415	48.85	14.3	34.55	VERTICAL
3699.399	48.83	14.2	34.63	VERTICAL

$\pi/4$ DQPSK Ch 78

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3705.411	48.87	14.3	34.57	VERTICAL
3715.431	48.86	14.5	34.36	VERTICAL
3707.415	48.85	14.3	34.55	VERTICAL
3709.419	48.83	14.3	34.53	VERTICAL
3701.403	48.82	14.3	34.52	VERTICAL
3719.439	48.81	14.5	34.31	VERTICAL

8DPSK Ch 0

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3713.427	48.88	14.5	34.38	VERTICAL
3705.411	48.87	14.3	34.57	HORIZONTAL
3707.415	48.85	14.3	34.55	VERTICAL
3699.399	48.83	14.2	34.63	VERTICAL
3709.419	48.83	14.3	34.53	VERTICAL
3717.435	48.83	14.5	34.33	VERTICAL

8DPSK Ch 39

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3705.411	48.87	14.3	34.57	VERTICAL
3707.415	48.85	14.3	34.55	VERTICAL
3699.399	48.83	14.2	34.63	VERTICAL
3709.419	48.83	14.3	34.53	VERTICAL
3717.435	48.83	14.5	34.33	VERTICAL
3701.403	48.82	14.3	34.52	VERTICAL

8DPSK Ch 78

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
3711.423	48.9	14.5	34.4	VERTICAL
3713.427	48.88	14.5	34.38	VERTICAL
3705.411	48.87	14.3	34.57	VERTICAL
3715.431	48.86	14.5	34.36	VERTICAL
3707.415	48.85	14.3	34.55	VERTICAL
3699.399	48.83	14.2	34.63	VERTICAL

Conclusion: PASS
Test graphs as below:




Fig.58. Radiated emission: GFSK, Channel 0, 30 MHz - 1 GHz




Fig.59. Radiated emission: GFSK, Channel 0, 1 GHz - 4 GHz




Fig.60. Radiated emission: GFSK, Channel 0, 4 GHz - 18 GHz




Fig.61. Radiated emission: GFSK, Channel 39, 30 MHz - 1 GHz




Fig.62. Radiated emission: GFSK, Channel 39, 1 GHz - 4 GHz




Fig.63. Radiated emission: GFSK, Channel 39, 4 GHz - 18 GHz




Fig.64. Radiated emission: GFSK, Channel 78, 30 MHz - 1 GHz




Fig.65. Fig.47 Radiated emission: GFSK, Channel 78, 1 GHz - 4 GHz




Fig.66. Radiated emission: GFSK, Channel 78, 4 GHz - 18 GHz




Fig.67. Radiated emission (Power): GFSK, low channel




Fig.68. Radiated emission (Power) GFSK, high channel














Fig.69. Radiated emission: GFSK, 18 GHz - 26 GHz



Fig.70. Radiated emission: $\pi/4$ DQPSK, Channel 0, 30 MHz - 1 GHzFig.71. Radiated emission: $\pi/4$ DQPSK, Channel 0, 1 GHz - 4 GHz


 Fig.72. Radiated emission: $\pi/4$ DQPSK, Channel 0, 4 GHz - 18 GHz

 Fig.73. Radiated emission: $\pi/4$ DQPSK, Channel 39, 30 MHz - 1 GHz

Fig.74. Radiated emission: $\pi/4$ DQPSK, Channel 39, 1 GHz - 4 GHzFig.75. Radiated emission: $\pi/4$ DQPSK, Channel 39, 4 GHz - 18 GHz


 Fig.76. Radiated emission: $\pi/4$ DQPSK, Channel 78, 30 MHz - 1 GHz

 Fig.77. Radiated emission: $\pi/4$ DQPSK, Channel 78, 1 GHz - 4 GHz

Fig.78. Radiated emission: $\pi/4$ DQPSK, Channel 78, 4 GHz - 18 GHzFig.79. Radiated emission (Power): $\pi/4$ DQPSK, low channel


 Fig.80. Radiated emission (Power): $\pi/4$ DQPSK, high channel

 Fig.81. Radiated emission: $\pi/4$ DQPSK, 18 GHz - 26 GHz




Fig.82. Radiated emission: 8DPSK, Channel 0, 30 MHz - 1 GHz




Fig.83. Radiated emission: 8DPSK, Channel 0, 1 GHz - 4 GHz




Fig.84. Radiated emission: 8DPSK, Channel 0, 4 GHz - 18 GHz




Fig.85. Radiated emission: 8DPSK, Channel 39, 30 MHz - 1 GHz




Fig.86. Radiated emission: 8DPSK, Channel 39, 1 GHz - 4 GHz




Fig.87. Radiated emission: 8DPSK, Channel 39, 4 GHz - 18 GHz




Fig.88. Radiated emission: 8DPSK, Channel 78, 30 MHz - 1 GHz




Fig.89. Radiated emission: 8DPSK, Channel 78, 1 GHz - 4 GHz




Fig.90. Radiated emission: 8DPSK, Channel 78, 4 GHz - 18 GHz




Fig.91. Radiated emission (Power): 8DPSK, low channel




Fig.92. Radiated emission (Power): 8DPSK, high channel




Fig.93. Radiated emission: 8DPSK, 18 GHz - 26 GHz

A.6. Time of Occupancy (Dwell Time)

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

The measurement is made according to Public notice DA 00-705 and ANSI C63.4

Measurement Result:

For GFSK

Channel	Packet	Dwell Time (ms)	Conclusion
39	DH1	Fig.94	P
		Fig.95	
	DH3	Fig.96	P
		Fig.97	
	DH5	Fig.98	P
		Fig.99	

For π/4 DQPSK


Channel	Packet	Dwell Time (ms)	Conclusion
39	DH1	Fig.100	P
		Fig.101	
	DH3	Fig.102	P
		Fig.103	
	DH5	Fig.104	P
		Fig.105	

For 8DPSK

Channel	Packet	Dwell Time (ms)	Conclusion
39	DH1	Fig.106	P
		Fig.107	
	DH3	Fig.108	P
		Fig.109	
	DH5	Fig.110	P
		Fig.111	


Conclusion: PASS

Test graphs as below:




Date: 15.APR.2011 09:02:30

Fig.94. Time of occupancy (Dwell Time): Channel 39, Packet DH1




Date: 15.APR.2011 09:02:17

Fig.95. Number of Transmissions Measurement:Channel 39,Packet DH1




Date: 15.APR.2011 09:03:48

Fig.96. Time of occupancy (Dwell Time): Channel 39, Packet DH3




Date: 15.APR.2011 09:03:36

Fig.97. Number of Transmissions Measurement:Channel 39,Packet DH3



Date: 15.APR.2011 09:05:07

Fig.98. Time of occupancy (Dwell Time): Channel 39, Packet DH5



Date: 15.APR.2011 09:04:55

Fig.99. Number of Transmissions Measurement:Channel 39,Packet DH5




Fig.100. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1






Fig.101. Number of Transmissions Measurement:Channel 39,Packet 2-DH1




Date: 15.APR.2011 09:25:56

Fig.102. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3




Date: 15.APR.2011 09:25:44

Fig.103. Number of Transmissions Measurement:Channel 39,Packet 2-DH3




Date: 15.APR.2011 09:27:15

Fig.104. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5




Date: 15.APR.2011 09:27:03

Fig.105. Number of Transmissions Measurement:Channel 39,Packet 2-DH5




Date: 15.APR.2011 09:46:44

Fig.106. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Date: 15.APR.2011 09:46:32

Fig.107. Number of Transmissions Measurement:Channel 39,Packet 3-DH1




Date: 15.APR.2011 09:48:06

Fig.108. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3




Date: 15.APR.2011 09:47:54

Fig.109. Number of Transmissions Measurement:Channel 39,Packet 3-DH3



Date: 15.APR.2011 09:49:25

Fig.110. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5



Date: 15.APR.2011 09:49:13

Fig.111. Number of Transmissions Measurement:Channel 39,Packet 3-DH5

A.7. 20dB Bandwidth**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

The measurement is made according to Public notice DA 00-705 and ANSI C63.4

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:**For GFSK**

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.112	913.46	NA
39	Fig.113	870.19	NA
78	Fig.114	870.19	NA

For π/4 DQPSK


Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.115	1259. 62	NA
39	Fig.116	1264.42	NA
78	Fig.117	1250.00	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.118	1264.42	NA
39	Fig.119	1254.81	NA
78	Fig.120	1264.42	NA


Conclusion: NA

Test graphs as below:




Date: 15.APR.2011 09:05:41

Fig.112. 20dB Bandwidth: GFSK, Channel 0




Date: 15.APR.2011 09:06:13

Fig.113. 20dB Bandwidth: GFSK, Channel 39




Date: 15.APR.2011 09:06:45

Fig.114. 20dB Bandwidth: GFSK, Channel 78




Date: 15.APR.2011 09:27:48

Fig.115. 20dB Bandwidth: π/4 DQPSK, Channel 0




Date: 15.APR.2011 09:28:20

 Fig.116. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 39



Date: 15.APR.2011 09:28:52

 Fig.117. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78




Date: 15.APR.2011 09:49:59

Fig.118. 20dB Bandwidth: 8DPSK, Channel 0



Date: 15.APR.2011 09:50:30

Fig.119. 20dB Bandwidth: 8DPSK, Channel 39



Date: 15.APR.2011 09:51:02

Fig.120. 20dB Bandwidth: 8DPSK, Channel 78

A.8. Carrier Frequency Separation

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth

The measurement is made according to Public notice DA 00-705 and ANSI C63.4

* Comment: This limit should be over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth, whichever is greater.

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)	Conclusion
39	Fig.121	995.19

For $\pi/4$ DQPSK


Channel	Carrier frequency separation (kHz)	Conclusion
39	Fig.122	1168.27

For 8DPSK

Channel	Carrier frequency separation (kHz)	Conclusion
39	Fig.123	1024.04


Conclusion: PASS

Test graphs as below:




Date: 15.APR.2011 09:08:49

Fig.121. Carrier frequency separation measurement: GFSK, Channel 39



Date: 15.APR.2011 09:30:56

 Fig.122. Carrier frequency separation measurement: $\pi/4$ DQPSK, Channel 39


Date: 15.APR.2011 09:53:07

Fig.123. Carrier frequency separation measurement: 8DPSK, Channel 39

A.9. Number of Hopping Channels

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

The measurement is made according to Public notice DA 00-705 and ANSI C63.4

Measurement Result:

For GFSK

Channel	Number of hopping channels	Conclusion
0~39	Fig.124	
40~78	Fig.125	P

For π/4 DQPSK


Channel	Number of hopping channels	Conclusion
0~39	Fig.126	
40~78	Fig.127	P

For 8DPSK

Channel	Number of hopping channels	Conclusion
0~39	Fig.128	
40~78	Fig.129	P


Conclusion: PASS

Test graphs as below:




Date: 15.APR.2011 09:10:54

Fig.124. Number of hopping frequencies: GFSK, Channel 0 - 39




Date: 15.APR.2011 09:12:55

Fig.125. Number of hopping frequencies: GFSK, Channel 40 - 78




Date: 15.APR.2011 09:33:00

Fig.126. Number of hopping frequencies: π/4 DQPSK, Channel 0 - 39




Date: 15.APR.2011 09:35:03

 Fig.127. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 40 - 78


Date: 15.APR.2011 09:55:10

Fig.128. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Date: 15.APR.2011 09:57:13

Fig.129. Number of hopping frequencies: 8DPSK, Channel 40 - 78

A.10. AC Powerline Conducted Emission**Test Condition**

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:**Bluetooth (Quasi-peak Limit)**

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		With Charger	
0.15 to 0.5	66 to 56	Fig.130	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Bluetooth (Average Limit)


Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)	Conclusion
		With Charger	
0.15 to 0.5	56 to 46	Fig.130	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to Public notice DA 00-705 and ANSI C63.4

Conclusion: PASS

Test graphs as below:


MEASUREMENT RESULT: "11A01097_7C_fin QP"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.150000	51.20	10.1	66	14.8	N	GND
0.378424	36.90	10.1	58	21.4	N	GND
0.397728	40.80	10.1	58	17.1	N	GND
0.422196	38.40	10.1	57	19.0	N	GND
0.708314	37.70	10.1	56	18.3	N	GND
3.129621	35.20	10.1	56	20.8	N	GND

MEASUREMENT RESULT: "11A01097_7C_fin AV"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.310136	30.70	10.1	50	19.2	N	GND
0.332507	32.40	10.1	49	16.9	N	GND
0.374678	27.40	10.1	48	21.0	N	GND
0.708314	26.00	10.1	46	20.0	N	GND
1.352430	22.90	10.1	46	23.1	N	GND
1.393410	24.30	10.1	46	21.7	N	GND

*** END OF REPORT BODY ***