



TEST REPORT

No. 2011TAR454

for

TCT Mobile Limited

GSM/GPRS/EDGE Quad bands mobile phone

Model Name: Diamond_US

Marketing Name: one touch 810A

FCC ID: RAD201

with

Hardware Version: PIO

Software Version: swC17

Issued Date: Sep 05, 2011

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China,100191.

Tel:+86(0)10-62304633-2604, Fax:+86(0)10-62304793, Email:welcome@emcite.com, web: www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS.....	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS	9
7. TEST EQUIPMENTS UTILIZED.....	10
ANNEX A: MEASUREMENT RESULTS.....	11
A.1 OUTPUT POWER (§22.913(A)/§24.232(B)).....	11
A.2 EMISSION LIMIT (§2.1051/§22.917§24.238).....	18
A.3 CONDUCTED EMISSION (§15.107§15.207)	23
A.4 FREQUENCY STABILITY (§2.1055/§24.235).....	30
A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I))	32
A.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B)).....	44
A.7 BAND EDGE COMPLIANCE (§22.917(B)/§24.238(B)).....	56
A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238).....	62

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai
Dian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: Aug 07, 2011
Testing End Date: Sep 05, 2011

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/GPRS/EDGE Quad bands mobile phone
Model Name	Diamond_US
Marketing Name	one touch 810A
FCC ID	RAD201
Frequency	GSM 850MHz; PCS 1900MHz
Antenna	Internal
Power supply	Battery or Charger (AC Adaptor)
Output power	32.53 dBm maximum EIRP measured for GSM1900
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N03	012818000020611	PIO	swC17
N04	012818000020587	PIO	swC17

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Charger	/
AE3	Charger	/

AE1

Model	CAB3120000C1
Manufacturer	BYD
Capacitance	850mAh
Nominal Voltage	3.8V

AE2

Model	CBA3120AG0C2
Manufacturer	BYD
Length of DC line	120cm

AE3

Model	CBA3002AG0C1
Manufacturer	BYD
Length of DC line	120cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/GPRS/EDGE Quad bands mobile phone with integrated antenna. It consists of normal options: lithium battery, charger Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Conducted Emission	15.107/15.207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P

7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESCI	100766	R&S	2011-12-06
2	Test Receiver	ESI40	831564/002	R&S	2011-12-12
3	BiLog Antenna	VULB9163	9163-175	Schwarzbeck	2011-12-05
4	BiLog Antenna	VULB9163	9163-302	Schwarzbeck	2011-12-10
5	Signal Generator	SMB100A	102063	R&S	2011-12-05
7	LISN	ESH2-Z5	829991/012	R&S	2011-12-20
8	Spectrum Analyzer	FSU26	200030	R&S	2011-12-18
9	Spectrum Analyzer	FSU46	100054	R&S	2011-12-14
10	Universal Radio Communication Tester	CMU200	100680	R&S	2011-12-23
11	Universal Radio Communication Tester	CMU200	109914	R&S	2011-12-21
12	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS	2012-12-31
13	Dual-Ridge Waveguide Horn Antenna	3117	00119021	ETS	2013-12-09
14	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2011-12-01
15	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2011-12-01
16	Climatic chamber	PL-2G	343074	ESPEC	2011-12-15

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER (§22.913(a)/§24.232(b))

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band;824.4MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

A.1.2.2 Test Condition

RBW	VBW	Sweep Time	Span
1MHz	1MHz	300ms	10MHz

GSM850

Limit

	Power step	Nominal Peak output power (dBm)	Target (dB)
GSM	5	33dBm(2W)	33±1
GPRS	3	33dBm(2W)	33±1
EGPRS	6	27dBm(0.5W)	27±1

Measurement result

GSM (GMSK)

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	5	32.50
836.6	5	32.56
848.8	5	32.60

GPRS (GMSK, 1Slot)

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	3	32.49
836.6	3	32.55
848.8	3	32.61

EGPRS (8PSK, 1Slot)

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	6	26.65
836.6	6	26.65
848.8	6	26.64

ANALYZER SETTINGS: VBW=RBW=1MHz; SPAN=10MHz;SWT=300ms

PCS1900

Limit

	Power step	Nominal Peak output power (dBm)	Target (dB)
GSM	0	30dBm(1W)	29±1
GPRS	3	30dBm(1W)	29±1
EGPRS	5	26dBm(0.4W)	25±1

Measurement result

GSM (GMSK)

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	0	29.21
1880.0	0	29.35
1909.8	0	29.43

GPRS (GMSK, 1Slot)

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	3	29.27
1880.0	3	29.40
1909.8	3	29.48

EGPRS (8PSK, 1Slot)

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	5	25.27
1880.0	5	25.41
1909.8	5	25.42

ANALYZER SETTINGS: VBW=RBW=1MHz; SPAN=10MHz;SWT=300ms

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.
The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} + P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

GSM 850-ERP 22.913(a)

Limits

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result

GSM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dBm)	Peak ERP(dBm)	Polarization
824.20	-17.31	2.27	-53.00	0.84	2.15	30.43	V
836.60	-16.40	2.26	-53.00	0.90	2.15	31.29	V
848.80	-16.70	2.32	-53.00	0.95	2.15	30.88	V

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dBm)	Peak ERP(dBm)	Polarization
824.20	-17.62	2.27	-53.00	0.84	2.15	30.12	V
836.60	-16.36	2.26	-53.00	0.90	2.15	31.33	V
848.80	-16.72	2.32	-53.00	0.95	2.15	30.86	V

EGPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dBm)	Peak ERP(dBm)	Polarization
824.20	-21.05	2.27	-53.00	0.84	2.15	26.69	V
836.60	-21.49	2.26	-53.00	0.90	2.15	26.20	V
848.80	-22.46	2.32	-53.00	0.95	2.15	25.12	V

Frequency:836.60 MHz

Peak ERP(dBm)= P_{Mea}(-16.36dBm)- P_{cl}(2.26dB)- P_{Ag}(-53dB)-G_a (0.90dB)-2.15dBm=31.33dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

PCS1900-EIRP 24.232(b)

Limits

	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)
EGPRS	5	≤33dBm (2W)

Measurement result

GSM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Peak EIRP(dBm)	Polarization
1850.20	-18.11	3.92	-50.00	-4.56	32.53	H
1880.00	-20.40	3.64	-50.00	-4.43	30.39	H
1909.80	-21.82	3.61	-50.00	-4.30	28.87	H

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Peak EIRP(dBm)	Polarization
1850.20	-18.87	3.92	-50.00	-4.56	31.77	H
1880.00	-19.97	3.64	-50.00	-4.43	30.82	H
1909.80	-20.71	3.61	-50.00	-4.30	29.98	H

EGPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Peak EIRP(dBm)	Polarization
1850.20	-22.46	3.92	-50.00	-4.56	28.18	H
1880.00	-24.17	3.64	-50.00	-4.43	26.62	H
1909.80	-24.92	3.61	-50.00	-4.30	25.77	H

Frequency: 1850.2MHz

Peak EIRP(dBm)= P_{Mea}(-18.11dBm)- P_{cl}(3.92dB)-P_{Ag}(-50dB)-G_a (-4.56dB) =32.53dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT (§2.1051/§22.917§24.238)


A.2.1 Measurement Method

The measurement procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the PCS1900 band and GSM850 band.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

GSM Mode Channel 128/824.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1648.39	-33.53	3.39	-5.45	2.15	-33.62	-13.00	H
2472.72	-39.32	4.21	-5.32	2.15	-40.36	-13.00	H
3296.74	-44.24	5.41	-7.41	2.15	-44.39	-13.00	V
4121.17	-54.88	6.76	-8.57	2.15	-55.22	-13.00	V
7733.49	-65.24	10.00	-11.63	2.15	-65.76	-13.00	V
8628.36	-66.93	9.29	-12.30	2.15	-66.07	-13.00	V

GSM Mode Channel 190/836.6MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1673.36	-37.41	3.36	-5.34	2.15	-37.58	-13.00	H
2509.44	-39.28	4.32	-5.42	2.15	-40.33	-13.00	H
3346.47	-45.06	5.59	-7.53	2.15	-45.27	-13.00	V
4182.70	-54.95	6.72	-8.61	2.15	-55.21	-13.00	V
6186.80	-58.39	7.01	-10.35	2.15	-57.20	-13.00	H
8977.25	-63.69	8.62	-12.58	2.15	-61.88	-13.00	H

GSM Mode Channel 251/848.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1737.10	-53.00	3.62	-5.06	2.15	-53.71	-13.00	H
2546.51	-39.62	4.37	-5.52	2.15	-40.62	-13.00	V
3395.07	-48.54	5.44	-7.65	2.15	-48.48	-13.00	V
4244.32	-54.72	6.62	-8.65	2.15	-54.84	-13.00	H
5942.05	-49.76	6.79	-10.18	2.15	-48.52	-13.00	H
7067.01	-67.61	8.82	-11.14	2.15	-67.44	-13.00	H

GSM Mode Channel 512/1850.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3700.45	-40.32	5.78	-8.14	-37.96	-13.00	V
5550.94	-58.59	6.76	-10.02	-55.33	-13.00	H
8854.02	-68.04	8.64	-12.48	-64.20	-13.00	V
10245.89	-62.70	8.36	-12.45	-58.61	-13.00	V
12951.73	-49.39	8.47	-13.24	-44.62	-13.00	V
14499.28	-56.85	8.89	-13.60	-52.14	-13.00	H

GSM Mode Channel 661/1880.0MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3760.03	-39.85	6.47	-8.21	-38.11	-13.00	H
5640.20	-53.63	6.79	-10.06	-50.36	-13.00	H
9399.76	-57.04	8.22	-12.60	-52.66	-13.00	V
11375.84	-61.99	8.46	-12.40	-58.05	-13.00	V
13160.25	-46.55	8.57	-13.46	-41.66	-13.00	V
15111.03	-56.72	8.82	-13.48	-52.06	-13.00	H

GSM Mode Channel 810/1909.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3819.21	-37.10	6.21	-8.28	-35.03	-13.00	H
5729.46	-51.58	6.84	-10.09	-48.33	-13.00	V
7650.02	-66.31	9.51	-11.55	-64.27	-13.00	V
10374.05	-63.56	8.53	-12.47	-59.62	-13.00	V
13368.41	-43.96	8.38	-13.67	-38.67	-13.00	V
17637.58	-58.99	10.42	-13.38	-56.03	-13.00	V

A.3 CONDUCTED EMISSION (§15.107§15.207)

The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.


A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.3.2 Measurement result

GSM850MHz-AE2




MEASUREMENT RESULT: "A06048_8C1_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line dB	PE
0.172500	51.20	10.1	65	13.6	L1	GND
0.600000	41.60	10.1	56	14.4	N	GND
2.060755	38.10	10.1	56	17.9	L1	GND
3.196243	42.40	10.1	56	13.6	L1	GND
5.315916	35.80	10.2	60	24.2	L1	GND
16.740650	36.00	10.3	60	24.0	L1	GND

MEASUREMENT RESULT: "A06048_8C1_fin AV"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
0.258000	32.80	10.1	52	18.7	L1	GND
0.600000	23.30	10.1	46	22.7	L1	GND
0.640500	36.10	10.1	46	9.9	N	GND
0.685500	34.90	10.1	46	11.1	N	GND
0.987000	33.50	10.1	46	12.5	N	GND
3.260649	32.00	10.1	46	14.0	L1	GND

GSM850MHz-AE3




MEASUREMENT RESULT: "A06048_8C2_fin QP"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
0.159000	58.70	10.1	66	6.8	L1	GND
0.213000	53.80	10.1	63	9.3	L1	GND
0.267000	48.90	10.1	61	12.3	L1	GND
2.346086	33.60	10.1	56	22.4	L1	GND
2.793548	36.50	10.1	56	19.5	L1	GND
3.196243	33.90	10.1	56	22.1	L1	GND

MEASUREMENT RESULT: "A06048_8C2_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
2.133972	22.10	10.1	46	23.9	L1	GND
2.187858	20.80	10.1	46	25.2	L1	GND
2.346086	23.40	10.1	46	22.6	L1	GND
2.793548	26.70	10.1	46	19.3	L1	GND
2.849839	24.00	10.1	46	22.0	L1	GND
3.410347	27.30	10.1	46	18.7	L1	GND

PCS1900MHz-AE2




MEASUREMENT RESULT: "A06048_19C1_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.172500	50.60	10.1	65	14.3	N	GND
0.600000	41.50	10.1	56	14.5	N	GND
0.987000	36.80	10.1	56	19.2	N	GND
2.936410	40.70	10.1	56	15.3	N	GND
4.835294	34.20	10.2	56	21.8	L1	GND
15.227098	36.30	10.2	60	23.7	L1	GND

MEASUREMENT RESULT: "A06048_19C1_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line dB	PE
0.298500	38.20	10.1	50	12.1	N	GND
0.384000	34.90	10.1	48	13.3	N	GND
0.640500	36.20	10.1	46	9.8	N	GND
0.685500	34.60	10.1	46	11.4	N	GND
0.942000	32.10	10.1	46	13.9	N	GND
3.293337	31.10	10.1	46	14.9	N	GND

PCS1900MHz-AE3




MEASUREMENT RESULT: "A06048_19C2_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line dB	PE
0.159000	54.80	10.1	66	10.7	L1	GND
0.208500	50.10	10.1	63	13.2	L1	GND
2.793548	42.80	10.1	56	13.2	L1	GND
2.892801	43.00	10.1	56	13.0	L1	GND
3.342984	41.70	10.1	56	14.3	L1	GND
3.844006	41.20	10.1	56	14.8	L1	GND

MEASUREMENT RESULT: "A06048_19C2_fin AV"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
2.793548	36.80	10.1	46	9.2	L1	GND
3.055943	32.30	10.1	46	13.7	L1	GND
3.133109	35.00	10.1	46	11.0	L1	GND
3.244427	33.00	10.1	46	13.0	L1	GND
3.293337	34.00	10.1	46	12.0	L1	GND
3.342984	30.30	10.1	46	15.7	L1	GND

MP3




MEASUREMENT RESULT: "A06048_MC_fin QP"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
0.168000	53.00	10.1	65	12.1	L1	GND
0.559500	40.80	10.1	56	15.2	N	GND
0.946500	40.70	10.1	56	15.3	N	GND
3.260649	40.90	10.1	56	15.1	L1	GND
5.450149	34.70	10.2	60	25.3	L1	GND
18.869387	30.80	10.3	60	29.2	N	GND

MEASUREMENT RESULT: "A06048_MC_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.217500	35.10	10.1	53	17.8	L1	GND
0.298500	20.10	10.1	50	30.2	L1	GND
0.384000	35.10	10.1	48	13.1	N	GND
0.559500	29.20	10.1	46	16.8	L1	GND
0.951000	32.70	10.1	46	13.3	N	GND
3.260649	32.70	10.1	46	13.3	N	GND

CAMERA



MEASUREMENT RESULT: "A06048_PC_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.168000	51.10	10.1	65	13.9	L1	GND
0.766500	33.60	10.1	56	22.4	L1	GND
0.987000	34.60	10.1	56	21.4	L1	GND
3.102012	40.50	10.1	56	15.5	L1	GND
5.786303	34.70	10.2	60	25.3	L1	GND
16.908475	37.50	10.3	60	22.5	L1	GND

MEASUREMENT RESULT: "A06048_PC_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line dB	PE
0.172500	27.40	10.1	55	27.4	N	GND
0.258000	37.40	10.1	52	14.0	N	GND
0.343500	33.30	10.1	49	15.8	N	GND
0.726000	32.00	10.1	46	14.0	N	GND
0.942000	34.10	10.1	46	11.9	N	GND
3.293337	33.60	10.1	46	12.4	N	GND

A.4 FREQUENCY STABILITY **(§2.1055/§24.235)**

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900, channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

GSM 850

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-20	0.023
3.8	-21	0.024
4.2	-19	0.022

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-21	0.024
-20	-20	0.023
-10	-20	0.023
0	-19	0.022
10	-19	0.022
20	-19	0.022
30	-20	0.023
40	-20	0.023
50	-21	0.024

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-43	0.038
3.8	-42	0.037
4.2	-39	0.034

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-43	0.038
-20	-42	0.037
-10	-42	0.037
0	-39	0.034
10	-39	0.034
20	-39	0.034
30	-42	0.037
40	-42	0.037
50	-43	0.038

A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
824.2	248.397
836.6	248.397
848.8	246.794


GSM 850

Channel 128-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 07:24:08

Channel 190-Occupied Bandwidth (-20dBc BW)



Date: 11.AUG.2011 07:24:35

Channel 251-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 07:25:03

GPRS 850(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
824.2	246.794
836.6	248.397
848.8	248.397


GPRS 850

Channel 128-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 08:22:46

Channel 190-Occupied Bandwidth (-20dBc BW)



Date: 11.AUG.2011 08:23:13

Channel 251-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 08:23:40

EGPRS 850(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20Bc BW)(kHz)
824.2	248.397
836.6	250.000
848.8	250.000


EGPRS 850

Channel 128-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 08:33:52

Channel 190-Occupied Bandwidth (-20dBc BW)



Date: 11.AUG.2011 08:34:20

Channel 251-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 08:34:47

PCS 1900(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
1850.2	250.000
1880.0	246.794
1909.8	248.397


PCS 1900

Channel 512-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 07:46:50

Channel 661-Occupied Bandwidth (-20dBc BW)



Date: 11.AUG.2011 07:47:17

Channel 810-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 07:47:43

GPRS 1900(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
1850.2	246.794
1880.0	246.794
1909.8	245.192


GPRS 1900

Channel 512-Occupied Bandwidth -20dBc BW)




Date: 11.AUG.2011 08:28:32

Channel 661-Occupied Bandwidth (-20dBc BW)



Date: 11.AUG.2011 08:28:59

Channel 810-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 08:29:26

EGPRS 1900(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
1850.2	248.397
1880.0	246.794
1909.8	248.397


EGPRS 1900

Channel 512-Occupied Bandwidth (-20dBc BW)




Date: 11.AUG.2011 08:38:59

Channel 661-Occupied Bandwidth (-20dBc BW)



Date: 11.AUG.2011 08:39:26

Channel 810-Occupied Bandwidth (-20dBc BW)



Date: 11.AUG.2011 08:39:53

A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))

A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	310.897
836.6	312.500
848.8	307.692


GSM 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 07:25:31

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 11.AUG.2011 07:25:59

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 07:26:26

GPRS 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	310.897
836.6	310.897
848.8	309.294


GPRS 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:24:09

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 11.AUG.2011 08:24:36

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:25:03

EGPRS 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	312.500
836.6	307.692
848.8	310.897


EGPRS 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:35:16

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 11.AUG.2011 08:35:43

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:36:10

PCS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	309.294
1880.0	310.897
1909.8	310.897


PCS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 07:48:12

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 11.AUG.2011 07:48:39

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 07:49:06

GPRS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	310.897
1880.0	310.897
1909.8	309.294


GPRS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:29:55

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 11.AUG.2011 08:30:22

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:30:50

EGPRS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	310.897
1880.0	312.500
1909.8	310.897


EGPRS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:40:22

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 11.AUG.2011 08:40:49

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 11.AUG.2011 08:41:17

A.7 BAND EDGE COMPLIANCE (\$22.917(b)/\$24.238(b))


GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 24.AUG.2011 06:57:16

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 24.AUG.2011 06:57:25

GPRS 850
LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 24.AUG.2011 07:11:00

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 24.AUG.2011 07:11:09

EGPRS 850
LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 24.AUG.2011 07:18:29

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 24.AUG.2011 07:18:38

PCS 1900
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 24.AUG.2011 07:02:57

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810




Date: 24.AUG.2011 07:03:05

GPRS 1900
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 24.AUG.2011 07:15:14

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810




Date: 24.AUG.2011 07:15:23

EGPRS 1900
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 24.AUG.2011 07:24:02

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 24.AUG.2011 07:24:11

A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 8.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


A. 8.3 Measurement result

GSM850

A.8.3.1 Channel 128: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 11.AUG.2011 07:27:52


A.8.3.2 Channel 128: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:28:20

A.8.3.3 Channel 128: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 11.AUG.2011 07:28:49

A.8.3.4 Channel 128: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:29:17

A.8.3.5 Channel 190: 30MHz – 1GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 11.AUG.2011 07:29:46


A.8.3.6 Channel 190: 1GHz –2.5GHz

Spurious emission limit –13dBm




Date: 11.AUG.2011 07:30:14

A.8.3.7 Channel 190: 2.5GHz –7.5GHz
Spurious emission limit –13dBm



Date: 11.AUG.2011 07:30:42

A.8.3.8 Channel 190: 7.5GHz –10GHz
Spurious emission limit –13dBm




Date: 11.AUG.2011 07:31:10

A.8.3.9 Channel 251: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 11.AUG.2011 07:31:39


A.8.3.10 Channel 251: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:32:08

A.8.3.11 Channel 251:2.5GHz – 7.5GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:32:36

A.8.3.12 Channel 251: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:33:04

A.8.3.13 Idle mode: 30MHz – 1GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:33:33

A.8.3.14 Idle mode: 1GHz – 2.5GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:34:01

A.8.3.15 Idle mode: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 11.AUG.2011 07:34:29

A.8.3.16 Idle mode: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:34:57

PCS1900

A.8.3.17 Channel 512: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:50:33

A.8.3.18 Channel 512: 1GHz – 2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 11.AUG.2011 07:51:01

A.8.3.19 Channel 512: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:51:29

A.8.3.20 Channel 512: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:51:58

A.8.3.21 Channel 512: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:52:26

A.8.3.22 Channel 512: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 11.AUG.2011 07:52:54


A.8.3.23 Channel 661: 30MHz – 1GHz
Spurious emission limit –13dBm



Date: 11.AUG.2011 07:53:23


A.8.3.24 Channel 661: 1GHz –2.5GHz
Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.




Date: 11.AUG.2011 07:53:51

A.8.3.25 Channel 661: 2.5GHz –7.5GHz
Spurious emission limit –13dBm




Date: 11.AUG.2011 07:54:19

A.8.3.26 Channel 661: 7.5GHz –10GHz
Spurious emission limit –13dBm




Date: 11.AUG.2011 07:54:48

A.8.3.27 Channel 661: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:55:16

A.8.3.28 Channel 661: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 11.AUG.2011 07:55:44


A.8.3.29 Channel 810: 30MHz – 1GHz
Spurious emission limit –13dBm.



Date: 11.AUG.2011 07:56:13


A.8.3.30 Channel 810: 1GHz – 2.5GHz
Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 11.AUG.2011 07:56:41

A.8.3.31 Channel 810:2.5GHz – 7.5GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:57:09

A.8.3.32 Channel 810: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:57:37

A.8.3.33 Channel 810: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:58:06

A.8.3.34 Channel 810: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:58:34

A.8.3.35 Idle mode: 30MHz – 1GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:59:03

A.8.3.36 Idle mode: 1GHz – 2.5GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:59:31

A.8.3.37 Idle mode: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 07:59:59

A.8.3.38 Idle mode: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 11.AUG.2011 08:00:27

A.8.3.39 Idle mode: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 11.AUG.2011 08:00:56

A.8.3.40 IDLE mode: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 11.AUG.2011 08:01:24

END OF REPORT