



# TEST REPORT

No. 2011TAR631

for

**TCT Mobile Limited**

**UMTS TriBand / GSM Quadband mobile phone**

**Model Name: Cocktail A**

**Marketing Name: one touch 995A**

**FCC ID: RAD214**

**IC ID:9238A-0007**

with

**Hardware Version: PIO4**

**Software Version: 21S**

**Issued Date: Jan 16, 2012**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

***DAR accreditation (DIN EN ISO/IEC 17025): No. DAT-P-114/01-01***

***FCC 2.948 Listed: No.733176***

***IC O.A.T.S listed: No.6629A-1***

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

Shouxiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China 100191

Tel:+86(0)10-62304633-2678, Fax:+86(0)10-62304793 Email:welcome@emcite.com. [www.emcite.com](http://www.emcite.com)

©Copyright. All rights reserved by TMC Beijing.

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>3</b>
1.1. TESTING LOCATION .....	3
1.2. TESTING ENVIRONMENT .....	3
1.3. PROJECT DATA .....	3
1.4. SIGNATURE .....	3
<b>2. CLIENT INFORMATION.....</b>	<b>4</b>
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
3.1. ABOUT EUT .....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	5
3.4. GENERAL DESCRIPTION .....	6
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>11</b>
A.1 OUTPUT POWER (§22.913(A)/§24.232(B)).....	11
A.2 EMISSION LIMIT (§2.1051/§22.917§24.238).....	15
A.3 CONDUCTED EMISSION (§15.107§15.207) .....	21
A.4 FREQUENCY STABILITY (§2.1055/§24.235) .....	26
A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I)).....	28
A.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B)).....	38
A.7 BAND EDGE COMPLIANCE (§22.917(B)/§24.238(B)) .....	48
A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238).....	50
A.9 RECEIVER RADIATION EMISSION.....	71

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT  
Address: Shouxiang Science Building, No 51, Xueyuan Road, Haidian District,  
Beijing, P.R.China  
Postal Code: 100191  
Telephone: 00861062304633  
Fax: 00861062304793


### 1.2. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: Dec 05, 2011  
Testing End Date: Jan 16, 2012

### 1.4. Signature



---

**Zi Xiaogang**  
**(Prepared this test report)**



---

**Sun Xiangqian**  
**(Reviewed this test report)**



---

**Lu Bingsong**  
**Deputy Director of the laboratory**  
**(Approved this test report)**

## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCT Mobile Limited  
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: Shanghai  
Country: China  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

### **2.2. Manufacturer Information**

Company Name: TCT Mobile Limited  
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: Shanghai  
Country: China  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	UMTS TriBand / GSM Quadband mobile phone
Model Name	Cocktail A
Marketing Name	one touch 995A
FCC ID	RAD214
IC ID	9238A-0007
Frequency	GSM 850MHz; PCS 1900MHz; WCDMA BAND II; WCDMA BAND V;
Antenna	Internal
Output power	26.84dBm maximum EIRP measured for WCDMA Band II
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
N03	012906000000342	PIO4	21S
N04	012906000000343	PIO4	21S

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>
AE1	Battery
AE2	Charger

##### AE1

Model	CAB31Y0006C1
Manufacturer	BYD
Capacitance	1500 mAh
Nominal Voltage	3.7V

##### AE2

Model	CBA3002AG0C1
Manufacturer	BYD
Length of DC line	120cm

\*AE ID: is used to identify the test sample in the lab internally.

#### **3.4. General Description**

The Equipment Under Test (EUT) is a model of UMTS TriBand / GSM Quandband mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.06
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.06
RSS-Gen	RSS-Gen — General Requirements and Information for the Certification of Radiocommunication Equipment	Issue 3, December 2010
RSS-132	Cellular Telephones Employing New Technologies Operating in the Bands 824-849 MHz and 869-894 MHz	Issue 2, September 2005
RSS-133	2 GHz Personal Communications Services	Issue 5, February 2009
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber** (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

**Control room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber** (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz



## 6. SUMMARY OF TEST RESULTS

### WCDMA Band II

Items	Test Name	Clause in FCC rules	Clause in IC rules RSS-Gen and RSS- 133	Section in this report	Verdict
1	Output Power	24.232(c)	6.4	A.1	P
2	Emission Limit	24.238, 2.1051	6.5	A.2	P
3	Frequency Stability	24.235, 2.1055	6.3	A.4	P
4	Occupied Bandwidth	2.1049(h)(i)	4.1/4.6.1	A.5	P
5	Emission Bandwidth	24.238(b)	4.6.1	A.6	P
6	Band Edge Compliance	24.238(b)	6.5	A.7	P
7	Conducted Spurious Emission	24.238, 2.1057	6.5	A.8	P

### WCDMA Band V

Items	Test Name	Clause in FCC rules	Clause in IC rules RSS-Gen and RSS-132	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	4.4	A.1	P
2	Emission Limit	22.917, 2.1051	4.5	A.2	P
3	Frequency Stability	22.235, 2.1055	4.3	A.4	P
4	Occupied Bandwidth	2.1049(h)(i)	4.1/4.6.1	A.5	P
5	Emission Bandwidth	22.917(b)	4.6.1	A.6	P
6	Band Edge Compliance	22.917(b)	4.5	A.7	P
7	Conducted Spurious Emission	22.917, 2.1057	4.5	A.8	P

### Receiver Radiated Emission

Items	Test Name	Clause in FCC rules	Clause in IC rules		Section in this report	Verdict
			RSS-132	RSS-133		
1	Receiver Radiated Emissions	15.109, 2.1053	4.6	6.6	A.9	P

## 7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESCI	100766	R&S	2012-12-06
2	Test Receiver	ESI40	831564/002	R&S	2012-07-12
3	BiLog Antenna	VULB9163	9163-175	Schwarzbeck	2012-07-05
4	BiLog Antenna	VULB9163	9163-302	Schwarzbeck	2012-07-10
5	Signal Generator	SMB100A	102063	R&S	2012-07-05
7	LISN	ESH2-Z5	829991/012	R&S	2012-07-20
8	Spectrum Analyzer	FSU26	200030	R&S	2012-12-18
9	Spectrum Analyzer	FSU46	100054	R&S	2012-10-14
10	Universal Radio Communication Tester	CMU200	100680	R&S	2012-12-23
11	Universal Radio Communication Tester	CMU200	109914	R&S	2012-07-21
12	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS	2012-08-31
13	Dual-Ridge Waveguide Horn Antenna	3117	00119021	ETS	2013-07-09
14	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2012-07-01
15	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2012-07-01
16	Climatic chamber	PL-2G	343074	ESPEC	2012-12-15

## ANNEX A: MEASUREMENT RESULTS

### A.1 OUTPUT POWER (§22.913(a)/§24.232(b))

#### A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

##### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak). These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V. (bottom, middle and top of operational frequency range).

##### Limit

According to FCC§2.1046.

##### A.1.2.2 Test Condition

RBW	VBW	Sweep Time	Span
10MHz	10MHz	800ms	50MHz

#### WCDMA Band II

##### Measurement result

WCDMA (Band II)	CH	Frequency(MHz)	output power(dBm)
	9262	1852.4	21.91
	9400	1880.0	21.70
	9538	1907.6	22.00

#### WCDMA Band V

##### Measurement result

WCDMA (Band V)	CH	Frequency(MHz)	output power(dBm)
	4132	826.4	22.22
	4183	836.6	22.02
	4233	846.6	22.19

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.  
The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} + P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### WCDMA Band II-EIRP

#### Limits

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

#### Measurement result

Frequency(MHz)	PMea(dBm)	Pcl(dB)	PAg(dB)	Ga Antenna Gain(dB)	Peak EIRP(dBm)	Polarization
1852.40	-21.69	6.02	-50.00	-4.55	26.84	H
1880.00	-22.27	7.05	-50.00	-4.43	25.11	H
1907.60	-19.26	8.90	-50.00	-4.31	26.15	H

Frequency: 1852.40 MHz

Peak EIRP(dBm)= P<sub>Mea</sub>(-21.69dBm)- P<sub>cl</sub>(6.02dB)- P<sub>Ag</sub>(-50.00dB)-G<sub>a</sub> (-4.55dB) =26.84dBm

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

### WCDMA Band V-ERP

#### Limits

	Burst Peak EIRP (dBm)
WCDMA Band V	≤38.45dBm

#### Measurement result

Frequency(MHz)	PMea(dBm)	Pcl(dB)	PAg(dB)	Ga Antenna Gain(dB)	Correction (dBm)	Peak ERP(dBm)	Polarization
826.40	-24.54	2.25	-53.00	0.85	2.15	23.21	H
836.60	-25.16	2.26	-53.00	0.90	2.15	22.53	H
846.60	-23.84	2.26	-53.00	0.94	2.15	23.81	H

Frequency: 846.60 MHz

Peak ERP(dBm)= P<sub>Mea</sub>(-23.84dBm) - P<sub>cl</sub>(2.26dB) - P<sub>Ag</sub>(-53.00dB) - G<sub>a</sub> (0.94dB)-2.15dBm=23.81dBm

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

## **A.2 EMISSION LIMIT (§2.1051/§22.917§24.238)**


### **A.2.1 Measurement Method**

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II and WCDMA Band V.

#### **The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as ( $P_r$ ).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .



### **A.2.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz) and WCDMA Band V (826.4MHz, 836.6MHz and 846.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II and WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

#### A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

#### A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency(MHz)	PMea(dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3707.30	-58.48	5.34	-8.15	-55.67	-13.00	H
5152.62	-65.28	7.24	-9.79	-62.73	-13.00	H
7413.45	-70.35	9.01	-11.35	-68.01	-13.00	V
10023.31	-67.37	8.52	-12.40	-63.49	-13.00	H
13233.00	-64.11	10.35	-13.53	-60.93	-13.00	V
16343.41	-59.88	11.33	-12.59	-58.62	-13.00	H

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency(MHz)	PMea(dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3758.67	-55.40	6.00	-8.21	-53.19	-13.00	V
7518.91	-65.14	8.12	-11.42	-61.84	-13.00	V
10119.79	-64.63	8.47	-12.42	-60.68	-13.00	H
13761.03	-63.98	11.37	-13.90	-61.45	-13.00	H
15599.91	-63.01	11.08	-13.32	-60.77	-13.00	H
17598.51	-58.05	11.96	-13.36	-56.65	-13.00	H

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency(MHz)	PMea(dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3816.60	-56.29	5.61	-8.28	-53.62	-13.00	H
5719.00	-54.26	10.09	-10.09	-54.26	-13.00	V
7626.63	-65.65	7.65	-11.53	-61.77	-13.00	V
10160.37	-66.84	8.53	-12.43	-62.94	-13.00	V
13552.47	-61.71	10.88	-13.82	-58.77	-13.00	H
14976.94	-64.40	11.35	-13.50	-62.25	-13.00	V

**WCDMA BAND V Mode Channel 4132/826.4MHz**

Frequency(MHz)	PMea(dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1528.32	-68.07	3.41	-5.98	2.15	-67.65	-13.00	H
3223.24	-67.30	5.09	-7.24	2.15	-67.30	-13.00	V
3932.56	-67.49	6.07	-8.42	2.15	-67.29	-13.00	H
5180.38	-67.61	7.40	-9.81	2.15	-67.35	-13.00	H
6700.26	-65.30	7.61	-10.80	2.15	-64.26	-13.00	V
8730.48	-66.34	8.06	-12.38	2.15	-64.17	-13.00	H

**WCDMA BAND V Mode Channel 4183/836.6MHz**

Frequency(MHz)	PMea(dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1613.19	-67.15	3.49	-5.60	2.15	-67.19	-13.00	V
2526.05	-58.81	4.32	-5.47	2.15	-59.81	-13.00	V
3538.76	-68.32	5.29	-7.95	2.15	-67.81	-13.00	V
4454.32	-70.28	6.27	-8.77	2.15	-69.93	-13.00	V
6125.78	-67.14	11.40	-10.30	2.15	-70.39	-13.00	V
7154.95	-64.07	8.82	-11.19	2.15	-63.85	-13.00	H

**WCDMA BAND V Mode Channel 4233/846.6MHz**

Frequency(MHz)	PMea(dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1668.32	-66.64	3.38	-5.36	2.15	-66.81	-13.00	V
2620.80	-55.64	4.25	-5.71	2.15	-56.33	-13.00	V
3632.02	-67.25	5.66	-8.06	2.15	-67.00	-13.00	H
4485.62	-66.33	6.46	-8.79	2.15	-66.15	-13.00	H
5130.02	-69.28	6.91	-9.78	2.15	-68.56	-13.00	V
8574.09	-65.73	7.71	-12.26	2.15	-63.33	-13.00	V

### A.3 CONDUCTED EMISSION (§15.107§15.207)

The measurement procedure in ANSI C63.4-2003 is used. Conducted Emission is measured with travel charger.


#### A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

\* Decreases with logarithm of the frequency

#### A.3.2 Measurement result

##### WCDMA Band II




#### MEASUREMENT RESULT: "11A09560\_WCC\_fin QP"

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line dB	PE
0.154500	46.80	10.1	66	19.0	N	GND
0.204000	43.70	10.1	63	19.7	L1	GND
2.162077	36.30	10.1	56	19.7	N	GND
2.210121	39.50	10.1	56	16.5	L1	GND
2.905989	36.40	10.1	56	19.6	L1	GND
3.128957	35.60	10.1	56	20.4	N	GND

**MEASUREMENT RESULT: "11A09560\_WCC\_fin AV"**

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
2.056734	30.60	10.1	46	15.4	L1	GND
2.162077	29.40	10.1	46	16.6	L1	GND
2.210121	30.20	10.1	46	15.8	L1	GND
2.905989	25.20	10.1	46	20.8	L1	GND
3.000388	20.00	10.1	46	26.0	N	GND
3.097854	24.60	10.1	46	21.4	L1	GND

**WCDMA Band V**




**MEASUREMENT RESULT: "11A09560\_WC\_fin QP"**

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
1.873500	37.40	10.1	56	18.6	L1	GND
2.608777	36.70	10.1	56	19.3	N	GND
2.781020	39.40	10.1	56	16.6	L1	GND
2.820188	41.20	10.1	56	14.8	L1	GND
3.091671	35.50	10.1	56	20.5	N	GND
3.282653	38.00	10.1	56	18.0	L1	GND

**MEASUREMENT RESULT: "11A09560\_WC\_fin AV"**

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
1.860000	25.40	10.1	46	20.6	L1	GND
2.162077	23.30	10.1	46	22.7	N	GND
2.413214	29.30	10.1	46	16.7	L1	GND
2.608777	30.90	10.1	46	15.1	L1	GND
2.764400	32.20	10.1	46	13.8	L1	GND
2.820188	30.90	10.1	46	15.1	L1	GND

**MP3**




**MEASUREMENT RESULT: "11A09560\_MC\_fin QP"**

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
2.309436	39.80	10.1	56	16.2	L1	GND
2.437443	38.20	10.1	56	17.8	L1	GND
2.929306	41.10	10.1	56	14.9	L1	GND
3.036573	39.60	10.1	56	16.4	L1	GND
3.154064	34.70	10.1	56	21.3	N	GND
3.211293	34.00	10.1	56	22.0	N	GND

**MEASUREMENT RESULT: "11A09560\_MC\_fin AV"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line	PE
2.201307	26.20	10.1	46	19.8	L1	GND
2.557171	30.90	10.1	46	15.1	L1	GND
2.736921	25.30	10.1	46	20.7	L1	GND
3.230600	26.10	10.1	46	19.9	N	GND
3.382523	30.50	10.1	46	15.5	L1	GND
3.430163	31.20	10.1	46	14.8	L1	GND

**CAMERA**



**MEASUREMENT RESULT: "11A09560\_CC\_fin QP"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line	PE
1.711500	41.50	10.1	56	14.5	L1	GND
1.896000	39.30	10.1	56	16.7	L1	GND
1.954500	35.10	10.1	56	20.9	N	GND
3.147768	41.50	10.1	56	14.5	L1	GND
3.513399	38.80	10.1	56	17.2	L1	GND
4.474266	35.20	10.2	56	20.8	L1	GND



**MEASUREMENT RESULT: "11A09560\_CC\_fin AV"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line dB	PE
1.711500	18.00	10.1	46	28.0	N	GND
1.945500	26.50	10.1	46	19.5	L1	GND
2.672081	30.70	10.1	46	15.3	L1	GND
3.315611	30.60	10.1	46	15.4	L1	GND
3.362309	32.60	10.1	46	13.4	L1	GND
3.423317	30.90	10.1	46	15.1	L1	GND

## **A.4 FREQUENCY STABILITY (§2.1055/§24.235)**

### **A.4.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **A.4.2 Measurement Limit**

#### **A.4.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

#### **A.4.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

#### A.4.3 Measurement results

##### WCDMA Band II

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-25	0.036
3.7	-22	0.032
4.2	-24	0.035

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-25	0.036
-20	-24	0.035
-10	-24	0.035
0	-22	0.032
10	-22	0.032
20	-22	0.032
30	-24	0.035
40	-24	0.035
50	-25	0.036

##### WCDMA Band V

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-25	0.035
3.7	-21	0.029
4.2	-23	0.032

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-25	0.035
-20	-23	0.032
-10	-23	0.032
0	-21	0.029
10	-21	0.029
20	-21	0.029
30	-23	0.032
40	-23	0.032
50	-25	0.035

## A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

### A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

#### WCDMA Band II(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
1852.4	4.150
1880.0	4.134
1907.6	4.150


#### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (-20dBc BW)




Date: 13.DEC.2011 06:56:57

### Channel 9400-Occupied Bandwidth (-20dBc BW)



Date: 13.DEC.2011 06:57:31

### Channel 9538-Occupied Bandwidth (-20dBc BW)




Date: 13.DEC.2011 06:58:06

### WCDMA Band II(-20dBc)-IC

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
1852.4	1.017
1880.0	1.915
1907.6	1.057


### WCDMA Band II

#### Channel 9262-Occupied Bandwidth Reference Level




Date: 13.DEC.2011 08:32:49

#### Channel 9262-Occupied Bandwidth (-20dBc BW)




Date: 13.DEC.2011 08:33:22

### Channel 9400-Occupied Bandwidth Reference Level




Date: 13.DEC.2011 08:34:16

### Channel 9400-Occupied Bandwidth (-20dBc BW)




Date: 13.DEC.2011 08:34:51

### Channel 9538-Occupied Reference Level (-20dBc BW)



Date: 13.DEC.2011 08:35:40

### Channel 9538-Occupied Bandwidth (-20dBc BW)



Date: 13.DEC.2011 08:36:12




**WCDMA Band V(-20dBc)**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
826.4	4.150
836.6	4.150
846.6	4.134


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (-20dBc BW)**




Date: 13.DEC.2011 07:16:31

**Channel 4183-Occupied Bandwidth (-20dBc BW)**



Date: 13.DEC.2011 07:17:05

### Channel 4233-Occupied Bandwidth (-20dBc BW)




Date: 13.DEC.2011 07:17:40

**WCDMA Band V(-20dBc)-IC**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
826.4	2.491
836.6	1.746
846.6	1.883


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth Reference Level**




Date: 13.DEC.2011 07:54:09

**Channel 4132-Occupied Bandwidth (-20dBc BW)**




Date: 13.DEC.2011 07:55:22

### Channel 4183-Occupied Reference Level




Date: 13.DEC.2011 07:56:52

### Channel 4183-Occupied Bandwidth (-20dBc BW)




Date: 13.DEC.2011 07:58:22

### Channel 4233-Occupied Bandwidth Reference Level



Date: 13.DEC.2011 08:00:24

### Channel 4233-Occupied Bandwidth (-20dBc BW)



Date: 13.DEC.2011 08:03:25

**A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))**

**A.6.1 Emission Bandwidth Results**


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

**WCDMA Band II(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
1852.4	4.503
1880.0	4.487
1907.6	4.487


**WCDMA Band II**

**Channel 9262-Occupied Bandwidth (-26dBc BW)**




Date: 13.DEC.2011 06:58:42

### Channel 9400-Occupied Bandwidth (-26dBc BW)



Date: 13.DEC.2011 06:59:16

### Channel 9538-Occupied Bandwidth (-26dBc BW)




Date: 13.DEC.2011 06:59:51

### WCDMA Band II(-26dBc)-IC

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
1852.4	1.153
1880.0	2.163
1907.6	1.314


### WCDMA Band II

#### Channel 9262-Occupied Bandwidth Reference Level



Date: 13.DEC.2011 08:32:49


#### Channel 9262-Occupied Bandwidth (-26dBc BW)



Date: 13.DEC.2011 08:34:01




### Channel 9400-Occupied Bandwidth Reference Level




Date: 13.DEC.2011 08:34:16

### Channel 9400-Occupied Bandwidth (-26dBc BW)




Date: 13.DEC.2011 08:35:25

### Channel 9538-Occupied Reference Level



Date: 13.DEC.2011 08:35:40

### Channel 9538-Occupied Bandwidth (-26dBc BW)




Date: 13.DEC.2011 08:36:51

**WCDMA Band V(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
826.40	4.455
836.60	4.471
846.60	4.455


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (-26dBc BW)**




Date: 13.DEC.2011 07:18:16

### Channel 4183-Occupied Bandwidth (-26dBc BW)



Date: 13.DEC.2011 07:18:51

### Channel 4233-Occupied Bandwidth (-26dBc BW)




Date: 13.DEC.2011 07:19:25

### WCDMA Band V (-26dBc)-IC

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
826.40	2.732
836.60	1.971
846.60	2.019


### WCDMA Band V

#### Channel 4132-Occupied Bandwidth Reference Level




Date: 13.DEC.2011 07:54:09

#### Channel 4132-Occupied Bandwidth (-26dBc BW)




Date: 13.DEC.2011 07:56:37

### Channel 4183-Occupied Reference Level




Date: 13.DEC.2011 07:56:52

### Channel 4183-Occupied Bandwidth (-26dBc BW)




Date: 13.DEC.2011 08:00:09

### Channel 4233-Occupied Bandwidth Reference Level



Date: 13.DEC.2011 08:00:24

### Channel 4233-Occupied Bandwidth (-26dBc BW)




Date: 13.DEC.2011 08:04:45






**WCDMA Band V**  
**LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132**



Date: 13.DEC.2011 07:19:37

**HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233**



Date: 13.DEC.2011 07:19:48

## **A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)**

### **A.8.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band V, data taken from 30 MHz to 10GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:  
The trace mode is set to MaxHold to get the highest signal at each frequency;  
Wait 25 seconds;  
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

#### **WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

### **A.8.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.8.3 Measurement result

#### WCDMA Band II

##### A.8.3.1 Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:00:45

##### A.8.3.2 Channel 9262: 1GHz –2.5GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 13.DEC.2011 07:01:14

### A.8.3.3 Channel 9262: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 13.DEC.2011 07:01:42


### A.8.3.4 Channel 9262: 7.5GHz –10GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:02:11

**A.8.3.5 Channel 9262: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:02:39

**A.8.3.6 Channel 9262: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 13.DEC.2011 07:03:08


**A.8.3.7 Channel 9400: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 13.DEC.2011 07:03:39


**A.8.3.8 Channel 9400: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 13.DEC.2011 07:04:08

**A.8.3.9 Channel 9400: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:04:36

**A.8.3.10 Channel 9400: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:05:05

**A.8.3.11 Channel 9400: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 13.DEC.2011 07:05:34


**A.8.3.12 Channel 9400: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 13.DEC.2011 07:06:02




**A.8.3.13 Channel 9538: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 13.DEC.2011 07:06:33


**A.8.3.14 Channel 9538: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 13.DEC.2011 07:07:02

**A.8.3.15 Channel 9538: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:07:30

**A.8.3.16 Channel 9538: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:07:59

**A.8.3.17 Channel 9538: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:08:27

**A.8.3.18 Channel 9538: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:08:56

**A.8.3.19 Idle mode: 30MHz –1GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:09:25

**A.8.3.20 Idle mode: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:09:54

**A.8.3.21 Idle mode: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:10:22

**A.8.3.22 Idle mode: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:10:51

**A.8.3.23 Idle mode: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 13.DEC.2011 07:11:19

**A.8.3.24 Idle mode: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:11:48

WCDMA Band V

A.8.3.25 Channel 4132: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 13.DEC.2011 07:20:19

A.8.3.26 Channel 4132: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:20:47

### A.8.3.27 Channel 4132: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 13.DEC.2011 07:21:16

### A.8.3.28 Channel 4132: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:21:44



### A.8.3.29 Channel 4183: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 13.DEC.2011 07:22:15

### A.8.3.30 Channel 4183: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:22:43

### A.8.3.31 Channel 4183: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 13.DEC.2011 07:23:12

### A.8.3.32 Channel 4183: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:23:40

### A.8.3.33 Channel 4233: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 13.DEC.2011 07:24:11

### A.8.3.34 Channel 4233: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:24:39

### A.8.3.35 Channel 4233: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 13.DEC.2011 07:25:08


### A.8.3.36 Channel 4233: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:25:36

**A.8.3.37 Idle mode: 30MHz – 1GHz**  
Spurious emission limit -13dBm.




Date: 13.DEC.2011 07:26:05

**A.8.3.38 Idle mode: 1GHz – 2.5GHz**  
Spurious emission limit -13dBm.




Date: 13.DEC.2011 07:26:33

**A.8.3.39 Idle mode: 2.5GHz – 7.5GHz**  
Spurious emission limit -13dBm.



Date: 13.DEC.2011 07:27:01

**A.8.3.40 Idle mode: 7.5GHz – 10GHz**  
Spurious emission limit -13dBm.



Date: 13.DEC.2011 07:27:30

## **A.9 RECEIVER RADIATION EMISSION**

### **Reference**

FCC: CFR Part 15.109, 2.1053

IC: RSS 132, Issue 2, Section 4.6. RSS 133, Issue 5, Section 6.6

### **A.9.1 Method of Measurement**


The measurement procedure in ANSI C64.4-2003 is used. The EUT is placed on a 80cm height non-conductive table locating on the center of turntable. From 30MHz-1GHz, the measurement distance is 10m. For frequency range above 1GHz, the measurement distance is 3m.

The EUT is measured with travel charger and the operating mode is idle without CMU200's signaling.

### **A.9.2 Method of Measurement**


Frequency of Emission (MHz)	Limit (dB $\mu$ V/m)	Measurement Distance (m)
30-88	30	10
88-216	33.5	10
216-960	36	10
960-1000	44	10
>1000	54	3

### **A. 9.3 Measurement results**



IF bandwidth: 120 kHz


Idle Mode: 30MHz-1GHz



RBW / VBW 1 MHz

Idle Mode: 1GHz-4GHz

FCC 4-18G



RBW / VBW 1 MHz

Idle Mode: 4GHz-18GHz

\*\*\*END OF REPORT\*\*\*