



TEST REPORT

No. 2011TAR568

for

TCT Mobile Limited

GSM dual band mobile phone

Mode Name: Maglev US

Marketing Name: one touch 310A

FCC ID: RAD216

with

Hardware Version: Proto

Software Version: V473

Issued Date: 2011-10-18

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

ShouXiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China 100191

Tel:+86(0)10-62304633-2678, Fax:+86(0)10-62304793 Email:welcme@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS	9
7. TEST EQUIPMENTS UTILIZED	10
ANNEX A: MEASUREMENT RESULTS.....	11
A.1 OUTPUT POWER.....	11
A.2 EMISSION LIMIT	16
A.3 CONDUCTED EMISSION (§15.107§15.207)	21
A.4 FREQUENCY STABILITY	26
A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I)).....	28
A.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B)).....	36
A.7 BAND EDGE COMPLIANCE (§22.917(B)/§24.238(B))	44
A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)	48

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: ShouXiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: 2011-10-17
Testing End Date: 2011-10-18

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 4/F, South Building, No.2966, Jinke Road, Zhangjiang High-Tech Park,
Pudong, Shanghai, 201203, P.R.China
Contact: Gong Zhizhou
Email: zhizhou.gong@jrdcom.com
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 4/F, South Building, No.2966, Jinke Road, Zhangjiang High-Tech Park,
Pudong, Shanghai, 201203, P.R.China
Contact: Gong Zhizhou
Email: zhizhou.gong@jrdcom.com
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM dual band mobile phone
Mode Name	Maglev US
Marketing Name	one touch 310A
FCC ID	RAD216
Frequency	GSM 850MHz; PCS 1900MHz;
Antenna	Internal
Power supply	Battery or Charger(AC Adaptor)
Output power	28.96 dBm maximum EIRP measured for GSM1900
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N03	012910000000295	Proto	V473
N03	012910000000436	Proto	V473

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Battery	/
AE3	Battery	/
AE4	Battery	/
AE5	Charger	/
AE6	Charger	/

AE1

Model	CAB229A000C1
Manufacturer	BAK
Capacitance	500mAh

AE2

Model	CAB2170000C1
Manufacturer	BYD
Capacitance	500mAh

AE3

Model	CAB30M0000C1
Manufacturer	BYD
Capacitance	650mAh

AE4

Model	CAB30B4000C1
Manufacturer	BYD
Capacitance	750mAh

AE5

Model	CBA3004AG0C1
Manufacturer	BYD
Length of DC line	120cm

AE6

Model	CBA30Y0AG0C2
Manufacturer	TENPAO
Length of DC line	120cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of GSM dual band mobile phone with integrated antenna. It consists of Hand Telephone Set and normal options: lithium battery, charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples under test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Conducted Emission	15.107/207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P

7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESS	847151/015	R&S	2011-12-30
2	Test Receiver	ESI40	831564/002	R&S	2011-12-10
3	BiLog Antenna	3142B	9908-1403	EMCO	2011-12-15
4	BiLog Antenna	3142B	9908-1405	EMCO	2011-12-19
5	Signal Generator	SMT06	831285/005	R&S	2011-12-25
6	Signal Generator	SMP04	100070	R&S	2011-12-19
7	LISN	ESH2-Z5	829991/012	R&S	2011-12
8	Spectrum Analyzer	FSU26	200030	R&S	2011-12-18
9	Universal Radio Communication Tester	CMU200	100680	R&S	2011-12-23
10	Dual-Ridge Waveguide Horn Antenna	3115	9906-5827	EMCO	2011-12
11	Dual-Ridge Waveguide Horn Antenna	3115	9906-5831	EMCO	2011-12
12	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2011-12
13	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2011-12
14	Climatic chamber	PL-2G	343074	ESPEC	2011-12-15

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band;824.4MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

GSM850

Limit

	Power step	Nominal Peak output power (dBm)	Target (dB)
GSM	5	33dBm(2W)	32±1
GPRS	3	33dBm(2W)	32±1

Measurement result

GSM

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	5	32.09
836.6	5	32.03
848.8	5	32.04

GPRS

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	3	32.07
836.6	3	31.99
848.8	3	32.00

PCS1900

Limit

	Power step	Nominal Peak output power (dBm)	Target (dB)
GSM	0	30dBm(1W)	29±2
GPRS	3	30dBm(1W)	29±2

Measurement result

GSM

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	0	29.17
1880.0	0	28.59
1909.8	0	28.66

GPRS

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	3	29.76
1880.0	3	29.12
1909.8	3	29.14

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is

connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- The cable loss (P_{cl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{cl} + G_a$$

- This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

GSM 850-ERP 22.913(a)

Limits

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result

GSM

Frequency (MHz)	Power Step	Peak ERP(dBm)	P_{cl} Cable Loss(dB)	G_a Antenna Gain(dB)	Correction (dBm)	P_{Mea} (dBm)	Polarity
824.2	5	28.32	20.5	5.3	2.15	4.67	Horizontal
836.6	5	28.44	20.5	5.3	2.15	4.79	Horizontal
848.8	5	27.95	20.5	5.3	2.15	4.30	Horizontal

GPRS

Frequency (MHz)	Power Step	Peak ERP(dBm)	P_{cl} Cable Loss(dB)	G_a Antenna Gain(dB)	Correction (dBm)	P_{Mea} (dBm)	Polarity
824.2	5	28.44	20.5	5.3	2.15	4.79	Horizontal
836.6	5	28.55	20.5	5.3	2.15	4.90	Horizontal
848.8	5	28.04	20.5	5.3	2.15	4.39	Horizontal

Frequency: 836.6MHz

$$\text{Peak ERP(dBm)} = P_{Mea}(4.90\text{dBm}) + P_{cl}(20.5\text{dB}) + G_a(5.3\text{dB}) - 2.15\text{dBm} = 28.55\text{dBm}$$

ANALYZER SETTINGS: RBW = VBW = 3MHz

PCS1900-EIRP 24.232(b)

Limits

	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)
EGPRS	5	≤33dBm (2W)

Measurement result

GSM

Frequency (MHz)	Power Step	Peak EIRP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	P _{Mea} (dBm)	Polarity
1850.2	0	28.76	-10.9	27.5	12.16	Horizontal
1880	0	28.92	-10.8	27.5	12.22	Horizontal
1909.8	0	28.41	-11.3	27.5	12.21	Horizontal

GPRS

Frequency (MHz)	Power Step	Peak EIRP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	P _{Mea} (dBm)	Polarity
1850.2	0	28.85	-10.9	27.5	12.25	Horizontal
1880	0	28.98	-10.8	27.5	12.28	Horizontal
1909.8	0	28.81	-11.3	27.5	12.61	Horizontal

Frequency: 1880.0MHz

Peak EIRP(dBm)= P_{Mea}(12.28dBm)+ P_{cl}(-10.8dB)+G_a (27.5dB) =29.98 dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the PCS1900 band ,GSM850 band.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The cable loss (P_{cl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P , in Watts) by at least $43 + 10\log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz) ,GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

GSM850

Channel 128/824.2MHz

Frequency (MHz)	Peak ERP(dBm)	P _{cl} Cable Loss	G _a Antenna Gain(dB)	Correction (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1648.2	-51.37	-40.8	25.2	2.15	-33.62	-13	Horizontal
2472.6	-43.26	-42.6	27.5	2.15	-26.01	-13	Horizontal
8051.2	-43.8	-44.5	37.5	2.15	-34.65	-13	Horizontal
9907.9	-41.44	-45.4	38.7	2.15	-32.59	-13	Horizontal

Channel 190/836.6MHz

Frequency (MHz)	Peak ERP(dBm)	P _{cl} Cable Loss	G _a Antenna Gain(dB)	Correction (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
2509.05	-43.95	-42.7	29.2	2.15	-28.3	-13	Horizontal
2510.25	-43.62	-42.3	29.2	2.15	-28.37	-13	Horizontal
2511.15	-45.52	-42.3	29.2	2.15	-30.27	-13	Horizontal
7932.1	-43.3	-43.9	37.4	2.15	-34.65	-13	Horizontal
9657.4	-41.54	-45.3	38.7	2.15	-32.79	-13	Vertical

Channel 251/848.8MHz

Frequency (MHz)	Peak ERP(dBm)	P _{cl} Cable Loss	G _a Antenna Gain(dB)	Correction (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1697.4	-49.97	-40.7	25.2	2.15	-32.32	-13	Vertical
2545.8	-43.78	-42.1	29.2	2.15	-28.73	-13	Horizontal
7895.2	-42.93	-44.4	37.4	2.15	-33.78	-13	Vertical
9920.5	-40.65	-45.3	38.7	2.15	-31.9	-13	Horizontal

PCS1900

Channel 512/1850.2MHz

Frequency (MHz)	Peak ERP (dBm)	P _{cl} Cable Loss	G _a Antenna Gain(dB)	P _{mea} (dBm)	Limit (dBm)	Polarity
2005.4	-43.45	-41.2	27.5	-29.75	-13	Vertical
8147.9	-42.74	-44.3	37.5	-35.94	-13	Horizontal
9950.3	-41.64	-45.3	38.7	-35.04	-13	Horizontal
12579.8	-37.94	-47.3	39.5	-30.14	-13	Vertical
17865.2	-28.56	-49.3	44.7	-23.96	-13	Vertical

Channel 661/1880.0MHz

Frequency (MHz)	Peak ERP (dBm)	P _{cl} Cable Loss	G _a Antenna Gain(dB)	P _{mea} (dBm)	Limit (dBm)	Polarity
2000.2	-43.64	-41.2	27.5	-29.94	-13	Vertical
3759.8	-46.04	-41.8	33.4	-37.64	-13	Horizontal
8114.3	-42.82	-44.1	37.5	-36.22	-13	Horizontal
9709.4	-41.29	-45.4	38.7	-34.59	-13	Horizontal
17458.4	-29.26	-51.2	43	-21.06	-13	Vertical

GSM Mode Channel 810/1909.8MHz

Frequency (MHz)	Peak ERP (dBm)	P _{cl} Cable Loss	G _a Antenna Gain(dB)	P _{mea} (dBm)	Limit (dBm)	Polarity
2000.1	-17.86	-41.2	27.5	-4.16	-13	Horizontal
2000.5	-20.69	-41.2	27.5	-6.99	-13	Vertical
2000.9	-23.35	-41.2	27.5	-9.65	-13	Horizontal
2001.9	-28.65	-41.2	27.5	-14.95	-13	Horizontal
2002.2	-31.03	-41.2	27.5	-17.33	-13	Horizontal
2002.7	-34.94	-41.2	27.5	-21.24	-13	Horizontal

A.3 CONDUCTED EMISSION (§15.107§15.207)

The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.

A.3.1 Limit


Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.3.2 Measurement result

GSM850MHz

For AE5




MEASUREMENT RESULT: "11A07639_8C_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line dB	PE
1.815000	42.60	10.1	56	13.4	L1	GND
2.198797	42.50	10.1	56	13.5	L1	GND
2.453796	42.90	10.1	56	13.1	L1	GND
2.503242	43.00	10.1	56	13.0	L1	GND
2.779650	43.80	10.1	56	12.2	L1	GND
2.835661	42.60	10.1	56	13.4	L1	GND

MEASUREMENT RESULT: "11A07639_8C_fin AV"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
1.608000	22.00	10.1	46	24.0	L1	GND
1.657500	34.10	10.1	46	11.9	L1	GND
2.020050	31.80	10.1	46	14.2	L1	GND
2.144642	34.50	10.1	46	11.5	L1	GND
2.198797	30.50	10.1	46	15.5	L1	GND
2.453796	32.60	10.1	46	13.4	L1	GND

For AE6



MEASUREMENT RESULT: "10TA768_28C_fin QP"


Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
0.170714	61.10	10.1	65	3.8	L1	FLO
0.386031	46.90	10.1	58	11.3	L1	GND
2.209244	40.30	10.1	56	15.7	L1	GND

MEASUREMENT RESULT: "10TA768_28C_fin AV"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
0.170714	45.70	10.1	55	9.2	N	GND

PCS1900MHz

For AE5




MEASUREMENT RESULT: "11A07639_PC_fin QP"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
0.154500	49.00	10.1	66	16.7	L1	GND
0.226500	49.10	10.1	63	13.5	L1	GND
0.375000	37.00	10.1	58	21.4	L1	GND
0.609000	39.70	10.1	56	16.3	L1	GND
0.618000	43.90	10.1	56	12.1	L1	GND
0.739500	40.90	10.1	56	15.1	L1	GND

MEASUREMENT RESULT: "11A07639_PC_fin AV"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
1.698000	32.60	10.1	46	13.4	L1	GND
1.747500	33.40	10.1	46	12.6	L1	GND
1.905000	31.90	10.1	46	14.1	L1	GND
1.954500	32.70	10.1	46	13.3	L1	GND
2.231944	26.50	10.1	46	19.5	L1	GND
2.429441	30.50	10.1	46	15.5	L1	GND

For AE6




MEASUREMENT RESULT: "10TA768_2PC_fin QP"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
0.170714	58.80	10.1	65	6.1	N	FLO
0.374678	42.30	10.1	58	16.1	L1	GND
2.102020	42.50	10.1	56	13.5	L1	FLO
2.187371	41.80	10.1	56	14.2	L1	GND

MEASUREMENT RESULT: "10TA768_2PC_fin AV"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line dB	PE
0.169024	44.20	10.1	55	10.8	N	GND

Camera



MEASUREMENT RESULT: "11A07639_CC_fin QP"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
0.361500	47.20	10.1	59	11.5	L1	GND
0.438000	44.70	10.1	57	12.4	L1	GND
0.496500	30.50	10.1	56	25.6	N	GND
0.519000	36.30	10.1	56	19.7	L1	GND
0.888000	31.30	10.1	56	24.7	L1	GND
0.906000	31.60	10.1	56	24.4	L1	GND

MEASUREMENT RESULT: "11A07639_CC_fin AV"

Frequency MHz	Level dBμV	Transd	Limit dB	Margin dBμV	Line	PE
1.261500	33.30	10.1	46	12.7	L1	GND
1.311000	33.40	10.1	46	12.6	L1	GND
2.322800	31.30	10.1	46	14.7	L1	GND
2.528337	30.70	10.1	46	15.3	L1	GND
2.724745	33.40	10.1	46	12.6	L1	GND
3.055943	35.20	10.1	46	10.8	L1	GND

A.4 FREQUENCY STABILITY

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 , channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

GSM 850

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	17	0.020
3.8	14	0.017
4.2	14	0.017

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	18	0.021
-20	18	0.021
-10	16	0.019
0	17	0.020
10	15	0.018
20	14	0.017
30	16	0.019
40	15	0.018
50	18	0.021

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	35	0.019
3.8	30	0.015
4.2	32	0.017

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	36	0.019
-20	35	0.019
-10	35	0.019
0	33	0.017
10	35	0.019
20	37	0.020
30	36	0.019
40	35	0.019
50	37	0.020

A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the USPCS frequency band. The table below lists the measured -20dBc BW (99%). Spectrum analyzer plots are included on the following pages.

GSM 850(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
824.2	248.397
836.6	246.794
848.8	246.794


GSM 850

Channel 128-Occupied Bandwidth (99%)




Date: 17.MAY.2010 05:04:10

Channel 190-Occupied Bandwidth (99%)



Date: 17.MAY.2010 05:04:37

Channel 251-Occupied Bandwidth (99%)




Date: 17.MAY.2010 05:05:04

GPRS 850(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
824.2	248.397
836.6	251.603
848.8	246.795


GPRS 850

Channel 128-Occupied Bandwidth (99%)




Date: 17.MAY.2010 04:47:28

Channel 190-Occupied Bandwidth (99%)



Date: 17.MAY.2010 04:47:55

Channel 251-Occupied Bandwidth (99%)




Date: 17.MAY.2010 04:48:22

PCS 1900(99%)


Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	250.000
1880.0	248.397
1909.8	245.192

**PCS 1900
Channel 512-Occupied Bandwidth (99%)**




Date: 17.MAY.2010 04:06:25

Channel 661-Occupied Bandwidth (99%)



Date: 17.MAY.2010 04:06:52

Channel 810-Occupied Bandwidth (99%)




Date: 17.MAY.2010 04:07:19

GPRS 1900(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	248.397
1880.0	248.397
1909.8	248.397


GPRS 1900

Channel 512-Occupied Bandwidth (99%)




Date: 17.MAY.2010 04:38:40

Channel 661-Occupied Bandwidth (99%)



Date: 17.MAY.2010 04:39:07

Channel 810-Occupied Bandwidth (99%)



Date: 17.MAY.2010 04:39:34

A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))

A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the PCS1900 band and GSM850 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	310.897
836.6	312.500
848.8	312.500


GSM 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 05:05:32

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 17.MAY.2010 05:06:00

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 05:06:27

GPRS 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	310.897
836.6	310.897
848.8	309.295


GPRS 850

Channel 128-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 04:48:50

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 17.MAY.2010 04:49:17

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 04:49:44

PCS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	310.897
1880.0	309.294
1909.8	307.692


PCS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 04:07:48

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 17.MAY.2010 04:08:15

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 04:08:42

GPRS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	310.897
1880.0	312.500
1909.8	309.295


GPRS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 04:40:03

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 17.MAY.2010 04:40:30

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 17.MAY.2010 04:40:57

A.7 BAND EDGE COMPLIANCE (§22.917(b)/§24.238(b))


GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 17.MAY.2010 05:12:26

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 17.MAY.2010 05:12:55

GPRS 850
LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 17.MAY.2010 04:52:55

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 17.MAY.2010 04:53:24

PCS 1900
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 17.MAY.2010 04:14:43

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810




Date: 17.MAY.2010 04:15:12

GPRS 1900
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 17.MAY.2010 04:44:10

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810



Date: 17.MAY.2010 04:44:38

A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 8.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

A. 8.3 Measurement result
GSM850


Harmonic	Tx ch. 128 Freq. (MHz)	Level (dBm)	Tx ch. 190 Freq. (MHz)	Level (dBm)	Tx ch. Freq. (MHz) 251	Level (dBm)
2	1648.4	nf	1673.2	nf	1697.6	nf
3	2472.6	nf	2509.8	nf	2546.4	nf
4	3296.8	nf	3346.4	nf	3395.2	nf
5	4121	nf	4183	nf	4244	nf
6	4945.2	nf	5019.6	nf	5092.8	nf
7	5769.4	nf	5856.2	nf	5941.6	nf
8	6593.6	nf	6692.8	nf	6790.4	nf
9	7417.8	nf	7529.4	nf	7639.2	nf
10	8242	nf	8366	nf	8488	nf

nf: Noise floor

A.8.3.1 Channel 128: 30MHz – 4GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.



Date: 17.MAY.2010 05:09:37


A.8.3.2 Channel 128: 4GHz – 10GHz
Spurious emission limit –13dBm.



Date: 17.MAY.2010 05:10:05


A.8.3.3 Channel 190: 30MHz – 4GHz
Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.



Date: 17.MAY.2010 05:10:34


A.8.3.4 Channel 190: 4GHz –10GHz
Spurious emission limit –13dBm



Date: 17.MAY.2010 05:11:01


A.8.3.5 Channel 251: 30MHz – 4GHz
Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 17.MAY.2010 05:11:30

A.8.3.6 Channel 251: 4GHz – 10GHz
Spurious emission limit –13dBm.



Date: 17.MAY.2010 05:11:58


A.8.3.7 Idle mode: 30MHz – 4GHz
Spurious emission limit –13dBm.



Date: 17.MAY.2010 05:13:23

A.8.3.8 Idle mode: 4GHz – 10GHz

Spurious emission limit -13dBm.



Date: 17.MAY.2010 05:13:51

PCS1900


Harmonic	Tx ch. 512 Freq. (MHz)	Level (dBm)	Tx ch. 661 Freq. (MHz)	Level (dBm)	Tx ch. 810 Freq. (MHz)	Level (dBm)
2	3700.4	nf	3760	nf	3819.6	nf
3	5550.6	nf	5640	nf	5729.4	nf
4	7400.8	nf	7520	nf	7639.2	nf
5	9251.0	nf	9400	nf	9549.0	nf
6	11101.2	nf	11280	nf	11458.8	nf
7	12951.4	nf	13160	nf	13368.6	nf
8	14801.6	nf	15040	nf	15278.4	nf
9	16651.8	nf	16920	nf	17188.2	nf
10	18502.0	nf	18800	nf	19098.0	nf

nf: Noise floor

A. 8.3.9 Channel 512: 30MHz – 4GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.



Date: 17.MAY.2010 04:11:53


A. 8.3.10 Channel 512: 4GHz – 20GHz
Spurious emission limit –13dBm.



Date: 17.MAY.2010 04:12:21


A. 8.3.11 Channel 661: 30MHz – 4GHz
Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.



Date: 17.MAY.2010 04:12:50


A. 8.3.12 Channel 661: 4GHz –20GHz
Spurious emission limit –13dBm



Date: 17.MAY.2010 04:13:18


A. 8.3.13 Channel 810: 30MHz – 4GHz
Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 17.MAY.2010 04:13:47

A. 8.3.14 Channel 810: 4GHz – 20GHz
Spurious emission limit –13dBm.




Date: 17.MAY.2010 04:14:15

A. 8.3.15 Idle mode: 30MHz – 4GHz
Spurious emission limit –13dBm.



Date: 17.MAY.2010 04:15:40

A. 8.3.16 Idle mode: 4GHz – 20GHz
Spurious emission limit -13dBm.



Date: 17.MAY.2010 04:16:08

END OF REPORT