



TEST REPORT

No. 2012TAR099

for

TCT Mobile Limited

UMTS TriBand / GSM Quadband mobile phone

Model Name: Cocktail S

Marketing Name: one touch 995S

FCC ID: RAD231

IC:9238A-0006

with

Hardware Version: PIO4

Software Version: 21S

Issued Date: Mar 21, 2012

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DAT-P-114/01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

Shouxiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China 100191

Tel:+86(0)10-62304633-2678, Fax:+86(0)10-62304793 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

CONTENTS

1.	TEST LABORATORY	3
1.1.	TESTING LOCATION	3
1.2.	TESTING ENVIRONMENT	3
1.3.	PROJECT DATA	3
1.4.	SIGNATURE	3
2.	CLIENT INFORMATION.....	4
2.1.	APPLICANT INFORMATION.....	4
2.2.	MANUFACTURER INFORMATION.....	4
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1.	ABOUT EUT	5
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4.	GENERAL DESCRIPTION	6
4.	REFERENCE DOCUMENTS	7
4.1.	REFERENCE DOCUMENTS FOR TESTING.....	7
5.	LABORATORY ENVIRONMENT	8
6.	SUMMARY OF TEST RESULTS	9
7.	TEST EQUIPMENTS UTILIZED	10
	ANNEX A: MEASUREMENT RESULTS.....	11
A.1	OUTPUT POWER ($\$22.913(A)/\$27.50(D)(2)$)	11
A.2	EMISSION LIMT ($\$2.1051/\$22.917\$27.53(G)$)	15
A.3	CONDUCTED EMISSION ($\$15.107\15.207)	21
A.4	FREQUENCY STABILITY ($\$2.1055/\27.54)	26
A.5	OCCUPIED BANDWIDTH ($\$2.1049(H)(I)$)	28
A.6	EMISSION BANDWIDTH ($\$22.917(B)/\$27.53(G)$)	38
A.7	BAND EDGE COMPLIANCE ($\$22.917(B)/\$27.53(G)$)	48
A.8	CONDUCTED SPURIOUS EMISSION ($\$2.1057/\$22.917/\$27.53(G)$)	50
A.9	RECEIVER RADIATION EMISSION.....	72

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: Shouxiang Science Building, No 51, Xueyuan Road, Haidian District,
Beijing, P.R.China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: Mar 05, 2012
Testing End Date: Mar 21, 2012

1.4. Signature

Zi Xiaogang
(Prepared this test report)

Sun Xiangqian
(Reviewed this test report)

Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	UMTS TriBand / GSM Quadband mobile phone
Model Name	Cocktail S
Marketing Name	one touch 995S
FCC ID	RAD231
IC	9238A-0006
Frequency	GSM 850MHz; PCS 1900MHz; WCDMA BAND IV; WCDMA BAND V;
Antenna	Internal
Output power	25.74 dBm maximum EIRP measured for WCDMA BAND IV
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N03	012997000000029	PIO4	21S
N04	012997000000011	PIO4	21S

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Charger

AE1

Model	CAB31Y0006C1
Manufacturer	BYD
Capacitance	1500 mAh
Nominal Voltage	3.7V

AE2

Model	CBA3002AG0C1
Manufacturer	BYD
Length of DC line	120cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of UMTS TriBand / GSM Quadband mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	V 10.1.09
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

WCDMA Band IV

Items	Test Name	Clause in FCC rules	Clause in IC rules RSS-Gen and RSS- 133	Section in this report	Verdict
1	Output Power	27.50(d)(2)	6.4	A.1	P
2	Emission Limit	27.53(g) 2.1051	6.5	A.2	P
3	CONDUCTED EMISSION	15.107/15.207			P
4	Frequency Stability	27.54, 2.1055	6.3	A.4	P
5	Occupied Bandwidth	2.1049(h)(i)	6.1/6.6	A.5	P
6	Emission Bandwidth	27.53(g)	4.6.1	A.6	P
7	Band Edge Compliance	27.53(g)	6.5	A.7	P
8	Conducted Spurious Emission	27.53(g), 2.1057	6.5	A.8	P

WCDMA Band V

Items	Test Name	Clause in FCC rules	Clause in IC rules RSS-Gen and RSS-132	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	4.4	A.1	P
2	Emission Limit	22.917, 2.1051	4.5	A.2	P
3	CONDUCTED EMISSION	15.107/15.207			P
4	Frequency Stability	22.235, 2.1055	4.3	A.4	P
5	Occupied Bandwidth	2.1049(h)(i)	4.1/4.6	A.5	P
6	Emission Bandwidth	22.917(b)	4.6.1	A.6	P
7	Band Edge Compliance	22.917(b)	4.5	A.7	P
8	Conducted Spurious Emission	22.917, 2.1057	4.5	A.8	P

Receiver Radiated Emission

Items	Test Name	Clause in FCC rules	Clause in IC rules		Section in this report	Verdict
			RSS-132	RSS-133		
1	Receiver Radiated Emissions	15.109 2.1053 ,	4.6	6.6	A.9	P

7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESCI	100766	R&S	2012-06-06
2	Test Receiver	ESI40	831564/002	R&S	2012-07-12
3	BiLog Antenna	VULB9163	9163-175	Schwarzbeck	2012-07-05
4	BiLog Antenna	VULB9163	9163-302	Schwarzbeck	2012-07-10
5	Signal Generator	SMB100A	102063	R&S	2012-07-05
7	LISN	ESH2-Z5	829991/012	R&S	2012-07-20
8	Spectrum Analyzer	FSU26	200030	R&S	2012-03-18
9	Spectrum Analyzer	FSU46	100054	R&S	2012-09-14
10	Universal Radio Communication Tester	CMU200	100680	R&S	2012-02-23
11	Universal Radio Communication Tester	CMU200	109914	R&S	2012-07-21
12	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS	2012-08-31
13	Dual-Ridge Waveguide Horn Antenna	3117	00119021	ETS	2013-07-09
14	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2012-07-01
15	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2012-07-01
16	Climatic chamber	PL-2G	343074	ESPEC	2012-02-15

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER (§22.913(a)/§27.50(d)(2))

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1712.4MHz, 1740MHz, and 1752.6MHz for WCDMA Band IV; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V. (bottom, middle and top of operational frequency range).

Limit

According to FCC§2.1046.

A.1.2.2 Test Condition

RBW	VBW	Sweep Time	Span
10MHz	10MHz	800ms	50MHz

WCDMA Band IV

Measurement result

WCDMA (Band IV)	CH	Frequency(MHz)	output power(dBm)
	1312	1712.4	22.65
	1450	1740	22.70
	1513	1752.6	22.77

WCDMA Band V

Measurement result

WCDMA (Band V)	CH	Frequency(MHz)	output power(dBm)
	4132	826.4	22.22
	4183	836.6	22.02
	4233	846.6	22.19

A.1.3 Radiated

A.1.3.1 Description


This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} + P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

WCDMA Band IV-EIRP
Limits

		Burst Peak EIRP (dBm)
WCDMA Band IV		30dBm (2W)

Measurement result

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Peak EIRP(dBm)	Polarization
1712.40	-25.77	3.66	-50.00	-5.17	25.74	H
1740.00	-25.44	4.36	-50.00	-5.04	25.24	H
1752.60	-25.67	3.85	-50.00	-4.99	25.47	H

Frequency: 1712.40MHz

 Peak EIRP(dBm)= P_{Mea}(-25.77dBm)- P_{cl}(3.66dB)- P_{Ag}(-50.00dB)-G_a (-5.17dB) =25.74dBm

ANALYZER SETTINGS: RBW = VBW = 3 MHz
WCDMA Band V-ERP
Limits

		Burst Peak EIRP (dBm)
WCDMA Band V		≤38.45dBm

Measurement result

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dBm)	Peak ERP(dBm)	Polarization
826.40	-24.03	2.25	-53.00	0.85	2.15	23.72	V
836.60	-23.55	2.26	-53.00	0.90	2.15	24.14	H
846.60	-22.74	2.26	-53.00	0.94	2.15	24.91	H

Frequency: 846.60MHz

 Peak ERP(dBm)= P_{Mea}(-22.74dBm) - P_{cl}(2.26dB) - P_{Ag}(-53.00dB) - G_a

(0.94dB)-2.15dBm=24.91dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT (§2.1051/§22.917§27.53(g))


A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 22.917 and Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the WCDMA Band V and WCDMA Band IV.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr) .
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 22.917 and Part 27.53 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz) and WCDMA Band IV(1712.4MHz, 1740MHz and 1752.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band V and WCDMA Band IV into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band IV	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band IV	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

WCDMA BAND IV Mode Channel 1312/1712.4MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3427.29	-53.86	4.94	-7.73	-51.07	-13.00	H
5148.67	-70.11	7.21	-9.79	-67.53	-13.00	H
6851.65	-67.60	7.46	-10.95	-64.11	-13.00	H
9999.19	-66.46	8.55	-12.40	-62.61	-13.00	H
13779.67	-63.19	11.39	-13.91	-60.67	-13.00	H

WCDMA BAND IV Mode Channel 1450/1740MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3482.32	-58.18	5.27	-7.86	-55.59	-13.00	H
6178.24	-72.28	10.82	-10.34	-72.76	-13.00	H
8648.16	-67.99	7.73	-12.32	-63.40	-13.00	H
10096.83	-63.70	8.44	-12.42	-59.72	-13.00	H
12196.15	-64.07	9.62	-12.58	-61.11	-13.00	V
17488.18	-61.16	11.82	-13.28	-59.70	-13.00	V

WCDMA BAND IV Mode Channel 1513/1752.6MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3503.68	-55.69	5.15	-7.90	-52.94	-13.00	H
5258.55	-65.47	7.58	-9.86	-63.19	-13.00	V
7007.23	-63.50	8.33	-11.10	-60.73	-13.00	V
10043.42	-61.94	8.50	-12.41	-58.03	-13.00	H
13560.30	-63.78	10.89	-13.82	-60.85	-13.00	V
15526.14	-62.18	11.00	-13.38	-59.80	-13.00	V

WCDMA BAND V Mode Channel 4132/826.4MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
3480.19	-66.88	5.28	-7.85	2.15	-66.46	-13.00	H
4996.63	-67.77	6.85	-9.69	2.15	-67.08	-13.00	H
5929.73	-66.55	13.59	-10.17	2.15	-72.12	-13.00	H
7096.87	-67.07	8.73	-11.16	2.15	-66.79	-13.00	H
8575.24	-66.14	7.71	-12.26	2.15	-63.74	-13.00	V
9338.85	-64.16	8.45	-12.60	2.15	-62.16	-13.00	V

WCDMA BAND V Mode Channel 4183/836.6MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
3239.73	-70.82	5.02	-7.28	2.15	-70.71	-13.00	V
4051.41	-70.61	6.00	-8.53	2.15	-70.23	-13.00	V
5520.68	-67.63	8.74	-10.01	2.15	-68.51	-13.00	V
6514.24	-67.27	7.73	-10.61	2.15	-66.54	-13.00	H
7219.39	-67.69	8.95	-11.23	2.15	-67.56	-13.00	V
7800.03	-68.03	7.50	-11.70	2.15	-65.98	-13.00	H

WCDMA BAND V Mode Channel 4233/846.6MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
3657.24	-67.58	5.75	-8.09	2.15	-67.39	-13.00	H
4656.53	-67.61	6.95	-9.08	2.15	-67.63	-13.00	H
5419.01	-67.35	8.07	-9.95	2.15	-67.62	-13.00	H
6648.17	-64.98	7.30	-10.75	2.15	-63.68	-13.00	V
7857.05	-66.56	7.62	-11.76	2.15	-64.57	-13.00	H
9058.06	-67.80	8.27	-12.60	2.15	-65.62	-13.00	V

A.3 CONDUCTED EMISSION (§15.107§15.207)

The measurement procedure in ANSI C63.4-2003 is used. Conducted Emission is measured with travel charger.


A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.3.2 Measurement result

WCDMA Band IV




MEASUREMENT RESULT: "12A00902_W1C_fin QP"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.186000	58.50	10.1	64	5.7	L1	GND
0.235500	55.20	10.1	62	7.0	N	GND
0.280500	52.50	10.1	61	8.3	N	GND
0.325500	48.10	10.1	60	11.4	N	GND
0.375000	46.50	10.1	58	11.9	N	GND
0.420000	44.00	10.1	57	13.5	N	GND

MEASUREMENT RESULT: "I2A00902_WIC_fin AV"


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line dB	PE
0.325500	38.90	10.1	50	10.7	N	GND
2.466839	24.20	10.1	46	21.8	L1	GND
2.747880	26.70	10.1	46	19.3	L1	GND
3.122712	25.60	10.1	46	20.4	L1	GND
3.541591	26.20	10.1	46	19.8	L1	GND
4.097718	24.60	10.2	46	21.4	L1	GND

WCDMA Band V

MEASUREMENT RESULT: "I1A09560_WC_fin QP"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line dB	PE
1.873500	37.40	10.1	56	18.6	L1	GND
2.608777	36.70	10.1	56	19.3	N	GND
2.781020	39.40	10.1	56	16.6	L1	GND
2.820188	41.20	10.1	56	14.8	L1	GND
3.091671	35.50	10.1	56	20.5	N	GND
3.282653	38.00	10.1	56	18.0	L1	GND

MEASUREMENT RESULT: "11A09560_WC_fin AV"


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
1.860000	25.40	10.1	46	20.6	L1	GND
2.162077	23.30	10.1	46	22.7	N	GND
2.413214	29.30	10.1	46	16.7	L1	GND
2.608777	30.90	10.1	46	15.1	L1	GND
2.764400	32.20	10.1	46	13.8	L1	GND
2.820188	30.90	10.1	46	15.1	L1	GND

MP3

MEASUREMENT RESULT: "12A00902_MC_fin QP"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.190500	57.40	10.1	64	6.6	L1	GND
0.235500	55.40	10.1	62	6.9	N	GND
0.280500	50.40	10.1	61	10.4	N	GND
0.330000	50.10	10.1	60	9.4	N	GND
0.375000	44.60	10.1	58	13.8	L1	GND
3.006389	32.00	10.1	56	24.0	N	GND

MEASUREMENT RESULT: "12A00902_MC_fin AV"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
2.491606	28.90	10.1	46	17.1	L1	GND
2.536815	25.40	10.1	46	20.6	L1	GND
2.865628	27.50	10.1	46	18.5	L1	GND
3.006389	20.90	10.1	46	25.1	N	GND
3.147768	24.80	10.1	46	21.2	L1	GND
3.722986	38.00	10.2	46	8.0	L1	GND

Camera

MEASUREMENT RESULT: "12A00902_CCC_fin QP"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.186000	55.80	10.1	64	8.4	L1	GND
0.231000	53.10	10.1	62	9.3	N	GND
0.276000	49.70	10.1	61	11.3	N	GND
0.325500	46.60	10.1	60	13.0	N	GND
2.958717	45.40	10.1	56	10.6	L1	GND
3.006389	44.90	10.1	56	11.1	L1	GND

MEASUREMENT RESULT: "I2A00902_CCC_fin AV"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
2.496589	37.10	10.1	46	8.9	L1	GND
3.006389	34.50	10.1	46	11.5	L1	GND
3.054829	22.10	10.1	46	23.9	N	GND
3.375771	33.80	10.1	46	12.2	L1	GND
3.423317	31.70	10.1	46	14.3	L1	GND
3.656637	25.90	10.1	46	20.1	L1	GND

A.4 FREQUENCY STABILITY (§2.1055/§27.54)

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II and WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1 Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

WCDMA Band IV

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-23	0.043
3.7	-22	0.041
4.2	-26	0.048

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-26	0.048
-20	-23	0.043
-10	-23	0.043
0	-22	0.041
10	-22	0.041
20	-22	0.041
30	-23	0.043
40	-23	0.043
50	-26	0.048

WCDMA Band V

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-25	0.035
3.7	-21	0.029
4.2	-23	0.032

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-25	0.035
-20	-23	0.032
-10	-23	0.032
0	-21	0.029
10	-21	0.029
20	-21	0.029
30	-23	0.032
40	-23	0.032
50	-25	0.035

A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band IV and WCDMA Band V. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

WCDMA Band IV(-20dBc)


Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(MHz)
1712.4	4.150
1740	4.134
1752.6	4.134

WCDMA Band IV


Channel 1312-Occupied Bandwidth (-20dBc BW)



Date: 12.MAR.2012 08:31:19

Channel 1450-Occupied Bandwidth (-20dBc BW)




Date: 12.MAR.2012 08:31:54


Channel 1513-Occupied Bandwidth (-20dBc)


Date: 12.MAR.2012 08:32:28


WCDMA Band IV(-20dBc)-IC

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(MHz)
1712.4	3.669
1740	3.814
1752.6	3.854



Channel 1312-Occupied Bandwidth Reference Level

Channel 1312-Occupied Bandwidth (-20dBc BW)


Channel 1450-Occupied Bandwidth Reference Level


Date: 12.MAR.2012 07:57:29


Channel 1450-Occupied Bandwidth (-20dBc BW)


Date: 12.MAR.2012 07:59:06


Channel 1513-Occupied Reference Level (-20dBc BW)

Channel 1513-Occupied Bandwidth (-20dBc BW)


WCDMA Band V(-20dBc)


Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(MHz)
826.4	4.150
836.6	4.150
846.6	4.134

WCDMA Band V
Channel 4132-Occupied Bandwidth (-20dBc BW)


Date: 13.DEC.2011 07:16:31

Channel 4183-Occupied Bandwidth (-20dBc BW)



Date: 13.DEC.2011 07:17:05

Channel 4233-Occupied Bandwidth (-20dBc BW)



Date: 13.DEC.2011 07:17:40

WCDMA Band V(-20dBc)-IC


Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(MHz)
826.4	2.491
836.6	1.746
846.6	1.883

WCDMA Band V
Channel 4132-Occupied Bandwidth Reference Level



Date: 13.DEC.2011 07:54:09

Channel 4132-Occupied Bandwidth (-20dBc BW)



Date: 13.DEC.2011 07:55:22

Channel 4183-Occupied Reference Level



Date: 13.DEC.2011 07:56:52

Channel 4183-Occupied Bandwidth (-20dBc BW)


Date: 13.DEC.2011 07:58:22

Channel 4233-OccUPIed Bandwidth Reference Level


Date: 13.DEC.2011 08:00:24

Channel 4233-OCCUPIed Bandwidth (-20dBc BW)


Date: 13.DEC.2011 08:03:25

A.6 EMISSION BANDWIDTH (§22.917(b)/§27.53(g))

A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band IV and WCDMA Band V. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

WCDMA Band IV(-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(MHz)
1712.4	4.471
1740	4.471
1752.6	4.455

WCDMA Band IV


Channel 1312-Occupied Bandwidth (-26dBc BW)



Date: 12.MAR.2012 08:33:04

Channel 1450-Occupied Bandwidth (-26dBc BW)




Date: 12.MAR.2012 08:33:39


Channel 1513-Occupied Bandwidth (-26dBc BW)


Date: 12.MAR.2012 08:34:13


WCDMA Band IV(-26dBc)-IC

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(MHz)
1712.4	4.214
1740	4.262
1752.6	4.238


Channel 1312-Occupied Bandwidth Reference Level

Channel 1312-Occupied Bandwidth (-26dBc BW)


Channel 1450-Occupied Bandwidth Reference Level



Date: 12.MAR.2012 07:57:29

Channel 1450-Occupied Bandwidth (-26dBc BW)


Date: 12.MAR.2012 08:01:16

Channel 1513-Occupied Reference Level



Date: 12.MAR.2012 08:01:32

Channel 1513-Occupied Bandwidth (-26dBc BW)



Date: 12.MAR.2012 08:05:46

WCDMA Band V(-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(MHz)
826.40	4.455
836.60	4.471
846.60	4.455

WCDMA Band V
Channel 4132-Occupied Bandwidth (-26dBc BW)


Date: 13.DEC.2011 07:18:16

Channel 4183-Occupied Bandwidth (-26dBc BW)



Date: 13.DEC.2011 07:18:51

Channel 4233-Occupied Bandwidth (-26dBc BW)



Date: 13.DEC.2011 07:19:25

WCDMA Band V (-26dBc)-IC



Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(MHz)
826.40	2.732
836.60	1.971
846.60	2.019


WCDMA Band V
Channel 4132-Occupied Bandwidth Reference Level


Date: 13.DEC.2011 07:54:09


Channel 4132-Occupied Bandwidth (-26dBc BW)


Date: 13.DEC.2011 07:56:37

Channel 4183-Occupied Reference Level

Channel 4183-Occupied Bandwidth (-26dBc BW)


Channel 4233-OccUPIed Bandwidth Reference Level


Date: 13.DEC.2011 08:00:24


Channel 4233-OCCUPIed Bandwidth (-26dBc BW)


Date: 13.DEC.2011 08:04:45

A.7 BAND EDGE COMPLIANCE (§22.917(b)/§27.53(g))


WCDMA Band IV

LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312




Date: 12.MAR.2012 08:34:24


HIGH BAND EDGE BLOCK-C (WCDMA Band IV) –Channel 1513



Date: 12.MAR.2012 08:34:36

WCDMA Band V
LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132


Date: 13.DEC.2011 07:19:37

HIGH BAND EDGE BLOCK-C (WCDMA Band V) –Channel 4233


Date: 13.DEC.2011 07:19:48

A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§27.53(g))

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band IV, data taken from 30 MHz to 20 GHz. For the equipment of WCDMA Band V, data taken from 30 MHz to 10 GHz
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
The trace mode is set to MaxHold to get the highest signal at each frequency;
Wait 25 seconds;
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

WCDMA Band IV Transmitter

Channel	Frequency (MHz)
1312	1712.40
1450	1740.00
1513	1752.60

WCDMA Band V Transmitter

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

A.8.2 Measurement Limit

Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a


limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.8.3 Measurement result

WCDMA Band IV

A. 8.3.1 Channel 1312: 30MHz –1GHz


Spurious emission limit –13dBm.



A. 8.3.2 Channel 1312: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.



A. 8.3.3 Channel 1312: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:39:17

A. 8.3.4 Channel 1312: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:39:46

A. 8.3.5 Channel 1312: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:40:14

A. 8.3.6 Channel 1312: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:40:42

A. 8.3.7 Channel 1450: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 12.MAR.2012 08:41:13

A. 8.3.8 Channel 1450: 1GHz –2.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 12.MAR.2012 08:41:41

A. 8.3.9 Channel 1450: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:42:10

A. 8.3.10 Channel 1450: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:42:38

A. 8.3.11 Channel 1450: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:43:06

A. 8.3.12 Channel 1450: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:43:34

A. 8.3.13 Channel 1513: 30MHz –1GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:44:06

A. 8.3.14 Channel 1513: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.


Date: 12.MAR.2012 08:44:34

A. 8.3.15 Channel 1513: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:45:02

A. 8.3.16 Channel 1513: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:45:30

A. 8.3.17 Channel 1513: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:45:58

A. 8.3.18 Channel 1513: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:46:27

A. 8.3.19 Idle mode: 30MHz –1GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:46:56

A.8.3.20 Idle mode: 1GHz –2.5GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:47:24

A.8.3.21 Idle mode: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:47:52

A.8.3.22 Idle mode: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:48:20

A.8.3.23 Idle mode: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:48:49

A.8.3.24 Idle mode: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 12.MAR.2012 08:49:17

WCDMA Band V
A.8.3.25 Channel 4132: 30MHz –1GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.


Date: 13.DEC.2011 07:20:19

A.8.3.26 Channel 4132: 1GHz – 2.5GHz


Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:20:47

A.8.3.27 Channel 4132: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.

A.8.3.28 Channel 4132: 7.5GHz – 10GHz

Spurious emission limit –13dBm.



A.8.3.29 Channel 4183: 30MHz –1GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.


Date: 13.DEC.2011 07:22:15

A.8.3.30 Channel 4183: 1GHz – 2.5GHz


Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:22:43

A.8.3.31 Channel 4183: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.

A.8.3.32 Channel 4183: 7.5GHz – 10GHz

Spurious emission limit –13dBm.



A.8.3.33 Channel 4233: 30MHz –1GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.


Date: 13.DEC.2011 07:24:11

A.8.3.34 Channel 4233: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 13.DEC.2011 07:24:39

A.8.3.35 Channel 4233: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




A.8.3.36 Channel 4233: 7.5GHz – 10GHz

Spurious emission limit –13dBm.



A.8.3.37 Idle mode: 30MHz – 1GHz


Spurious emission limit -13dBm.



Date: 13.DEC.2011 07:26:05

A.8.3.38 Idle mode: 1GHz – 2.5GHz


Spurious emission limit -13dBm.



Date: 13.DEC.2011 07:26:33

A.8.3.39 Idle mode: 2.5GHz – 7.5GHz


Spurious emission limit -13dBm.



Date: 13.DEC.2011 07:27:01

A.8.3.40 Idle mode: 7.5GHz – 10GHz

Spurious emission limit -13dBm.



Date: 13.DEC.2011 07:27:30

A.9 RECEIVER RADIATION EMISSION

Reference

FCC: CFR Part 15.109, 2.1053

IC: RSS 132, Issue 2, Section 4.6. RSS 133, Issue 5, Section 6.6

A.9.1 Method of Measurement


The measurement procedure in ANSI C64.4-2003 is used. The EUT is placed on a 80cm height non-conductive table locating on the center of turntable. From 30MHz-1GHz, the measurement distance is 10m. For frequency range above 1GHz, the measurement distance is 3m.

The EUT is measured with travel charger and the operating mode is idle without CMU200's signaling.

A.9.2 Method of Measurement


Frequency of Emission (MHz)	Limit (dB μ V/m)	Measurement Distance (m)
30-88	30	10
88-216	33.5	10
216-960	36	10
960-1000	44	10
>1000	54	3

A.9.3 Measurement results



IF bandwidth: 120 kHz


Idle Mode: 30MHz-1GHz



RBW / VBW 1 MHz

Idle Mode: 1GHz-4GHz

FCC 4-18G



RBW / VBW 1 MHz

Idle Mode: 4GHz-18GHz