



TEST REPORT

No. 2012TAR044

for

TCT Mobile Limited

HSUPA/HSDPA/UMTS dual band / GSM quad bands mobile phone

Model Name: GIN S

Marketing Name: one touch 918S

FCC ID: RAD260

IC No.: 9238A-0008

with

Hardware Version: PIO

Software Version: SW31H_AWS

Issued Date: 2012-02-20

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633-2678 , Fax:+86(0)10-62304633-2504 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT.....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. EUT SET-UPS	6
4. REFERENCE DOCUMENTS.....	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS.....	9
7. TEST EQUIPMENTS UTILIZED.....	10
ANNEX A: MEASUREMENT RESULTS	11

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52, Huayuan beilu, Haidian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304633

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: Jan. 21st, 2012
Testing End Date: Jan. 30th, 2012


1.4. Signature



Qu Pengfei
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@jrdcom.com
Telephone: 0086-21-61460890
Fax: 0086 21 61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-61460890
Fax: 0086 21 61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	HSUPA/HSDPA/UMTS dual band / GSM quad bands mobile phone
Model Name	GIN S
Marketing Name	one touch 918S
FCC ID	RAD260
IC Number	9238A-0008
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	013122000000775	PIO	SW31H_AWS

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	B2641105B9A
AE2	Battery	BAK2011060100318
AE3	Travel charger	/
AE4	USB cable	/
AE5	USB cable	/
AE6	USB cable	/
AE7	USB cable	/

AE1

Model	CAB31P0000C1
Manufacturer	BYD
Capacitance	1300mAh
Nominal voltage	3.7V

AE2

Model	CAB31P0000C2
Manufacturer	BAK
Capacitance	1300mAh
Nominal voltage	3.7V

AE3

Model	CBA3002AG0C1
Manufacturer	BYD
Length of cable	123cm

AE4

Model	CDA3122005C1
Manufacturer	Juwei
Length of cable	101cm

AE5

Model	CDA3122005C2
Manufacturer	Shenhua
Length of cable	101cm

AE6

Model	CDA3122002C1
Manufacturer	Juwei
Length of cable	101cm

AE7

Model	CDA3122002C2
Manufacturer	Shenhua
Length of cable	101cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1/AE2+ AE3	Charging mode
Set.2	EUT1+ AE1/AE2+ AE4	USB mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-10 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003
ICES-003	Spectrum Management and Telecommunications Policy Interference-Causing Equipment Standard Digital Apparatus	Issue 4

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Fully-anechoic chamber2 (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Items	Test Name	Clause in FCC rules	Clause in IC rules	Section in this report	Verdict
1	Radiated Emission	15.109(a)	Section 5.5	A.1	P
2	Conducted Emission	15.107(a)	Section 5.3	A.2	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESCI	100344	R&S	2012-03-28
2	Test Receiver	ESCI	100766	R&S	2012-04-11
3	Test Receiver	ESI40	831564/002	R&S	2013-02-12
4	BiLog Antenna	VUL9163	302	Schwarzbeck	2014-02-10
5	LISN	ESH2-Z5	829991/012	R&S	2012-04-17
6	Universal Radio Communication Tester	CMU200	100680	R&S	2012-09-05
7	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	2012-12-16
8	PC	OPTIPLEX 755	3908243625	DELL	N/A
9	Monitor	E178FPc	CN-OWR979-6 4180-7AJ-D2M S	DELL	N/A
10	Printer	DeskJet D2368	TH72E12G7Q	HP	N/A
11	Keyboard	L100	CN0RH659658 907ATOI40	DELL	N/A
12	Mouse	VR-301	692722550019 8	XINGYU	N/A

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

Reference

FCC: CFR Part 15.109(a)

IC: ICES-003 Section 5.5.

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.1.3 Measurement Limit

Limit from CFR Part 15.109(a)

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

Limit from ICES-003 Section 5.5

Frequency range (MHz)	Field strength limits* (dB μ V/m)
30 to 230	40
230 to 1000	47

*Note: The original limit is defined at 10m test distance. This limit is calculated according to CISPR requirements.

A.1.4 Test Condition

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz (IF bandwidth)	5
1000-4000	1MHz/1MHz	15

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Set.1 Charging mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dBuV)	Polarity
3699.399	38.99	-19.5	33.4	25.09	VERTICAL
3701.403	38.98	-19.4	33.4	24.98	HORIZONTAL
3697.395	38.94	-19.5	33.4	25.04	VERTICAL
3703.407	38.92	-19.4	33.4	24.92	VERTICAL
3695.391	38.89	-19.5	33.4	24.99	VERTICAL
3705.411	38.87	-19.4	33.4	24.87	VERTICAL

Set.2 USB mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{mea} (dBuV)	Polarity
3699.399	39.08	-19.5	33.4	25.18	VERTICAL
3697.395	39.06	-19.5	33.4	25.16	HORIZONTAL
3701.403	39.04	-19.4	33.4	25.04	VERTICAL
3695.391	39.02	-19.5	33.4	25.12	VERTICAL
3703.407	39.02	-19.4	33.4	25.02	VERTICAL
3707.415	38.97	-19.4	33.4	24.97	HORIZONTAL




Figure A.1 Radiated Emission from 30MHz to 1GHz (Set.1, Charging mode)




Figure A.2 Radiated Emission from 1GHz to 4GHz (Set.1, Charging mode)




Figure A.3 Radiated Emission from 30MHz to 1GHz (Set.2, USB mode)




Figure A.4 Radiated Emission from 1GHz to 4GHz (Set.2, USB mode)

A.2 Conducted Emission (§15.107(a))

Reference

FCC: CFR Part 15.107(a)

IC: ICES-003 Section 5.3.

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 7.2.

A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results




Figure A.5 Conducted Emission (Set.1, Charging mode)

MEASUREMENT RESULT: "12A00395_CC_fin QP"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.163500	64.90	10.1	65	0.4	L1	GND
0.217500	60.60	10.1	63	2.3	L1	GND
0.271500	57.50	10.1	61	3.6	L1	GND
0.325500	53.00	10.1	60	6.6	L1	GND
0.379500	49.60	10.1	58	8.7	N	GND
0.433500	46.50	10.1	57	10.7	N	GND

MEASUREMENT RESULT: "12A00395_CC_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.163500	49.80	10.1	55	5.5	N	GND
0.217500	45.90	10.1	53	7.0	N	GND
0.271500	43.40	10.1	51	7.7	N	GND
2.650811	33.70	10.1	46	12.3	L1	GND
2.814559	30.30	10.1	46	15.7	L1	GND
3.141486	26.60	10.1	46	19.4	L1	GND




Figure A.6 Conducted Emission (Set.2, USB mode)

MEASUREMENT RESULT: "12A00395_UC_fin QP"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.267000	39.40	10.1	61	21.8	N	GND
0.834000	34.90	10.1	56	21.1	N	GND
1.306500	35.50	10.1	56	20.5	N	GND
2.259233	37.90	10.1	56	18.1	N	GND
2.365476	36.80	10.1	56	19.2	N	GND
3.649339	37.50	10.1	56	18.5	L1	GND

MEASUREMENT RESULT: "12A00395_UC_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.226500	40.10	10.1	53	12.4	N	GND
0.757500	34.40	10.1	46	11.6	N	GND
0.834000	33.80	10.1	46	12.2	N	GND
1.306500	32.80	10.1	46	13.2	N	GND
1.383000	32.00	10.1	46	14.0	N	GND
1.806000	33.20	10.1	46	12.8	N	GND

END OF REPORT