



TEST REPORT

No. 2012TAR027

for

TCT Mobile Limited

UMTS Dual Band / GSM Quadband mobile phone

Model Name: Gemini

Marketing Name: Alcatel OT871A

FCC ID: RAD264

with

Hardware Version: 05

Software Version: SW980

Issued Date: 2012-09-02

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633-2678 , Fax:+86(0)10-62304633-2504 Email:welcme@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY.....	3
1.1. TESTING LOCATION.....	3
1.2. TESTING ENVIRONMENT.....	3
1.3. PROJECT DATA.....	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE).....	5
3.1. ABOUT EUT.....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST.....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. EUT SET-UPS.....	6
4. REFERENCE DOCUMENTS.....	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS.....	9
7. TEST EQUIPMENTS UTILIZED.....	10
ANNEX A: MEASUREMENT RESULTS.....	11

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52, Huayuan beilu, Haidian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304633

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: Jan. 13, 2012
Testing End Date: Jan. 17, 2012


1.4. Signature



Qu Pengfei
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@jrdcom.com
Telephone: 0086-21-61460890
Fax: 0086 21 61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-61460890
Fax: 0086 21 61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	UMTS Dual Band / GSM Quadband mobile phone
Model Name	Gemini
Marketing Name	Alcatel OT871A
FCC ID	RAD264
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	0131600000000012	05	SW980

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	B073152B20A
AE2	Battery	/
AE3	Travel charger	/
AE4	Travel charger	/
AE5	USB cable	/
AE6	USB cable	/

AE1

Model	CAB3120000C1
Manufacturer	BYD
Capacitance	850mAh
Nominal voltage	3.7V

AE2

Model	CAB3120000C3
Manufacturer	BAK
Capacitance	850mAh
Nominal voltage	3.7V

AE3

Model	CBA3001AG0C1
Manufacturer	BYD
Length of cable	10cm

AE4

Model	CBA3001AG0C2
Manufacturer	Tenpao
Length of cable	10cm

AE5

Model	CDA3122005C2
Manufacturer	Shenghua
Length of cable	100cm

AE6

Model	CDA3122005C1
Manufacturer	Juwei
Length of cable	100cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1/AE2+ AE3+AE5/AE6	Charging mode
Set.2	EUT1+ AE1/AE2+ AE5/AE6	USB mode
Set.3	EUT1+ AE1/AE2+ AE4+AE5/AE6	Charging mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-10 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Fully-anechoic chamber2 (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Clause	List	Clause in FCC rules	Verdict
1	Radiated Emission	15.109(a)	P
2	Conducted Emission	15.107(a)	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESCI	100344	R&S	2012-03-28
2	Test Receiver	ESCI	100766	R&S	2012-04-11
3	Test Receiver	ESI40	831564/002	R&S	2012-02-11
4	BiLog Antenna	VUL9163	302	Schwarzbeck	2012-02-10
5	LISN	ESH2-Z5	829991/012	R&S	2012-04-17
6	Universal Radio Communication Tester	CMU200	100680	R&S	2012-09-05
7	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	2012-02-18
8	PC	OPTIPLEX 755	3908243625	DELL	N/A
9	Monitor	E178FPc	CN-OWR979-6 4180-7AJ-D2M S	DELL	N/A
10	Printer	DeskJet D2368	TH72E12G7Q	HP	N/A
11	Keyboard	L100	CN0RH659658 907ATOI40	DELL	N/A
12	Mouse	VR-301	692722550019 8	XINGYU	N/A

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.1.3 Measurement Limit

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

A.1.4 Test Condition

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Set.1 Charging mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dBuV)	Polarity
3699.399	38.70	-19.5	33.4	24.80	VERTICAL
3701.403	38.69	-19.4	33.4	24.69	VERTICAL
3697.395	38.65	-19.5	33.4	24.75	VERTICAL
3703.407	38.63	-19.4	33.4	24.63	VERTICAL
3693.387	38.62	-19.5	33.4	24.72	VERTICAL
3535.070	38.60	-19.4	33.4	24.60	HORIZONTAL

Set.3 Charging mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dBuV)	Polarity
3701.403	38.49	-19.4	33.4	24.49	VERTICAL
3703.407	38.47	-19.4	33.4	24.47	VERTICAL
3699.399	38.44	-19.5	33.4	24.54	HORIZONTAL
3705.411	38.41	-19.4	33.4	24.41	VERTICAL
3697.395	38.39	-19.5	33.4	24.49	VERTICAL
3707.415	38.39	-19.4	33.4	24.39	HORIZONTAL

Set.2 USB mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{mea} (dBuV)	Polarity
3699.399	38.73	-19.5	33.4	24.83	VERTICAL
3701.403	38.69	-19.4	33.4	24.69	VERTICAL
3697.395	38.68	-19.5	33.4	24.78	VERTICAL
3695.391	38.67	-19.5	33.4	24.77	VERTICAL
3703.407	38.63	-19.4	33.4	24.63	VERTICAL
3705.411	38.61	-19.4	33.4	24.61	VERTICAL




Figure A.1 Radiated Emission from 30MHz to 1GHz (Set.1, Charging mode)




Figure A.2 Radiated Emission from 1GHz to 4GHz (Set.1, Charging mode)




Figure A.3 Radiated Emission from 30MHz to 1GHz (Set.3, Charging mode)




Figure A.4 Radiated Emission from 1GHz to 4GHz (Set.3, Charging mode)




Figure A.5 Radiated Emission from 30MHz to 1GHz (Set.2, USB mode)




Figure A.6 Radiated Emission from 1GHz to 4GHz (Set.2, USB mode)

A.2 Conducted Emission (§15.107(a))

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 7.2.

A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results




Figure A.7 Conducted Emission (Set.1, Charging mode)

MEASUREMENT RESULT: "12A00275_CC_fin QP"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.357000	23.70	10.1	59	35.1	N	GND
0.415500	37.60	10.1	58	20.0	N	GND
0.708000	31.10	10.1	56	24.9	N	GND
0.892500	29.20	10.1	56	26.8	N	GND
3.147768	20.40	10.1	56	35.6	L1	GND
14.807678	17.30	10.2	60	42.7	L1	GND

MEASUREMENT RESULT: "12A00275_CC_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.276000	20.70	10.1	51	30.3	N	GND
0.415500	31.20	10.1	48	16.3	N	GND
0.658500	26.40	10.1	46	19.6	N	GND
0.888000	23.70	10.1	46	22.3	N	GND
2.398792	14.20	10.1	46	31.8	N	GND
15.442198	7.30	10.2	50	42.7	L1	GND




Figure A.8 Conducted Emission (Set.3, Charging mode)

MEASUREMENT RESULT: "12A00275_CC_fin QP"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.321000	43.70	10.1	60	16.0	L1	GND
0.609000	37.00	10.1	56	19.0	L1	GND
0.937500	33.70	10.1	56	22.3	L1	GND
2.496589	33.00	10.1	56	23.0	L1	GND
5.228824	20.70	10.2	60	39.3	L1	GND
16.298123	21.30	10.3	60	38.7	L1	GND

MEASUREMENT RESULT: "12A00275_CC_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.321000	37.10	10.1	50	12.6	L1	GND
0.582000	28.60	10.1	46	17.4	L1	GND
0.937500	27.40	10.1	46	18.6	L1	GND
1.689000	25.70	10.1	46	20.3	L1	GND
2.496589	24.40	10.1	46	21.6	L1	GND
3.141486	22.10	10.1	46	23.9	L1	GND




Figure A.9 Conducted Emission (Set.2, USB mode)

MEASUREMENT RESULT: "12A00275_UC_fin QP"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.226500	42.00	10.1	63	20.6	L1	GND
0.267000	39.30	10.1	61	21.9	L1	GND
0.757500	33.30	10.1	56	22.7	L1	GND
0.829500	36.10	10.1	56	19.9	L1	GND
1.302000	37.20	10.1	56	18.8	L1	GND
3.843925	37.50	10.1	56	18.5	N	GND

MEASUREMENT RESULT: "12A00275_UC_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.226500	40.20	10.1	53	12.4	L1	GND
0.717000	33.90	10.1	46	12.1	L1	GND
0.829500	34.30	10.1	46	11.7	L1	GND
1.302000	33.90	10.1	46	12.1	L1	GND
1.378500	34.10	10.1	46	11.9	L1	GND
1.801500	33.30	10.1	46	12.7	L1	GND

END OF REPORT