



TEST REPORT

No. 2012TAR349

for

TCT Mobile Limited

HSUPA/HSDPA/UMTS triband / GSM quadband mobile phone

Model Name: Sherry_US

Marketing Name: ONE TOUCH 903A

FCC ID: RAD273

with

Hardware Version: PIO01

Software Version: v917-4-US

Issued Date: 2012-07-24

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629B-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633-2561 , Fax:+86(0)10-62304633-2504 Email:welcom@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT.....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. EUT SET-UPS	6
4. REFERENCE DOCUMENTS.....	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS.....	9
7. TEST EQUIPMENTS UTILIZED.....	10
ANNEX A: MEASUREMENT RESULTS	11

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 0086-10-62304633-2561
Fax: 0086-10-62304633-2504

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: Jul. 13th, 2012
Testing End Date: Jul. 16th, 2012

1.4. Signature



Qu Pengfei
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@jrdcom.com
Telephone: 0086-21-61460890
Fax: 0086 21 61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, E building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China.
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-61460890
Fax: 0086 21 61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	HSUPA/HSDPA/UMTS triband / GSM quadband mobile phone
Model Name	Sherry_US
Marketing Name	ONE TOUCH 903A
FCC ID	RAD273
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	013251000021315	PIO01	v917-4-US

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Battery	/
AE3	Travel charger	/
AE4	Travel charger	/
AE5	USB cable	/
AE6	USB cable	/
AE7	USB cable	/
AE8	USB cable	/

AE1

Model	CAB31P0000C1
Manufacturer	BYD
Capacitance	1300 mAh
Nominal voltage	3.7V

AE2

Model	CAB31P0000C2
Manufacturer	BAK
Capacitance	1300 mAh
Nominal voltage	3.7V

AE3

Model	CBA3002AG0C1
Manufacturer	BYD
Length of cable	121 cm

AE4

Model CBA3002AG0C3
 Manufacturer Yingju
 Length of cable 124 cm

AE5

Model CDA3122005C1
 Manufacturer Juwei
 Length of cable 100cm

AE6

Model CDA3122005C2
 Manufacturer Shenhua
 Length of cable 100cm

AE7

Model CDA3122002C1
 Manufacturer Juwei
 Length of cable 100cm

AE8

Model CDA3122002C2
 Manufacturer Shenhua
 Length of cable 100cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1/AE2 + AE3	Charging mode
Set.2	EUT1+ AE1/AE2 + AE4	Charging mode
Set.3	EUT1+ AE1/AE2 + AE7/AE8	USB mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-10 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Control room/ conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber FAC-3 (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

Semi-anechoic chamber SAC-2 (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Clause	List	Clause in FCC rules	Verdict
1	Radiated Emission	15.109(a)	P
2	Conducted Emission	15.107(a)	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESU26	100376	R&S	2012-11-08
2	EMI Antenna	VULB 9163	514	Schwarzbeck	2014-11-10
3	EMI Antenna	3117	00139065	ETS-Lindgren	2014-07-31
4	LISN	ESH2-Z5	829991/012	R&S	2013-04-16
5	Test Receiver	ESCI	100344	R&S	2013-03-28
6	Universal Radio Communication Tester	CMU200	116455	R&S	2013-05-20
7	Universal Radio Communication Tester	CMU200	100680	R&S	2012-09-05
9	PC	OPTIPLEX 755	3908243625	DELL	N/A
10	Monitor	E178FPc	CN-OWR979-6 4180-7AJ-D2M S	DELL	N/A
11	Printer	DeskJet D2368	TH72E12G7Q	HP	N/A
12	Keyboard	L100	CN0RH659658 907ATOI40	DELL	N/A
13	Mouse	VR-301	692722550019 8	XINGYU	N/A

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.1.3 Measurement Limit

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

A.1.4 Test Condition

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Set.1 Charging mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dBuV)	Polarity
2776.800	38.9	-26.3	33.8	31.471	VERTICAL
2772.000	38.8	-26.3	33.8	31.348	VERTICAL
2779.800	38.8	-26.3	33.8	31.323	HORIZONTAL
2769.800	38.7	-26.3	33.8	31.283	VERTICAL
2775.200	38.7	-26.3	33.8	31.278	HORIZONTAL
2776.000	38.7	-26.3	33.8	31.264	VERTICAL

Set.2 Charging mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dBuV)	Polarity
2777.200	38.8	-26.3	33.8	31.340	HORIZONTAL
2772.600	38.8	-26.3	33.8	31.316	VERTICAL
2774.800	38.8	-26.3	33.8	31.300	HORIZONTAL
2775.400	38.8	-26.3	33.8	31.286	VERTICAL
2771.800	38.8	-26.3	33.8	31.265	HORIZONTAL
2773.200	38.7	-26.3	33.8	31.204	HORIZONTAL

Set.3 USB mode

Frequency(MHz)	Result(dBuV/m)	G_{PL} (dB)	G_A (dB/m)	P_{mea} (dBuV)	Polarity
3000.000	39.1	-28.3	34.1	33.313	VERTICAL
2776.800	38.9	-26.3	33.8	31.359	HORIZONTAL
2777.400	38.8	-26.3	33.8	31.339	HORIZONTAL
2776.600	38.8	-26.3	33.8	31.307	VERTICAL
2776.400	38.8	-26.3	33.8	31.302	HORIZONTAL
2776.200	38.8	-26.3	33.8	31.286	VERTICAL




Figure A.1 Radiated Emission from 30MHz to 1GHz (Set.1, Charging mode)




Figure A.2 Radiated Emission from 1GHz to 3GHz (Set.1, Charging mode)




Figure A.3 Radiated Emission from 3GHz to 4GHz (Set.1, Charging mode)




Figure A.4 Radiated Emission from 30MHz to 1GHz (Set.2, Charging mode)




Figure A.5 Radiated Emission from 1GHz to 3GHz (Set.2, Charging mode)




Figure A.6 Radiated Emission from 3GHz to 4GHz (Set.2, Charging mode)




Figure A.7 Radiated Emission from 30MHz to 1GHz (Set.3, USB mode)




Figure A.8 Radiated Emission from 1GHz to 3GHz (Set.3, USB mode)

15b RE - 3GHz-4GHz




Figure A.9 Radiated Emission from 3GHz to 4GHz (Set.3, USB mode)

A.2 Conducted Emission (§15.107(a))

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 7.2.

A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 755, and the serial number of the PC is 3908243625. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results




Figure A.10 Conducted Emission (Set.1, Charging mode)

Final Result 1

Frequency (MHz)	QuasiPeak (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
2.067355	44.2	GND	L1	10.0	11.8	56.0
2.119679	48.4	GND	L1	10.0	7.6	56.0
2.506558	49.0	GND	L1	10.0	7.0	56.0
2.510166	47.9	GND	L1	10.0	8.1	56.0
2.557701	49.0	GND	L1	10.0	7.0	56.0
2.989658	43.0	GND	N	10.0	13.0	56.0

Final Result 2

Frequency (MHz)	Average (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
1.764533	40.4	GND	L1	10.0	5.6	46.0
1.963937	33.2	GND	L1	10.0	12.8	46.0
2.117496	25.8	GND	L1	10.0	20.2	46.0
2.264074	41.3	GND	L1	10.0	4.7	46.0
2.476704	22.9	GND	L1	10.0	23.1	46.0
3.227172	28.0	GND	L1	10.0	18.0	46.0




Figure A.11 Conducted Emission (Set.2, Charging mode)

Final Result 1

Frequency (MHz)	QuasiPeak (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
0.849605	48.0	GND	L1	10.3	8.0	56.0
0.851888	47.0	GND	L1	10.3	9.0	56.0
1.395766	47.5	GND	L1	10.3	8.5	56.0
1.941000	46.3	GND	L1	10.3	9.7	56.0
2.359792	44.5	GND	L1	10.4	11.5	56.0
4.794646	43.2	GND	L1	10.5	12.8	56.0

Final Result 2

Frequency (MHz)	Average (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
0.308341	41.9	GND	L1	10.2	8.1	50.0
1.353424	37.4	GND	L1	10.3	8.6	46.0
1.395766	36.5	GND	L1	10.3	9.5	46.0
1.431192	37.5	GND	L1	10.3	8.5	46.0
1.497773	34.9	GND	L1	10.3	11.1	46.0
1.860354	34.5	GND	L1	10.3	11.5	46.0




Figure A.12 Conducted Emission (Set.3, USB mode)

Final Result 1

Frequency (MHz)	QuasiPeak (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
4.126883	35.6	GND	L1	10.4	20.4	56.0
4.140930	37.9	GND	L1	10.4	18.1	56.0
4.637332	32.6	GND	L1	10.5	23.4	56.0
4.723914	37.0	GND	L1	10.5	19.0	56.0
4.943817	36.0	GND	L1	10.5	20.0	56.0
5.019811	36.3	GND	L1	10.5	23.7	60.0

Final Result 2

Frequency (MHz)	Average (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
0.780037	29.7	GND	L1	10.3	16.3	46.0
0.849218	29.1	GND	L1	10.3	16.9	46.0
2.622888	24.0	GND	L1	10.4	22.0	46.0
2.633268	29.7	GND	L1	10.4	16.3	46.0
4.861653	30.5	GND	L1	10.5	15.5	46.0
4.870322	29.7	GND	L1	10.5	16.3	46.0

END OF REPORT