



# SAR TEST REPORT

No. 2012SAR00119

For

**TCT Mobile Limited**

**GSM/EGPRS Quadband mobile phone**

**Mode Name: Conet 1SIM**

**Marketing Name: ONE TOUCH 815**

With

**Hardware Version: Proto**

**Software Version: V213**

**FCCID: RAD308**

**Issued Date: 2012-11-27**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

TMC Beijing, Telecommunication Metrology Center of MIIT

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2079, Fax:+86(0)10-62304633 Email:welcomed@emcite.com. [www.emcite.com](http://www.emcite.com)

### Revision Version

<b>Report Number</b>	<b>Revision</b>	<b>Date</b>	<b>Memo</b>
2012SAR00119	00	2012-11-27	Initial creation of test report

## TABLE OF CONTENT

<b>1 TEST LABORATORY .....</b>	<b>5</b>
1.1 TESTING LOCATION .....	5
1.2 TESTING ENVIRONMENT.....	5
1.3 PROJECT DATA .....	5
1.4 SIGNATURE.....	5
<b>2 STATEMENT OF COMPLIANCE .....</b>	<b>6</b>
<b>3 CLIENT INFORMATION .....</b>	<b>7</b>
3.1 APPLICANT INFORMATION .....	7
3.2 MANUFACTURER INFORMATION .....	7
<b>4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>8</b>
4.1 ABOUT EUT .....	8
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	8
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	8
<b>5 TEST METHODOLOGY .....</b>	<b>9</b>
5.1 APPLICABLE LIMIT REGULATIONS .....	9
5.2 APPLICABLE MEASUREMENT STANDARDS.....	9
<b>6 SPECIFIC ABSORPTION RATE (SAR).....</b>	<b>10</b>
6.1 INTRODUCTION.....	10
6.2 SAR DEFINITION.....	10
<b>7 SAR MEASUREMENT SETUP .....</b>	<b>11</b>
7.1 MEASUREMENT SET-UP .....	11
7.2 DASY4 OR DASY5 E-FIELD PROBE SYSTEM.....	12
7.3 E-FIELD PROBE CALIBRATION .....	12
7.4 OTHER TEST EQUIPMENT .....	13
7.4.1 DATA ACQUISITION ELECTRONICS(DAE) .....	13
7.4.2 ROBOT.....	14
7.4.3 MEASUREMENT SERVER.....	14
7.4.4 DEVICE HOLDER FOR PHANTOM.....	15
7.4.5 PHANTOM.....	15
<b>8. POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM .....</b>	<b>17</b>
8.1 GENERAL CONSIDERATIONS.....	17
8.2 BODY-WORN DEVICE .....	18
8.3 DESKTOP DEVICE.....	18
8.4 DUT SETUP PHOTOS .....	20
<b>9 TISSUE SIMULATING LIQUIDS .....</b>	<b>21</b>
9.1 EQUIVALENT TISSUES.....	21

9.2 DIELECTRIC PERFORMANCE .....	21
<b>10 SYSTEM VALIDATION .....</b>	<b>23</b>
10.1 SYSTEM VALIDATION .....	23
10.2 SYSTEM SETUP .....	23
<b>11 MEASUREMENT PROCEDURES .....</b>	<b>25</b>
11.1 TESTS TO BE PERFORMED.....	25
11.2 MEASUREMENT PROCEDURE.....	27
11.3 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR .....	28
11.4 POWER DRIFT .....	28
<b>12 CONDUCTED OUTPUT POWER.....</b>	<b>29</b>
12.1 GSM MEASUREMENT RESULT .....	29
12.2 WI-FI AND BT MEASUREMENT RESULT .....	30
<b>13 SIMULTANEOUS TX SAR CONSIDERATIONS.....</b>	<b>32</b>
13.1 INTRODUCTION.....	32
13.2 TRANSMIT ANTENNA SEPARATION DISTANCES .....	32
13.3 SIMULTANEOUS TRANSMISSION FOR EUT .....	32
<b>14 SAR TEST RESULT .....</b>	<b>34</b>
14.1 THE EVALUATION OF MULTI-BATTERIES .....	34
14.2 SAR TEST RESULT .....	34
<b>15 MEASUREMENT UNCERTAINTY .....</b>	<b>37</b>
<b>16 MAIN TEST INSTRUMENTS.....</b>	<b>38</b>
<b>ANNEX A GRAPH RESULTS.....</b>	<b>39</b>
<b>ANNEX B SYSTEM VALIDATION RESULTS .....</b>	<b>102</b>
<b>ANNEX C PROBE CALIBRATION CERTIFICATE .....</b>	<b>108</b>
<b>ANNEX D DIPOLE CALIBRATION CERTIFICATE .....</b>	<b>119</b>

## 1 Test Laboratory

### 1.1 Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT  
Address: No 52, Huayuan beilu, Haidian District, Beijing, P.R.China  
Postal Code: 100191  
Telephone: +86-10-62304633  
Fax: +86-10-62304793

### 1.2 Testing Environment

Temperature: 18°C~25 °C,  
Relative humidity: 30%~ 70%  
Ground system resistance: < 0.5 Ω  
Ambient noise & Reflection: < 0.012 W/kg

### 1.3 Project Data


Project Leader: Qi Dianyuan  
Test Engineer: Lin Xiaojun  
Testing Start Date: November 22, 2012  
Testing End Date: November 26, 2012

### 1.4 Signature



---

Lin Xiaojun  
(Prepared this test report)



---

Qi Dianyuan  
(Reviewed this test report)



---

Xiao Li  
Deputy Director of the laboratory  
(Approved this test report)

## 2 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for TCT Mobile Limited GSM/EGPRS Quadband mobile phone Conet 1SIM / ONE TOUCH 815 are as follows (with expanded uncertainty 18.5%)

**Table 2.1: Max. SAR Measured (1g)**

Band	Position	SAR 1g (W/Kg)
GSM 850	Head	0.703
	Body	1.11
GSM 1900	Head	0.758
	Body	1.09
Wi-Fi	Head	0.668
	Body	0.546

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1999.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The measurement together with the test system set-up is described in chapter 7 of this test report. A detailed description of the equipment under test can be found in chapter 3 of this test report. The maximum SAR value is obtained at the case of **(Table 2.1)**, and the values are: **1.11 (1g)**.

### 3 Client Information

#### 3.1 Applicant Information

Company Name: TCT Mobile Limited  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: ShangHai  
Postal Code: 201203  
Country: P.R.China  
Contact: Gong Zhizhou  
Email: zhizhou.gong@jrdcom.com  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

#### 3.2 Manufacturer Information

Company Name: TCT Mobile Limited  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: ShangHai  
Postal Code: 201203  
Country: P.R.China  
Contact: Gong Zhizhou  
Email: zhizhou.gong@jrdcom.com  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

## 4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

### 4.1 About EUT

Description:	GSM/EGPRS Quadband mobile phone
Model name:	Conet 1SIM
Marketing name:	ONE TOUCH 815
Operating mode(s):	GSM 850/900/1800/1900, BT, Wi-Fi 825 – 848.8 MHz (GSM 850)
Tested Tx Frequency:	1850.2 – 1910 MHz (GSM 1900) 2412 – 2462 MHz (Wi-Fi)
GPRS Multislot Class:	12
GPRS capability Class:	B
EGPRS Multislot Class:	12
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Accessories/Body-worn configurations:	Headset
Hotspot mode:	Support simultaneous transmission of hotspot and voice(or data)
Form factor:	10.6 cm × 5.8 cm

### 4.2 Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	866663010121117 / 866663010122123 / 866663010121109 / 866663010122107	Proto	V213

\*EUT ID: is used to identify the test sample in the lab internally.

**Note:** It is performed to test SAR with the EUT (866663010121117 / 866663010122123) and conducted power with the EUT (866663010121109 / 866663010122107).

### 4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	CAB3120000C1	/	BYD
AE2	Battery	CAB3120000C3	/	BAK
AE3	Headset	CCB3160A11C2	/	Shunda
AE4	Headset	CCB3160A11C4	/	Meihao
AE5	Headset	CCB3160A15C2	/	Shunda
AE6	Headset	CCB3160A15C4	/	Meihao

\*AE ID: is used to identify the test sample in the lab internally.

**Note:** AE3 and AE5 are the same, so they can use the same results. AE4 and AE6 are the same, so they can use the same results.



## 5 TEST METHODOLOGY

### 5.1 Applicable Limit Regulations

**ANSI C95.1–1999:** IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

### 5.2 Applicable Measurement Standards

**IC RSS-102 ISSUE4:** Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

**IEEE 1528–2003:** Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

**OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01):** Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.

**KDB648474 D01 SAR Handsets Multi Xmitter and Ant, v01r05:** SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas.

**KDB248227:** SAR measurement procedures for 802.112abg transmitters.

**KDB941225 :** SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

## 6 Specific Absorption Rate (SAR)

### 6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### 6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy ( $dW$ ) absorbed by (dissipated in) an incremental mass ( $dm$ ) contained in a volume element ( $dv$ ) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left( \frac{\delta T}{\delta t} \right)$$

Where:  $C$  is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$


Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of tissue and  $E$  is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

## 7 SAR MEASUREMENT SETUP

### 7.1 Measurement Set-up

The Dasy4 or DASY5 system for performing compliance tests is illustrated above graphically. This system consists of the following items:



**Picture 7.1 SAR Lab Test Measurement Set-up**

- A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY4 or DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as
- warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

## 7.2 Dasy4 or DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 or DASY5 software reads the reflection during a software approach and looks for the maximum using 2<sup>nd</sup> order curve fitting. The approach is stopped at reaching the maximum.

### Probe Specifications:

<b>Model:</b>	<b>ES3DV3, EX3DV4</b>
<b>Frequency</b>	<b>10MHz — 6.0GHz(EX3DV4)</b>
<b>Range:</b>	<b>10MHz — 4GHz(ES3DV3)</b>
<b>Calibration:</b>	<b>In head and body simulating tissue at Frequencies from 835 up to 5800MHz</b>
<b>Linearity:</b>	<b>± 0.2 dB(30 MHz to 6 GHz) for EX3DV4 ± 0.2 dB(30 MHz to 4 GHz) for ES3DV3</b>
<b>Dynamic Range:</b>	<b>10 mW/kg — 100W/kg</b>
<b>Probe Length:</b>	<b>330 mm</b>
<b>Probe Tip</b>	
<b>Length:</b>	<b>20 mm</b>
<b>Body Diameter:</b>	<b>12 mm</b>
<b>Tip Diameter:</b>	<b>2.5 mm (3.9 mm for ES3DV3)</b>
<b>Tip-Center:</b>	<b>1 mm (2.0mm for ES3DV3)</b>
<b>Application:</b>	<b>SAR Dosimetry Testing Compliance tests of mobile phones Dosimetry in strong gradient fields</b>



Picture 7.2 Near-field Probe



Picture 7.3 E-field Probe

## 7.3 E-field Probe Calibration

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm<sup>2</sup>) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed

in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/ cm<sup>2</sup>:

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

$\Delta t$  = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

$\Delta T$  = Temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

$\sigma$  = Simulated tissue conductivity,

$\rho$  = Tissue density (kg/m<sup>3</sup>).


## 7.4 Other Test Equipment

### 7.4.1 Data Acquisition Electronics(DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Picture7.4: DAE

### 7.4.2 Robot

The SPEAG DASY system uses the high precision robots (DASY4: RX90XL; DASY5: RX160L) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)



Picture 7.5 DASY 4



Picture 7.6 DASY 5

### 7.4.3 Measurement Server

The Measurement server is based on a PC/104 CPU board with CPU (dasy4: 166 MHz, Intel Pentium; DASY5: 400 MHz, Intel Celeron), chipdisk (DASY4: 32 MB; DASY5: 128MB), RAM (DASY4: 64 MB, DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.





Picture 7.7 Server for DASY 4



Picture 7.8 Server for DASY 5

#### 7.4.4 Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of  $\pm 0.5\text{mm}$  would produce a SAR uncertainty of  $\pm 20\%$ . Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric


parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.



Picture 7.9-1: Device Holder



Picture 7.9-2: Laptop Extension Kit

#### 7.4.5 Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to represent the 90<sup>th</sup> percentile of the population. The phantom enables the dissymmetric evaluation

of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

Shell Thickness:  $2 \pm 0.2$  mm

Filling Volume: Approx. 25 liters

Dimensions: 810 x 1000 x 500 mm (H x L x W)

Available: Special




**Picture 7.10: SAM Twin Phantom**



## 8. Position of the wireless device in relation to the phantom


### 8.1 General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.




- $w_t$  Width of the handset at the level of the acoustic
- $w_b$  Width of the bottom of the handset
- A Midpoint of the width  $w_t$  of the handset at the level of the acoustic output
- B Midpoint of the width  $w_b$  of the bottom of the handset

Picture 8.1-a Typical “fixed” case handset      Picture 8.1-b Typical “clam-shell” case handset




Picture 8.2 Cheek position of the wireless device on the left side of SAM



Picture 8.3 Tilt position of the wireless device on the left side of SAM

## 8.2 Body-worn device

A typical example of a body-worn device is a mobile phone, wireless enabled PDA or other battery operated wireless device with the ability to transmit while mounted on a person's body using a carry accessory approved by the wireless device manufacturer.




Picture 8.4 Test positions for body-worn devices

## 8.3 Desktop device

A typical example of a desktop device is a wireless enabled desktop computer placed on a table or desk when used.

The DUT shall be positioned at the distance and in the orientation to the phantom that corresponds to the intended use as specified by the manufacturer in the user instructions. For devices that employ an external antenna with variable positions, tests shall be performed for all antenna positions specified. Picture 8.5 show positions for desktop device SAR tests. If the intended use is not specified, the device shall be tested directly against the flat phantom.



**Picture 8.5 Test positions for desktop devices**

**8.4 DUT Setup Photos****Picture 8.6**

## 9 Tissue Simulating Liquids

### 9.1 Equivalent Tissues

The liquid used for the frequency range of 800-3000 MHz consisted of water, sugar, salt, preventol, glycol monobutyl and Cellulose. The liquid has been previously proven to be suited for worst-case. The Table 9.1 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528 and IEC 62209.

**Table 9.1: Composition of the Tissue Equivalent Matter**

Frequency (MHz)	835 Head	835 Body	1900 Head	1900 Body	2450 Head	2450 Body
Ingredients (% by weight)						
Water	41.45	52.5	55.242	69.91	58.79	72.60
Sugar	56.0	45.0	\	\	\	\
Salt	1.45	1.4	0.306	0.13	0.06	0.18
Preventol	0.1	0.1	\	\	\	\
Cellulose	1.0	1.0	\	\	\	\
Glycol Monobutyl	\	\	44.452	29.96	41.15	27.22
Dielectric Parameters	$\epsilon=41.5$	$\epsilon=55.2$	$\epsilon=40.0$	$\epsilon=53.3$	$\epsilon=39.2$	$\epsilon=52.7$
Target Value	$\sigma=0.90$	$\sigma=0.97$	$\sigma=1.40$	$\sigma=1.52$	$\sigma=1.80$	$\sigma=1.95$


**Table 9.2: Targets for tissue simulating liquid**

Frequency (MHz)	Liquid Type	Conductivity ( $\sigma$ )	$\pm 5\%$ Range	Permittivity ( $\epsilon$ )	$\pm 5\%$ Range
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3

### 9.2 Dielectric Performance

**Table 9.3: Dielectric Performance of Tissue Simulating Liquid**

Measurement Date: 835 MHz <b>November 26, 2012</b> 1900 MHz <b>November 23, 2012</b> 2450 MHz <b>November 22, 2012</b>				
/	Type	Frequency	Permittivity $\epsilon$	Conductivity $\sigma$ (S/m)
<b>Measurement value</b>	Head	835 MHz	41.19	0.89
	Body	835 MHz	54.25	0.988
	Head	1900 MHz	40.73	1.389
	Body	1900 MHz	52.39	1.50
	Head	2450 MHz	39.51	1.827
	Body	2450 MHz	52.06	1.963



**Picture 9.1: Liquid depth in the Head Phantom (850 MHz)**



**Picture 9.2 Liquid depth in the Flat Phantom (1900MHz)**



**Picture 9.3 Liquid depth in the Flat Phantom (2450MHz)**


## 10 System Validation

### 10.1 System Validation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

### 10.2 System Setup


In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



**Picture 10.1 System Setup for System Evaluation**

The output power on dipole port must be calibrated to 24 dBm (250mW) before dipole is connected.





Picture 10.2 Photo of Dipole Setup

**Table 10.1: System Validation of Head**

Measurement Date: 835 MHz <u>November 26, 2012</u> 1900 MHz <u>November 23, 2012</u> 2450 MHz <u>November 22, 2012</u>							
Verification results	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
	835 MHz	6.07	9.30	5.96	9.28	-1.81%	-0.22%
	1900 MHz	20.6	39.1	19.84	38.52	-3.69%	-1.48%
2450 MHz	24.4	52.4	23.88	51.20	-2.13%	-2.29%	

**Table 10.2: System Validation of Body**

Measurement Date: 835 MHz <u>November 26, 2012</u> 1900 MHz <u>November 23, 2012</u> 2450 MHz <u>November 22, 2012</u>							
Verification results	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
	835 MHz	6.20	9.36	6.08	9.44	-1.94%	0.85%
	1900 MHz	21.3	39.9	21.56	40.80	1.22%	2.26%
2450 MHz	23.6	50.4	23.36	50.80	-1.02%	0.79%	



## 11 Measurement Procedures

### 11.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in Picture 11.1.


**Step 1:** The tests described in 11.2 shall be performed at the channel that is closest to the centre of the transmit frequency band ( $f_c$ ) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in Chapter 8),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e.,  $N_c > 3$ ), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

**Step 2:** For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 11.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

**Step 3:** Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 11.1 Block diagram of the tests to be performed

## 11.2 Measurement procedure

The following procedure shall be performed for each of the test conditions (see Picture 11.1) described in 11.1:

- a) Measure the local SAR at a test point within 8 mm or less in the normal direction from the inner surface of the phantom.
- b) Measure the two-dimensional SAR distribution within the phantom (area scan procedure). The boundary of the measurement area shall not be closer than 20 mm from the phantom side walls. The distance between the measurement points should enable the detection of the location of local maximum with an accuracy of better than half the linear dimension of the tissue cube after interpolation. A maximum grid spacing of 20 mm for frequencies below 3 GHz and  $(60/f \text{ [GHz]})$  mm for frequencies of 3 GHz and greater is recommended. The maximum distance between the geometrical centre of the probe detectors and the inner surface of the phantom shall be 5 mm for frequencies below 3 GHz and  $\delta \ln(2)/2$  mm for frequencies of 3 GHz and greater, where  $\delta$  is the plane wave skin depth and  $\ln(x)$  is the natural logarithm. The maximum variation of the sensor-phantom surface shall be  $\pm 1$  mm for frequencies below 3 GHz and  $\pm 0.5$  mm for frequencies of 3 GHz and greater. At all measurement points the angle of the probe with respect to the line normal to the surface should be less than  $5^\circ$ . If this cannot be achieved for a measurement distance to the phantom inner surface shorter than the probe diameter, additional uncertainty evaluation is needed.
- c) From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that are not within the zoom-scan volume; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR limit. This is consistent with the 2 dB threshold already stated;
- d) Measure the three-dimensional SAR distribution at the local maxima locations identified in step c). The horizontal grid step shall be  $(24/f[\text{GHz}])$  mm or less but not more than 8 mm. The minimum zoom size of 30 mm by 30 mm and 30 mm for frequencies below 3 GHz. For higher frequencies, the minimum zoom size of 22 mm by 22 mm and 22 mm. The grid step in the vertical direction shall be  $(8-f[\text{GHz}])$  mm or less but not more than 5 mm, if uniform spacing is used. If variable spacing is used in the vertical direction, the maximum spacing between the two closest measured points to the phantom shell shall be  $(12 / f[\text{GHz}])$  mm or less but not more than 4 mm, and the spacing between further points shall increase by an incremental factor not exceeding 1.5. When variable spacing is used, extrapolation routines shall be tested with the same spacing as used in measurements. The maximum distance between the geometrical centre of the probe detectors and the inner surface of the phantom shall be 5 mm for frequencies below 3 GHz and  $\delta \ln(2)/2$  mm for frequencies of 3 GHz and greater, where  $\delta$  is the plane wave skin depth and  $\ln(x)$  is the natural logarithm. Separate grids shall be centered on each of the local SAR maxima found in step c). Uncertainties due to field distortion between the media boundary and the dielectric enclosure of the probe should also be minimized, which is achieved if the distance between the phantom surface and physical tip of the probe is larger than probe tip diameter. Other methods may utilize correction procedures for these boundary effects that enable high precision measurements closer than half the probe diameter. For all measurement points, the angle of the probe with respect to the flat phantom surface shall be less than  $5^\circ$ . If this cannot be achieved an additional uncertainty evaluation is needed.
- e) Use post processing( e.g. interpolation and extrapolation ) procedures to determine the local SAR values at the spatial resolution needed for mass averaging.

### **11.3 Bluetooth & Wi-Fi Measurement Procedures for SAR**

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

### **11.4 Power Drift**

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 14.1 to Table 14.8 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

## 12 Conducted Output Power

### 12.1 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (8960) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

**Table 12.1: The conducted power measurement results for GSM850/1900**

GSM 850MHZ	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	33.19	33.25	33.29
GSM 1900MHZ	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1800MHz)	Channel 512(1850.2MHz)
	29.96	29.98	29.86

**Table 12.2: The conducted power measurement results for GPRS and EGPRS**

GSM 850 GPRS	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	33.19	33.26	33.29	-9.03dB	24.16	24.23	24.26
2 Txslots	30.66	30.74	30.79	-6.02dB	24.64	24.72	24.77
3Txslots	28.95	29.04	29.09	-4.26dB	24.69	24.78	24.83
<b>4 Txslots</b>	27.90	27.99	28.05	-3.01dB	<b>24.89</b>	<b>24.98</b>	<b>25.04</b>
GSM 850 EGPRS	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	33.18	33.25	33.28	-9.03dB	24.15	24.22	24.25
2 Txslots	30.65	30.73	30.78	-6.02dB	24.63	24.71	24.76
3Txslots	28.94	29.03	29.08	-4.26dB	24.68	24.77	24.82
<b>4 Txslots</b>	27.89	27.98	28.04	-3.01dB	<b>24.88</b>	<b>24.97</b>	<b>25.03</b>
PCS1900 GPRS	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.96	29.97	29.85	-9.03dB	20.93	20.94	20.82
<b>2 Txslots</b>	29.09	29.07	28.97	-6.02dB	<b>23.07</b>	<b>23.05</b>	<b>22.95</b>
3Txslots	26.70	26.68	26.54	-4.26dB	22.44	22.42	22.28
4 Txslots	25.93	25.90	25.76	-3.01dB	22.92	22.89	22.75
PCS1900 EGPRS	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.96	29.97	29.85	-9.03dB	20.93	20.94	20.82
<b>2 Txslots</b>	29.09	29.07	28.97	-6.02dB	<b>23.07</b>	<b>23.05</b>	<b>22.95</b>
3Txslots	26.70	26.68	26.54	-4.26dB	22.44	22.42	22.28
4 Txslots	25.92	25.90	25.75	-3.01dB	22.91	22.89	22.74

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

**According to the conducted power as above, the body measurements are performed with 4Txslots for GSM850 and 2Txslots for GSM1900.**

**Note: According to the KDB941225 D03, “when SAR tests for EDGE or EGPRS mode is necessary, GMSK modulation should be used”. So the conducted power is measured with GMSK for GPRS and EGPRS.**

## 12.2 Wi-Fi and BT Measurement result

The output power of BT antenna is as following:

Channel	Ch 0 2402 MHz	Ch 39 2441 Mhz	Ch 78 2480 MHz
Peak Conducted Output Power (dBm)	2.84	3.39	4.87

The average conducted power for WiFi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1	17.69	17.59	17.58	17.38
6	17.76	17.71	17.75	17.34
11	17.95	17.90	17.93	17.51

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	15.02	14.87	14.68	14.51	14.36	14.05	13.62	13.48
6	15.06	14.99	14.91	14.55	14.38	14.11	13.66	13.54
11	15.24	15.14	14.89	14.74	14.57	14.30	13.85	13.73

20M 802.11n (dBm)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	13.26	13.06	12.66	12.49	12.18	11.91	11.76	11.66
6	13.18	13.00	12.83	12.67	12.37	11.90	11.78	11.69
11	13.48	13.29	12.91	12.74	12.44	12.18	12.05	11.74

40M 802.11n (dBm)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
3	12.85	12.32	12.01	11.68	11.01	10.50	10.45	10.39
6	12.81	12.47	11.94	11.71	11.21	10.63	10.42	10.38
9	13.00	12.54	12.25	11.75	11.34	10.93	10.74	10.36

The peak conducted power for WiFi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1	21.17	21.43	22.83	24.29
6	/	/	/	24.53
11	/	/	/	24.79

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	23.54	23.56	23.33	23.31	23.68	23.66	23.83	23.80
6	/	/	/	/	/	/	23.85	/
11	/	/	/	/	/	/	23.98	/

20M 802.11n (dBm)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	21.79	21.55	21.48	22.02	21.84	21.91	21.94	21.97
6	/	/	/	22.09	/	/	/	/
11	/	/	/	22.36	/	/	/	/

40M 802.11n (dBm)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
3	21.56	21.36	21.39	21.68	21.67	21.74	21.70	21.50
6	/	/	/	/	/	21.74	/	/
9	/	/	/	/	/	21.94	/	/

SAR is not required for 802.11g channels if the output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels, and for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate. According to the above conducted power, the EUT should be tested for “802.11b, 1Mbps, channel 11”.

## 13 Simultaneous TX SAR Considerations


### 13.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

For this device, the BT and WiFi can transmit simultaneous with other transmitters.

### 13.2 Transmit Antenna Separation Distances

The distance between BT antenna and RF antenna is  $< 2.5\text{cm}$ . The distance between WiFi antenna and RF antenna is  $> 2.5\text{cm}$  and  $< 5\text{cm}$ . The location of the antennas inside mobile phone is shown below:



Picture 13.1 Antenna Locations

### 13.3 Simultaneous Transmission for EUT

Table 13.1: Summary of Transmitters

Band/Mode	F(GHz)	$P_{\text{ref}}$ power threshold (mW)	RF output power (mW)
Bluetooth	2.441	12.3	3.07
2.4GHz WLAN 802.11 b/g/n	2.45	12.2	62.37

Note: According to the KDB 648474 D01,  $P_{\text{ref}} = 60/2f$ .



According to the conducted power measurement result, we can draw the conclusion that: stand-alone SAR and simultaneous transmission SAR for Bluetooth should not be performed. Stand-alone SAR for WiFi should be performed. Then, simultaneous transmission SAR for WiFi is considered with measurement results of GSM and WiFi.

**Table 13.2 SAR Evaluation Requirements for Multiple Transmitter Handsets**

	Individual Transmitter	Simultaneous Transmission
<b>Licensed Transmitters</b>	<u>Routine evaluation required</u>	<b>SAR not required:</b> Unlicensed only
<b>Unlicensed Transmitters</b>	<p><b>When there is no simultaneous transmission –</b></p> <ul style="list-style-type: none"> <li>○ output <math>\leq 60/f</math>: SAR not required</li> <li>○ output <math>&gt; 60/f</math>: stand-alone SAR required</li> </ul> <p><b>When there is simultaneous transmission –</b></p> <p><u>Stand-alone SAR not required when</u></p> <ul style="list-style-type: none"> <li>○ output <math>\leq 2 \cdot P_{Ref}</math> and antenna is <math>\geq 5.0</math> cm from other antennas</li> <li>○ output <math>\leq P_{Ref}</math> and antenna is <math>\geq 2.5</math> cm from other antennas</li> <li>○ output <math>\leq P_{Ref}</math> and antenna is <math>&lt; 2.5</math> cm from other antennas, each with either output power <math>\leq P_{Ref}</math> or 1-g SAR <math>&lt; 1.2</math> W/kg</li> </ul> <p><u>Otherwise stand-alone SAR is required</u></p> <p><b>When stand-alone SAR is required</b></p> <ul style="list-style-type: none"> <li>○ test SAR on highest output channel for each wireless mode and exposure condition</li> <li>○ if SAR for highest output channel is <math>&gt; 50\%</math> of SAR limit, evaluate all channels according to normal procedures</li> </ul>	<p>○ when stand-alone 1-g SAR is not required and antenna is <math>\geq 5</math> cm from other antennas</p> <p><u>Licensed &amp; Unlicensed</u></p> <ul style="list-style-type: none"> <li>○ when the sum of the 1-g SAR is <math>&lt; 1.6</math> W/kg for all simultaneous transmitting antennas</li> <li>○ when SAR to peak location separation ratio of simultaneous transmitting antenna pair is <math>&lt; 0.3</math></li> </ul> <p><b>SAR required:</b></p> <p><u>Licensed &amp; Unlicensed</u></p> <p>antenna pairs with SAR to peak location separation ratio <math>\geq 0.3</math>; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition</p> <p><b>Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply</b></p>

**Table 13.3: The sum of SAR values for GSM and WiFi**

	Position	GSM	WiFi	Sum
<b>Maximum SAR value for Head</b>	Right hand, Touch cheek	0.758	0.668	<b>1.426</b>
<b>Maximum SAR value for Body</b>	Toward Ground	1.11	0.476	<b>1.586</b>
	Right Side	0.644	0.546	<b>1.19</b>

According to the above table, the sum of SAR values for GSM and WiFi  $< 1.6$ W/kg. So the simultaneous transmission SAR is not required for WiFi transmitter.

## 14 SAR Test Result

### 14.1 The evaluation of multi-batteries

We'll perform the head measurement in all bands with the primary battery depending on the evaluation of multi-batteries and retest on highest value point with other batteries. Then, repeat the measurement in the Body test.

Table 14.1: The evaluation of multi-batteries for Head Test

Frequency		Mode/Band	Side	Test Position	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
848.8	251	GSM850	Left	Touch	CAB3120000C1	0.695	-0.17
848.8	251	GSM850	Left	Touch	CAB3120000C3	0.703	-0.02

Note: According to the values in the above table, the battery, CAB3120000C3, is the primary battery. We'll perform the head measurement with this battery and retest on highest value point with others.

Table 14.2: The evaluation of multi-batteries for Body Test

Frequency		Mode/Band	Headset	Test Position	Spacing (mm)	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.						(W/kg)	
1909.8	810	GPRS	\	Ground	10	CAB3120000C1	1.01	-0.07
1909.8	810	GPRS	\	Ground	10	CAB3120000C3	1.03	-0.12

Note: According to the values in the above table, the battery, CAB3120000C3, is the primary battery. We'll perform the Body measurement with this battery and retest on highest value point with others.

### 14.2 SAR Test Result

Table 14.3: SAR Values (GSM 850 MHz Band - Head)

Frequency		Mode/Band	Side	Test Position	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
848.8	251	Speech	Left	Touch	CAB3120000C3	0.703	-0.02
836.6	190	Speech	Left	Touch	CAB3120000C3	0.617	-0.19
824.2	128	Speech	Left	Touch	CAB3120000C3	0.599	-0.15
848.8	251	Speech	Left	Tilt	CAB3120000C3	0.451	-0.09
836.6	190	Speech	Left	Tilt	CAB3120000C3	0.428	-0.18
824.2	128	Speech	Left	Tilt	CAB3120000C3	0.394	-0.09
848.8	251	Speech	Right	Touch	CAB3120000C3	0.570	-0.18
836.6	190	Speech	Right	Touch	CAB3120000C3	0.519	0.08
824.2	128	Speech	Right	Touch	CAB3120000C3	0.484	0.01
848.8	251	Speech	Right	Tilt	CAB3120000C3	0.426	-0.12
836.6	190	Speech	Right	Tilt	CAB3120000C3	0.431	-0.13
824.2	128	Speech	Right	Tilt	CAB3120000C3	0.414	-0.08

Table 14.4: SAR Values (GSM 850 MHz Band - Body)

Frequency		Mode/ Band	Headset	Test Position	Spacing (mm)	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.						(W/kg)	
824.2	128	GPRS	\	Phantom	10	CAB3120000C3	0.796	0.03
848.8	251	GPRS	\	Ground	10	CAB3120000C3	1.11	-0.01
836.6	190	GPRS	\	Ground	10	CAB3120000C3	1.1	0.03
824.2	128	GPRS	\	Ground	10	CAB3120000C3	1.02	-0.08
824.2	128	GPRS	\	Left	10	CAB3120000C3	0.716	-0.02
824.2	128	GPRS	\	Right	10	CAB3120000C3	0.644	-0.01
824.2	128	GPRS	\	Bottom	10	CAB3120000C3	0.075	0.03
848.8	251	EGPRS	\	Ground	10	CAB3120000C3	1.06	-0.08
848.8	251	Speech	CCB3160A11C2	Ground	10	CAB3120000C3	0.714	-0.18
848.8	251	Speech	CCB3160A11C4	Ground	10	CAB3120000C3	0.666	-0.07
848.8	251	GPRS	\	Ground	10	CAB3120000C1	1.05	-0.03

Table 14.5: SAR Values (GSM 1900 MHz Band - Head)

Frequency		Mode/Band	Side	Test Position	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
1909.8	810	Speech	Left	Touch	CAB3120000C3	0.434	0.07
1880	661	Speech	Left	Touch	CAB3120000C3	0.446	0.03
1850.2	512	Speech	Left	Touch	CAB3120000C3	0.455	0.01
1909.8	810	Speech	Left	Tilt	CAB3120000C3	0.252	-0.03
1880	661	Speech	Left	Tilt	CAB3120000C3	0.295	0.03
1850.2	512	Speech	Left	Tilt	CAB3120000C3	0.271	-0.01
1909.8	810	Speech	Right	Touch	CAB3120000C3	0.613	-0.15
1880	661	Speech	Right	Touch	CAB3120000C3	0.758	-0.04
1850.2	512	Speech	Right	Touch	CAB3120000C3	0.722	-0.00
1909.8	810	Speech	Right	Tilt	CAB3120000C3	0.223	-0.10
1880	661	Speech	Right	Tilt	CAB3120000C3	0.248	-0.01
1850.2	512	Speech	Right	Tilt	CAB3120000C3	0.223	0.03
1880	661	Speech	Right	Touch	CAB3120000C1	0.731	-0.00

Table 14.6: SAR Values (GSM 1900 MHz Band - Body)

Frequency		Mode/Band	Headset	Test Position	Spacing (mm)	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.						(W/kg)	
1909.8	810	GPRS	\	Phantom	10	CAB3120000C3	0.763	0.02
1909.8	810	GPRS	\	Ground	10	CAB3120000C3	1.03	-0.12
1880	661	GPRS	\	Ground	10	CAB3120000C3	1.09	-0.03
1850.2	512	GPRS	\	Ground	10	CAB3120000C3	1.07	0.10
1909.8	810	GPRS	\	Left	10	CAB3120000C3	0.199	0.07
1909.8	810	GPRS	\	Right	10	CAB3120000C3	0.234	-0.03
1909.8	810	GPRS	\	Bottom	10	CAB3120000C3	1.05	-0.14
1880	661	GPRS	\	Bottom	10	CAB3120000C3	0.878	0.10

1850.2	512	GPRS	\	Bottom	10	CAB3120000C3	0.896	-0.09
1909.8	810	EGPRS	\	Ground	10	CAB3120000C3	1.02	0.06
1880	661	EGPRS	\	Ground	10	CAB3120000C3	1.07	0.05
1850.2	512	EGPRS	\	Ground	10	CAB3120000C3	1.07	0.06
1880	661	Speech	CCB3160A11C2	Ground	10	CAB3120000C3	0.729	0.03
1880	661	Speech	CCB3160A11C4	Ground	10	CAB3120000C3	0.607	-0.03

Table 14.7: SAR Values (WiFi 802.11b - Head)

Frequency		Mode/Band	Side	Test Position	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
2462	11	802.11b, 1Mbps	Left	Touch	CAB3120000C3	0.233	0.15
2462	11	802.11b, 1Mbps	Left	Tilt	CAB3120000C3	0.161	-0.10
2462	11	802.11b, 1Mbps	Right	Touch	CAB3120000C3	0.668	-0.13
2462	11	802.11b, 1Mbps	Right	Tilt	CAB3120000C3	0.094	-0.01

Table 14.8: SAR Values (WiFi 802.11b - Body)

Frequency		Mode/Band	Test Position	Spacing (mm)	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
2462	11	802.11b, 1Mbps	Phantom	10	CAB3120000C3	0.046	0.16
2462	11	802.11b, 1Mbps	Ground	10	CAB3120000C3	0.476	-0.06
2462	11	802.11b, 1Mbps	Right	10	CAB3120000C3	0.546	-0.19

## 15 Measurement Uncertainty

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
<b>Measurement system</b>										
1	Probe calibration	B	5.5	N	1	1	1	5.5	5.5	$\infty$
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	$\infty$
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	$\infty$
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
5	Detection limit	B	1.0	N	1	1	1	0.6	0.6	$\infty$
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	$\infty$
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	$\infty$
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	$\infty$
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	$\infty$
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	$\infty$
11	Probe positioned mech. restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	$\infty$
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	$\infty$
<b>Test sample related</b>										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	$\infty$
<b>Phantom and set-up</b>										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	$\infty$
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	$\infty$
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	$\infty$

continue										
No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u'_c = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$						9.25	9.12	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						18.5	18.2	

## 16 MAIN TEST INSTRUMENTS

**Table 16.1: List of Main Instruments**

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	E5071C	MY46110673	February 14, 2012	One year
02	Power meter	NRVD	102083	September 11, 2012	One year
03	Power sensor	NRV-Z5	100542		
04	Signal Generator	E4438C	MY49070393	November 13, 2012	One Year
05	Amplifier	VTL5400	0505	No Calibration Requested	
06	BTS	8960	MY50263375	January 30, 2012	One year
07	E-field Probe	SPEAG ES3DV3	3149	April 24, 2012	One year
08	DAE	SPEAG DAE4	771	November 20, 2012	One year
09	Dipole Validation Kit	SPEAG D835V2	443	May 03, 2012	One year
10	Dipole Validation Kit	SPEAG D1900V2	541	May 09, 2012	One year
11	Dipole Validation Kit	SPEAG D2450V2	853	May 02, 2012	One year

\*\*\*END OF REPORT BODY\*\*\*

## ANNEX A GRAPH RESULTS

### 850 Left Cheek High

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 41.008$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Cheek High/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.754 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.664 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.890 mW/g

**SAR(1 g) = 0.703 mW/g; SAR(10 g) = 0.532 mW/g**

Maximum value of SAR (measured) = 0.728 mW/g





Fig. 1 850MHz CH251



**Fig. 1-1 Z-Scan at power reference point (850 MHz CH251)**



### 850 Left Cheek Middle

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 41.165$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Cheek Middle/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.679 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.173 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.770 mW/g

**SAR(1 g) = 0.617 mW/g; SAR(10 g) = 0.470 mW/g**

Maximum value of SAR (measured) = 0.642 mW/g




Fig. 2 850 MHz CH190

**850 Left Cheek Low**

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 0.88 \text{ mho/m}$ ;  $\epsilon_r = 41.305$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.4^\circ\text{C}$       Liquid Temperature:  $22.0^\circ\text{C}$

Communication System: GSM; Frequency:  $824.2 \text{ MHz}$ ; Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Cheek Low/Area Scan (61x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.659 \text{ mW/g}$


**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $13.434 \text{ V/m}$ ; Power Drift =  $-0.15 \text{ dB}$

Peak SAR (extrapolated) =  $0.737 \text{ mW/g}$

**SAR(1 g) =  $0.599 \text{ mW/g}$ ; SAR(10 g) =  $0.458 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.621 \text{ mW/g}$



**Fig. 3 850 MHz CH128**

### 850 Left Tilt High

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 41.008$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Tilt High/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.481 mW/g

**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.892 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.565 mW/g

**SAR(1 g) = 0.451 mW/g; SAR(10 g) = 0.339 mW/g**

Maximum value of SAR (measured) = 0.473 mW/g




Fig.4 850 MHz CH251

**850 Left Tilt Middle**

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 41.165$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Tilt Middle/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.447 mW/g


**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.821 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.538 mW/g

**SAR(1 g) = 0.428 mW/g; SAR(10 g) = 0.324 mW/g**

Maximum value of SAR (measured) = 0.450 mW/g



**Fig.5 850 MHz CH190**

### 850 Left Tilt Low

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 41.305$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Tilt Low/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.433 mW/g

**Tilt Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.501 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.489 mW/g

**SAR(1 g) = 0.394 mW/g; SAR(10 g) = 0.302 mW/g**

Maximum value of SAR (measured) = 0.409 mW/g




Fig. 6 850 MHz CH128

### 850 Right Cheek High

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 41.008$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM; Frequency: 848.8 MHz; Duty Cycle: 1:8.30042

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Cheek High/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.588 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.699 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.702 mW/g

**SAR(1 g) = 0.570 mW/g; SAR(10 g) = 0.434 mW/g**

Maximum value of SAR (measured) = 0.591 mW/g




Fig. 7 850 MHz CH251



### 850 Right Cheek Middle

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 41.165$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Cheek Middle/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.560 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.089 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.628 mW/g

**SAR(1 g) = 0.519 mW/g; SAR(10 g) = 0.403 mW/g**

Maximum value of SAR (measured) = 0.536 mW/g




Fig. 8 850 MHz CH190

**850 Right Cheek Low**

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 0.88 \text{ mho/m}$ ;  $\epsilon_r = 41.305$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.4^\circ\text{C}$       Liquid Temperature:  $22.0^\circ\text{C}$

Communication System: GSM; Frequency:  $824.2 \text{ MHz}$ ; Duty Cycle: 1:8.30042

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Cheek Low/Area Scan (61x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.510 \text{ mW/g}$


**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $11.664 \text{ V/m}$ ; Power Drift =  $0.01 \text{ dB}$

Peak SAR (extrapolated) =  $0.584 \text{ mW/g}$

**SAR(1 g) =  $0.484 \text{ mW/g}$ ; SAR(10 g) =  $0.373 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.506 \text{ mW/g}$



**Fig. 9 850 MHz CH128**



### 850 Right Tilt High

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 41.008$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Tilt High/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.449 mW/g

**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.213 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.526 mW/g

**SAR(1 g) = 0.426 mW/g; SAR(10 g) = 0.322 mW/g**

Maximum value of SAR (measured) = 0.447 mW/g




Fig.10 850 MHz CH251

### 850 Right Tilt Middle

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 41.165$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Tilt Middle/Area Scan (61x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.459 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.521 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.523 mW/g

**SAR(1 g) = 0.431 mW/g; SAR(10 g) = 0.328 mW/g**

Maximum value of SAR (measured) = 0.450 mW/g




Fig.11 850 MHz CH190

**850 Right Tilt Low**

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Head 835 MHz

Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 0.88 \text{ mho/m}$ ;  $\epsilon_r = 41.305$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.4^\circ\text{C}$       Liquid Temperature:  $22.0^\circ\text{C}$

Communication System: GSM 850 Frequency:  $824.2 \text{ MHz}$  Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.26, 6.26, 6.26)

**Tilt Low/Area Scan (61x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.435 \text{ mW/g}$


**Tilt Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $14.337 \text{ V/m}$ ; Power Drift =  $-0.08 \text{ dB}$

Peak SAR (extrapolated) =  $0.505 \text{ mW/g}$

**SAR(1 g) =  $0.414 \text{ mW/g}$ ; SAR(10 g) =  $0.316 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.432 \text{ mW/g}$



**Fig. 12 850 MHz CH128**

### 850 Body Toward Phantom Low

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.981$  mho/m;  $\epsilon_r = 54.364$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Phantom Low/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.840 mW/g

**Toward Phantom Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.889 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.978 mW/g

**SAR(1 g) = 0.796 mW/g; SAR(10 g) = 0.609 mW/g**

Maximum value of SAR (measured) = 0.834 mW/g




Fig. 13 850 MHz CH128

### 850 Body Toward Ground High

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 1.007$  mho/m;  $\epsilon_r = 54.121$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 848.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Ground High/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.17 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 33.778 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.419 mW/g

**SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.818 mW/g**

Maximum value of SAR (measured) = 1.17 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 33.778 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.391 mW/g

**SAR(1 g) = 0.999 mW/g; SAR(10 g) = 0.698 mW/g**

Maximum value of SAR (measured) = 1.12 mW/g




Fig. 14 850 MHz CH251




Fig. 14-1 Z-Scan at power reference point (850 MHz CH251)

### 850 Body Toward Ground Middle

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.994$  mho/m;  $\epsilon_r = 54.237$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 836.6 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Ground Middle/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.16 mW/g

**Toward Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 33.680 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.398 mW/g

**SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.814 mW/g**

Maximum value of SAR (measured) = 1.16 mW/g

**Toward Ground Middle/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 33.680 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.403 mW/g

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.709 mW/g**

Maximum value of SAR (measured) = 1.13 mW/g




Fig. 15 850 MHz CH190



### 850 Body Toward Ground Low

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.981$  mho/m;  $\epsilon_r = 54.364$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Ground Low/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.08 mW/g

**Toward Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 32.549 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.294 mW/g

**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.755 mW/g**

Maximum value of SAR (measured) = 1.07 mW/g

**Toward Ground Low/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 32.549 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.260 mW/g

**SAR(1 g) = 0.942 mW/g; SAR(10 g) = 0.668 mW/g**

Maximum value of SAR (measured) = 1.04 mW/g




Fig. 16 850 MHz CH128



### 850 Body Left Side Low

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.981$  mho/m;  $\epsilon_r = 54.364$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Left Side Low/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.771 mW/g

**Left Side Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 28.165 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.953 mW/g

**SAR(1 g) = 0.716 mW/g; SAR(10 g) = 0.507 mW/g**

Maximum value of SAR (measured) = 0.761 mW/g




Fig. 17 850 MHz CH128

### 850 Body Right Side Low

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.981$  mho/m;  $\epsilon_r = 54.364$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Right Side Low/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.695 mW/g

**Right Side Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.396 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.871 mW/g

**SAR(1 g) = 0.644 mW/g; SAR(10 g) = 0.448 mW/g**

Maximum value of SAR (measured) = 0.684 mW/g




Fig. 18 850 MHz CH128

### 850 Body Bottom Side Low

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.981$  mho/m;  $\epsilon_r = 54.364$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Bottom Side Low/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.0802 mW/g

**Bottom Side Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.234 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.117 mW/g

**SAR(1 g) = 0.075 mW/g; SAR(10 g) = 0.048 mW/g**

Maximum value of SAR (measured) = 0.0797 mW/g




Fig. 19 850 MHz CH128

### 850 Body Toward Ground High with EGPRS

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 1.007$  mho/m;  $\epsilon_r = 54.121$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 EGPRS Frequency: 848.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Ground High/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.12 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 32.752 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.362 mW/g

**SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.783 mW/g**

Maximum value of SAR (measured) = 1.12 mW/g




Fig. 20 850 MHz CH251

### 850 Body Toward Ground High with Headset CCB3160A11C2

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 1.007$  mho/m;  $\epsilon_r = 54.121$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Ground High/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.756 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 28.492 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.946 mW/g

**SAR(1 g) = 0.714 mW/g; SAR(10 g) = 0.521 mW/g**

Maximum value of SAR (measured) = 0.758 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 28.492 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.961 mW/g

**SAR(1 g) = 0.662 mW/g; SAR(10 g) = 0.467 mW/g**

Maximum value of SAR (measured) = 0.747 mW/g




Fig. 21 850 MHz CH251

### 850 Body Toward Ground High with Headset CCB3160A11C4

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 1.007$  mho/m;  $\epsilon_r = 54.121$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Ground High/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.713 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.114 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.841 mW/g

**SAR(1 g) = 0.666 mW/g; SAR(10 g) = 0.495 mW/g**

Maximum value of SAR (measured) = 0.700 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.114 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.771 mW/g

**SAR(1 g) = 0.557 mW/g; SAR(10 g) = 0.396 mW/g**

Maximum value of SAR (measured) = 0.634 mW/g




Fig. 22 850 MHz CH251

### 850 Body Toward Ground High with battery CAB3120000C1

Date: 2012-11-26

Electronics: DAE4 Sn771

Medium: Body 835 MHz

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 1.007$  mho/m;  $\epsilon_r = 54.121$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.4°C      Liquid Temperature: 22.0°C

Communication System: GSM 850 GPRS Frequency: 848.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3149 ConvF(6.14, 6.14, 6.14)

**Toward Ground High/Area Scan (61x111x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.10 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 32.658 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.343 mW/g

**SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.777 mW/g**

Maximum value of SAR (measured) = 1.10 mW/g




Fig. 23 850 MHz CH251