



SAR TEST REPORT

No. 2013SAR00077

For

TCT Mobile Limited

HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone

Model Name: Megane 1SIM AWS

Marketing Name: ONE TOUCH 5020W

with

Hardware Version: PIO

Software Version: v2I55-0

FCC ID: RAD356

Issued Date: 2013-05-29



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of MIIT

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2079, Fax:+86(0)10-62304633 Email:welcomed@emcite.com. www.emcite.com

Revision Version

Report Number	Revision	Date	Memo
2013SAR00077	00	2013-05-29	Initial creation of test report

TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 TESTING LOCATION	5
1.2 TESTING ENVIRONMENT.....	5
1.3 PROJECT DATA	5
1.4 SIGNATURE.....	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION.....	8
3.1 APPLICANT INFORMATION	8
3.2 MANUFACTURER INFORMATION	8
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	9
4.1 ABOUT EUT	9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	9
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	10
5 TEST METHODOLOGY	10
5.1 APPLICABLE LIMIT REGULATIONS	10
5.2 APPLICABLE MEASUREMENT STANDARDS.....	10
6 SPECIFIC ABSORPTION RATE (SAR).....	11
6.1 INTRODUCTION.....	11
6.2 SAR DEFINITION.....	11
7 TISSUE SIMULATING LIQUIDS.....	12
7.1 TARGETS FOR TISSUE SIMULATING LIQUID	12
7.2 DIELECTRIC PERFORMANCE	12
8 SYSTEM VERIFICATION.....	16
8.1 SYSTEM SETUP.....	16
8.2 SYSTEM VERIFICATION.....	17
9 MEASUREMENT PROCEDURES	18
9.1 TESTS TO BE PERFORMED	18
9.2 GENERAL MEASUREMENT PROCEDURE.....	19
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR	20
9.4 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR	21
9.5 POWER DRIFT.....	21
10 AREA SCAN BASED 1-G SAR	22
10.1 REQUIREMENT OF KDB.....	22
10.2 FAST SAR ALGORITHMS	22
11 CONDUCTED OUTPUT POWER.....	23

11.1 MANUFACTURING TOLERANCE	23
11.2 GSM MEASUREMENT RESULT	25
11.3 WCDMA MEASUREMENT RESULT.....	26
11.4 WI-FI AND BT MEASUREMENT RESULT	27
12 SIMULTANEOUS TX SAR CONSIDERATIONS	29
12.1 INTRODUCTION.....	29
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES	29
12.3 SAR MEASUREMENT POSITIONS	30
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	30
13 EVALUATION OF SIMULTANEOUS.....	31
14 SAR TEST RESULT.....	32
14.1 SAR RESULTS FOR FAST SAR.....	32
14.2 SAR RESULTS FOR STANDARD PROCEDURE.....	39
15 SAR MEASUREMENT VARIABILITY.....	41
16 MEASUREMENT UNCERTAINTY	43
17 MAIN TEST INSTRUMENTS	47
ANNEX A GRAPH RESULTS.....	48
ANNEX B SYSTEM VERIFICATION RESULTS.....	71
ANNEX C SAR MEASUREMENT SETUP	78
ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	84
ANNEX E EQUIVALENT MEDIA RECIPES	87
ANNEX F SYSTEM VALIDATION	88
ANNEX G PROBE CALIBRATION CERTIFICATE	89
ANNEX H DIPOLE CALIBRATION CERTIFICATE.....	100
ANNEX I DIPOLE QUALIFICATION FOR THE EXTENDED 3-YEAR CALIBRATION INTERVAL	124

1 Test Laboratory

1.1 Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52, Huayuan beilu, Haidian District, Beijing, P.R.China
Postal Code: 100191
Telephone: +86-10-62304633
Fax: +86-10-62304793

1.2 Testing Environment

Temperature: 18°C~25 °C,
Relative humidity: 30%~ 70%
Ground system resistance: < 0.5 Ω
Ambient noise & Reflection: < 0.012 W/kg


1.3 Project Data

Project Leader: Qi Dianyuan
Test Engineer: Lin Xiaojun
Testing Start Date: May 22, 2013
Testing End Date: May 24, 2013

1.4 Signature



Lin Xiaojun
(Prepared this test report)



Qi Dianyuan
(Reviewed this test report)



Xiao Li
Deputy Director of the laboratory
(Approved this test report)

2 Statement of Compliance

This EUT is a variant product and the report of original sample is No. RXA1304-0001SAR01R1 issued by TA Technology (Shanghai) Co., Ltd.

According to the client request, we quote the conducted output power for all bands and the relevant information of original sample for WiFi, including system verification, conducted output power, test results and graph results.

The maximum results of Specific Absorption Rate (SAR) found during testing for TCT Mobile Limited HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone Megane 1SIM AWS / ONE TOUCH 5020W are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g (W/Kg)	Equipment Class
Head (Separation Distance 0mm)	GSM 850	0.88	PCE
	PCS 1900	0.31	
	UMTS FDD 2	0.63	
	UMTS FDD 4	0.80	
	UMTS FDD 5	1.04	
	WLAN 2.4 GHz	0.17	DTS
Body-worn (Separation Distance 10mm)	GSM 850	1.27	PCE
	PCS 1900	1.18	
	UMTS FDD 2	1.31	
	UMTS FDD 4	1.17	
	UMTS FDD 5	1.23	
	WLAN 2.4 GHz	0.12	DTS

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1999.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The highest reported SAR value is obtained at the case of **(Table 2.1)**, and the values are: **1.31 W/kg (1g)**.

Table 2.2: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	1.04	0.11	1.15
	Right hand, Touch cheek	0.88	0.17	1.05
Highest reported SAR value for Body	Rear	1.31	0.11	1.42
	Left	0.98	0.12	1.10

Table 2.3: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	1.04	0.19	1.23
Highest reported SAR value for Body	Rear	1.31	0.19	1.50

BT* - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **1.50 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

3 Client Information

3.1 Applicant Information

Company Name:	TCT Mobile Limited
Address /Post:	12F/B, TCL Tower, Gaoxin Nanyi Road, Nanshan District, Shenzhen, Guangdong,P.R. China
City:	Shenzhen
Postal Code:	/
Country:	P.R.China
Contact:	Lv Meixian
Email:	meixian.lv@tcl.com
Telephone:	0086 755 33956929
Fax:	0086 755 36645072

3.2 Manufacturer Information

Company Name:	TCT Mobile Limited
Address /Post:	12F/B, TCL Tower, Gaoxin Nanyi Road, Nanshan District, Shenzhen, Guangdong,P.R. China
City:	Shenzhen
Postal Code:	/
Country:	P.R.China
Contact:	Lv Meixian
Email:	meixian.lv@tcl.com
Telephone:	0086 755 33956929
Fax:	0086 755 36645072

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	HSUPA/HSDPA/UMTS triband/GSM quadband mobile phone
Model name:	Megane 1SIM AWS
Marketing name:	ONE TOUCH 5020W
Operating mode(s):	GSM 850/900/1800/1900, WCDMA 850/1700/1900, BT, Wi-Fi
Tested Tx Frequency:	825 – 848.8 MHz (GSM 850)
	1850.2 – 1910 MHz (GSM 1900)
	826.4–846.6 MHz (WCDMA850 Band V)
	1712.4 – 1752.6 MHz (WCDMA 1700 Band IV)
	1852.4–1907.6 MHz (WCDMA1900 Band II)
	2412 – 2462 MHz (Wi-Fi 2.4G)
GPRS/EGPRS Multislot Class:	12
GPRS capability Class:	B
WCDMA UE Category:	6
Release Version:	GSM: R99
	GPRS: R99
	UMTS: R6
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Accessories/Body-worn configurations:	Headset
Hotspot mode:	Support simultaneous transmission of hotspot and voice(or data)
Form factor:	121.5mm × 64mm

4.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
EUT1	013584000151629	PIO	v2I55-0
EUT2	013584000000529	PIO	v2I55-0

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1 and conducted power with the EUT2.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	CAB60BA000C1	/	SCUD
AE2	Headset	CCB3160A15C1	/	Juwei
AE3	Headset	CCB3160A15C4	/	Meihao
AE4	Headset	CCB3160A11C1	/	Juwei
AE5	Headset	CCB3160A11C4	/	Meihao

*AE ID: is used to identify the test sample in the lab internally.

Note: AE2 and AE4 are the same, so they can use the same results. AE3 and AE5 are the same, so they can use the same results.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.

KDB447498 D01: General RF Exposure Guidance v05: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 SAR Handsets Multi Xmitter and Ant v01: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v02: SAR Measurement Procedures for 3G Devices

KDB941225 D06 Hot Spot SAR v01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227: SAR measurement procedures for 802.112abg transmitters

KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01: SAR Measurement Requirements for 100 MHz to 6 GHz

KDB865664 D02 SAR Reporting v01: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid

Frequency (MHz)	Liquid Type	Conductivity (σ)	$\pm 5\%$ Range	Permittivity (ϵ)	$\pm 5\%$ Range
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1750	Head	1.37	1.30~1.44	40.08	38.1~42.1
1750	Body	1.49	1.42~1.56	53.4	50.7~56.1
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3


7.2 Dielectric Performance

Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ϵ	Drift (%)	Conductivity σ (S/m)	Drift (%)
2013-05-22	Head	835 MHz	40.37	-2.72	0.925	2.78
	Body	835 MHz	54.41	-1.43	0.986	1.65
2013-05-24	Head	1750 MHz	39.34	-1.85	1.388	1.31
	Body	1750 MHz	52.16	-2.32	1.514	1.61
2013-05-23	Head	1900 MHz	39.06	-2.35	1.418	1.29
	Body	1900 MHz	52.63	-1.26	1.529	0.59
2013-04-17	Head	2450 MHz	38.53	-1.71	1.86	3.33
2013-04-18	Body	2450 MHz	51.69	-1.92	1.903	-2.41

Note: The dielectric parameter of 2450MHz is measured by TA Technology (Shanghai) Co., Ltd.


Please refer to the report No.RXA1304-0001SAR01R1.




Picture 7-1: Liquid depth in the Head Phantom (835 MHz)




Picture 7-2: Liquid depth in the Flat Phantom (835 MHz)




Picture 7-3: Liquid depth in the Head Phantom (1750 MHz)



Picture 7-4 Liquid depth in the Flat Phantom (1750MHz)



Picture 7-5: Liquid depth in the Head Phantom (1900 MHz)




Picture 7-6 Liquid depth in the Flat Phantom (1900MHz)


8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2013-05-22	835 MHz	6.07	9.30	5.92	9.04	-2.47%	-2.80%
2013-05-24	1750 MHz	19.3	36.2	19.64	36.92	1.76%	1.99%
2013-05-23	1900 MHz	20.6	39.1	20.20	38.48	-1.94%	-1.59%
2013-04-17	2450 MHz	25.4	53.8	24.88	54.80	-2.05%	1.86%

Note: The system verification of 2450MHz is performed by TA Technology (Shanghai) Co., Ltd.
Please refer to the report No.RXA1304-0001SAR01R1.

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2013-05-22	835 MHz	6.20	9.36	6.40	9.64	3.23%	2.99%
2013-05-24	1750 MHz	20.1	37.4	19.72	36.48	-1.89%	-2.46%
2013-05-23	1900 MHz	21.3	39.9	21.68	40.80	1.78%	2.26%
2013-04-18	2450 MHz	24.2	51.7	24.80	50.00	2.48%	-3.29%

Note: The system verification of 2450MHz is performed by TA Technology (Shanghai) Co., Ltd.
Please refer to the report No.RXA1304-0001SAR01R1.

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1 Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be

documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

		≤ 3 GHz	> 3 GHz	
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm	
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$	
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}		≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm	
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.		
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
<p>Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <i>reported</i> SAR from the area scan based <i>I-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>				

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH_n), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	3.0	2.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.0	0.0	21	81

9.4 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.5 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 14.2 to Table 14.25 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

11.1 Manufacturing tolerance

Table 11.1: GSM Speech

GSM 850			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	32.0	32.0	32.0
Tolerance \pm (dB)	1	1	1
GSM 1900			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	29.5	29.5	29.5
Tolerance \pm (dB)	1	1	1

Table 11.2: GPRS and EGPRS

GSM 850 GPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	32.0	32.0	32.0
	Tolerance \pm (dB)	1	1	1
2 Txslots	Target (dBm)	29.5	29.5	29.5
	Tolerance \pm (dB)	1	1	1
3Txslots	Target (dBm)	27.5	27.5	27.5
	Tolerance \pm (dB)	1	1	1
4 Txslots	Target (dBm)	27	27	27
	Tolerance \pm (dB)	1	1	1
GSM 850 EGPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	32.0	32.0	32.0
	Tolerance \pm (dB)	1	1	1
2 Txslots	Target (dBm)	29.5	29.5	29.5
	Tolerance \pm (dB)	1	1	1
3Txslots	Target (dBm)	27.5	27.5	27.5
	Tolerance \pm (dB)	1	1	1
4 Txslots	Target (dBm)	27	27	27
	Tolerance \pm (dB)	1	1	1
GSM 1900 GPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	29.5	29.5	29.5
	Tolerance \pm (dB)	1	1	1
2 Txslots	Target (dBm)	28	28	28
	Tolerance \pm (dB)	1	1	1
3Txslots	Target (dBm)	26.5	26.5	26.5
	Tolerance \pm (dB)	1	1	1
4 Txslots	Target (dBm)	25	25	25
	Tolerance \pm (dB)	1	1	1

GSM 1900 EGPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	29.5	29.5	29.5
	Tolerance \pm (dB)	-1 ~ +0.7	-1 ~ +0.7	-1 ~ +0.7
2 Txslots	Target (dBm)	28	28	28
	Tolerance \pm (dB)	1	1	1
3Txslots	Target (dBm)	26.5	26.5	26.5
	Tolerance \pm (dB)	1	1	1
4 Txslots	Target (dBm)	25	25	25
	Tolerance \pm (dB)	1	1	1

Table 11.3: WCDMA

	Mode	Target (dBm)	Tolerance \pm (dB)
WCDMA 850	RMC	22.5	-1.5 ~ +1.0
	HSDPA sub-test1	22.5	-1.5 ~ +1.0
	HSDPA sub-test2	21.5	-1.0 ~ +1.0
	HSDPA sub-test3	21.0	-1.0 ~ +1.0
	HSDPA sub-test4	21.0	-1.0 ~ +1.0
	HSUPA sub-test1	20.5	-1.0 ~ +1.0
	HSUPA sub-test2	19.5	-1.0 ~ +1.0
	HSUPA sub-test3	20.0	-1.0 ~ +1.0
	HSUPA sub-test4	19.5	-1.0 ~ +1.0
	HSUPA sub-test5	21.0	-1.0 ~ +1.0
WCDMA 1700	RMC	22.5	-1.5 ~ +1.0
	HSDPA sub-test1	22.5	-1.5 ~ +1.0
	HSDPA sub-test2	21.5	-1.0 ~ +1.0
	HSDPA sub-test3	21.0	-1.0 ~ +1.0
	HSDPA sub-test4	21.0	-1.0 ~ +1.0
	HSUPA sub-test1	20.5	-1.0 ~ +1.0
	HSUPA sub-test2	19.5	-1.0 ~ +1.0
	HSUPA sub-test3	20.0	-1.0 ~ +1.0
	HSUPA sub-test4	19.5	-1.0 ~ +1.0
	HSUPA sub-test5	21.0	-1.0 ~ +1.0
WCDMA 1900	RMC	22.5	-1.5 ~ +1.0
	HSDPA sub-test1	22.5	-1.5 ~ +1.0
	HSDPA sub-test2	21.5	-1.0 ~ +1.0
	HSDPA sub-test3	21.0	-1.0 ~ +1.0
	HSDPA sub-test4	21.0	-1.0 ~ +1.0
	HSUPA sub-test1	20.5	-1.0 ~ +1.0
	HSUPA sub-test2	19.5	-1.0 ~ +1.0
	HSUPA sub-test3	20.0	-1.0 ~ +1.0
	HSUPA sub-test4	19.5	-1.0 ~ +1.0
	HSUPA sub-test5	21.0	-1.0 ~ +1.0

Table 11.4: Bluetooth

Bluetooth			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6.5	8	8.5
Tolerance ±(dB)	1	1	1

Table 11.5: WiFi

Mode	Target (dBm)	Tolerance ±(dB)
802.11 b	13.0	1
802.11 g	12.5	1
802.11n-HT20 (MCS0~MCS6)	12.5	1
802.11n-HT20 (MCS7)	10.5	1
802.11n-HT40 (MCS0~MCS6)	12.5	1
802.11n-HT40 (MCS7)	10.5	1

11.2 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.6: The conducted power measurement results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	32.43	32.46	32.49
GSM 1900MHz	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	29.59	29.86	29.94

Table 11.7: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	32.43	32.46	32.48	-9.03dB	23.40	23.43	23.45
2 Txslots	29.62	29.66	29.68	-6.02dB	23.60	23.64	23.66
3Txslots	27.58	27.64	27.64	-4.26dB	23.32	23.38	23.38
4 Txslots	27.60	27.63	27.66	-3.01dB	24.59	24.62	24.65
GSM 850 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	32.43	32.46	32.50	-9.03dB	23.40	23.43	23.47
2 Txslots	29.62	29.65	29.60	-6.02dB	23.60	23.63	23.58
3Txslots	27.58	27.62	27.65	-4.26dB	23.32	23.36	23.39
4 Txslots	27.60	27.62	27.65	-3.01dB	24.59	24.61	24.64

PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.58	29.86	29.93	-9.03dB	20.55	20.83	20.90
2 Txslots	27.90	28.18	28.24	-6.02dB	21.88	22.16	22.22
3Txslots	26.34	26.65	26.70	-4.26dB	22.08	22.39	22.44
4 Txslots	25.38	25.70	25.77	-3.01dB	22.37	22.69	22.76
PCS1900 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.59	29.86	29.94	-9.03dB	20.56	20.83	20.91
2 Txslots	27.90	28.18	28.25	-6.02dB	21.88	22.16	22.23
3Txslots	26.34	26.65	26.71	-4.26dB	22.08	22.39	22.45
4 Txslots	25.38	25.71	25.77	-3.01dB	22.37	22.70	22.76

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 4Txslots for GSM850 and PCS1900.

Note: According to the KDB941225 D03, “when SAR tests for EDGE or EGPRS mode is necessary, GMSK modulation should be used”.

11.3 WCDMA Measurement result

Table 11.8: The conducted Power for WCDMA850/1700/1900

Item	band	FDDV result		
	ARFCN	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)
WCDMA	\	22.57	22.61	22.79
HSDPA	1	22.50	22.60	22.84
	2	21.41	21.53	21.83
	3	20.93	21.06	21.37
	4	20.90	21.03	21.34
HSUPA	1	20.78	20.68	20.98
	2	19.50	19.59	19.89
	3	20.21	20.31	20.72
	4	19.76	19.68	19.98
	5	20.89	20.87	21.56

Item	band	FDDIV result		
	ARFCN	1513 (1752.6MHz)	1412 (1732.4MHz)	1312 (1712.4MHz)
WCDMA	\	22.90	23.14	22.95
HSDPA	1	22.84	23.14	22.89
	2	21.79	22.12	21.78
	3	21.33	21.67	21.33
	4	21.30	21.63	21.30
HSUPA	1	20.54	20.76	20.50
	2	20.00	20.10	19.85
	3	20.14	20.39	20.19
	4	19.98	20.09	19.87
	5	21.58	21.79	21.53
Item	band	FDDII result		
	ARFCN	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)
WCDMA	\	23.06	22.96	23.01
HSDPA	1	23.02	22.94	22.99
	2	21.97	21.85	21.83
	3	21.51	21.40	21.40
	4	21.48	21.38	21.37
HSUPA	1	20.86	20.55	20.73
	2	20.01	19.94	19.95
	3	20.47	20.34	20.35
	4	20.04	20.11	20.01
	5	21.45	21.38	21.15

Note: HSDPA&HSUPA body SAR for WCDMA850/1700/1900 are not required, because maximum average output power of each RF channel with HSDPA&HSUPA active is not 1/4 dB higher than that measured without HSDPA&HSUPA.

11.4 Wi-Fi and BT Measurement result

The output power of BT antenna is as following:

Mode	Conducted Power (dBm)		
	Channel 0 (2402MHz)	Channel 39 (2441MHz)	Channel 78 (2480MHz)
GFSK	6.68	8.19	8.61
EDR2M-4_DQPSK	6.58	8.06	8.48
EDR3M-8DPSK	6.82	8.30	8.73

The average conducted power for Wi-Fi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1	12.96	12.92	13.01	12.90
6	13.35	13.36	13.36	13.34
11	13.14	13.17	13.22	13.18

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	12.60	12.43	12.58	12.46	12.30	12.34	12.35	12.13
6	13.04	13.01	12.81	12.91	12.71	12.70	12.74	12.69
11	12.93	12.82	12.83	12.90	12.76	12.73	12.79	12.52

802.11n (dBm) - HT20

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	12.59	12.50	12.59	12.38	12.21	12.39	12.15	10.46
6	13.02	12.77	12.87	12.85	12.85	12.64	12.64	10.78
11	12.86	12.76	12.85	12.83	12.60	12.82	12.57	10.77

802.11n (dBm) - HT40

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
3	12.68	12.64	12.60	12.32	12.35	12.30	12.37	10.39
6	12.74	12.59	12.56	12.51	12.54	12.51	12.56	10.50
9	12.65	12.67	12.64	12.61	12.60	12.34	12.36	10.52

SAR is not required for 802.11g channels if the output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels, and for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 0.25dB higher than those measured at the lowest data rate.


According to the above conducted power, the EUT should be tested for 802.11b, 1Mbps, channel 6.

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter. For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Picture 12.1 Antenna Locations

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	Yes	No	Yes	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Appendix A

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Picture 12.2 Power Thresholds

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
			dBm	mW	
Bluetooth	2.441	19	8.73	7.46	Yes
2.4GHz WLAN 802.11 b	2.45	19	13.36	21.68	No

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	1.04	0.11	1.15
	Right hand, Touch cheek	0.88	0.17	1.05
Highest reported SAR value for Body	Rear	1.31	0.11	1.42
	Left	0.98	0.12	1.10

Table 13.2: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	1.04	0.19	1.23
Highest reported SAR value for Body	Rear	1.31	0.19	1.50

BT* - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Mode/Band	F (GHz)	Distance (mm)	Upper limit of power *		Estimated _{1g} (W/kg)
			dBm	mW	
Bluetooth	2.441	10	9.5	8.91	0.19

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm) · [$\sqrt{f(\text{GHz})/x}$] W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:

According to the above tables, the sum of reported SAR values is < 1.6 W/kg. So the simultaneous transmission SAR with volume scans is not required.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom.

The distance is 10mm and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-g SAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or more than 1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power in chapter 11.

Table 14.1: Duty Cycle

Mode	Duty Cycle
Speech for GSM850/1900	1:8.3
GPRS&EGPRS for GSM850/1900	1:2
WCDMA850/1700/1900 and WiFi	1:1

14.1 SAR results for Fast SAR

Table 14.2: SAR Values (GSM 850 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Ambient Temperature: 22.8 °C		Liquid Temperature: 22.3 °C		Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.				Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)			
848.8	251	Left	Touch	Fig.1	32.43	33	0.585	0.67	0.768	0.88	0.04
836.6	190	Left	Touch	/	32.46	33	0.515	0.58	0.746	0.84	-0.15
824.2	128	Left	Touch	/	32.49	33	0.491	0.55	0.711	0.80	0.02
848.8	251	Left	Tilt	/	32.43	33	0.319	0.36	0.461	0.53	0.04
836.6	190	Left	Tilt	/	32.46	33	0.315	0.36	0.454	0.51	0.03
824.2	128	Left	Tilt	/	32.49	33	0.304	0.34	0.437	0.49	-0.05
848.8	251	Right	Touch	/	32.43	33	0.467	0.53	0.678	0.77	0.08
836.6	190	Right	Touch	/	32.46	33	0.526	0.60	0.693	0.78	0.01
824.2	128	Right	Touch	/	32.49	33	0.458	0.52	0.664	0.75	0.01
848.8	251	Right	Tilt	/	32.43	33	0.343	0.39	0.496	0.57	0.00
836.6	190	Right	Tilt	/	32.46	33	0.344	0.39	0.495	0.56	0.07
824.2	128	Right	Tilt	/	32.49	33	0.336	0.38	0.483	0.54	-0.00

Table 14.3: SAR Values (GSM 850 MHz Band - Body)

Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	GPRS (4)	Front	/	27.60	28	0.700	0.77	0.915	1.00	-0.10
836.6	190	GPRS (4)	Front	/	27.63	28	0.691	0.75	0.899	0.98	0.02
824.2	128	GPRS (4)	Front	/	27.66	28	0.686	0.74	0.895	0.97	-0.06
848.8	251	GPRS (4)	Rear	/	27.60	28	0.832	0.91	1.1	1.21	-0.07
836.6	190	GPRS (4)	Rear	/	27.63	28	0.852	0.93	1.13	1.23	-0.10
824.2	128	GPRS (4)	Rear	Fig.2	27.66	28	0.883	0.95	1.17	1.27	-0.05
848.8	251	GPRS (4)	Left	/	27.60	28	0.625	0.69	0.886	0.97	-0.02
836.6	190	GPRS (4)	Left	/	27.63	28	0.634	0.69	0.898	0.98	0.02
824.2	128	GPRS (4)	Left	/	27.66	28	0.614	0.66	0.868	0.94	0.00
848.8	251	GPRS (4)	Right	/	27.60	28	0.575	0.63	0.824	0.90	0.01
836.6	190	GPRS (4)	Right	/	27.63	28	0.589	0.64	0.841	0.92	0.04
824.2	128	GPRS (4)	Right	/	27.66	28	0.577	0.62	0.821	0.89	-0.03
836.6	190	GPRS (4)	Bottom	/	27.63	28	0.093	0.10	0.156	0.17	0.08
848.8	251	EGPRS (4)	Rear	/	27.60	28	0.792	0.87	1.06	1.16	-0.03
836.6	190	EGPRS (4)	Rear	/	27.62	28	0.845	0.92	1.13	1.23	0.10
824.2	128	EGPRS (4)	Rear	/	27.65	28	0.852	0.92	1.12	1.21	0.04
848.8	251	Speech	Rear Headset1	/	32.43	33	0.648	0.74	0.866	0.99	-0.02
836.6	190	Speech	Rear Headset1	/	32.46	33	0.691	0.78	0.926	1.05	0.01
824.2	128	Speech	Rear Headset1	/	32.49	33	0.693	0.78	0.927	1.04	-0.02
848.8	251	Speech	Rear Headset2	/	32.43	33	0.618	0.70	0.823	0.94	-0.11
836.6	190	Speech	Rear Headset2	/	32.46	33	0.667	0.76	0.891	1.01	-0.01
824.2	128	Speech	Rear Headset2	/	32.49	33	0.689	0.77	0.915	1.03	0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A15C1, Headset2 is CCB3160A15C4.

Table 14.4: SAR Values (GSM 1900 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
Ambient Temperature: 22.7°C Liquid Temperature: 22.2°C											
1909.8	810	Left	Touch	Fig.3	29.59	30.5	0.149	0.18	0.248	0.31	0.11
1880	661	Left	Touch	/	29.86	30.5	0.0999	0.12	0.172	0.20	-0.19
1850.2	512	Left	Touch	/	29.94	30.5	0.0820	0.09	0.140	0.16	0.11
1909.8	810	Left	Tilt	/	29.59	30.5	0.0655	0.08	0.119	0.15	-0.09
1880	661	Left	Tilt	/	29.86	30.5	0.0478	0.06	0.0843	0.10	-0.00
1850.2	512	Left	Tilt	/	29.94	30.5	0.0282	0.03	0.0451	0.05	-0.03
1909.8	810	Right	Touch	/	29.59	30.5	0.147	0.18	0.242	0.30	-0.13
1880	661	Right	Touch	/	29.86	30.5	0.133	0.15	0.234	0.27	0.14
1850.2	512	Right	Touch	/	29.94	30.5	0.122	0.14	0.214	0.24	0.12
1909.8	810	Right	Tilt	/	29.59	30.5	0.0654	0.08	0.112	0.14	-0.09
1880	661	Right	Tilt	/	29.86	30.5	0.0509	0.06	0.0857	0.10	0.12
1850.2	512	Right	Tilt	/	29.94	30.5	0.0390	0.04	0.0647	0.07	0.17

Table 14.5: SAR Values (GSM 1900 MHz Band - Body)

Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
Ambient Temperature: 22.7°C Liquid Temperature: 22.2°C											
1880	661	GPRS (4)	Front	/	25.70	26	0.333	0.36	0.533	0.57	0.02
1909.8	810	GPRS (4)	Rear	Fig.4	25.38	26	0.596	0.69	1.02	1.18	0.06
1880	661	GPRS (4)	Rear	/	25.70	26	0.524	0.56	0.887	0.95	0.01
1850.2	512	GPRS (4)	Rear	/	25.77	26	0.458	0.48	0.769	0.81	0.02
1880	661	GPRS (4)	Left	/	25.70	26	0.0885	0.09	0.138	0.15	0.10
1880	661	GPRS (4)	Right	/	25.70	26	0.119	0.13	0.201	0.22	0.02
1909.8	810	GPRS (4)	Bottom	/	25.38	26	0.565	0.65	0.972	1.12	0.01
1880	661	GPRS (4)	Bottom	/	25.70	26	0.472	0.51	0.809	0.87	-0.01
1850.2	512	GPRS (4)	Bottom	/	25.77	26	0.410	0.43	0.700	0.74	0.01
1909.8	810	EGPRS (4)	Rear	/	25.38	26	0.587	0.68	1	1.15	-0.01
1909.8	810	Speech	Rear Headset1	/	29.59	30.5	0.399	0.49	0.694	0.86	0.03
1909.8	810	Speech	Rear Headset2	/	29.59	30.5	0.395	0.49	0.688	0.85	0.05

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A15C1, Headset2 is CCB3160A15C4.

Table 14.6: SAR Values (WCDMA 850 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
Ambient Temperature: 22.8 °C Liquid Temperature: 22.3 °C											
846.6	4233	Left	Touch	Fig.5	22.57	23.5	0.633	0.78	0.837	1.04	-0.13
836.4	4182	Left	Touch	/	22.61	23.5	0.528	0.65	0.767	0.94	-0.08
826.4	4132	Left	Touch	/	22.79	23.5	0.495	0.58	0.718	0.85	0.09
846.6	4233	Left	Tilt	/	22.57	23.5	0.321	0.40	0.464	0.57	0.11
836.4	4182	Left	Tilt	/	22.61	23.5	0.304	0.37	0.438	0.54	-0.18
826.4	4132	Left	Tilt	/	22.79	23.5	0.293	0.35	0.423	0.50	0.02
846.6	4233	Right	Touch	/	22.57	23.5	0.541	0.67	0.712	0.88	0.01
836.4	4182	Right	Touch	/	22.61	23.5	0.487	0.60	0.707	0.87	0.12
826.4	4132	Right	Touch	/	22.79	23.5	0.469	0.55	0.681	0.80	0.04
846.6	4233	Right	Tilt	/	22.57	23.5	0.343	0.42	0.494	0.61	0.05
836.4	4182	Right	Tilt	/	22.61	23.5	0.331	0.41	0.476	0.58	0.00
826.4	4132	Right	Tilt	/	22.79	23.5	0.328	0.39	0.471	0.55	0.04

Table 14.7: SAR Values (WCDMA 850 MHz Band - Body)

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
Ambient Temperature: 22.8 °C Liquid Temperature: 22.3 °C										
846.6	4233	Front	/	22.57	23.5	0.630	0.78	0.822	1.02	0.00
836.4	4182	Front	/	22.61	23.5	0.650	0.80	0.849	1.04	0.03
826.4	4132	Front	/	22.79	23.5	0.616	0.73	0.801	0.94	-0.01
846.6	4233	Rear	Fig.6	22.57	23.5	0.744	0.92	0.994	1.23	0.00
836.4	4182	Rear	/	22.61	23.5	0.680	0.83	0.906	1.11	0.01
826.4	4132	Rear	/	22.79	23.5	0.716	0.84	0.953	1.12	-0.02
836.4	4182	Left	/	22.61	23.5	0.487	0.60	0.690	0.85	-0.05
836.4	4182	Right	/	22.61	23.5	0.501	0.61	0.718	0.88	0.00
836.4	4182	Bottom	/	22.61	23.5	0.0871	0.11	0.146	0.18	0.01
846.6	4233	Rear Headset1	/	22.57	23.5	0.523	0.65	0.692	0.86	0.01
846.6	4233	Rear Headset2	/	22.57	23.5	0.552	0.68	0.742	0.92	0.11

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A15C1, Headset2 is CCB3160A15C4.

Table 14.8: SAR Values (WCDMA 1700 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1752.6	1513	Left	Touch	/	22.90	23.5	0.324	0.37	0.508	0.58	-0.07
1732.4	1412	Left	Touch	/	23.14	23.5	0.401	0.44	0.631	0.69	0.02
1712.4	1312	Left	Touch	/	22.95	23.5	0.333	0.38	0.565	0.64	0.03
1752.6	1513	Left	Tilt	/	22.90	23.5	0.110	0.13	0.200	0.23	0.11
1732.4	1412	Left	Tilt	/	23.14	23.5	0.148	0.16	0.268	0.29	0.02
1712.4	1312	Left	Tilt	/	22.95	23.5	0.145	0.16	0.260	0.30	0.00
1752.6	1513	Right	Touch	/	22.90	23.5	0.352	0.40	0.590	0.68	0.01
1732.4	1412	Right	Touch	Fig.7	23.14	23.5	0.446	0.48	0.740	0.80	0.03
1712.4	1312	Right	Touch	/	22.95	23.5	0.357	0.41	0.598	0.68	0.04
1752.6	1513	Right	Tilt	/	22.90	23.5	0.151	0.17	0.256	0.29	0.05
1732.4	1412	Right	Tilt	/	23.14	23.5	0.177	0.19	0.303	0.33	0.01
1712.4	1312	Right	Tilt	/	22.95	23.5	0.165	0.19	0.282	0.32	0.01

Table 14.9: SAR Values (WCDMA 1700 MHz Band - Body)

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1752.6	1513	Front	/	22.90	23.5	0.533	0.61	0.850	0.98	-0.00
1732.4	1412	Front	/	23.14	23.5	0.592	0.64	0.940	1.02	0.03
1712.4	1312	Front	/	22.95	23.5	0.557	0.63	0.888	1.01	0.05
1752.6	1513	Rear	Fig.8	22.90	23.5	0.628	0.72	1.02	1.17	0.01
1732.4	1412	Rear	/	23.14	23.5	0.631	0.69	1.02	1.11	0.03
1712.4	1312	Rear	/	22.95	23.5	0.611	0.69	0.994	1.13	0.04
1732.4	1412	Left	/	23.14	23.5	0.136	0.15	0.218	0.24	0.02
1732.4	1412	Right	/	23.14	23.5	0.109	0.12	0.176	0.19	-0.19
1732.4	1412	Bottom	/	23.14	23.5	0.420	0.46	0.694	0.75	-0.04
1752.6	1513	Rear Headset1	/	22.90	23.5	0.607	0.70	0.992	1.14	0.01
1732.4	1412	Rear Headset1		23.14	23.5	0.583	0.63	0.951	1.03	0.02
1712.4	1312	Rear Headset1		22.95	23.5	0.501	0.57	0.817	0.93	0.03
1752.6	1513	Rear Headset2	/	22.90	23.5	0.568	0.65	0.922	1.06	0.03
1732.4	1412	Rear Headset2		23.14	23.5	0.573	0.62	0.929	1.01	0.01

1712.4	1312	Rear Headset2		22.95	23.5	0.561	0.64	0.914	1.04	0.03
--------	------	---------------	--	-------	------	-------	-------------	-------	-------------	------

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A15C1, Headset2 is CCB3160A15C4.

Table 14.10: SAR Values (WCDMA 1900 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Ambient Temperature: 22.7°C		Liquid Temperature: 22.2°C		Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.				Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)			
1907.6	9538	Left	Touch	/	23.06	23.5	0.237	0.26	0.392	0.43	0.08
1880	9400	Left	Touch	/	22.96	23.5	0.167	0.19	0.287	0.32	0.17
1852.4	9262	Left	Touch	/	23.01	23.5	0.153	0.17	0.263	0.29	0.12
1907.6	9538	Left	Tilt	/	23.06	23.5	0.109	0.12	0.195	0.22	0.09
1880	9400	Left	Tilt	/	22.96	23.5	0.0743	0.08	0.129	0.15	0.12
1852.4	9262	Left	Tilt	/	23.01	23.5	0.0458	0.05	0.0752	0.08	0.09
1907.6	9538	Right	Touch	/	23.06	23.5	0.286	0.32	0.484	0.54	0.11
1880	9400	Right	Touch	/	22.96	23.5	0.294	0.33	0.506	0.57	0.10
1852.4	9262	Right	Touch	Fig.9	23.01	23.5	0.326	0.36	0.562	0.63	0.19
1907.6	9538	Right	Tilt	/	23.06	23.5	0.133	0.15	0.218	0.24	0.07
1880	9400	Right	Tilt	/	22.96	23.5	0.109	0.12	0.180	0.20	0.03
1852.4	9262	Right	Tilt	/	23.01	23.5	0.0915	0.10	0.154	0.17	0.09

Table 14.11: SAR Values (WCDMA 1900 MHz Band - Body)

Frequency		Test Position	Figure No.	Ambient Temperature: 22.7°C		Liquid Temperature: 22.2°C		Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.			Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)			
1880	9400	Front	/	22.96	23.5	0.451	0.51	0.711	0.81	-0.06
1907.6	9538	Rear	Fig.10	23.06	23.5	0.693	0.77	1.18	1.31	0.07
1880	9400	Rear	/	22.96	23.5	0.651	0.74	1.11	1.26	0.01
1852.4	9262	Rear	/	23.01	23.5	0.608	0.68	1.02	1.14	0.02
1880	9400	Left	/	22.96	23.5	0.0937	0.11	0.145	0.16	0.02
1880	9400	Right	/	22.96	23.5	0.15	0.17	0.252	0.29	-0.05
1907.6	9538	Bottom	/	23.06	23.5	0.628	0.69	1.07	1.18	0.02
1880	9400	Bottom	/	22.96	23.5	0.606	0.69	1.03	1.17	-0.00
1852.4	9262	Bottom	/	23.01	23.5	0.545	0.61	0.923	1.03	-0.04
1907.6	9538	Rear Headset1	/	23.06	23.5	0.632	0.70	1.08	1.20	-0.00
1880	9400	Rear Headset1	/	22.96	23.5	0.579	0.66	0.977	1.11	0.03
1852.4	9262	Rear Headset1	/	23.01	23.5	0.537	0.60	0.898	1.01	0.00

1907.6	9538	Rear Headset2	/	23.06	23.5	0.619	0.69	1.05	1.16	0.01
1880	9400	Rear Headset2	/	22.96	23.5	0.610	0.69	1.02	1.16	0.10
1852.4	9262	Rear Headset2	/	23.01	23.5	0.542	0.61	0.902	1.01	0.01

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A15C1, Headset2 is CCB3160A15C4.

Table 14.12: SAR Values (Wi-Fi 802.11b 1Mbps - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2437	6	Left	Touch	/	13.35	14	0.055	0.06	0.099	0.11	-0.133
2437	6	Left	Tilt	/	13.35	14	0.045	0.05	0.087	0.10	-0.090
2437	6	Right	Touch	Fig.11	13.35	14	0.075	0.09	0.147	0.17	0.055
2437	6	Right	Tilt	/	13.35	14	0.058	0.07	0.128	0.15	0.016

Note: The SAR values of WiFi is performed by TA Technology (Shanghai) Co., Ltd.

Please refer to the report No.RXA1304-0001SAR01R1.

Table 14.13: SAR Values (Wi-Fi 802.11b 1Mbps - Body)

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2437	6	Front	/	13.35	14	0.042	0.05	0.069	0.08	0.053
2437	6	Rear	/	13.35	14	0.053	0.06	0.094	0.11	-0.020
2437	6	Left	Fig.12	13.35	14	0.054	0.06	0.107	0.12	0.075
2437	6	Top		13.35	14	0.039	0.05	0.075	0.09	0.096

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The SAR values of WiFi is performed by TA Technology (Shanghai) Co., Ltd.

Please refer to the report No.RXA1304-0001SAR01R1.

14.2 SAR results for Standard procedure

There is zoom scan measurement to be added for the highest measured SAR in each exposure configuration/band.

Table 14.14: SAR Values (GSM 850 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	Left	Touch	Fig.1	32.43	33	0.585	0.67	0.768	0.88	0.04

Table 14.15: SAR Values (GSM 850 MHz Band - Body)

Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
824.2	128	GPRS (4)	Rear	Fig.2	27.66	28	0.883	0.95	1.17	1.27	-0.05

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.16: SAR Values (GSM 1900 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	Left	Touch	Fig.3	29.59	30.5	0.149	0.18	0.248	0.31	0.11

Table 14.17: SAR Values (GSM 1900 MHz Band - Body)

Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	GPRS (4)	Rear	Fig.4	25.38	26	0.596	0.69	1.02	1.18	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.18: SAR Values (WCDMA 850 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
846.6	4233	Left	Touch	Fig.5	22.57	23.5	0.633	0.78	0.837	1.04	-0.13

Table 14.19: SAR Values (WCDMA 850 MHz Band - Body)

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
846.6	4233	Rear	Fig.6	22.57	23.5	0.744	0.92	0.994	1.23	0.00

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.20: SAR Values (WCDMA 1700 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1732.4	1412	Right	Touch	Fig.7	23.14	23.5	0.446	0.48	0.740	0.80	0.03

Table 14.21: SAR Values (WCDMA 1700 MHz Band - Body)

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1752.6	1513	Rear	Fig.8	22.90	23.5	0.628	0.72	1.02	1.17	0.01

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.22: SAR Values (WCDMA 1900 MHz Band - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1852.4	9262	Right	Touch	Fig.9	23.01	23.5	0.326	0.36	0.562	0.63	0.19

Table 14.23: SAR Values (WCDMA 1900 MHz Band - Body)

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1907.6	9538	Rear	Fig.10	23.06	23.5	0.693	0.77	1.18	1.31	0.07

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.24: SAR Values (Wi-Fi 802.11b 1Mbps - Head)

Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2437	6	Right	Touch	Fig.11	13.35	14	0.075	0.09	0.147	0.17	0.055

Note: The SAR values of WiFi is performed by TA Technology (Shanghai) Co., Ltd.

Please refer to the report No.RXA1304-0001SAR01R1.

Table 14.25: SAR Values (Wi-Fi 802.11b 1Mbps - Body)

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2437	6	Left	Fig.12	13.35	14	0.054	0.06	0.107	0.12	0.075

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The SAR values of WiFi is performed by TA Technology (Shanghai) Co., Ltd.

Please refer to the report No.RXA1304-0001SAR01R1.

15 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Table 15.1: SAR Measurement Variability for Body GSM 850 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
824.2	128	Rear	10	1.17	1.16	1.01	/

Table 15.2: SAR Measurement Variability for Body GSM 1900 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1909.8	810	Rear	10	1.02	1	1.02	/

Table 15.3: SAR Measurement Variability for Head WCDMA 850 (1g)

Frequency		Side	Test Position	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
846.6	4233	Left	Touch	0.837	0.836	1.00	/

Table 15.4: SAR Measurement Variability for Body WCDMA 850 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
846.6	4233	Rear	10	0.994	0.932	1.07	/

Table 15.5: SAR Measurement Variability for Body WCDMA 1700 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1752.6	1513	Rear	10	1.02	1.02	1.00	/

Table 15.6: SAR Measurement Variability for Body WCDMA 1900 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1907.6	9538	Rear	10	1.18	1.18	1.00	/

16 Measurement Uncertainty

16.1 Measurement Uncertainty for Normal SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	5.5	N	1	1	1	5.5	5.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521

Combined standard uncertainty	$u_c = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$							9.25	9.12	257
Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$							18.5	18.2	

16.2 Measurement Uncertainty for Normal SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.5	N	1	1	1	6.5	6.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	∞
13	Post-processing	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43

20	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$						10.8	10.7	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						21.6	21.4	

16.3 Measurement Uncertainty for Fast SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	5.5	N	1	1	1	5.5	5.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	7.0	R	$\sqrt{3}$	1	1	4.0	4.0	∞
Test sample related										
15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞

Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						10.1	9.95	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						20.2	19.9	

16.4 Measurement Uncertainty for Fast SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.5	N	1	1	1	6.5	6.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	14.0	R	$\sqrt{3}$	1	1	8.1	8.1	∞

Test sample related										
15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						13.3	13.2	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						26.6	26.4	

17 MAIN TEST INSTRUMENTS

Table 17.1: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	E5071C	MY46110673	February 15, 2013	One year
02	Power meter	NRVD	102083	September 11, 2012	One year
03	Power sensor	NRV-Z5	100542		
04	Signal Generator	E4438C	MY49070393	November 13, 2012	One Year
05	Amplifier	60S1G4	0331848	No Calibration Requested	
06	BTS	E5515C	MY48363198	July 11, 2012	One year
07	E-field Probe	SPEAG EX3DV4	3846	December 20, 2012	One year
08	DAE	SPEAG DAE4	771	November 20, 2012	One year
09	Dipole Validation Kit	SPEAG D835V2	443	May 03, 2012	Three year
10	Dipole Validation Kit	SPEAG D1750V2	1003	May 08, 2012	Three year
11	Dipole Validation Kit	SPEAG D1900V2	541	May 09, 2012	Three year

END OF REPORT BODY

ANNEX A Graph Results

850 Left Cheek High

Date: 2013-5-22

Electronics: DAE4 Sn771

Medium: Head 850 MHz

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 0.94$ mho/m; $\epsilon_r = 40.182$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.8°C Liquid Temperature: 22.3°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: EX3DV4 - SN3846 ConvF(9.18, 9.18, 9.18)

Cheek High/Area Scan (61x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.799 W/kg

Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.370 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.935 W/kg

SAR(1 g) = 0.768 W/kg; SAR(10 g) = 0.585 W/kg

Maximum value of SAR (measured) = 0.802 W/kg




Fig.1 850MHz CH251




Fig. 1-1 Z-Scan at power reference point (850 MHz CH251)

850 Body Rear Low

Date: 2013-5-22

Electronics: DAE4 Sn771

Medium: Body 850 MHz

Medium parameters used (interpolated): $f = 825$ MHz; $\sigma = 0.976$ mho/m; $\epsilon_r = 54.521$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.8°C Liquid Temperature: 22.3°C

Communication System: GSM 850 GPRS Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: EX3DV4 - SN3846 ConvF(9.04, 9.04, 9.04)

Rear Low/Area Scan (61x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.23 W/kg

Rear Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.406 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.46 W/kg

SAR(1 g) = 1.17 W/kg; SAR(10 g) = 0.883 W/kg

Maximum value of SAR (measured) = 1.22 W/kg




Fig.2 850 MHz CH128




Fig. 2-1 Z-Scan at power reference point (850 MHz CH128)

1900 Left Cheek High

Date: 2013-5-23

Electronics: DAE4 Sn771

Medium: Head 1900 MHz

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.421$ mho/m; $\epsilon_r = 39.016$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.7°C Liquid Temperature: 22.2°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: EX3DV4 - SN3846 ConvF(8.01, 8.01, 8.01)

Cheek High/Area Scan (61x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.252 W/kg

Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.347 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.383 W/kg

SAR(1 g) = 0.248 W/kg; SAR(10 g) = 0.149 W/kg

Maximum value of SAR (measured) = 0.269 W/kg




Fig.3 1900 MHz CH810




Fig. 3-1 Z-Scan at power reference point (1900 MHz CH810)

1900 Body Rear High

Date: 2013-5-23

Electronics: DAE4 Sn771

Medium: Body 1900 MHz

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.541$ mho/m; $\epsilon_r = 52.606$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.7°C Liquid Temperature: 22.2°C

Communication System: GSM 1900MHz GPRS Frequency: 1909.8 MHz Duty Cycle: 1:2

Probe: EX3DV4 - SN3846 ConvF(7.37, 7.37, 7.37)

Rear High/Area Scan (61x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.18 W/kg

Rear High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.971 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.596 W/kg

Maximum value of SAR (measured) = 1.12 W/kg




Fig.4 1900 MHz CH810




Fig.4-1 Z-Scan at power reference point (1900 MHz CH810)

WCDMA 850 Left Cheek High

Date: 2013-5-22

Electronics: DAE4 Sn771

Medium: Head 850 MHz

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.937$ mho/m; $\epsilon_r = 40.21$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.8°C Liquid Temperature: 22.3°C

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN3846 ConvF(9.18, 9.18, 9.18)

Cheek High/Area Scan (61x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.882 W/kg

Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.363 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.837 W/kg; SAR(10 g) = 0.633 W/kg

Maximum value of SAR (measured) = 0.865 W/kg




Fig.5 WCDMA 850 CH4233




Fig. 5-1 Z-Scan at power reference point (WCDMA 850 CH4233)

WCDMA 850 Body Rear High

Date: 2013-5-22

Electronics: DAE4 Sn771

Medium: Body 850 MHz

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.997$ mho/m; $\epsilon_r = 54.266$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.8°C Liquid Temperature: 22.3°C

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN3846 ConvF(9.04, 9.04, 9.04)

Rear High/Area Scan (61x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.05 W/kg

Rear High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 29.970 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.994 W/kg; SAR(10 g) = 0.744 W/kg

Maximum value of SAR (measured) = 1.04 W/kg




Fig.6 WCDMA 850 CH4233




Fig. 6-1 Z-Scan at power reference point (WCDMA850 CH4233)

WCDMA 1700 Right Cheek Middle

Date: 2013-5-24

Electronics: DAE4 Sn771

Medium: Head 1750 MHz

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 39.416$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.7°C Liquid Temperature: 22.2°C

Communication System: WCDMA1700; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN3846 ConvF(8.39, 8.39, 8.39)

Cheek Middle/Area Scan (61x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.791 W/kg

Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.127 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.740 W/kg; SAR(10 g) = 0.446 W/kg

Maximum value of SAR (measured) = 0.798 W/kg




Fig.7 WCDMA 1700 CH1412