



TEST REPORT

No. 2013TAR363

for

TCT Mobile Limited

GSM/GPRS quadband mobile phone

Model Name: Tigris 1SIM

Marketing Name: ALCATEL 3000G

FCC ID : RAD363

with

Hardware Version: PIO

Software Version: VA14

Issued Date: 2013-05-07

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. D-PL-12123-01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629B

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology
3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China,100191.
Tel:+86(0)10-62304633-2604, Fax:+86(0)10-62304793, Email:welcome@emcite.com, web: www.emcite.com

CONTENTS

1.	TEST LABORATORY	3
1.1.	TESTING LOCATION	3
1.2.	TESTING ENVIRONMENT.....	3
1.3.	PROJECT DATA	3
1.4.	SIGNATURE	3
2.	CLIENT INFORMATION.....	4
2.1.	APPLICANT INFORMATION.....	4
2.2.	MANUFACTURER INFORMATION.....	4
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1.	ABOUT EUT	5
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4.	NORMAL ACCESSORY SETTING.....	6
3.5.	GENERAL DESCRIPTION	6
4.	REFERENCE DOCUMENTS.....	7
4.1.	REFERENCE DOCUMENTS FOR TESTING.....	7
5.	LABORATORY ENVIRONMENT	8
6.	SUMMARY OF TEST RESULTS	9
7.	TEST EQUIPMENTS UTILIZED	10
	ANNEX A: MEASUREMENT RESULTS.....	11
A.1	OUTPUT POWER.....	11
A.2	EMISSION LIMIT.....	17
A.3	CONDUCTED EMISSION	23
A.4	FREQUENCY STABILITY	30
A.5	OCCUPIED BANDWIDTH	32
A.6	EMISSION BANDWIDTH.....	40
A.7	BAND EDGE COMPLIANCE	48
A.8	CONDUCTED SPURIOUS EMISSION.....	52

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai
Dian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2013-04-22
Testing End Date: 2013-05-06

1.4. Signature

Zi Xiaogang
(Prepared this test report)

Sun Xiangqian
(Reviewed this test report)

Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCT Mobile Limited
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCT Mobile Limited
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-61460890
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/GPRS quadband mobile phone
Model Name	Tigris 1SIM
Marketing Name	ALCATEL 3000G
FCC ID	RAD363
Frequency	GSM 850MHz; PCS 1900MHz
GPRS operation mode	Class B
GPRS Class	Class 12
Antenna	Integrated
Power supply	Battery or Charger (AC Adaptor)
Output power	31.10dBm maximum EIRP measured for PCS1900
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N28	860517020002434	PIO	VA14
N03	860517020002061	PIO	VA14

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Battery
AE3	Charger
AE4	Charger

AE1

Model	CAB22D0000C1
Manufacturer	SCUD
Capacitance	650mAh
Nominal voltage	3.8V

AE2

Model	CAB30M0000C2
Manufacturer	BAK
Capacitance	650mAh

Nominal voltage	3.8V
AE3	
Model	CBA3002AG0C1
Manufacturer	BYD
Length of cable	120cm
AE4	
Model	CBA3002AG0C3
Manufacturer	YingJu
Length of cable	120cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery was used during the test;

3.5. General Description

The Equipment Under Test (EUT) is a model of GSM/GPRS quadband mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-12 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-12 Edition
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003
KDB971168 D01	Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems	2011

5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber 2 (8.6 meters × 6.1 meters × 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

Semi-anechoic chamber 2 / Fully-anechoic chamber 3 (10 meters × 6.7 meters × 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

6. SUMMARY OF TEST RESULTS

GSM 850

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	A.1	P
2	Emission Limit	22.917, 2.1051	A.2	P
3	CONDUCTED EMISSION	15.107/15.207	A.3	P
4	Frequency Stability	22.235, 2.1055	A.4	P
5	Occupied Bandwidth	2.1049(h)(i)	A.5	P
6	Emission Bandwidth	22.917(b)	A.6	P
7	Band Edge Compliance	22.917(b)	A.7	P
8	Conducted Spurious Emission	22.917, 2.1057	A.8	P

PCS 1900

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	24.232(b)	A.1	P
2	Emission Limit	24.238, 2.1051	A.2	P
3	CONDUCTED EMISSION	15.107/15.207	A.3	P
4	Frequency Stability	24.235, 2.1055	A.4	P
5	Occupied Bandwidth	2.1049(h)(i)	A.5	P
6	Emission Bandwidth	24.238(b)	A.6	P
7	Band Edge Compliance	24.238(b)	A.7	P
8	Conducted Spurious Emission	24.238, 2.1057	A.8	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESCI	100344	R&S	2014-03-27
3	Test Receiver	ESU26	100376	R&S	2013-11-07
4	EMI Antenna	VULB 9163	514	Schwarzbeck	2014-11-10
5	EMI Antenna	3117	00139065	ETS-Lindgren	2014-07-31
6	LISN	ESH2-Z5	829991/012	R&S	2014-04-15
7	Universal Radio Communication Tester	CMU200	102228	R&S	2013-07-07
8	Universal Radio Communication Tester	E5515C	MY48361083	Agilent	2014-03-15
9	Spectrum Analyzer	E4440A	MY48250642	Agilent	2014-03-04
10	EMI Antenna	9117	177	Schwarzbeck	2014-06-29
11	EMI Antenna	VULB 9163	482	Schwarzbeck	2014-02-17
12	EMI Antenna	3117	00119024	ETS-Lindgren	2014-02-02
13	EMI Antenna	3117	00058889	ETS-Lindgren	2014-02-02
14	Signal Generator	N5183A	MY49060052	Agilent	2014-03-18
15	Climatic chamber	PL-2G	343074	ESPEC	2013-05-12

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.4MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

A.1.2.2 Test Condition

RBW	VBW	Sweep Time	Span
1MHz	1MHz	300ms	10MHz

GSM850

Limit

	Power step	Nominal Peak output power (dBm)	Power & Multislot class	Operation class
GSM	5	33dBm(2W)	4	/
GPRS	3	33dBm(2W)	12	B

Measurement result

GSM (GMSK)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	5	32.13
836.6	5	32.15
848.8	5	32.16

GPRS (GMSK, 1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	3	32.12
836.6	3	32.15
848.8	3	32.17

PCS1900**Limit**

	Power step	Nominal Peak output power (dBm)	Power & Multislot class	Operation class
GSM	0	30dBm(1W)	1	/
GPRS	3	30dBm(1W)	12	B
EGPRS	3	30dBm(1W)	12	B

Measurement result**GSM (GMSK)**

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	0	28.91
1880.0	0	28.84
1909.8	0	28.87

GPRS (GMSK, 1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	3	28.89
1880.0	3	28.83
1909.8	3	28.86

A.1.3 Radiated

A.1.3.1 Description


This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is

connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

GSM 850-ERP 22.913(a)**Limits**

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)

Measurement result**GSM**

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Polarization
824.20	-18.45	2.07	-53.00	0.84	2.15	29.49	H
836.60	-18.01	2.08	-53.00	0.90	2.15	29.86	H
848.80	-18.47	2.09	-53.00	0.95	2.15	29.34	H

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Polarization
824.20	-18.12	2.07	-53.00	0.84	2.15	29.82	H
836.60	-17.84	2.08	-53.00	0.90	2.15	30.03	H
848.80	-18.31	2.09	-53.00	0.95	2.15	29.50	H

Frequency: 836.60MHz

Peak ERP(dBm)= P_{Mea}(-17.84dBm)- P_{cl}(2.08dB) - P_{Ag}(-53.00dB) - G_a (0.90dB)-2.15dB=30.03dBm**ANALYZER SETTINGS: RBW = VBW = 3MHz**

PCS1900-EIRP 24.232(b)**Limits**

	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)

Measurement result**GSM**

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Polarization
1850.20	-21.47	3.19	-50.00	-5.60	30.94	V
1880.00	-19.42	3.11	-50.00	-3.25	30.72	V
1909.80	-19.95	3.18	-50.00	-3.73	30.60	V

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Polarization
1850.20	-21.62	3.19	-50.00	-5.60	30.79	V
1880.00	-19.04	3.11	-50.00	-3.25	31.10	V
1909.80	-20.12	3.18	-50.00	-3.73	30.43	V

Frequency: 1880.00MHz

Peak EIRP(dBm)= P_{Mea}(-19.04dBm) - P_{cl}(3.11dB) - P_{Ag}(-50.00dB) - G_a (-3.25dB) =31.10dBm**ANALYZER SETTINGS: RBW = VBW = 3MHz**

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurement procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the

substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of PCS1900 (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 and GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

GSM Mode Channel 128/824.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
1648.36	-34.37	2.91	-5.45	2.15	-33.98	-13.00	V
3296.34	-50.88	4.22	-7.41	2.15	-49.84	-13.00	V
4120.60	-53.55	4.68	-8.57	2.15	-51.81	-13.00	V
6283.24	-64.24	5.87	-10.43	2.15	-61.83	-13.00	V
8089.01	-65.63	6.98	-11.95	2.15	-62.81	-13.00	H
9065.99	-48.65	7.53	-12.60	2.15	-45.73	-13.00	V

GSM Mode Channel 190/836.6MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
1673.00	-36.44	2.97	-5.34	2.15	-36.22	-13.00	V
3064.19	-66.76	3.98	-6.85	2.15	-66.04	-13.00	H
4183.24	-58.35	4.68	-8.61	2.15	-56.57	-13.00	V
5668.94	-68.40	5.47	-10.07	2.15	-65.95	-13.00	H
8365.77	-57.98	7.31	-12.12	2.15	-55.32	-13.00	H
9203.59	-53.70	7.67	-12.60	2.15	-50.92	-13.00	V

GSM Mode Channel 251/848.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
1697.58	-38.88	2.95	-5.23	2.15	-38.75	-13.00	V
3395.14	-53.43	4.22	-7.65	2.15	-52.15	-13.00	H
4243.41	-59.19	4.75	-8.65	2.15	-57.44	-13.00	H
6300.27	-68.10	5.90	-10.44	2.15	-65.71	-13.00	V
8487.48	-49.87	7.01	-12.19	2.15	-46.84	-13.00	H
9337.52	-52.62	7.65	-12.60	2.15	-49.82	-13.00	H

GSM Mode Channel 512/1850.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3700.16	-54.96	4.44	-8.14	-51.26	-13.00	V
7401.05	-47.15	6.42	-11.34	-42.23	-13.00	V
9251.23	-38.91	7.65	-12.60	-33.96	-13.00	V
12951.39	-45.22	8.86	-13.24	-40.84	-13.00	H
14801.16	-50.39	9.69	-13.54	-46.54	-13.00	V
16651.17	-35.14	10.34	-12.40	-33.08	-13.00	V

GSM Mode Channel 661/1880.0MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3759.75	-52.76	4.52	-8.21	-49.07	-13.00	V
5639.90	-61.88	5.45	-10.06	-57.27	-13.00	H
7520.21	-45.81	6.82	-11.42	-41.21	-13.00	H
9399.95	-44.11	7.45	-12.60	-38.96	-13.00	H
13159.81	-51.89	9.14	-13.46	-47.57	-13.00	H
16919.41	-35.66	10.57	-12.40	-33.83	-13.00	V

GSM Mode Channel 810/1909.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3819.59	-52.71	4.49	-8.28	-48.92	-13.00	V
5729.20	-63.39	5.55	-10.09	-58.85	-13.00	V
7638.88	-50.26	6.73	-11.54	-45.45	-13.00	H
9548.58	-47.70	7.78	-12.58	-42.90	-13.00	V
13368.69	-55.93	9.07	-13.67	-51.33	-13.00	V
17187.72	-34.05	10.27	-12.74	-31.58	-13.00	V

A.3 CONDUCTED EMISSION


The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.

A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.3.2 Measurement result GSM850MHz -AE3




Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.159001	52.3	GND	L1	8.6	13.2	65.5
0.208501	50.0	GND	N	8.9	13.3	63.3
0.262501	45.3	GND	L1	9.0	16.0	61.4
2.751001	35.8	GND	N	9.9	20.2	56.0
2.805001	32.7	GND	N	9.9	23.3	56.0
2.854501	37.3	GND	N	9.9	18.7	56.0

Final Result 2


Frequency (MHz)	CAverage (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.159001	39.8	GND	L1	8.6	15.7	55.5
0.262501	36.4	GND	L1	9.0	15.0	51.4
0.366001	36.1	GND	L1	9.3	12.5	48.6
2.755501	21.7	GND	L1	9.8	24.3	46.0
2.809501	24.2	GND	L1	9.8	21.8	46.0
2.859001	25.1	GND	L1	9.8	20.9	46.0

GSM850MHz -AE4

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.744001	45.8	GND	N	9.9	10.2	56.0
1.207501	46.2	GND	N	9.9	9.8	56.0
1.495501	41.7	GND	L1	9.8	14.3	56.0
3.835501	46.3	GND	L1	9.8	9.7	56.0
4.123501	46.0	GND	L1	9.8	10.0	56.0
4.195501	46.1	GND	L1	9.8	9.9	56.0

Final Result 2


Frequency (MHz)	CAverage (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
1.135501	37.2	GND	N	9.9	8.8	46.0
1.630501	37.1	GND	N	9.9	8.9	46.0
1.702501	37.6	GND	N	9.9	8.4	46.0
1.738501	36.8	GND	N	9.9	9.2	46.0
4.195501	38.3	GND	L1	9.8	7.7	46.0
4.227001	37.6	GND	L1	9.8	8.4	46.0

PCS1900MHz –AE3

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.154501	51.7	GND	N	8.8	14.0	65.8
2.670001	39.4	GND	N	9.9	16.6	56.0
2.724001	40.2	GND	N	9.9	15.8	56.0
2.827501	38.1	GND	L1	9.8	17.9	56.0
3.223501	32.7	GND	L1	9.8	23.3	56.0
3.376501	33.2	GND	N	9.8	22.8	56.0

Final Result 2


Frequency (MHz)	CAverage (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.366001	32.9	GND	L1	9.3	15.7	48.6
2.674501	30.1	GND	L1	9.8	15.9	46.0
2.724001	29.2	GND	L1	9.8	16.8	46.0
2.778001	28.8	GND	L1	9.8	17.2	46.0
2.827501	30.8	GND	L1	9.8	15.2	46.0
3.367501	30.5	GND	L1	9.8	15.5	46.0

PCS1900MHz –AE4

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.663001	46.8	GND	L1	9.8	9.2	56.0
0.690001	45.9	GND	N	9.9	10.1	56.0
0.730501	45.4	GND	N	9.9	10.6	56.0
0.762001	45.3	GND	N	9.9	10.7	56.0
1.212001	47.4	GND	L1	9.8	8.6	56.0
2.283001	41.5	GND	N	9.9	14.5	56.0

Final Result 2


Frequency (MHz)	CAverage (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.289501	43.0	GND	L1	9.0	7.5	50.5
0.690001	38.5	GND	N	9.9	7.5	46.0
0.726001	38.2	GND	N	9.9	7.8	46.0
0.762001	37.9	GND	N	9.9	8.1	46.0
1.243501	37.4	GND	L1	9.8	8.6	46.0
4.240501	37.1	GND	L1	9.8	8.9	46.0

MP3

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
2.715001	37.9	GND	N	9.9	18.1	56.0
2.764501	40.5	GND	N	9.9	15.5	56.0
2.814001	41.4	GND	N	9.9	14.6	56.0
2.868001	39.8	GND	N	9.9	16.2	56.0
3.205501	38.9	GND	L1	9.8	17.1	56.0
3.255001	39.3	GND	N	9.8	16.7	56.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
2.764501	30.8	GND	N	9.9	15.2	46.0
2.814001	32.0	GND	N	9.9	14.0	46.0
2.868001	32.7	GND	L1	9.8	13.3	46.0
3.246001	30.4	GND	L1	9.8	15.6	46.0
3.349501	31.3	GND	L1	9.8	14.7	46.0
3.399001	31.8	GND	L1	9.8	14.2	46.0

CAMERA

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
2.760001	40.7	GND	L1	9.8	15.3	56.0
2.814001	39.7	GND	L1	9.8	16.3	56.0
2.868001	39.1	GND	N	9.9	16.9	56.0
3.300001	39.3	GND	N	9.8	16.7	56.0
3.349501	39.4	GND	N	9.8	16.6	56.0
3.453001	38.9	GND	N	9.8	17.1	56.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
2.656501	30.7	GND	L1	9.8	15.3	46.0
2.710501	31.4	GND	L1	9.8	14.6	46.0
2.760001	33.7	GND	L1	9.8	12.3	46.0
2.809501	32.0	GND	L1	9.8	14.0	46.0
2.863501	31.6	GND	L1	9.8	14.4	46.0
3.394501	31.7	GND	L1	9.8	14.3	46.0

A.4 FREQUENCY STABILITY

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 and channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

GSM 850

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-13	0.016
3.8	-12	0.014
4.2	-15	0.018

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-13	0.015
-20	-13	0.015
-10	-14	0.016
0	-17	0.021
10	-13	0.016
20	-9	0.011
30	-13	0.015
40	-13	0.016
50	-17	0.020

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	16	0.008
3.8	22	0.012
4.2	26	0.014

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	23	0.012
-20	20	0.010
-10	30	0.016
0	21	0.011
10	33	0.018
20	22	0.012
30	22	0.012
40	22	0.012
50	36	0.019

A.5 OCCUPIED BANDWIDTH

A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-20dBc)


Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
824.2	241.987
836.6	244.391
848.8	241.987

GSM 850


Channel 128-Occupied Bandwidth (-20dBc BW)



Date: 3.MAY.2013 06:29:44

Channel 190-Occupied Bandwidth (-20dBc BW)



Date: 3.MAY.2013 06:30:16

Channel 251-Occupied Bandwidth (-20dBc BW)



Date: 3.MAY.2013 06:30:48

GPRS 850(-20dBc)


Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
824.2	245.192
836.6	244.391
848.8	243.590

GPRS 850
Channel 128-Occupied Bandwidth (-20dBc BW)


Date: 3.MAY.2013 07:01:06

Channel 190-Occupied Bandwidth (-20dBc BW)



Date: 3.MAY.2013 07:01:38

Channel 251-Occupied Bandwidth (-20dBc BW)



Date: 3.MAY.2013 07:02:10

PCS 1900(-20dBc)


Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
1850.2	242.788
1880.0	245.192
1909.8	244.391

PCS 1900
Channel 512-Occupied Bandwidth (-20dBc BW)


Date: 3.MAY.2013 06:43:23

Channel 661-Occupied Bandwidth (-20dBc BW)



Date: 3.MAY.2013 06:43:55

Channel 810-Occupied Bandwidth (-20dBc BW)



Date: 3.MAY.2013 06:44:27

GPRS 1900(-20dBc)


Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(kHz)
1850.2	243.590
1880.0	245.192
1909.8	242.788

GPRS 1900
Channel 512-Occupied Bandwidth -20dBc BW)


Date: 3.MAY.2013 07:05:45

Channel 661-Occupied Bandwidth (-20dBc BW)


Date: 3.MAY.2013 07:06:17

Channel 810-Occupied Bandwidth (-20dBc BW)


Date: 3.MAY.2013 07:06:49

A.6 EMISSION BANDWIDTH

A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	306.891
836.6	304.487
848.8	306.090

GSM 850


Channel 128-Occupied Bandwidth (-26dBc BW)



Date: 3.MAY.2013 06:31:22

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 3.MAY.2013 06:31:54

Channel 251-Occupied Bandwidth (-26dBc BW)



Date: 3.MAY.2013 06:32:26

GPRS 850(-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
824.2	303.686
836.6	302.885
848.8	305.288

GPRS 850
Channel 128-Occupied Bandwidth (-26dBc BW)


Date: 3.MAY.2013 07:02:44

Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 3.MAY.2013 07:03:16


Channel 251-Occupied Bandwidth (-26dBc BW)


Date: 3.MAY.2013 07:03:48


PCS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	304.487
1880.0	307.692
1909.8	305.288

PCS 1900
Channel 512-Occupied Bandwidth (-26dBc BW)


Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 3.MAY.2013 06:45:33

Channel 810-Occupied Bandwidth (-26dBc BW)



Date: 3.MAY.2013 06:46:06

GPRS 1900(-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	304.487
1880.0	304.487
1909.8	309.295

GPRS 1900
Channel 512-Occupied Bandwidth (-26dBc BW)


Date: 3.MAY.2013 07:07:23

Channel 661-Occupied Bandwidth (-26dBc BW)


Date: 3.MAY.2013 07:07:55


Channel 810-Occupied Bandwidth (-26dBc BW)


Date: 3.MAY.2013 07:08:27

A.7 BAND EDGE COMPLIANCE


GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 3.MAY.2013 06:32:40


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 3.MAY.2013 06:32:54

GPRS 850
LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 3.MAY.2013 07:04:02

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 3.MAY.2013 07:04:16

PCS 1900
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 3.MAY.2013 06:46:19

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810


Date: 3.MAY.2013 06:46:33

GPRS 1900
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512


Date: 3.MAY.2013 07:08:41

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810


Date: 3.MAY.2013 07:08:55

A.8 CONDUCTED SPURIOUS EMISSION

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 10 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
The trace mode is set to MaxHold to get the highest signal at each frequency;
Wait 25 seconds;
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 8.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


A. 8.3 Measurement result

GSM850

A.8.3.1 Channel 128: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 3.MAY.2013 06:33:23

A.8.3.2 Channel 128: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:33:51

A.8.3.3 Channel 128: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:34:19

A.8.3.4 Channel 128: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:34:47

A.8.3.5 Channel 190: 30MHz – 1GHz


Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.


Date: 3.MAY.2013 06:35:16

A.8.3.6 Channel 190: 1GHz –2.5GHz


Spurious emission limit –13dBm



Date: 3.MAY.2013 06:35:44

A.8.3.7 Channel 190: 2.5GHz –7.5GHz


Spurious emission limit –13dBm



Date: 3.MAY.2013 06:36:12

A.8.3.8 Channel 190: 7.5GHz –10GHz


Spurious emission limit –13dBm



Date: 3.MAY.2013 06:36:40

A.8.3.9 Channel 251: 30MHz – 1GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.


Date: 3.MAY.2013 06:37:09

A.8.3.10 Channel 251: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:37:37

A.8.3.11 Channel 251:2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:38:06

A.8.3.12 Channel 251: 7.5GHz – 10GHz


Spurious emission limit –13dBm.




Date: 3.MAY.2013 06:38:34

A.8.3.13 Idle mode: 30MHz – 1GHz

Spurious emission limit –13dBm.



A.8.3.14 Idle mode: 1GHz – 2.5GHz

Spurious emission limit –13dBm.



A.8.3.15 Idle mode: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:39:58

A.8.3.16 Idle mode: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:40:27

PCS1900
A.8.3.17 Channel 512: 30MHz – 1GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:47:02

A.8.3.18 Channel 512: 1GHz – 2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.


Date: 3.MAY.2013 06:47:30

A.8.3.19 Channel 512: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:47:58

A.8.3.20 Channel 512: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:48:26

A.8.3.21 Channel 512: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:48:55

A.8.3.22 Channel 512: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:49:23

A.8.3.23 Channel 661: 30MHz – 1GHz


Spurious emission limit –13dBm



Date: 3.MAY.2013 06:49:52

A.8.3.24 Channel 661: 1GHz –2.5GHz


Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.


Date: 3.MAY.2013 06:50:20

A.8.3.25 Channel 661: 2.5GHz –7.5GHz


Spurious emission limit –13dBm



Date: 3.MAY.2013 06:50:48

A.8.3.26 Channel 661: 7.5GHz –10GHz


Spurious emission limit –13dBm



Date: 3.MAY.2013 06:51:16

A.8.3.27 Channel 661: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:51:44

A.8.3.28 Channel 661: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:52:12

A.8.3.29 Channel 810: 30MHz – 1GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:52:41

A.8.3.30 Channel 810: 1GHz – 2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.



Date: 3.MAY.2013 06:53:09

A.8.3.31 Channel 810:2.5GHz – 7.5GHz

Spurious emission limit –13dBm.



A.8.3.32 Channel 810: 7.5GHz – 10GHz

Spurious emission limit –13dBm.



A.8.3.33 Channel 810: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:54:34

A.8.3.34 Channel 810: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:55:02

A.8.3.35 Idle mode: 30MHz – 1GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:55:30

A.8.3.36 Idle mode: 1GHz – 2.5GHz


Spurious emission limit –13dBm.




Date: 3.MAY.2013 06:55:59

A.8.3.37 Idle mode: 2.5GHz – 7.5GHz

Spurious emission limit –13dBm.



A.8.3.38 Idle mode: 7.5GHz – 10GHz

Spurious emission limit –13dBm.



A.8.3.39 Idle mode: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:57:23

A.8.3.40 IDLE mode: 15GHz –20GHz

Spurious emission limit –13dBm.



Date: 3.MAY.2013 06:57:51

*****END OF REPORT*****