



# TEST REPORT

## No. 2013TAR707

for

**TCT Mobile Limited**

**HSUPA/HSDPA/UMTS triband / GSM quadband mobile phone**

**Model Name: DiabloX A**

**Marketing Name: ONE TOUCH 6040A**

**FCC ID : RAD370**

with

**Hardware Version: PIO**

**Software Version: vB1D-2-US**

**Issued Date: 2013-10-16**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

***DAR accreditation (DIN EN ISO/IEC 17025): No. D-PL-12123-01-01***

***FCC 2.948 Listed: No.733176***

***IC O.A.T.S listed: No.6629B***

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China,100191.

Tel:+86(0)10-62304633-2604, Fax:+86(0)10-62304633, Email:welcome@emcite.com, web: [www.emcite.com](http://www.emcite.com)

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>3</b>
<b>1.1. TESTING LOCATION .....</b>	<b>3</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>3</b>
<b>1.3. PROJECT DATA .....</b>	<b>3</b>
<b>1.4. SIGNATURE .....</b>	<b>3</b>
<b>2. CLIENT INFORMATION.....</b>	<b>4</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>4</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>4</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
<b>3.1. ABOUT EUT .....</b>	<b>5</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>5</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>5</b>
<b>3.4. NORMAL ACCESSORY SETTING.....</b>	<b>6</b>
<b>3.5. GENERAL DESCRIPTION .....</b>	<b>6</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>7</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>11</b>
<b>A.1 OUTPUT POWER.....</b>	<b>11</b>
<b>A.2 EMISSION LIMIT.....</b>	<b>17</b>
<b>A.3 CONDUCTED EMISSION .....</b>	<b>22</b>
<b>A.4 FREQUENCY STABILITY .....</b>	<b>27</b>
<b>A.5 OCCUPIED BANDWIDTH .....</b>	<b>29</b>
<b>A.6 EMISSION BANDWIDTH .....</b>	<b>37</b>
<b>A.7 BAND EDGE COMPLIANCE.....</b>	<b>45</b>
<b>A.8 CONDUCTED SPURIOUS EMISSION .....</b>	<b>49</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT  
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai  
Dian District, Beijing, P. R. China  
Postal Code: 100191  
Telephone: 00861062304633  
Fax: 00861062304633


### 1.2. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: 2013-06-08  
Testing End Date: 2013-10-16

### 1.4. Signature



---

**Zi Xiaogang**  
**(Prepared this test report)**



---

**Sun Xiangqian**  
**(Reviewed this test report)**



---

**Lu Bingsong**  
**Deputy Director of the laboratory**  
**(Approved this test report)**

## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCT Mobile Limited  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China.  
City: Shanghai  
Postal Code: 201203  
Country: China  
Contact Person: Gong Zhizhou  
Contact Email: zhizhou.gong@jrdcom.com  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

### **2.2. Manufacturer Information**

Company Name: TCT Mobile Limited  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China.  
City: Shanghai  
Postal Code: 201203  
Country: China  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	HSUPA/HSDPA/UMTS triband / GSM quadband mobile phone
Model Name	DiabloX A
Marketing Name	ONE TOUCH 6040A
FCC ID	RAD370
Frequency	GSM 850MHz; PCS 1900MHz; WCDMA Band II; WCDMA Band V
Release	R99
HSDPA category	8
HSUPA category	7
Antenna	Integrated
Power supply	Battery or Charger (AC Adaptor)
Output power	23.72dBm maximum EIRP measured for Band II
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
N31	013682000610196	PIO	vB1D-2-US
N32	013682000610121	PIO	vB1D-2-US

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>	
AE1	Battery	/
AE2	Battery	/
AE3	Travel charger	/

##### **AE1**

Model	CAC2000009C1
Manufacturer	BYD
Capacitance	2000 mAh
Nominal voltage	3.8V

##### **AE2**

Model	CAC2000005C2
Manufacturer	SCUD
Capacitance	2000 mAh

Nominal voltage	3.8V
AE3	
Model	CBA0003AG0C1
Manufacturer	BYD
Length of cable	/

\*AE ID: is used to identify the test sample in the lab internally..

#### **3.4. Normal Accessory setting**

Fully charged battery was used during the test.

#### **3.5. General Description**

The Equipment Under Test (EUT) is a model of HSUPA/HSDPA/UMTS triband / GSM quadband mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.12
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.12
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003
KDB971168 D01	Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems	2011

## 5. LABORATORY ENVIRONMENT

**Control room / conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters × 6.1 meters × 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters × 6.7 meters × 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



## 6. SUMMARY OF TEST RESULTS

### WCDMA Band II

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	24.232(c)	A.1	P
2	Emission Limit	24.238, 2.1051	A.2	P
3	CONDUCTED EMISSION	15.107/15.207	A.3	P
4	Frequency Stability	24.235, 2.1055	A.4	P
5	Occupied Bandwidth	2.1049(h)(i)	A.5	P
6	Emission Bandwidth	24.238(b)	A.6	P
7	Band Edge Compliance	24.238(b)	A.7	P
8	Conducted Spurious Emission	24.238, 2.1057	A.8	P

### WCDMA Band V

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	A.1	P
2	Emission Limit	22.917, 2.1051	A.2	P
3	CONDUCTED EMISSION	15.107/15.207	A.3	P
4	Frequency Stability	22.235, 2.1055	A.4	P
5	Occupied Bandwidth	2.1049(h)(i)	A.5	P
6	Emission Bandwidth	22.917(b)	A.6	P
7	Band Edge Compliance	22.917(b)	A.7	P
8	Conducted Spurious Emission	22.917, 2.1057	A.8	P

## 7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESCI	100344	R&S	2014-03-28
2	Test Receiver	ESU26	100376	R&S	2013-11-07
3	EMI Antenna	VULB 9163	514	Schwarzbeck	2014-11-10
4	EMI Antenna	3117	00139065	ETS-Lindgren	2014-07-31
5	LISN	ESH2-Z5	829991/012	R&S	2014-04-14
6	Universal Radio Communication Tester	CMU200	102228	R&S	2014-06-23
7	Universal Radio Communication Tester	E5515C	MY48361083	Agilent	2014-03-16
8	Spectrum Analyzer	E4440A	MY48250642	Agilent	2014-03-04
9	EMI Antenna	9117	177	Schwarzbeck	2014-06-29
10	EMI Antenna	VULB 9163	482	Schwarzbeck	2014-02-17
11	EMI Antenna	3117	00119024	ETS-Lindgren	2014-02-02
12	EMI Antenna	3117	00058889	ETS-Lindgren	2014-02-02
13	Signal Generator	N5183A	MY49060052	Agilent	2014-03-18
14	Climate chamber	SH-241	92003546	ESPEC	2014-05-11

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Digital Radio Communication tester (CMU-200).

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; 826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V (bottom, middle and top of operational frequency range).

#### **Limit**

##### **A.1.2.2 Test Condition**

RBW	VBW	Sweep Time	Span
10MHz	10MHz	800ms	50MHz

#### **WCDMA Band II**

##### **Measurement result**

##### **QPSK**

WCDMA (Band II)	CH	Frequency(MHz)	output power(dBm)
	9262	1852.4	24.06
	9400	1880.0	24.01
	9538	1907.6	23.56

##### **16QAM**

WCDMA (Band II)	CH	Frequency(MHz)	output power(dBm)
	9262	1852.4	21.23
	9400	1880.0	21.22
	9538	1907.6	21.35

#### **WCDMA Band V**

##### **Measurement result**

##### **QPSK**

WCDMA (Band V)	CH	Frequency(MHz)	output power(dBm)
	4132	826.4	23.49
	4183	836.6	24.06
	4233	846.6	23.76

**16QAM**

	CH	Frequency(MHz)	output power(dBm)
WCDMA (Band V)	4132	826.4	20.96
	4183	836.6	21.00
	4233	846.6	20.93

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts." Rule Part 27.50(d)(2) specifies, "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to a peak EIRP of 1 watt."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the

reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

**WCDMA Band II-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band II	33dBm (2W)

**Measurement result**

**QPSK**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Polarization
1852.40	-30.97	3.18	-50.00	-5.58	21.43	H
1880.00	-29.27	3.11	-50.00	-3.25	20.87	H
1907.60	-26.41	3.18	-50.00	-2.08	22.49	H

Frequency: 1907.60MHz

Peak EIRP(dBm)= P<sub>Mea</sub>(-29.41dBm)- P<sub>cl</sub>(3.18dB)- P<sub>Ag</sub>(-50.00dB)-G<sub>a</sub> (-2.08dB) =22.49dBm

**16QAM**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Polarization
1852.40	-29.28	3.18	-50.00	-4.55	22.09	H
1880.00	-28.79	3.11	-50.00	-4.43	22.53	H
1907.60	-27.41	3.18	-50.00	-4.31	23.72	H

Frequency: 1907.60MHz

Peak EIRP(dBm)= P<sub>Mea</sub>(-27.41dBm)- P<sub>cl</sub>(3.18dB)- P<sub>Ag</sub>(-50.00dB)-G<sub>a</sub> (-4.31dB) =23.72dBm

**ANALYZER SETTINGS: RBW = VBW = 5MHz**

**WCDMA Band V-ERP**

**Limits**

	Burst Peak ERP (dBm)
WCDMA Band V	38.45dBm (7W)

**Measurement result**

**QPSK**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Polarization
826.40	-26.90	2.07	-53.00	0.85	2.15	21.03	H
836.60	-27.19	2.08	-53.00	0.90	2.15	20.68	V
846.60	-27.05	2.09	-53.00	0.94	2.15	20.77	H

Frequency: 826.40MHz

Peak ERP(dBm)= P<sub>Mea</sub>(-26.90dBm)- P<sub>cl</sub>(2.07dB)- P<sub>Ag</sub>(-53.00dB)-G<sub>a</sub> (0.85dB)-2.15dB=21.03dBm

**16QAM**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Polarization
826.40	-27.26	2.07	-53.00	0.85	2.15	20.67	H
836.60	-26.69	2.08	-53.00	0.90	2.15	21.18	H
846.60	-26.87	2.09	-53.00	0.94	2.15	20.95	H

Frequency: 836.60MHz

Peak ERP(dBm)= P<sub>Mea</sub>(-26.69dBm)- P<sub>cl</sub>(2.08dB)- P<sub>Ag</sub>(-53.00dB)-G<sub>a</sub> (0.90dB)-2.15dB=21.18dBm

**ANALYZER SETTINGS: RBW = VBW = 5MHz**



## A.2 EMISSION LIMIT


### A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II, WCDMA Band V.

#### **The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as ( $P_r$ ).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the

receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### **A.2.2 Measurement Limit**

Part 24.238 , Part 22.917 and Part 27.53 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz) , WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II, WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3867.72	-39.82	4.53	-8.34	-36.01	-13.00	V
5559.45	-34.59	5.44	-10.02	-30.01	-13.00	V
7270.39	-40.83	6.34	-11.26	-35.91	-13.00	V
10273.77	-40.20	7.61	-12.45	-35.36	-13.00	V
13256.25	-41.55	9.06	-13.56	-37.05	-13.00	H
16256.81	-40.00	10.19	-12.69	-37.50	-13.00	H

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3761.56	-39.53	4.52	-8.21	-35.84	-13.00	H
5637.51	-36.35	5.45	-10.06	-31.74	-13.00	H
6840.02	-36.41	6.17	-10.94	-31.64	-13.00	V
8465.23	-41.62	6.92	-12.18	-36.36	-13.00	V
10143.29	-37.29	7.90	-12.43	-32.76	-13.00	V
15032.34	-32.64	9.67	-13.49	-28.82	-13.00	H

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3875.31	-45.09	4.52	-8.35	-41.26	-13.00	H
5136.23	-44.25	5.24	-9.78	-39.71	-13.00	H
7785.73	-41.14	6.63	-11.69	-36.08	-13.00	H
10114.10	-43.21	8.13	-12.42	-38.92	-13.00	H
13954.60	-39.75	9.22	-13.98	-34.99	-13.00	V
16135.03	-39.57	10.32	-12.84	-37.05	-13.00	V

**WCDMA BAND V Mode Channel 4132/826.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
1388.02	-50.25	2.68	-5.05	2.15	-50.03	-13.00	V
1963.99	-53.88	3.20	-4.06	2.15	-55.17	-13.00	V
3027.91	-39.11	3.96	-6.77	2.15	-38.45	-13.00	V
3835.21	-37.52	4.53	-8.30	2.15	-35.90	-13.00	V
5156.34	-40.00	5.23	-9.79	2.15	-37.59	-13.00	V
8932.44	-41.44	7.38	-12.55	2.15	-38.42	-13.00	H

**WCDMA BAND V Mode Channel 4183/836.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
1809.44	-40.91	3.07	-4.74	2.15	-41.39	-13.00	H
2513.52	-42.76	3.59	-5.44	2.15	-43.06	-13.00	H
3487.32	-40.00	4.26	-7.87	2.15	-38.54	-13.00	H
4715.77	-39.24	4.97	-9.19	2.15	-37.17	-13.00	V
6253.90	-40.00	5.82	-10.40	2.15	-37.57	-13.00	V
7743.34	-43.53	6.62	-11.64	2.15	-40.66	-13.00	H

**WCDMA BAND V Mode Channel 4233/846.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
1694.84	-47.76	2.95	-5.24	2.15	-47.62	-13.00	H
2536.24	-40.15	3.62	-5.49	2.15	-40.43	-13.00	H
3330.32	-38.21	4.15	-7.49	2.15	-37.02	-13.00	V
4613.83	-38.80	4.96	-9.00	2.15	-36.91	-13.00	V
6405.89	-39.71	5.82	-10.52	2.15	-37.16	-13.00	V
8102.49	-40.00	6.90	-11.96	2.15	-37.09	-13.00	H

### **A.3 CONDUCTED EMISSION**


The measurement procedure in ANSI C63.4-2003 is used. Conducted Emission is measured with travel charger.

#### **A.3.1 Limit**

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

\* Decreases with logarithm of the frequency

**A.3.2 Measurement result**  
**WCDMA Band II**




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.684501	47.0	GND	N	9.9	9.0	56.0
1.725001	47.2	GND	N	9.9	8.8	56.0
1.774501	45.3	GND	N	9.9	10.7	56.0
1.801501	45.9	GND	N	9.9	10.1	56.0
1.837501	45.6	GND	N	9.9	10.4	56.0
2.512501	43.4	GND	N	9.9	12.6	56.0

**Final Result 2**

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.856501	35.1	GND	N	9.9	10.9	46.0
1.684501	37.9	GND	N	9.9	8.1	46.0
1.725001	38.3	GND	N	9.9	7.7	46.0
1.734001	36.9	GND	N	9.9	9.1	46.0
1.774501	36.5	GND	N	9.9	9.5	46.0
1.824001	35.6	GND	N	9.9	10.4	46.0

WCDMA Band V



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.684501	46.6	GND	N	9.9	9.4	56.0
1.765501	46.7	GND	N	9.9	9.3	56.0
1.828501	45.9	GND	N	9.9	10.1	56.0
1.842001	45.4	GND	N	9.9	10.6	56.0
1.878001	45.1	GND	N	9.9	10.9	56.0
2.580001	43.9	GND	N	9.9	12.1	56.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.829501	35.2	GND	N	9.9	10.8	46.0
0.861001	36.2	GND	N	9.9	9.8	46.0
1.716001	35.9	GND	N	9.9	10.1	46.0
1.779001	36.9	GND	N	9.9	9.1	46.0
1.797001	37.4	GND	N	9.9	8.6	46.0
1.869001	35.6	GND	N	9.9	10.4	46.0



MP3




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.635001	44.6	GND	N	9.9	11.4	56.0
1.684501	47.0	GND	N	9.9	9.0	56.0
1.725001	47.0	GND	N	9.9	9.0	56.0
1.765501	46.3	GND	N	9.9	9.7	56.0
1.801501	45.7	GND	N	9.9	10.3	56.0
1.819501	43.7	GND	N	9.9	12.3	56.0

**Final Result 2**

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.684501	38.0	GND	N	9.9	8.0	46.0
1.716001	36.5	GND	N	9.9	9.5	46.0
1.725001	38.2	GND	N	9.9	7.8	46.0
1.734001	37.0	GND	N	9.9	9.0	46.0
1.765501	37.7	GND	N	9.9	8.3	46.0
1.797001	37.0	GND	N	9.9	9.0	46.0

Camera



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.639501	45.5	GND	N	9.9	10.5	56.0
1.689001	46.9	GND	N	9.9	9.1	56.0
1.752001	45.9	GND	N	9.9	10.1	56.0
1.801501	45.4	GND	N	9.9	10.6	56.0
1.833001	45.5	GND	N	9.9	10.5	56.0
2.634001	42.7	GND	N	9.9	13.3	56.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.820501	36.1	GND	N	9.9	9.9	46.0
1.689001	37.8	GND	N	9.9	8.2	46.0
1.729501	37.9	GND	N	9.9	8.1	46.0
1.738501	36.8	GND	N	9.9	9.2	46.0
1.770001	37.3	GND	N	9.9	8.7	46.0
1.851001	35.4	GND	N	9.9	10.6	46.0

## **A.4 FREQUENCY STABILITY**

### **A.4.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II, WCDMA Band V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **A.4.2 Measurement Limit**

#### **A.4.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

#### **A.4.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

#### A.4.3 Measurement results

##### WCDMA Band II

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-8	0.004
3.8	-7	0.003
4.2	-11	0.006

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-14	0.007
-20	14	0.008
-10	12	0.006
0	12	0.006
10	4	0.002
20	7	0.004
30	-14	0.007
40	12	0.006
50	-13	0.007

##### WCDMA Band V

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-8	0.009
3.8	-4	0.005
4.2	-10	0.012

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-10	0.011
-20	-6	0.008
-10	-9	0.011
0	-8	0.009
10	8	0.010
20	9	0.011
30	8	0.010
40	-3	0.003
50	6	0.008

## A.5 OCCUPIED BANDWIDTH

### A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

#### WCDMA Band II(-20dBc)-QPSK

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
1852.4	4.167
1880.0	4.183
1907.6	4.183


#### WCDMA Band II

##### Channel 9262-Occupied Bandwidth (-20dBc BW)-QPSK




Date: 22.JUN.2013 08:42:34

### Channel 9400-Occupied Bandwidth (-20dBc BW)-QPSK



Date: 22.JUN.2013 08:43:09

### Channel 9538-Occupied Bandwidth (-20dBc BW)-QPSK




Date: 22.JUN.2013 08:43:43

### WCDMA Band II(-20dBc)-16QAM

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
1852.4	4.167
1880.0	4.167
1907.6	4.167


### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (-20dBc BW)-16QAM




Date: 26.SEP.2013 10:35:25

#### Channel 9400-Occupied Bandwidth (-20dBc BW)-16QAM



Date: 26.SEP.2013 10:36:44

### Channel 9538-Occupied Bandwidth (-20dBc BW)-16QAM



Date: 26.SEP.2013 10:38:07




### WCDMA Band V(-20dBc)-QPSK

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
826.4	4.167
836.6	4.151
846.6	4.183


### WCDMA Band V

#### Channel 4132-Occupied Bandwidth (-20dBc BW)-QPSK




Date: 22.JUN.2013 09:00:47

#### Channel 4183-Occupied Bandwidth (-20dBc BW)-QPSK



Date: 22.JUN.2013 09:01:22

### Channel 4233-Occupied Bandwidth (-20dBc BW)-QPSK




Date: 22.JUN.2013 09:01:56

**WCDMA Band V(-20dBc)-16QAM**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
826.4	4.167
836.6	4.167
846.6	4.167


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (-20dBc BW)-16QAM**




Date: 26.SEP.2013 11:01:26

**Channel 4183-Occupied Bandwidth (-20dBc BW)-16QAM**



Date: 26.SEP.2013 11:02:59

### Channel 4233-Occupied Bandwidth (-20dBc BW)-16QAM



Date: 26.SEP.2013 11:04:11

## A.6 EMISSION BANDWIDTH

### A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

#### WCDMA Band II(-26dBc)-QPSK

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
1852.4	4.487
1880.0	4.503
1907.6	4.487


#### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (-26dBc BW)-QPSK




Date: 22.JUN.2013 08:44:20

### Channel 9400-Occupied Bandwidth (-26dBc BW)-QPSK



Date: 22.JUN.2013 08:44:54

### Channel 9538-Occupied Bandwidth (-26dBc BW)-QPSK




Date: 22.JUN.2013 08:45:29

**WCDMA Band II(-26dBc)-16QAM**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
1852.4	4.503
1880.0	4.487
1907.6	4.503


**WCDMA Band II**

**Channel 9262-Occupied Bandwidth (-26dBc BW)-16QAM**




Date: 26.SEP.2013 10:39:35

**Channel 9400-Occupied Bandwidth (-26dBc BW)-16QAM**



Date: 26.SEP.2013 10:40:38

### Channel 9538-Occupied Bandwidth (-26dBc BW)-16QAM



Date: 26.SEP.2013 10:41:54




**WCDMA Band V(-26dBc)-QPSK**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
826.40	4.471
836.60	4.471
846.60	4.487


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (-26dBc BW)-QPSK**




Date: 22.JUN.2013 09:02:33

### Channel 4183-Occupied Bandwidth (-26dBc BW)-QPSK



Date: 22.JUN.2013 09:03:07

### Channel 4233-Occupied Bandwidth (-26dBc BW)-QPSK




Date: 22.JUN.2013 09:03:42

**WCDMA Band V(-26dBc)-16QAM**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
826.40	4.471
836.60	4.455
846.60	4.455


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (-26dBc BW)-16QAM**




Date: 26.SEP.2013 11:08:11

**Channel 4183-Occupied Bandwidth (-26dBc BW)-16QAM**



Date: 26.SEP.2013 11:09:24

### Channel 4233-Occupied Bandwidth (-26dBc BW)-16QAM




Date: 26.SEP.2013 11:10:22

## A.7 BAND EDGE COMPLIANCE


### WCDMA Band II

#### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262-QPSK




Date: 22.JUN.2013 08:45:45

#### HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538-QPSK




Date: 22.JUN.2013 08:46:01

### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262-16QAM




Date: 26.SEP.2013 10:43:13

### HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538-16QAM




Date: 26.SEP.2013 10:44:03

**WCDMA Band V**  
**LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132-QPSK**




Date: 22.JUN.2013 09:03:58

**HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233-QPSK**




Date: 22.JUN.2013 09:04:14

### LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132-16QAM



Date: 26.SEP.2013 11:11:12

### HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233-16QAM



Date: 26.SEP.2013 11:11:50



## **A.8 CONDUCTED SPURIOUS EMISSION**

### **A.8.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band V, data taken from 30 MHz to 10GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:  
The trace mode is set to MaxHold to get the highest signal at each frequency;  
Wait 25 seconds;  
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

#### **WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

### **A. 8.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.8.3 Measurement result

#### WCDMA Band II

##### A. 8.3.1 Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:46:33

##### A.8.3.2 Channel 9262: 1GHz –2.5GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 22.JUN.2013 08:47:01

### A.8.3.3 Channel 9262: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 22.JUN.2013 08:47:29


### A.8.3.4 Channel 9262: 7.5GHz –10GHz

Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:47:58

**A.8.3.5 Channel 9262: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:48:26

**A.8.3.6 Channel 9262: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 22.JUN.2013 08:48:55


**A. 8.3.7 Channel 9400: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 22.JUN.2013 08:49:26


**A.8.3.8 Channel 9400: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 22.JUN.2013 08:49:54

**A.8.3.9 Channel 9400: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:50:23

**A.8.3.10 Channel 9400: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:50:51

**A.8.3.11 Channel 9400: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:51:20

**A.8.3.12 Channel 9400: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 22.JUN.2013 08:51:48


**A. 8.3.13 Channel 9538: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 22.JUN.2013 08:52:19

**A.8.3.14 Channel 9538: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 22.JUN.2013 08:52:48




**A.8.3.15 Channel 9538: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:53:16

**A.8.3.16 Channel 9538: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:53:44

**A.8.3.17 Channel 9538: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:54:13

**A.8.3.18 Channel 9538: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:54:41

**A. 8.3.19 Idle mode: 30MHz –1GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:55:10

**A.8.3.20 Idle mode: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:55:39

**A.8.3.21 Idle mode: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:56:07

**A.8.3.22 Idle mode: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:56:36

**A.8.3.23 Idle mode: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 22.JUN.2013 08:57:04

**A.8.3.24 Idle mode: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 08:57:32

**WCDMA Band V**

**A. 8.3.25 Channel 4132: 30MHz –1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 22.JUN.2013 09:04:45


**A. 8.3.26 Channel 4132: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 22.JUN.2013 09:05:13

**A. 8.3.27 Channel 4132: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 22.JUN.2013 09:05:41

**A. 8.3.28 Channel 4132: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 09:06:09

### A. 8.3.29 Channel 4183: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 22.JUN.2013 09:06:40

### A.8.3.30 Channel 4183: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 22.JUN.2013 09:07:08




**A. 8.3.31 Channel 4183: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 22.JUN.2013 09:07:37

**A. 8.3.32 Channel 4183: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 09:08:05

**A. 8.3.33 Channel 4233: 30MHz –1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 22.JUN.2013 09:08:36


**A. 8.3.34 Channel 4233: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 22.JUN.2013 09:09:04

**A. 8.3.35 Channel 4233: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 09:09:32

**A. 8.3.36 Channel 4233: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 22.JUN.2013 09:10:00

**A. 8.3.37 Idle mode: 30MHz – 1GHz**  
Spurious emission limit -13dBm.




Date: 22.JUN.2013 09:10:29

**A.8.3.38 Idle mode: 1GHz – 2.5GHz**  
Spurious emission limit -13dBm.




Date: 22.JUN.2013 09:10:57

**A.8.3.39 Idle mode: 2.5GHz – 7.5GHz**  
Spurious emission limit -13dBm.



Date: 22.JUN.2013 09:11:25

**A.8.3.40 Idle mode: 7.5GHz – 10GHz**  
Spurious emission limit -13dBm.



Date: 22.JUN.2013 09:11:54

\*\*\*END OF REPORT\*\*\*