



FCC Part 15C TEST REPORT

Issued to

TCT Mobile Limited

For

Tablet

Model Name: : ONE TOUCH T016, ONE TOUCH TAB 7HD
 Trade Name: : ALCATEL
 Brand Name: : ALCATEL
 FCC ID: : RAD394
 Standard: : 47 CFR Part 15 Subpart C
 Test date: : 2013-3-11 to 2013-5-13
 Issue date: : 2013-5-13

Shenzhen MORLAB Communication Technology Co., Ltd.

Tested by Nie Quan

Nie Quan

(Test Engineer)

Date 2013.5.13

Approved by Zeng Dexin

(Department Manager)

Date 2013.5.13

Review by Peng Huarui

Peng Huarui

(Project Manager)

Date 2013.5.13



The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it, or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

DIRECTORY

1. GENERAL INFORMATION	3
1.1. EUT Description	3
1.2. Test Standards and Results.....	4
1.3. Table for Test Modes.....	4
1.4. Facilities and Accreditations	5
2. 47 CFR PART 15C REQUIREMENTS.....	6
2.1. Duty cycle	6
2.2. Peak Output Power.....	9
2.3. Bandwidth.....	18
2.4. Conducted Spurious Emissions.....	27
2.5. Power spectral density (PSD)	36
2.6. Band Edge.....	45
2.7. Conducted Emission	57
2.8. Radiated Emission.....	60
2.9. RF exposure evaluation.....	84

Change History		
Issue	Date	Reason for change
1.0	April 3, 2013	First edition
2.0	May 13, 2013	Second edition

1. General Information

1.1. EUT Description

EUT Type: Tablet
Serial No.....: (n.a, marked #1 by test site)
Hardware Version: V1.2
Software Version: V109
Applicant: TCT Mobile Limited
5F, C building, No. 232, Liang Jing Road, ZhangJiang
High-Tech Park, Pudong Area, Shanghai, P.R. China. 201203
Manufacturer: TCL COMMUNICATION TECHNOLOGY HOLDINGS
LIMITED.
70 Huifeng 4rd,ZhongKai Hi-tech Development
District ,Huizhou,Guangdong 516006 P.R.China
Frequency Range.....: 802.11b/g/n-20MHz: 2.412GHz - 2.462GHz
802.11n-40MHz: 2.422GHz - 2.452GHz
Channel Number.....: 802.11b/g/n-20MHz: 11
802.11n-40MHz: 7
Modulation Type: DSSS (802.11b), OFDM (802.11g/n)
Antenna Type.....: PCB Antenna
Antenna Gain.....: 2.0dBi

Note 1: The EUT is Tablet, it contains WIFI Module operating at 2.4GHz ISM band; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

Note 2: For 802.11b/g/n-20MHz, the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \cdot (n-1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).
For 802.11n-40MHz, the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \cdot (n-1)$ ($3 \leq n \leq 9$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 3 (2422MHz), 6 (2437MHz) and 9 (2452MHz).

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 4: The antenna connector of EUT is designed with permanent attachment and no consideration of replacement.

Note 5: The duty cycle in this report is for reporting purposes only.

1.2. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Wi-Fi, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-09 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	---	Duty Cycle	---
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	Bandwidth	PASS
4	15.247(d)	Conducted Spurious Emission	PASS
5	15.247(d)	Band Edge	PASS
6	15.207	Conducted Emission	PASS
7	15.209 ,15.247(d)	Radiated Emission	PASS
8	15.247(d)	Power spectral density (PSD)	PASS
9	15.247(i), 1.1307&2.1093	RF exposure evaluation	PASS

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.4 2009.-

These RF tests were performed according to the method of measurements prescribed in KDB558074 D01 V02 10/04/2012.

1.3. Table for Test Modes

Modulation technology	Modulation Type	Transfer Rate (Mbps)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n-20MHz)	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
OFDM (802.11n-40MHz)	BPSK	13.5
	QPSK	27/40.5
	16QAM	54/81/108
	64QAM	121.5/135

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. Investigation has been done on all the possible configurations for searching the worst cases. This report only show the worst-case of all data rate.

1.4. Facilities and Accreditations

1.4.1. Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2009, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.

1.4.2. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR Part 15C Requirements


2.1. Duty cycle

2.1.1. Requirement

None: for reporting purposes only.

2.1.2. Test Description

A. Test Setup:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm.


B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSL3	1300_2502K03_102467_y7	2012.05	2013.05

2.1.3. Results


The middle channel are selected to perform testing to verify the duty cycle of the Module.

Test Mode	Channel	Frequency (MHz)	Duty cycle	Refer to Plot
802.11b	6	2437	100%	Plot A
802.11g			100%	Plot B
802.11n-20			100%	Plot C
802.11n-40			100%	Plot D




Date: 13.MAY.2013 12:42:56

(Plot A: Channel 6: 2437MHz @ 802.11b)




Date: 13.MAY.2013 12:43:44

(Plot B: Channel 6: 2437MHz @ 802.11g)



Date: 13.MAY.2013 12:44:19

(Plot C: Channel 6: 2437MHz @ 802.11n-20)



Date: 13.MAY.2013 12:44:59

(Plot D: Channel 6: 2437MHz @ 802.11n-40)


2.2. Peak Output Power

2.2.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.2.2. Test Description

A. Test Setup:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E7405A	US44210471	2012.05	2013.05


2.2.3. Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.


2.2.3.1. 802.11b Test mode

Channel	Frequency (MHz)	Rate (Mbps)	Measured Output Peak Power		Refer to Plot	Limit		Verdict
			dBm	W		dBm	W	
1	2412	1Mbps	16.06	0.040365	Plot A	30	1	PASS
6	2437	1Mbps	16.37	0.043351	Plot B			PASS
11	2462	1Mbps	16.72	0.046989	Plot C			PASS


Agilent 12:09:52 Mar 15, 2013 R T S



(Plot A: Channel 1: 2412MHz @ 802.11b)



(Plot B: Channel 6: 2437MHz @ 802.11b)




(Plot C: Channel 11: 2462MHz @ 802.11b)

2.2.3.2. 802.11g Test mode

Channel	Frequency (MHz)	Rate (Mbps)	Measured Output Peak Power		Refer to Plot	Limit		Verdict
			dBm	W		dBm	W	
1	2412	6Mbps	15.53	0.035727	Plot D	30	1	PASS
6	2437	6Mbps	15.66	0.036813	Plot E			PASS
11	2462	6Mbps	16.23	0.041976	Plot F			PASS

Agilent 12:14:02 Mar 15, 2013 R T S



Center 2.412 GHz Span 50 MHz
#Res BW 5 MHz #VBW 3 MHz Sweep 4 ms (401 pts)

Channel Power


15.53 dBm / 20.0000 MHz

Power Spectral Density


-57.48 dBm/Hz



(Plot D: Channel 1: 2412MHz @ 802.11g)



(Plot E: Channel 6: 2437MHz @ 802.11g)




(Plot F: Channel 11: 2462MHz @ 802.11g)


2.2.3.3. 802.11n-20MHz Test mode

Channel	Frequency (MHz)	Rate (Mbps)	Measured Output Peak Power		Refer to Plot	Limit		Verdict
			dBm	W		dBm	W	
1	2412	6.5 Mbps	13.19	0.020845	Plot G	30	1	PASS
6	2437	6.5 Mbps	13.97	0.024946	Plot H			PASS
11	2462	6.5 Mbps	14.53	0.028379	Plot I			PASS


Agilent 13:44:23 Mar 15, 2013 R T S



(Plot G: Channel 1: 2412MHz @ 802.11n-20MHz)



(Plot H: Channel 6: 2437MHz @ 802.11n-20MHz)




(Plot I: Channel 11: 2462MHz @ 802.11n-20MHz)

2.2.3.4. 802.11n-40MHz Test mode

Channel	Frequency (MHz)	Rate (Mbps)	Measured Output Peak Power		Refer to Plot	Limit		Verdict
			dBm	W		dBm	W	
3	2422	13.5Mbps	13.74	0.023659	Plot J	30	1	PASS
6	2437	13.5Mbps	14.03	0.025293	Plot K			PASS
9	2452	13.5Mbps	14.76	0.029923	Plot L			PASS

Agilent 13:53:47 Mar 15, 2013 R T S



Center 2.422 GHz Span 50 MHz
#Res BW 5 MHz #VBW 3 MHz Sweep 4 ms (401 pts)

Channel Power


Power Spectral Density

13.74 dBm / 40.0000 MHz


-62.28 dBm/Hz



(Plot J: Channel 3: 2422MHz @ 802.11n-40MHz)



(Plot K: Channel 6: 2437MHz @ 802.11n-40MHz)



(Plot L: Channel 9: 2452MHz @ 802.11n-40MHz)


2.3. Bandwidth

2.3.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Test Description

A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2012.05	2013.05

2.3.3. Test Result


The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.

2.3.3.1. 802.11b Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Rate (Mbps)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
1	2412	1Mbps	10.1875	Plot A	≥ 500	PASS
6	2437	1Mbps	9.9375	Plot B	≥ 500	PASS
11	2462	1Mbps	9.6875	Plot C	≥ 500	PASS


B. Test Plots:



(Plot A: Channel 1: 2412MHz @ 802.11b)



(Plot B: Channel 6: 2437 MHz @ 802.11b)




(Plot C: Channel 11: 2462MHz @ 802.11b)

2.3.3.2. 802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Rate (Mbps)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
1	2412	6Mbps	16.5625	Plot D	≥ 500	PASS
6	2437	6Mbps	16.6250	Plot E	≥ 500	PASS
11	2462	6Mbps	16.5625	Plot F	≥ 500	PASS


B. Test Plots:



(Plot D: Channel 1: 2412MHz @ 802.11g)



(Plot E: Channel 6: 2437MHz @ 802.11g)




(Plot F: Channel 11: 2462MHz @ 802.11g)

2.3.3.3. 802.11n-20 Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Rate (Mbps)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
1	2412	6.5Mbps	17.8125	Plot G	≥ 500	PASS
6	2437	6.5Mbps	17.8125	Plot H	≥ 500	PASS
11	2462	6.5Mbps	17.8125	Plot I	≥ 500	PASS


B. Test Plots:



(Plot G: Channel 1: 2412MHz @ 802.11n-20)



(Plot H: Channel 6: 2437MHz @ 802.11n-20)




(Plot I: Channel 11: 2462MHz @ 802.11n-20)

2.3.3.4. 802.11n-40MHz Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Rate (Mbps)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
3	2422	13.5Mbps	36.5000	Plot J	≥ 500	PASS
6	2437	13.5Mbps	36.5000	Plot K	≥ 500	PASS
9	2452	13.5Mbps	36.5000	Plot L	≥ 500	PASS


B. Test Plots:



(Plot J: Channel 3: 2422MHz @ 802.11n-40)



(Plot K: Channel 6: 2437MHz @ 802.11n-40)



(Plot L: Channel 9: 2452MHz @ 802.11n-40)


2.4. Conducted Spurious Emissions

2.4.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.4.2. Test Description

C. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

D. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2012.05	2013.05

2.4.3. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.


2.4.3.1. 802.11b Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Rate (Mbps)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
					Carrier Level	Calculated -20dBc Limit	
1	2412	1Mbps	-34.18	Plot A.1	5.204	-14.8	PASS
6	2437	1Mbps	-34.08	Plot B.1	6.592	-13.4	PASS
11	2462	1Mbps	-34.02	Plot C.1	7.402	-12.6	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.



(Plot A.1: Channel = 1, 30MHz to 25GHz)



(Plot B.1: Channel = 6, 30MHz to 25GHz)



(Plot C.1: Channel = 11, 30MHz to 25GHz)


2.4.3.2. 802.11g Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Rate (Mbps)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
					Carrier Level	Calculated -20dBc Limit	
1	2412	6Mbps	-43.87	Plot D.1	0.684	-19.3	PASS
6	2437	6Mbps	-46.72	Plot E.1	1.265	-18.7	PASS
11	2462	6Mbps	-44.12	Plot F.1	2.993	-17.0	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.



(Plot D.1: Channel = 1, 30MHz to 25GHz)



(Plot E.1: Channel = 6, 30MHz to 25GHz)



(Plot F.1: Channel = 11, 30MHz to 25GHz)


2.4.3.3. 802.11n -20MHz Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Rate (Mbps)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
					Carrier Level	Calculated -20dBc Limit	
1	2412	6.5Mbps	-43.98	Plot G.1	0.19	-20.0	PASS
6	2437	6.5Mbps	-43.67	Plot H.1	0.985	-18.0	PASS
11	2462	6.5Mbps	-43.22	Plot I.1	2.752	-17.2	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.



(Plot G.1: Channel = 1, 30MHz to 25GHz)



(Plot H.1: Channel = 6, 30MHz to 25GHz)



(Plot I.1: Channel = 11, 30MHz to 25GHz)


2.4.3.4. 802.11n-40MHz Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Rate (Mbps)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
					Carrier Level	Calculated -20dBc Limit	
3	2422	13.5Mbps	-43.91	Plot J.1	-2.132	-22.1	PASS
6	2437	13.5Mbps	-44.65	Plot K.1	-1.224	-21.2	PASS
9	2452	13.5Mbps	-45.01	Plot L.1	-0.638	-20.6	PASS

B. Test Plot:


Note: the power of the Module transmitting frequency should be ignored.



(Plot J.1: Channel = 3, 30MHz to 25GHz)



(Plot K.1: Channel = 6, 30MHz to 25GHz)



(Plot L.1: Channel = 9, 30MHz to 25GHz)


2.5. Power spectral density (PSD)

2.5.1. Requirement

According to FCC section 15.247(d), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

2.5.2. Test Description

A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2012.05	2013.05

2.5.3. Test Result


The lowest, middle and highest channels are tested to verify the band edge emissions.

2.5.3.1. 802.11b Test mode


A. Test Verdict:

Spectral power density (dBm/3kHz)						
Channel	Frequency (MHz)	Rate (Mbps)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	1Mbps	-6.916	Plot A	8	PASS
6	2437	1Mbps	-6.792	Plot B	8	PASS
11	2462	1Mbps	-5.645	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB						


B. Test Plots:



(Plot A: Channel = 1 @ 802.11b)



(Plot B: Channel = 6 @ 802.11b)




(Plot C: Channel = 11 @ 802.11b)

2.5.3.2. 802.11g Test mode


A. Test Verdict:

Spectral power density (dBm/3kHz)						
Channel	Frequency (MHz)	Rate (Mbps)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	6Mbps	-11.97	Plot A	8	PASS
6	2437	6Mbps	-12.02	Plot B	8	PASS
11	2462	6Mbps	-10.71	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB						


B. Test Plots:



(Plot D: Channel = 1 @ 802.11g)



(Plot E: Channel = 6 @ 802.11g)




(Plot F: Channel = 11 @ 802.11g)

2.5.3.3. 802.11n-20MHz Test mode


A. Test Verdict:

Spectral power density (dBm/3kHz)						
Channel	Frequency (MHz)	Rate (Mbps)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
1	2412	6.5Mbps	-13.10	Plot A	8	PASS
6	2437	6.5Mbps	-13.53	Plot B	8	PASS
11	2462	6.5Mbps	-11.65	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB						


B. Test Plots:



(Plot G: Channel = 1 @ 802.11n-20MHz)



(Plot H: Channel = 6 @ 802.11n-20MHz)




(Plot I: Channel = 11 @ 802.11n-20MHz)

2.5.3.4. 802.11n-40MHz Test mode


A. Test Verdict:

Spectral power density (dBm/3kHz)						
Channel	Frequency (MHz)	Rate (Mbps)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
3	2412	13.5Mbps	-16.22	Plot A	8	PASS
6	2437	13.5Mbps	-15.46	Plot B	8	PASS
9	2462	13.5Mbps	-15.22	Plot C	8	PASS
Measurement uncertainty: ± 1.3 dB						


B. Test Plots:



(Plot J: Channel = 3 @ 802.11n-40MHz)



(Plot K: Channel = 6 @ 802.11n-40MHz)



(Plot L: Channel = 9 @ 802.11n-40MHz)


2.6. Band Edge

2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.6.2. Test Description

A. Test Setup



The Module of the EUT is powered by the Battery charged with the AC Adapter. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2012.5	2013.05
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2012.5	2014.05
Test Antenna	Schwarzbeck	BBHA 9120C	9120C-384	2012.5	2013.05

2.6.3. Test Result

The lowest and highest channels are tested to verify the band edge emissions.

The measurement results are obtained as below:

$$E \text{ [dB } \mu \text{ V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


2.6.3.1. 802.11b Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2347.04	PK	40.00	-30.93	32.56	41.63	74	Pass
1	2354.32	AV	35.29	-30.93	32.56	36.92	54	Pass
11	2498.67	PK	39.42	-29.05	32.50	42.87	74	Pass
11	2490.12	AV	37.13	-29.05	32.50	40.58	54	Pass


B. Test Plots:




(Plot A1: Channel = 1 PEAK @ 802.11b)



(Plot A2: Channel = 1 AVG @ 802.11b)



(Plot B1: Channel = 11 PEAK @ 802.11b)



(Plot B2: Channel = 11 AVG @ 802.11b)


2.6.3.2. 802.11g Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2399.12	PK	43.28	-30.93	32.56	44.91	74	Pass
1	2399.40	AV	36.81	-30.93	32.56	38.44	54	Pass
11	2485.09	PK	39.74	-29.05	32.50	43.19	74	Pass
11	2486.61	AV	37.76	-29.05	32.50	41.21	54	Pass


B. Test Plots:




(Plot C1: Channel = 1 PEAK @ 802.11g)



(Plot C2: Channel = 1 AVG @ 802.11g)



(Plot D1: Channel = 11 PEAK @ 802.11g)



(Plot D2: Channel = 11 AVG @ 802.11g)


2.6.3.3. 802.11n-20MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBμV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2397.44	PK	43.08	-30.93	32.56	44.71	74	Pass
1	2399.40	AV	40.16	-30.93	32.56	41.79	54	Pass
11	2494.97	PK	39.67	-29.05	32.50	43.12	74	Pass
11	2486.70	AV	37.86	-29.05	32.50	41.31	54	Pass


B. Test Plots:




(Plot E1: Channel = 1 PEAK @ 802.11n-20)



(Plot E2: Channel = 1 AVG @ 802.11n-20)



(Plot F1: Channel = 11 PEAK @ 802.11n-20)



(Plot F2: Channel = 11 AVG @ 802.11n-20)


2.6.3.4. 802.11n-40MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
3	2345.92	PK	39.33	-30.93	32.56	40.96	74	Pass
3	2348.16	AV	36.88	-30.93	32.56	38.51	54	Pass
9	2484.90	PK	42.50	-29.05	32.50	45.95	74	Pass
9	2486.99	AV	40.62	-29.05	32.50	44.07	54	Pass


B. Test Plots:




(Plot G1: Channel = 3 PEAK@802.11n-40)



(Plot G2: Channel = 3 AVG@802.11n-40)



(Plot H1: Channel = 9 PEAK@802.11n-40)



(Plot H1: Channel = 9 AVG@802.11n-40)

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

The EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The factors of the site are calibrated to correct the reading. During the measurement, the EUT is activated and controlled by the Wi-Fi Service Supplier (SS) via a Common Antenna.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2012.05	2013.05
LISN	Schwarzbeck	NSLK 8127	812744	2012.05	2013.05
Service Supplier	R&S	CMU200	100448	2012.05	2013.05
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)


2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.


A. Test setup:

The EUT configuration of the emission tests is EUT + Charger.

B. Test Plots:



(Plot A: L Phase)



(Plot B: N Phase)

2.8. Radiated Emission

2.8.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:


1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.8.2. Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The EUT of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the EUT is activated and controlled by the Wireless Router via a Common Antenna, and is set to operate under hopping-on test mode.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 2GHz) and Horn Test Antenna (above 2GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2012.05	2013.05
Receiver	Agilent	E7405A	US44210471	2012.05	2013.05
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2012.05	2014.05
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2012.05	2013.05

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	9120C-963	2012.05	2013.05
Test Antenna - Horn	R&S	HL050S7	71688	2012.05	2013.05
Test Antenna -Loop	Schwarzbeck	FMZB 1519	1519-022	2012.05	2013.05

2.8.3. Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB } \mu \text{ V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

2.8.3.1. 802.11b Test mode

A. Test Verdict for Harmonics:

The Fundamental Emissions


The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dB μ V/m)		Antenna Polarization	Refer to Plot
		PK	AV		
1	2412	84.03	N/A	Horizontal	Plot A.2
		84.45	N/A	Vertical	Plot A.3
6	2437	80.80	N/A	Horizontal	Plot B.2
		81.33	N/A	Vertical	Plot B.3
11	2462	78.08	N/A	Horizontal	Plot C.2
		78.14	N/A	Vertical	Plot C.3


Also refer to following plots for the emissions falling in the restricted bands.

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1




(Plot A.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
758.105	33.57	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	84.03	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
11503.741	34.90	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot A.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	24.99	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
2412.000	84.45	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
16825.436	36.05	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot A.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot B.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
158.204	23.81	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
2437.000	80.80	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
17154.613	35.93	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot B.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
37.257	24.09	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
2437.000	81.33	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
11229.426	34.97	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot B.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot C.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	28.34	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
758.105	35.97	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	78.08	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
24341.646	34.65	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot C.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
131.596	22.91	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
758.105	28.30	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	78.14	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
22421.446	34.91	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot C.3: Antenna Vertical, 30MHz to 25GHz)

2.8.3.2. 802.11g Test mode

A. Test Verdict for Harmonics:

The Fundamental Emissions

The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dB μ V/m)		Antenna Polarization	Refer to Plot
		PK	AV		
1	2412	84.62	N/A	Horizontal	Plot D.2
		84.08	N/A	Vertical	Plot D.3
6	2437	80.70	N/A	Horizontal	Plot E.2
		82.05	N/A	Vertical	Plot E.3
11	2462	77.08	N/A	Horizontal	Plot F.2
		78.05	N/A	Vertical	Plot F.3


Also refer to following plots for the emissions falling in the restricted bands.

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1




(Plot D.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
758.105	33.80	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.000	84.62	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
17209.476	36.03	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot D.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	24.48	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
2412.000	84.08	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
16496.259	36.19	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot D.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot E.1: 9kHz to 30MHz)



(Plot E.2: Antenna Horizontal, 30MHz to 25GHz)


Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
153.367	24.69	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
2437.000	80.70	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
17209.476	36.53	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	24.38	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
2437.000	82.05	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
15508.728	35.66	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot E.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot F.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	28.66	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
758.105	35.58	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	77.08	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
18690.773	36.11	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot F.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	23.37	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
758.105	28.56	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2462.000	78.05	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
24835.411	35.68	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot F.3: Antenna Vertical, 30MHz to 25GHz)

2.8.3.3. 802.11n-20MHz Test mode

A. Test Verdict for Harmonics:

The Fundamental Emissions


The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel 1	Frequency (MHz)	Fundamental Emission (dB μ V/m)		Antenna Polarization	Refer to Plot
		PK	AV		
1	2412	84.93	N/A	Horizontal	Plot G.2
		84.21	N/A	Vertical	Plot G.3
6	2437	81.54	N/A	Horizontal	Plot H.2
		82.14	N/A	Vertical	Plot H.3
11	2462	77.50	N/A	Horizontal	Plot I.2
		77.88	N/A	Vertical	Plot I.3


Also refer to following plots for the emissions falling in the restricted bands.

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1




(Plot G.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
758.105	34.14	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2412.00	84.93	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
17154.613	35.60	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot G.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
42.095	24.53	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
2412.000	84.21	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
11064.838	35.23	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot G.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6




(Plot H.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
155.786	24.47	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
2437.000	81.54	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
16551.122	35.96	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot H.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	24.39	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
758.105	28.98	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	82.14	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
24231.920	35.03	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot H.3: Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




(Plot I.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	28.90	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
758.105	35.59	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2462.000	77.50	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
22092.269	35.29	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot I.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
150.948	21.83	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
2462.000	77.88	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
20281.796	35.22	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot I.3: Antenna Vertical, 30MHz to 25GHz)

2.8.3.4. 802.11n-40MHz Test mode

The maximum radiated emission is searched using PK, if the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV or QP detectors.

A. Test Verdict for Harmonics:

The Fundamental Emissions


The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dBμV/m)		Antenna Polarization	Refer to Plot
		PK	AV		
3	2422	78.41	N/A	Horizontal	Plot A.2
		78.27	N/A	Vertical	Plot A.3
6	2437	77.38	N/A	Horizontal	Plot B.2
		76.79	N/A	Vertical	Plot B.3
9	2452	76.14	N/A	Horizontal	Plot C.2
		76.03	N/A	Vertical	Plot C.3


Also refer to following plots for the emissions falling in the restricted bands.

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 3




(Plot A.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	27.79	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
758.105	35.37	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2422.000	78.41	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
24177.057	35.06	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot A.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
758.105	28.72	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2422.000	78.27	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
24231.920	35.54	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot A.3: Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 6




(Plot B.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	27.84	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
758.105	36.13	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2437.000	77.38	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
24177.057	35.53	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(Plot B.2: Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	23.13	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
758.105	29.47	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2437.000	76.79	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
17044.888	36.54	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot B.3: Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 9




(Plot C.1: 9kHz to 30MHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	28.22	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
758.105	35.86	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2452.000	76.14	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
24286.783	35.94	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot C.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
252.544	22.01	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
758.105	27.94	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2452.000	76.03	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
18855.362	36.33	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot C.3: Antenna Vertical, 30MHz to 25GHz)

2.9. RF exposure evaluation

2.9.1. Requirement

According to § 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of Commission's guideline.

2.9.2. Result:

Please refer to SAR report.

**** END OF REPORT ****