

FCC RF Test Report


APPLICANT : TCT Mobile Limited
EQUIPMENT : Module
BRAND NAME : ALCATEL
 one touch
MODEL NAME : one touch M8000
FCC ID : RAD382
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jun. 13, 2013 and testing was completed on Oct. 23, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Site	7
1.8 Applied Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration and system.....	11
2.4 Measurement Results Explanation Example	12
3 TEST RESULT.....	13
3.1 Conducted Output Power Measurement.....	13
3.2 Peak-to-Average Ratio	15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	25
3.4 Occupied Bandwidth and 26dB Bandwidth Measurement.....	31
3.5 Band Edge Measurement.....	55
3.6 Conducted Spurious Emission Measurement.....	70
3.7 Field Strength of Spurious Radiation Measurement	89
3.8 Frequency Stability Measurement.....	105
4 LIST OF MEASURING EQUIPMENTS	111
5 UNCERTAINTY OF EVALUATION.....	112
APPENDIX A. SETUP PHOTOGRAPHS	

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d) §27.50(d)(5)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(b) §27.53(g)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(g)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(g)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(g)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 20.24 dB at 2510.000 MHz
3.8	§2.1055 §22.355 §24.235 §27.54	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

TCT Mobile Limited

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.2 Manufacturer

TCL COMMUNICATION TECHNOLOGY HOLDINGS LIMITED

70 Huifeng 4rd., ZhongKai Hi-tech Development District, Huizhou, Guangdong 516006 P.R.China (TCL Mobile Communication Co., LTD. Huizhou)

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Module
Brand Name	ALCATEL one touch
Model Name	one touch M8000
FCC ID	RAD382
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/LTE
HW Version	V3.0
SW Version	VL_131101_40J00B_40G000_070G0G_0041000(V)
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz
Maximum (Peak) Output Power to Antenna	GSM850 : 32.54 dBm GSM1900 : 29.64 dBm WCDMA Band V : 22.85 dBm WCDMA Band IV : 21.92 dBm WCDMA Band II : 22.91 dBm
Antenna Type	IFA Antenna
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA / DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) DC-HSDPA: 64QAM HSPA+: 16QAM (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.1981	0.01 ppm	242KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.0635	0.01 ppm	248KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0156	0.01 ppm	4M18F9W
Part 24	GSM1900 GPRS class 8	GMSK	0.0695	0.02 ppm	242KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.0286	0.03 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.0384	0.01 ppm	4M18F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.0379	0.01 ppm	4M18F9W

1.7 Testing Site

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-SZ	03CH01-SZ	831040

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 101, Complex Building C, Guanlong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL:+86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	Sporton Site No.		
	OTA01-SZ		

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note: The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, RMC 12.2Kbps mode for WCDMA band IV, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GPRS (GMSK, 1 Tx slot) – CS1	32.54	32.46	32.39	29.24	29.58	29.64
GPRS (GMSK, 2 Tx slots) – CS1	29.70	29.53	29.40	28.18	28.45	28.56
GPRS (GMSK, 3 Tx slots) – CS1	27.05	26.99	26.93	24.13	24.46	24.55
GPRS (GMSK, 4 Tx slots) – CS1	25.79	25.77	25.70	23.01	23.28	23.35
EDGE (8PSK, 1 Tx slot) – MCS5	26.34	26.35	26.38	25.70	25.89	26.03
EDGE (8PSK, 2 Tx slots) – MCS5	23.05	23.02	23.10	22.49	22.76	22.99
EDGE (8PSK, 3 Tx slots) – MCS5	21.70	21.77	21.74	21.08	21.32	21.59
EDGE (8PSK, 4 Tx slots) – MCS5	20.70	20.52	20.65	19.82	20.02	20.38

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Tx Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Rx Channel	4357	4407	4458	9662	9800	9938	1537	1638	1738
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2Kbps	22.85	22.28	21.84	22.57	22.91	22.75	21.75	21.74	21.92
HSDPA Subtest-1	21.02	21.26	20.86	21.13	21.28	21.22	20.15	20.35	20.95
HSDPA Subtest-2	21.02	21.19	20.90	20.98	21.42	21.17	20.23	20.15	20.98
HSDPA Subtest-3	21.14	21.25	20.96	21.14	21.44	21.15	20.25	20.21	21.17
HSDPA Subtest-4	21.08	21.32	20.86	21.19	21.33	21.14	20.28	20.18	21.14
DC-HSDPA Subtest-1	20.92	20.95	20.49	20.27	20.33	20.19	19.58	20.10	20.38
DC-HSDPA Subtest-2	20.78	20.67	20.28	20.21	20.18	20.14	19.43	19.83	20.22
DC-HSDPA Subtest-3	20.46	20.44	20.16	20.11	19.97	19.93	19.29	19.61	20.02
DC-HSDPA Subtest-4	20.44	20.40	20.02	19.94	19.84	19.81	19.09	19.43	19.73
HSUPA Subtest-1	21.12	20.90	20.34	20.47	20.58	20.55	19.96	19.96	19.81
HSUPA Subtest-2	19.87	20.30	19.69	20.06	20.21	20.13	19.79	19.77	19.64
HSUPA Subtest-3	19.63	19.95	19.37	19.72	19.81	19.75	18.92	18.93	18.77
HSUPA Subtest-4	19.92	20.23	19.67	20.92	21.07	21.05	20.09	20.08	19.95
HSUPA Subtest-5	19.94	20.24	19.66	20.08	20.14	20.12	19.82	19.78	19.64
HSPA+ (16QAM) Subtest-1	20.93	20.96	20.51	20.43	20.70	20.25	19.93	20.16	20.36

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 7.5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 7.5 + 10 = 17.5 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.54	32.46	32.39	26.34	26.35	26.38	22.85	22.28	21.84
Conducted Power (Watts)	1.79	1.76	1.73	0.43	0.43	0.43	0.19	0.17	0.15

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.24	29.58	29.64	25.70	25.89	26.03	22.57	22.91	22.75
Conducted Power (Watts)	0.84	0.91	0.92	0.37	0.39	0.40	0.18	0.20	0.19

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	21.75	21.74	21.92
Conducted Power (Watts)	0.15	0.15	0.16

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.37	0.39	0.41	2.89	2.91	2.87	3.60	3.60	3.56


AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	3.48	3.52	3.52



3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 22.OCT.2013 17:39:34


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 22.OCT.2013 17:38:10



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 22.OCT.2013 17:41:05




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
---------------	----------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 22.OCT.2013 17:49:32


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 22.OCT.2013 17:46:30



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 22.OCT.2013 17:50:48



Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)




Complementary Cumulative Distribution Function (100000 samples)

Trace 1
 Mean 20.98 dBm
 Peak 24.89 dBm
 Crest 3.91 dB

10 % 1.80 dB
 1 % 2.88 dB
 .1 % 3.48 dB
 .01 % 3.76 dB

Date: 22.OCT.2013 19:49:29

Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1
 Mean 20.90 dBm
 Peak 24.89 dBm
 Crest 3.99 dB

10 % 1.80 dB
 1 % 2.88 dB
 .1 % 3.52 dB
 .01 % 3.80 dB

Date: 22.OCT.2013 19:48:22



Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1
 Mean 21.14 dBm
 Peak 25.17 dBm
 Crest 4.04 dB


10 % 1.76 dB
 1 % 2.92 dB
 .1 % 3.52 dB
 .01 % 3.84 dB

Date: 22.OCT.2013 19:50:34




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 22.OCT.2013 16:42:48


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 22.OCT.2013 16:41:41



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1
Mean 20.78 dBm
Peak 24.82 dBm
Crest 4.04 dB

10 %	1.80 dB
1 %	2.96 dB
.1 %	3.56 dB
.01 %	3.88 dB

Date: 22.OCT.2013 16:42:08

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band).

3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-26.62	-48.12	0.00	-1.08	20.42	0.1101
836.40	-24.38	-48.28	0.00	-0.93	22.97	0.1981
848.80	-24.80	-48.35	0.00	-0.76	22.79	0.1899
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-29.66	-47.97	0.00	-1.08	17.23	0.0528
836.40	-25.50	-48.01	0.00	-0.93	21.58	0.1439
848.80	-26.91	-48.05	0.00	-0.76	20.38	0.1091

GSM850 (EDGE class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-29.02	-48.12	0.00	-1.08	18.02	0.0635
836.40	-29.56	-48.28	0.00	-0.93	17.79	0.0602
848.80	-29.83	-48.35	0.00	-0.76	17.76	0.0598
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-30.62	-47.97	0.00	-1.08	16.27	0.0424
836.40	-30.54	-48.01	0.00	-0.93	16.54	0.0451
848.80	-31.93	-48.05	0.00	-0.76	15.36	0.0344



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-35.12	-48.12	0.00	-1.08	11.92	0.0156
836.40	-36.55	-48.28	0.00	-0.93	10.80	0.0120
846.60	-37.35	-48.35	0.00	-0.76	10.24	0.0106
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-36.82	-47.97	0.00	-1.08	10.07	0.0102
836.40	-38.30	-48.01	0.00	-0.93	8.78	0.0075
846.60	-40.85	-48.05	0.00	-0.76	6.44	0.0044

3.3.6 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-35.42	-51.88	0.00	1.96	18.42	0.0695
1880.00	-37.50	-52.99	0.00	2.00	17.49	0.0560
1909.80	-38.96	-54.28	0.00	1.98	17.30	0.0537
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-36.55	-52.13	0.00	1.96	17.54	0.0567
1880.00	-36.91	-53.17	0.00	2.00	18.26	0.0670
1909.80	-38.46	-54.13	0.00	1.98	17.65	0.0582

GSM1900 (EDGE class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-39.28	-51.88	0.00	1.96	14.56	0.0286
1880.00	-41.24	-52.99	0.00	2.00	13.75	0.0237
1909.80	-42.87	-54.28	0.00	1.98	13.39	0.0218
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-40.20	-52.13	0.00	1.96	13.89	0.0245
1880.00	-41.54	-53.17	0.00	2.00	13.63	0.0231
1909.80	-42.35	-54.13	0.00	1.98	13.76	0.0238



WCDMA Band IV (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-38.27	-51.88	0.00	1.96	15.57	0.0360
1732.60	-40.45	-52.99	0.00	2.00	14.54	0.0284
1752.60	-40.47	-54.28	0.00	1.98	15.79	0.0379
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-39.69	-52.13	0.00	1.96	14.40	0.0275
1732.60	-41.45	-53.17	0.00	2.00	13.72	0.0236
1752.60	-40.85	-54.13	0.00	1.98	15.26	0.0336

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-40.37	-51.88	0.00	1.96	13.47	0.0222
1880.00	-41.59	-52.99	0.00	2.00	13.40	0.0219
1907.60	-42.68	-54.28	0.00	1.98	13.58	0.0228
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-41.37	-52.13	0.00	1.96	12.72	0.0187
1880.00	-39.50	-53.17	0.00	2.00	15.67	0.0369
1907.60	-40.27	-54.13	0.00	1.98	15.84	0.0384

3.4 Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	240.00	242.00	240.00	242.00	248.00	242.00
26dB BW (kHz)	300.00	300.00	298.00	314.00	308.00	314.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	242.00	242.00	240.00	246.00	246.00	244.00
26dB BW (kHz)	298.00	300.00	302.00	306.00	312.00	304.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.160	4.160	4.180
26dB BW (MHz)	4.680	4.680	4.660

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.160	4.160	4.180
26dB BW (MHz)	4.680	4.680	4.680




PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.180	4.160	4.180
26dB BW (MHz)	4.680	4.680	4.680



3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.OCT.2013 14:10:37


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.OCT.2013 14:00:21




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.OCT.2013 14:08:54


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.OCT.2013 13:59:34




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 22.OCT.2013 14:07:41

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 22.OCT.2013 14:00:57




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
---------------	---------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.OCT.2013 15:38:20


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 22.OCT.2013 15:35:23




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.OCT.2013 15:39:46


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 22.OCT.2013 15:34:06




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 22.OCT.2013 15:41:09

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 22.OCT.2013 15:33:06




Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
---------------	----------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.OCT.2013 14:39:54


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.OCT.2013 14:37:15




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 22.OCT.2013 14:41:34

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 22.OCT.2013 14:36:23




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
---------------	----------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.OCT.2013 15:00:13


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 22.OCT.2013 14:58:14




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 22.OCT.2013 15:02:26


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 22.OCT.2013 14:57:09




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 22.OCT.2013 15:04:35

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 22.OCT.2013 14:54:12




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 22.OCT.2013 16:02:15


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 22.OCT.2013 16:06:11




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 22.OCT.2013 16:00:48


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 22.OCT.2013 16:07:03




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 22.OCT.2013 16:03:32

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 22.OCT.2013 16:05:26




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 22.OCT.2013 19:05:20


26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 22.OCT.2013 19:07:51




99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 22.OCT.2013 19:03:15


26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 22.OCT.2013 19:14:10




99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 22.OCT.2013 19:01:23

26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)




Date: 22.OCT.2013 19:20:58




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 22.OCT.2013 16:38:32


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 22.OCT.2013 16:37:00




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 22.OCT.2013 16:41:18


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 22.OCT.2013 16:34:01




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 22.OCT.2013 16:39:34

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 22.OCT.2013 16:34:59

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures


1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.00dB	Maximum 26dB Bandwidth :	0.300MHz
Band Edge :	-15.27dBm	Measurement Value :	-15.27dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 22.OCT.2013 14:13:13

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.00dB	Maximum 26dB Bandwidth :	0.300MHz
Band Edge :	-17.67dBm	Measurement Value :	-17.67dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 22.OCT.2013 14:13:58

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-25.57dBm	Measurement Value :	-25.77dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 22.OCT.2013 15:29:10

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-25.54dBm	Measurement Value :	-25.74dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 22.OCT.2013 15:30:40

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.03dB	Maximum 26dB Bandwidth :	0.302MHz
Band Edge :	-19.42dBm	Measurement Value :	-19.45dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 22.OCT.2013 14:48:06

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.03dB	Maximum 26dB Bandwidth :	0.302MHz
Band Edge :	-21.68dBm	Measurement Value :	-21.71dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 22.OCT.2013 14:47:01

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.17dB	Maximum 26dB Bandwidth :	0.312MHz
Band Edge :	-24.42dBm	Measurement Value :	-24.59dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 22.OCT.2013 14:50:26

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.17dB	Maximum 26dB Bandwidth :	0.312MHz
Band Edge :	-27.74dBm	Measurement Value :	-27.91dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 22.OCT.2013 14:52:07

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-29.64dBm	Measurement Value :	-26.34dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 22.OCT.2013 16:13:16

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-30.57dBm	Measurement Value :	-27.27dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 22.OCT.2013 16:12:49

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-30.03dBm	Measurement Value :	-26.73dBm

Lower Band Edge Plot on Channel 1312 (1712.4 MHz)




Date: 22.OCT.2013 18:57:24

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-31.09dBm	Measurement Value :	-27.79dBm

Higher Band Edge Plot on Channel 1513 (1752.6 MHz)




Date: 22.OCT.2013 18:59:16

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-30.29dBm	Measurement Value :	-26.99dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 22.OCT.2013 16:43:33

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.680MHz
Band Edge :	-30.73dBm	Measurement Value :	-27.43dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 22.OCT.2013 16:43:59

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$


3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.OCT.2013 14:15:15


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.OCT.2013 14:18:42




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.OCT.2013 14:20:09

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 22.OCT.2013 14:20:54




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.OCT.2013 15:25:34


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.OCT.2013 15:20:57




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.OCT.2013 15:22:45

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 22.OCT.2013 15:24:01




Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.OCT.2013 14:28:35


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.OCT.2013 14:29:17




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.OCT.2013 14:25:43


Conducted Spurious Emission Plot between 7GHz ~ 13.6G



Date: 22.OCT.2013 14:26:28



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 22.OCT.2013 14:27:25




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.OCT.2013 15:09:22


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.OCT.2013 15:08:01




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.OCT.2013 15:13:20


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 22.OCT.2013 15:14:21



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 22.OCT.2013 15:15:36




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 22.OCT.2013 16:16:16

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 22.OCT.2013 16:18:39

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.OCT.2013 16:22:16

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 22.OCT.2013 16:23:18




Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1732.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.OCT.2013 19:24:39


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.OCT.2013 19:39:33




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.OCT.2013 19:42:51


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 22.OCT.2013 19:44:20



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 22.OCT.2013 19:45:11




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 22.OCT.2013 16:30:25


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 22.OCT.2013 16:31:22




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 22.OCT.2013 16:25:51


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 22.OCT.2013 16:26:59



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 22.OCT.2013 16:27:46

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	24~25°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-44.59	-13	-31.59	-60.57	-47.56	0.88	6.00	H	Pass
2510	-33.24	-13	-20.24	-58.38	-35.85	1.08	5.84	H	Pass
3346	-61.68	-13	-48.68	-72.28	-66.05	1.14	7.66	H	Pass



Band :	GSM850	Temperature :	24~25°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.24	-13	-35.24	-61.09	-51.21	0.88	6.00	V	Pass
2510	-41.48	-13	-28.48	-63.50	-44.09	1.08	5.84	V	Pass
3346	-60.57	-13	-47.57	-72.40	-64.94	1.14	7.66	V	Pass



Band :	GSM850	Temperature :	24~25°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-49.34	-13	-36.34	-64.10	-52.31	0.88	6.00	H	Pass
2510	-43.45	-13	-30.45	-66.98	-46.06	1.08	5.84	H	Pass
3346	-61.54	-13	-48.54	-72.14	-65.91	1.14	7.66	H	Pass



Band :	GSM850	Temperature :	24~25°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-58.37	-13	-45.37	-69.00	-61.34	0.88	6.00	V	Pass
2510	-49.52	-13	-36.52	-69.60	-52.13	1.08	5.84	V	Pass
3346	-60.75	-13	-47.75	-72.58	-65.12	1.14	7.66	V	Pass



Band :	GSM1900	Temperature :	24~25°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.21	-13	-43.21	-68.36	-62.95	1.28	8.02	H	Pass
5640	-55.01	-13	-42.01	-73.00	-63.43	1.58	10.00	H	Pass
7520	-53.65	-13	-40.65	-75.59	-63.97	1.78	12.10	H	Pass



Band :	GSM1900	Temperature :	24~25°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-53.77	-13	-40.77	-68.8	-60.51	1.28	8.02	V	Pass
5640	-53.03	-13	-40.03	-70.11	-61.45	1.58	10	V	Pass
7520	-53.75	-13	-40.75	-76	-64.07	1.78	12.1	V	Pass



Band :	GSM1900	Temperature :	24~25°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.46	-13	-43.46	-68.61	-63.20	1.28	8.02	H	Pass
5640	-55.08	-13	-42.08	-73.07	-63.50	1.58	10.00	H	Pass
7520	-52.55	-13	-39.55	-74.49	-62.87	1.78	12.10	H	Pass



Band :	GSM1900	Temperature :	24~25°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-55.39	-13	-42.39	-70.42	-62.13	1.28	8.02	V	Pass
5640	-56.09	-13	-43.09	-73.17	-64.51	1.58	10	V	Pass
7520	-53.21	-13	-40.21	-75.46	-63.53	1.78	12.1	V	Pass



Band :	WCDMA Band V	Temperature :	24~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF EIRP H 130101 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-56.41	-13	-43.41	-69.33	-59.38	0.88	6.00	H	Pass
2510	-49.21	-13	-36.21	-70.66	-51.82	1.08	5.84	H	Pass
3346	-62.22	-13	-49.22	-72.82	-66.59	1.14	7.66	H	Pass



Band :	WCDMA Band V	Temperature :	24~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-56.38	-13	-43.38	-67.01	-59.35	0.88	6.00	V	Pass
2510	-51.27	-13	-38.27	-70.55	-53.88	1.08	5.84	V	Pass
3346	-59.92	-13	-46.92	-71.75	-64.29	1.14	7.66	V	Pass



Band :	WCDMA Band IV	Temperature :	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%
Test Engineer :	Gavin Zhang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465.20	-58.81	-13	-45.81	-69.89	-38.20	1.15	7.54	H	Pass
5197.80	-49.72	-13	-36.72	-68.68	-68.60	1.51	9.80	H	Pass
6930.40	-51.19	-13	-38.19	-74.81	-67.90	1.75	11.51	H	Pass



Band :	WCDMA Band IV	Temperature :	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%
Test Engineer :	Gavin Zhang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465.2	-55.74	-13	-42.74	-68.6	-43.20	1.15	7.54	V	Pass
5197.8	-44.14	-13	-31.14	-63.54	-70.30	1.51	9.80	V	Pass
6930.4	-47.05	-13	-34.05	-70.38	-64.60	1.75	11.51	V	Pass



Band :	WCDMA Band II	Temperature :	24~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-57.29	-13	-44.29	-69.44	-64.03	1.28	8.02	H	Pass
5640	-50.32	-13	-37.32	-68.31	-58.74	1.58	10.00	H	Pass
7520	-52.87	-13	-39.87	-74.81	-63.19	1.78	12.10	H	Pass



Band :	WCDMA Band II	Temperature :	24~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-SZ
 Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-54.15	-13	-41.15	-69.18	-60.89	1.28	8.02	V	Pass
5640	-50.03	-13	-37.03	-67.11	-58.45	1.58	10	V	Pass
7520	-50.98	-13	-37.98	-73.23	-61.30	1.78	12.1	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-11	-0.01	8	+0.01	PASS
-20	-10	-0.01	7	+0.01	
-10	-10	-0.01	-7	-0.01	
0	-8	-0.01	7	+0.01	
10	-9	-0.01	8	+0.01	
20	-10	-0.01	-7	-0.01	
30	-9	-0.01	-7	-0.01	
40	-10	-0.01	8	+0.01	
50	-10	-0.01	-8	-0.01	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-35	-0.02	-29	-0.02	PASS
-20	-30	-0.02	-32	-0.02	
-10	-32	-0.02	-35	-0.02	
0	27	+0.01	-28	-0.01	
10	22	+0.01	-34	-0.02	
20	25	+0.01	-44	-0.02	
30	-28	-0.01	-39	-0.02	
40	23	+0.01	-42	-0.02	
50	-26	-0.01	-51	-0.03	



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-4	+0.01	PASS
-20	-3	+0.01	
-10	-3	+0.01	
0	-2	+0.01	
10	-3	+0.01	
20	-2	+0.01	
30	-4	+0.01	
40	-3	+0.01	
50	-3	+0.01	

Band :	WCDMA Band IV	Channel :	1413
Limit (ppm) :	2.5	Frequency :	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	14	+0.01	PASS
-20	12	+0.01	
-10	13	+0.01	
0	10	+0.01	
10	12	+0.01	
20	8	+0.01	
30	8	+0.01	
40	7	+0.01	
50	9	+0.01	



Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-15	-0.01	PASS
-20	-13	-0.01	
-10	-13	-0.01	
0	12	+0.01	
10	-11	-0.01	
20	-10	-0.01	
30	-10	-0.01	
40	-12	-0.01	
50	-14	-0.01	

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	3.8	-10	-0.01	2.5	PASS
		BEP	-8	-0.01		
		4.2	-9	-0.01		
	EDGE class 8	3.8	-7	-0.01		
		BEP	-7	-0.01		
		4.2	-8	-0.01		
GSM 1900 CH661	GPRS class 8	3.8	25	+0.01		
		BEP	27	+0.01		
		4.2	28	+0.01		
	EDGE class 8	3.8	-44	-0.02		
		BEP	-40	-0.02		
		4.2	-42	-0.02		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	-2	+0.01		
		BEP	-3	+0.01		
		4.2	-3	+0.01		
WCDMA Band IV CH1413	RMC 12.2Kbps	3.8	8	+0.01		
		BEP	7	+0.01		
		4.2	8	+0.01		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	-10	-0.01		
		BEP	-9	+0.01		
		4.2	-11	-0.01		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.45 V.



4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 28, 2013	Oct. 22, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV30	100845	9kHz~30GHz	Nov. 06, 2012	Oct. 22, 2013	Nov. 05, 2013	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	N/A	Mar. 28, 2013	Oct. 22, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA2411B	1207253	N/A	Mar. 28, 2013	Oct. 22, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	N/A	Mar. 28, 2013	Oct. 22, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	Apr. 04, 2013	Oct. 22, 2013~ Oct. 23, 2013	Apr. 03, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 27, 2012	Oct. 22, 2013~ Oct. 23, 2013	Oct. 26, 2013	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30MHz~2GHz	Nov. 03, 2012	Oct. 22, 2013~ Oct. 23, 2013	Nov. 02, 2013	Radiation (03CH01-SZ)
Turn Table	EM Electronic	EM 1000	N/A	0 ~ 360 degree	N/A	Oct. 22, 2013~ Oct. 23, 2013	N/A	Radiation (03CH01-SZ)
Antenna Mast	EM electronic	EM 1000	N/A	1 m - 4 m	N/A	Oct. 22, 2013~ Oct. 23, 2013	N/A	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3GHz Gain 30dB	Mar. 28, 2013	Oct. 22, 2013~ Oct. 23, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 28, 2013	Oct. 22, 2013~ Oct. 23, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
SHF-EHF -Horn	Schwarzbeck	BBHA9170	BBHA9170249	14GHz~40GHz	Nov. 23, 2012	Oct. 22, 2013~ Oct. 23, 2013	Nov. 22, 2013	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Aug. 21, 2013	Oct. 22, 2013~ Oct. 23, 2013	Aug. 20, 2014	ERP/EIRP (OTA01-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000MHz	N/A	Oct. 22, 2013~ Oct. 23, 2013	N/A	ERP/EIRP (OTA01-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	N/A	Oct. 22, 2013~ Oct. 23, 2013	N/A	ERP/EIRP (OTA01-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	N/A	Oct. 22, 2013~ Oct. 23, 2013	N/A	ERP/EIRP (OTA01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.90
---	------