



TEST REPORT

Report No.: SRTC2014-H024-E0021

Product Name: GSM/GPRS/EDGE/UMTS

Digital Mobile Phone with Bluetooth and WiFi

Product Model: 6037B

Applicant: TCT Mobile Limited

Manufacturer: TCT Mobile Limited

Specification: FCC Part 15, Subpart C (October 9, 2012 edition)

FCC ID: RAD457

The State Radio_monitoring_center Testing Center (SRTC)

No.80 Beilishi Road Xicheng District Beijing, China

Tel: 86-10-68009202 Fax: 86-10-68009205

CONTENTS

1. General information	3
1.1 Notes of the test report	3
1.2 Information about the testing laboratory.....	3
1.3 Applicant's details	3
1.4 Manufacturer's details.....	3
1.5 Application details	4
1.6 Reference specification.....	4
1.7 Information of EUT	4
1.7.1 General information.....	4
1.7.2 EUT details	5
1.7.3 Auxiliary equipment details.....	5
2. Test information	7
2.1 Summary of the test results.....	7
2.2 Test result.....	8
2.2.1 Occupied Bandwidth	8
2.2.2 Peak Power Output	14
2.2.3 Spurious RF Conducted Emissions	21
2.2.4 Spurious Radiated Emissions.....	40
2.2.5 Band Edge Compliance	49
2.2.6 Dwell Time	66
2.2.7 Channel Separation	73
2.2.8 Number of Hopping Frequencies	75
2.3. Measurement Uncertainty	77
2.4. List of test equipment.....	78
Appendix	79

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Address: No.80 Beilishi Road, Xicheng District, Beijing China
City: Beijing
Country or Region: China
Contacted person: Wang Junfeng
Tel: +86 10 68009181 +86 10 68009202
Fax: +86 10 68009195 +86 10 68009205
Email: wangjf@srrc.org.cn / wangjunfeng@srtc.org.cn

1.3 Applicant's details

Company: TCT Mobile Limited
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area
City: Shanghai
Country or Region: P.R.China
Grantee Code: RAD
Contacted person: Gong Zhizhou
Tel: +86-21-61460890
Fax: +86-21-61460602
Email: zhizhou.gong@tcl.com

1.4 Manufacturer's details

Company: TCT Mobile Limited
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area
City: Shanghai
Country or Region: P.R.China
Contacted person: Gong Zhizhou
Tel: +86-21-61460890
Fax: +86-21-61460602
Email: zhizhou.gong@tcl.com

1.5 Application details

Date of reception of test sample: 3rd March 2014

Date of test: 5th March 2014 to 24th March 2014

1.6 Reference specification

FCC Part 15, Subpart C (October 9, 2012 edition)

1.7 Information of EUT

1.7.1 General information

Name of EUT	GSM/GPRS/EDGE/UMTS Digital Mobile Phone with Bluetooth and WiFi
FCC ID	RAD457
Frequency Range	2.4GHz~2.4835GHz
Number of Channel	79
Modulation Type	GFSK, $\pi/4$ DQPSK, 8DPSK
Duplex Mode	TDD
Channel Spacing	1MHz
Data Rate	1Mbps, 2 Mbps, 3 Mbps
Antenna Type	Fixed Internal
Power Supply	Battery or Charger
Rated Power Supply Voltage	3.8V
HW Version	PIO
SW Version	v3EH9-US

1.7.2 EUT details

Product Name	Product Model	IMEI
GSM/GPRS/EDGE/UMTS Digital Mobile Phone with Bluetooth and WiFi	6037B	014017009000082

1.7.3 Auxiliary equipment details

Equipment	Charger
Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD.
Model Number	one touch UC12US
Input Voltage	100V-240V a.c.
Output Voltage	5.0V d.c.
Frequency	50/60Hz

Equipment	Charger
Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD.
Model Number	one touch UC12EU
Input Voltage	100V-240V a.c.
Output Voltage	5.0V d.c.
Frequency	50/60Hz

Equipment	Charger
Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD.
Model Number	one touch UC12UK
Input Voltage	100V-240V a.c.
Output Voltage	5.0V d.c.
Frequency	50/60Hz

Equipment	Battery
Manufacturer	SCUD (FUJIAN) Electronics Co., Ltd.
Model Number	TLp020C2
Capacity	2000mAh
Rated Voltage	4.35V d.c.

Equipment	Data Cable
Manufacturer	Huizhou Shenghua Industry Co., Ltd.
Model Number	CDA0000025C1

Equipment	Data Cable
Manufacturer	Shenzhen Juwei Electronics Co., Ltd.
Model Number	CDA0000025C2




Note: As the information described above, there are three different models of charger manufactured by the same company and two different models of data cable manufactured by two different companies.

The relevant tests have been performed in order to verify in which combination case (EUT exercised by only one model of charger and one model of data cable) the EUT would have the worst features. So all the tests shown in this test report are performed when the EUT exercised by the charger one touch UC12US and the data cable CDA0000025C1.

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	Occupied Bandwidth	15.247(a)(1)	Pass
2	Peak Power Output	15.247(b)(1)	Pass
3	Spurious RF Conducted Emissions	15.247(d)	Pass
4	Spurious Radiated Emissions	15.247(d)/15.35(b)/15.209	Pass
5	Band Edge Compliance	15.247(d)	Pass
6	Dwell Time	15.247(a)(1)(iii)	Pass
7	Channel Separation	15.247(a)(1)	Pass
8	Number of Hopping Frequencies	15.247(a)(1)(iii)	Pass

This Test Report Is Issued by: Mr. Song Qizhu Director of the test lab 	Checked by: Mr. Wang Junfeng Deputy director of the test lab 
Tested by: Mr. Li Bin Test engineer 	Issued date: 2014.04.04

2.2 Test result

2.2.1 Occupied Bandwidth

2.2.1.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.1kPa

2.2.1.2 Test Description


The measurement is made according to ANSI C63.10-2009 Section 6.9.1 and Public notice DA 00-705.

The Equipment Under Test (EUT) was setup in a shielded room to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical.

The results recorded were measured with the modulation which produces the worst-case (widest) occupied bandwidth. The resolution bandwidth for measuring the reference level and the occupied bandwidth was 10 kHz.

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss.



2.2.1.3 Test limit

FCC Part15.247(a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

2.2.1.4 Test result

Modulation type: GFSK


Carrier frequency (MHz)	Channel No.	20 dB bandwidth(kHz)
2402	0	757.7
2441	39	757.9
2480	78	758.1

Modulation type: $\pi/4$ DQPSK


Carrier frequency (MHz)	Channel No.	20 dB bandwidth(kHz)
2402	0	1185.9
2441	39	1189.3
2480	78	1186.1

Modulation type: 8DPSK


Carrier frequency (MHz)	Channel No.	20 dB bandwidth(kHz)
2402	0	1215.1
2441	39	1215.3
2480	78	1215.1




Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: GFSK



Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: GFSK




Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: GFSK




Date: 5.MAR.2014 10:08:06

Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: $\pi/4$ DQPSK




Date: 5.MAR.2014 10:08:25

Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: $\pi/4$ DQPSK




Date: 5.MAR.2014 10:08:37

Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: $\pi/4$ DQPSK




Date: 5.MAR.2014 10:08:52

Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: 8DPSK



Date: 5.MAR.2014 10:09:02

Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: 8DPSK



Date: 5.MAR.2014 10:09:14

Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: 8DPSK

2.2.2 Peak Power Output

2.2.2.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.1kPa

2.2.2.2 Test Description

The measurement is made according to ANSI C63.10-2009 Section 6.10.1 and Public notice DA 00-705.


The Equipment Under Test (EUT) was set up in a shielded room to perform the output power measurements.

The results recorded were measured with the modulation which produces the worst-case (highest) output power.

The resolution bandwidth for measuring the output power was 2 MHz.

The reference level of the spectrum analyzer was set higher than the output power of the EUT.

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss.



2.2.2.3 Test limit

FCC Part15.247(b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW) →

Modulation type	GFSK	$\pi/4$ DQPSK	8DPSK
Maximum Output Power	30dBm	30dBm	30dBm


2.2.2.4 Test Condition

Hopping Mode	Modulation type	RBW	VBW	Span	Sweep time
Hopping OFF	GFSK	2MHz	3MHz	8MHz	1ms
Hopping OFF	$\pi/4$ DQPSK	2MHz	3MHz	8MHz	1ms
Hopping OFF	8DPSK	2MHz	3MHz	8MHz	1ms


2.2.2.5 Test result

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2441MHz (Ch39)	2480MHz (Ch78)
GFSK	6.62	7.56	7.47
$\pi/4$ DQPSK	2.00	2.85	3.02
8DPSK	2.03	2.81	2.95


Modulation type	Peak Power Output (dBm)		
	2402MHz (Ch0)	2441MHz (Ch39)	2480MHz (Ch78)
GFSK	7.09	7.93	8.13
$\pi/4$ DQPSK	6.76	7.44	7.67
8DPSK	6.78	7.88	8.05




Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: GFSK




Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: GFSK




Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: GFSK




Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: $\pi/4$ DQPSK




Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: $\pi/4$ DQPSK




Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: $\pi/4$ DQPSK



Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: 8DPSK



Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: 8DPSK



Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: 8DPSK

2.2.3 Spurious RF Conducted Emissions

2.2.3.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.1kPa

2.2.3.2 Test Description

The measurement is made according to ANSI C63.10-2009 Section 6.7 and Public notice DA 00-705.


The Equipment Under Test (EUT) was set up in a shielded room to perform the spurious emissions measurements.

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss.

Analyzer settings:

- Detector: Peak-Maxhold
- Frequency range: 30 ~25000 MHz
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz

The reference value for the measurement of the spurious RF conducted emissions is determined during the test “band edge compliance” (cf. chapter 4.5). This value is used to calculate the 20 dBc limit.



2.2.3.3 Test limit

FCC Part15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

2.2.3.4 Test result

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: GFSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---

Carrier frequency (MHz): 2441

Channel No.:39

Modulation type: GFSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---


Carrier frequency (MHz): 2480

Channel No.:78


Modulation type: GFSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---


Note: The Reference value see 2.2.5 Band Edge Compliance



Date: 28.MAR.2014 12:15:51




Date: 28.MAR.2014 13:13:27




Date: 28.MAR.2014 12:59:14


Carrier frequency (MHz): 2402
 Channel No.:0
 Modulation type: GFSK



Date: 28.MAR.2014 12:16:47




Date: 28.MAR.2014 13:13:51




Date: 28.MAR.2014 12:59:32


Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: GFSK



Date: 28.MAR.2014 12:16:59



Date: 28.MAR.2014 13:14:11



Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: GFSK

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---

Carrier frequency (MHz): 2441

Channel No.:39

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---


Carrier frequency (MHz): 2480

Channel No.:78


Modulation type: $\pi/4$ DQPSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---


Note: The Reference value see 2.2.5 Band edge compliance



Date: 28.MAR.2014 12:17:11




Date: 28.MAR.2014 13:14:51





Date: 28.MAR.2014 13:00:00


Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: $\pi/4$ DQPSK




Date: 28.MAR.2014 12:56:17




Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: $\pi/4$ DQPSK



Date: 28.MAR.2014 12:56:36



Date: 28.MAR.2014 13:15:21



Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: $\pi/4$ DQPSK

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: 8DPSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---

Carrier frequency (MHz): 2441

Channel No.:39

Modulation type: 8DPSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---


Carrier frequency (MHz): 2480

Channel No.:78


Modulation type: 8DPSK

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta dB
---	---	---	---	---
---	---	---	---	---


Note: The Reference value see 2.2.5 Band edge compliance




Date: 28.MAR.2014 12:57:20




Date: 28.MAR.2014 13:15:52




Carrier frequency (MHz): 2402
Channel No.:0
Modulation type: 8DPSK






Date: 28.MAR.2014 13:16:06




Date: 28.MAR.2014 13:01:14


Carrier frequency (MHz): 2441
Channel No.:39
Modulation type: 8DPSK



Date: 28.MAR.2014 12:57:50



Date: 28.MAR.2014 13:16:19



Carrier frequency (MHz): 2480
Channel No.:78
Modulation type: 8DPSK

2.2.4 Spurious Radiated Emissions

2.2.4.1 Ambient condition

Temperature	Relative humidity	Pressure
24.3°C	36.2%	100.2kPa

2.2.4.2 Test Description

The measurement is made according to ANSI C63.10-2009 Section 6.3 - 6.6 and Public notice DA 00-705.


The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The radiated emissions measurements were made in a typical installation configuration.

Then start the test software ES-K1. Sweep the whole frequency band through the range from 30MHz to 1GHz or above, using receive log period antenna HL562 or Ridge horn antenna HF906.

During the test, the antenna height and EUT azimuth were varied in order to identify the maximum level of emission from the EUT. The height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees. The measurements shall be repeated with orthogonal polarization of the test antenna. The results (reference to 2.2.4.4) shall be showed the worst case of the three orthogonal axes.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing.



2.2.4.3 Test limit

FCC Part15.247(d):

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part15.209:

Radiated Emission Limits

Frequency of Emission(MHz)	Limits	
	Detector	Unit (dB μ V/m)
30~88	Quasi-peak	40.0
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46.0
960~1000	Quasi-peak	54.0
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54.0
	Peak	74.0

FCC Part15.35(b):

..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dB μ V/m) = 20 log (Limit (μ V/m)/1 μ V/m)

2.2.4.4 Test result

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

The worst case attitude: The mobile lay down.

For GFSK
Channel No.:39

Frequency(MHz)	Result(dBuV/m)	A _{Rpl} (dB)	P _{mea} (dBuV/m)	Polarity
38.56	12.80	15.20	25.75	Vertical
77.92	8.10	7.90	0.20	Vertical
499.90	16.50	18.20	-1.70	Vertical
550.16	17.70	19.40	-1.70	Vertical
940.04	31.00	25.70	5.30	Vertical
944.78	28.90	25.70	3.20	Vertical

For $\pi/4$ DQPSK
Channel No.:39


Frequency(MHz)	Result(dBuV/m)	A _{Rpl} (dB)	P _{mea} (dBuV/m)	Polarity
40.00	12.90	16.20	-3.3	Vertical
77.62	7.80	7.80	0.00	Vertical
481.30	16.40	18.10	-1.70	Vertical
558.62	17.90	19.50	-1.60	Vertical
644.30	19.50	21.00	-1.50	Vertical
943.40	31.10	25.70	5.40	Vertical

For 8DPSK
Channel No.:39

Frequency(MHz)	Result(dBuV/m)	A _{Rpl} (dB)	P _{mea} (dBuV/m)	Polarity
40.00	12.80	16.20	-3.40	Vertical
77.74	7.70	7.90	-0.20	Vertical
451.06	15.30	17.20	-1.90	Vertical
478.72	16.30	18.10	-1.80	Vertical
534.32	17.50	19.10	-1.60	Vertical
940.04	30.60	25.70	4.90	Vertical

Carrier frequency (MHz): 2441


Channel No.:39



Frequency Range: 30MHz-1000MHz

Detector: QP mode


Modulation type: GFSK




Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode


Modulation type: GFSK



Frequency Range: 3GHz-18GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK




Frequency Range: 18GHz-25GHz
 Detector: Av mode and PK mode
 Modulation type: GFSK



Frequency Range: 30MHz-1000 MHz

Detector: QP mode


Modulation type: $\pi/4$ DQPSK




Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode


Modulation type: $\pi/4$ DQPSK



Frequency Range: 3GHz-18GHz
 Detector: Av mode and PK mode
 Modulation type: $\pi/4$ DQPSK




Frequency Range: 18GHz-25GHz
 Detector: Av mode and PK mode
 Modulation type: $\pi/4$ DQPSK



Frequency Range: 30MHz-1000 MHz

Detector: QP mode


Modulation type: 8DPSK




Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode

Modulation type: 8DPSK



Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK



Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: 8DPSK

2.2.5 Band Edge Compliance

2.2.5.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.1kPa

2.2.5.2 Test Description

The measurement is made according to ANSI C63.10-2009 Section 6.9.2 and Public notice DA 00-705.

2.2.5.2.1 RF Conducted Measurement:

The Equipment Under Test (EUT) was set up in a shielded room to perform the spurious emissions measurements.

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss.

For the first measurement the EUT is set to transmit on the lowest channel (2402 MHz). The lower band edge is 2390 MHz.


Analyzer settings:

- Detector: Peak
- RBW= 100 kHz
- VBW= 300 kHz

For the second measurement the EUT is set to transmit on the highest channel (2480MHz). The higher band edge is 2483.5 MHz.

Analyzer settings:

- Detector: Peak
- RBW= 100 kHz
- VBW= 300 kHz




2.2.5.2.2 RF Radiated Measurement

The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The radiated emissions measurements were made in a typical installation configuration.

During the test, the antenna height and EUT azimuth were varied in order to identify the maximum level of emission from the EUT. The height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing.



2.2.5.3 Test limit

FCC Part15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

2.2.5.4 Test result

RF Conducted Measurement

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: GFSK

Frequency MHz	Hopping Mode	Measured value dBm	Reference value dBm	Limit dBm	Delta dB
2390	Hopping OFF	-53.42	6.91	-13.09	60.33
2390	Hopping ON	-55.01	6.30	-13.70	61.31

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: GFSK

Frequency MHz	Hopping Mode	Measured value dBm	Reference value dBm	Limit dBm	Delta dB
2483.5	Hopping OFF	-50.27	7.97	-12.03	58.24
2483.5	Hopping ON	-54.07	7.35	-12.65	61.42

RF Radiated Measurement

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: GFSK

Frequency MHz	Hopping Mode	Correction Factor dB/m	Reading Level dBuV	Emission Level dBuV/m	Detector
2402	Hopping OFF	2.70	82.73	85.43	Peak
2402	Hopping ON	2.70	81.54	84.24	Peak

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: GFSK

Frequency MHz	Hopping Mode	Correction Factor dB/m	Reading Level dBuV	Emission Level dBuV/m	Detector
2480	Hopping OFF	2.50	84.37	86.87	Peak
2480	Hopping ON	2.50	82.74	85.24	Peak

Band Edge Test Data

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: GFSK

Frequency MHz	Hopping Mode	Fundamental (dBuV/m)	Delta dB	Band Edge Field Strength (dBuV/m)	Detector
2390	Hopping OFF	85.43	60.33	25.10	Peak
2390	Hopping ON	84.24	61.31	22.93	Peak

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: GFSK

Frequency MHz	Hopping Mode	Fundamental (dBuV/m)	Delta dB	Band Edge Field Strength (dBuV/m)	Detector
2483.5	Hopping OFF	86.87	58.24	28.63	Peak
2483.5	Hopping ON	85.24	61.42	23.82	Peak

Note:


The Band Edge Field Strength was calculated using the Fundamental and Conducted Band Edge

measurements per the Marker-Delta Method with the following formula:


Band Edge field Strength = F - Delta

F = Fundamental field Strength (Peak or Average)


Delta= Conducted Band Edge Delta (Peak or Average)




Carrier frequency (MHz): 2402
Channel No.:0, Hopping OFF
Modulation type: GFSK




Carrier frequency (MHz): 2402
Channel No.:0, Hopping ON
Modulation type: GFSK




Carrier frequency (MHz): 2441
Channel No.:39, Hopping OFF
Modulation type: GFSK



Carrier frequency (MHz): 2441
Channel No.:39, Hopping ON
Modulation type: GFSK



Carrier frequency (MHz): 2480
Channel No.:78, Hopping OFF
Modulation type: GFSK



Carrier frequency (MHz): 2480
Channel No.:78, Hopping ON
Modulation type: GFSK

RF Conducted Measurement

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Hopping Mode	Measured value dBm	Reference value dBm	Limit dBm	Delta dB
2390	Hopping OFF	-53.47	6.04	-13.96	59.51
2390	Hopping ON	-54.07	5.97	-14.03	60.04

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Hopping Mode	Measured value dBm	Reference value dBm	Limit dBm	Delta dB
2483.5	Hopping OFF	-51.62	7.08	-12.92	58.70
2483.5	Hopping ON	-54.53	6.88	-13.12	61.41

RF Radiated Measurement

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Hopping Mode	Correction Factor dB/m	Reading Level dBuV	Emission Level dBuV/m	Detector
2402	Hopping OFF	2.70	81.54	84.24	Peak
2402	Hopping ON	2.70	82.65	85.35	Peak

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Hopping Mode	Correction Factor dB/m	Reading Level dBuV	Emission Level dBuV/m	Detector
2480	Hopping OFF	2.50	82.93	85.43	Peak
2480	Hopping ON	2.50	83.86	86.36	Peak

Band Edge Test Data

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Hopping Mode	Fundamental (dBuV/m)	Delta dB	Band Edge Field Strength (dBuV/m)	Detector
2390	Hopping OFF	84.24	59.51	24.73	Peak
2390	Hopping ON	85.35	60.04	25.31	Peak

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: $\pi/4$ DQPSK

Frequency MHz	Hopping Mode	Fundamental (dBuV/m)	Delta dB	Band Edge Field Strength (dBuV/m)	Detector
2483.5	Hopping OFF	85.43	58.70	26.73	Peak
2483.5	Hopping ON	86.36	61.41	24.95	Peak

Note:


The Band Edge Field Strength was calculated using the Fundamental and Conducted Band Edge

measurements per the Marker-Delta Method with the following formula:


Band Edge field Strength = F - Delta

F = Fundamental field Strength (Peak or Average)


Delta= Conducted Band Edge Delta (Peak or Average)



Carrier frequency (MHz): 2402
Channel No.:0, Hopping OFF
Modulation type: $\pi/4$ DQPSK




Carrier frequency (MHz): 2402
Channel No.:0, Hopping ON
Modulation type: $\pi/4$ DQPSK




Date: 5.MAR.2014 10:54:13

Carrier frequency (MHz): 2441
Channel No.:39, Hopping OFF
Modulation type: $\pi/4$ DQPSK




Date: 5.MAR.2014 10:55:06

Carrier frequency (MHz): 2441
Channel No.:39, Hopping ON
Modulation type: $\pi/4$ DQPSK



Carrier frequency (MHz): 2480
Channel No.:78, Hopping OFF
Modulation type: $\pi/4$ DQPSK



Carrier frequency (MHz): 2480
Channel No.:78, Hopping ON
Modulation type: $\pi/4$ DQPSK

RF Conducted Measurement

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: 8DPSK

Frequency MHz	Hopping Mode	Measured value dBm	Reference value dBm	Limit dBm	Delta dB
2390	Hopping OFF	-55.17	6.01	-13.99	61.18
2390	Hopping ON	-53.75	5.74	-14.26	59.49

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: 8DPSK

Frequency MHz	Hopping Mode	Measured value dBm	Reference value dBm	Limit dBm	Delta dB
2483.5	Hopping OFF	-52.38	7.09	-12.91	59.47
2483.5	Hopping ON	-54.79	6.41	-13.59	61.20

RF Radiated Measurement

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: 8DPSK

Frequency MHz	Hopping Mode	Correction Factor dB/m	Reading Level dBuV	Emission Level dBuV/m	Detector
2402	Hopping OFF	2.70	82.62	85.32	Peak
2402	Hopping ON	2.70	81.67	84.37	Peak

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: 8DPSK

Frequency MHz	Hopping Mode	Correction Factor dB/m	Reading Level dBuV	Emission Level dBuV/m	Detector
2480	Hopping OFF	2.50	83.18	85.68	Peak
2480	Hopping ON	2.50	84.39	86.89	Peak

Band Edge Test Data

Carrier frequency (MHz): 2402

Channel No.:0

Modulation type: 8DPSK

Frequency MHz	Hopping Mode	Fundamental (dBuV/m)	Delta dB	Band Edge Field Strength (dBuV/m)	Detector
2390	Hopping OFF	85.32	61.18	24.14	Peak
2390	Hopping ON	84.37	59.49	24.88	Peak

Carrier frequency (MHz): 2480

Channel No.:78

Modulation type: 8DPSK

Frequency MHz	Hopping Mode	Fundamental (dBuV/m)	Delta dB	Band Edge Field Strength (dBuV/m)	Detector
2483.5	Hopping OFF	85.68	59.47	26.21	Peak
2483.5	Hopping ON	86.89	61.20	25.69	Peak

Note:


The Band Edge Field Strength was calculated using the Fundamental and Conducted Band Edge

measurements per the Marker-Delta Method with the following formula:


Band Edge field Strength = F - Delta

F = Fundamental field Strength (Peak or Average)


Delta= Conducted Band Edge Delta (Peak or Average)




Carrier frequency (MHz): 2402
Channel No.:0, Hopping OFF
Modulation type: 8DPSK




Carrier frequency (MHz): 2402
Channel No.:0, Hopping ON
Modulation type: 8DPSK




Carrier frequency (MHz): 2441
Channel No.:39, Hopping OFF
Modulation type: 8DPSK



Carrier frequency (MHz): 2441
Channel No.:39, Hopping ON
Modulation type: 8DPSK



Carrier frequency (MHz): 2480
Channel No.:78, Hopping OFF
Modulation type: 8DPSK



Carrier frequency (MHz): 2480
Channel No.:78, Hopping ON
Modulation type: 8DPSK

2.2.6 Dwell Time

2.2.6.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.1kPa

2.2.6.2 Test Description

The measurement is made according to Public notice DA 00-705 and ANSI C63.4-2009.

The Equipment Under Test (EUT) was set up in a shielded room to perform the dwell time measurements.

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss.


The time slot length is measured of three different packet types which are available in the Bluetooth technology. Those are DH1, DH3 and DH5 packets.

The dwell time is calculated by:

Dwell time = time slot length * hop rate * 31.6/ number of hopping channels

with:

- hop rate=1600/2 * 1/s for DH1 packets =800
- hop rate=1600/4 * 1/s for DH3 packets =400
- hop rate=1600/6 * 1/s for DH5 packets =266.67
- number of hopping channels=79
- 31.6 s=0.4 seconds multiplied by the number of hopping channels=0.4s * 79



2.2.6.3 Test limit

FCC Part15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6 seconds.

2.2.6.4 Test result


Modulation type: GFSK

Packet type	Time slot length ms	Dwell time	Dwell time ms
DH1	0.3695	time slot length *31.6 *1600/2 /79	116.992
DH3	1.6236	time slot length * 31.6 *1600/4 /79	259.776
DH5	2.8851	time slot length * 31.6 *1600/6 /79	307.744




Date: 5.MAR.2014 11:28:17

Carrier frequency (MHz): 2441
Packet type: DH1
Modulation type: GFSK




Carrier frequency (MHz): 2441
Packet type: DH3
Modulation type: GFSK



Carrier frequency (MHz): 2441
Packet type: DH5
Modulation type: GFSK

Modulation type: $\pi/4$ DQPSK

Packet type	Time slot length ms	Dwell time	Dwell time ms
DH1	0.3740	time slot length *31.6 *1600/2 /79	119.680
DH3	1.6236	time slot length * 31.6 *1600/4 /79	259.776
DH5	2.8706	time slot length * 31.6 *1600/6 /79	306.197




Date: 5.MAR.2014 11:11:21


Carrier frequency (MHz): 2441

Packet type: DH1


Modulation type: $\pi/4$ DQPSK




Carrier frequency (MHz): 2441
Packet type: DH3
Modulation type: $\pi/4$ DQPSK



Carrier frequency (MHz): 2441
Packet type: DH5
Modulation type: $\pi/4$ DQPSK



Carrier frequency (MHz): 2441
Packet type:DH3
Modulation type: 8DPSK



Carrier frequency (MHz): 2441
Packet type:DH5
Modulation type: 8DPSK

2.2.7 Channel Separation

2.2.7.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.1kPa

2.2.7.2 Test Description


The measurement is made according to Public notice DA 00-705 and ANSI C63.4-2009.

The Equipment Under Test (EUT) was set up in a shielded room to perform the channel separation measurements.

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss.

Analyzer settings:

- Detector: Peak-Max hold
- Span: 3 MHz
- Centre Frequency: 2441 MHz
- Resolution Bandwidth (RBW): 30 kHz
- Video Bandwidth (VBW): 1 MHz
- Sweep Time: Coupled




2.2.7.3 Test limit

FCC Part15.247(a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

2.2.7.4 Test result

Op-mode	Channel separation MHz
Hopping mode	1



Op-mode: Hopping mode

2.2.8 Number of Hopping Frequencies

2.2.8.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.1kPa

2.2.8.2 Test Description


The measurement is made according to Public notice DA 00-705 and ANSI C63.4-2009.

The Equipment Under Test (EUT) was set up in a shielded room to perform the number of hopping frequencies measurement.

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss.

Analyzer settings:

- Detector: Peak-Maxhold
- Start frequency: 2400 MHz
- Stop frequency: 2483.5 MHz
- Resolution Bandwidth (RBW): 30 kHz
- Video Bandwidth (VBW): 1 MHz
- Sweep Time: Coupled




2.2.8.3 Test limit

FCC Part15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

2.2.8.4 Test result

Op-mode	Result
Hopping mode	79



Op-mode: Hopping mode

2.3. Measurement Uncertainty

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

2.4. List of test equipment

No.	Name/ Model	Manufacturer	S/N	Cal Due date
1.	Spectrum Analyzer FSV	ROHDE&SCHWARZ	101065	2014.8
2.	Signal Generator MG3700A	Anritsu	6200677084	2014.8
3.	Bluetooth Test Set MT8852B	Anritsu	1142010	2015.2
4.	Cable 104EA	SUCOFLEX	9272/4EA	2014.8
5.	Cable 104EA	SUCOFLEX	9266/4EA	2014.8
6.	Power Splitter 11850C	Agilent	026057	2014.8
7.	12.65m×8.03m×7.50m Fully-Anechoic Chamber	FRANKONIA	----	----
8.	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	----
9.	Turn table Diameter:1m	HD	----	----
10.	Turn table Diameter:5m	HD	----	----
11.	Antenna master FAC(MA4.0)	MATURO	----	----
12.	Antenna master SAC(MA4.0)	MATURO	----	----
13.	9.080m×5.255m×3.525m Shielding room	FRANKONIA	----	----
14.	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100030	2014.8
15.	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100029	2014.8
16.	HL562 Ultra log antenna	R&S	100016	2014.8
17.	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2014.8
18.	ESI 40 EMI test receiver	R&S	100015	2014.8
19.	Radio tester	CMU 200	114667	2014.8
20.	ESCS30 EMI test receiver	R&S	100029	2014.8
21.	HL562 Receive antenna	R&S	100167	2014.8
22.	ESH3-Z5 LISN	R&S	100020	2014.8

Appendix

Appendix1 Test Setup