


FCC Test Report


APPLICANT : TCT Mobile Limited
EQUIPMENT : Tablet PC
BRAND NAME : ALCATEL
MODEL NAME : ONE TOUCH P321
MARKETING NAME : ALCATEL ONE TOUCH POP8
FCC ID : RAD467
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jan. 06, 2014 and testing was completed on Mar. 28, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Louis Wu / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Feature of Equipment Under Test..... 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 6

 1.6. Test Site 7

 1.7. Applied Standards 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system..... 11

 2.4. EUT Operation Test Setup 11

3. TEST RESULT 12

 3.1. Test of AC Conducted Emission Measurement 12

 3.2. Test of Radiated Emission Measurement 18

4. LIST OF MEASURING EQUIPMENT 23

5. UNCERTAINTY OF EVALUATION 24

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC410304-01	Rev. 01	Initial issue of report	May 20, 2014



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 6.82 dB at 0.150 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 2.74 dB at 240.060 MHz for Quasi-Peak

1. General Description

1.1. Applicant

TCT Mobile Limited

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.2. Manufacturer

TCT Mobile Limited

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.3. Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	ALCATEL
Model Name	ONE TOUCH P321
Marketing Name	ALCATEL ONE TOUCH POP8
FCC ID	RAD467
EUT supports Radios application	WLAN2.4GHz 802.11bgn HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	V5.0
SW Version	BAQ
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz
Antenna Type	WLAN : Monopole Antenna Bluetooth : Monopole Antenna
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth 4.0 - LE : GFSK Bluetooth 3.0 EDR : GFSK, $\pi/4$ -DQPSK, 8-DPSK GPS : BPSK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	FCC Registration No.
	CO01-KS	149928

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH01-SZ	831040

1.7. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2003

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	Note 1
2.	Data application transferred mode (EUT connected with notebook)	☒	☒	☒

Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Note 1: Testing for this mode is not required or not the worst case.


Remark: For signal above 1GHz, the worst case was test item 2.

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: USB Cable (Charging from Adapter) + Bluetooth Idle + WLAN Idle + Battery 1 + Camera + Earphone <Fig.1> Mode 2: USB Cable (Charging from Adapter) + Bluetooth Idle + WLAN Idle + Battery 2 + MPEG4 + Earphone <Fig.1> Mode 3: USB Cable (Data Link with Notebook) + Bluetooth Idle + WLAN Idle + Battery 1 + GPS Rx + Earphone <Fig.2>
Radiated Emissions < 1GHz	1/2	Mode 1: USB Cable (Charging from Adapter) + Bluetooth Idle + WLAN Idle + Battery 1 + Camera + Earphone <Fig.1> Mode 2: USB Cable (Charging from Adapter) + Bluetooth Idle + WLAN Idle + Battery 2 + MPEG4 + Earphone <Fig.1> Mode 3: USB Cable (Data Link with Notebook) + Bluetooth Idle + WLAN Idle + Battery 1 + GPS Rx + Earphone <Fig.2>
Radiated Emissions ≥ 1GHz	2	Mode 1: USB Cable (Data Link with Notebook) + Bluetooth Idle + WLAN Idle + Battery 1 + GPS Rx + Earphone <Fig.2>
Remark: <ol style="list-style-type: none"> The worst case of AC is mode 1; and the USB Link Mode of AC is mode 3, the test data of these modes were reported. The worst case of RE < 1G is mode 3; only the test data of this mode was reported. Link with Notebook means data application transferred mode between EUT and Notebook. 		

2.2. Connection Diagram of Test System



<Fig. 1>



<Fig. 2>

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMW 500	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
4.	WLAN AP	D-link	DIR-815	KA2IR815A1	N/A	Unshielded, 1.8m
5.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A
6.	Bluetooth Earphone	Nokia	BH-106	661AB-BH106	Shielded, 0.5 m	N/A
7.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 0.9 m DC O/P: Shielded, 1.8 m
8.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
9.	MicroSD Card	SanDisk	8G class 4	FCC DoC	N/A	N/A
10.	iPod nano 8GB	Apple	MC690ZP/A	FCC DoC	Shielded, 1.2 m	N/A
11.	iPod Earphone	Apple	MC690ZP/A	FCC DoC	Shielded, 1.6 m	N/A
12.	iPod	Apple	A1199	FCC DoC	Shielded, 1.2 m	N/A
13.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2 m	N/A

2.4. EUT Operation Test Setup

The EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Execute the program, "Winthrax" under WIN7 installed in notebook for files transfer with EUT via USB cable.
2. Execute "GPS Test" or turn on GPS function to make the EUT receive continuous signals from GPS station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Eligah Wang	Relative Humidity :	35~37%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	USB Cable (Charging from Adapter) + Bluetooth Idle + WLAN Idle + Battery 1 + Camera + Earphone		




Site : C001-KS
 Condition: FCC CLASS-B LISN-L20130306 LINE
 Project : (FC) 410304-01
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	50.12	-15.75	65.87	37.51	1.91	10.70	QP
2	0.15	47.82	-8.05	55.87	35.21	1.91	10.70	Average
3	0.20	41.08	-22.54	63.62	29.50	1.00	10.58	QP
4	0.20	37.98	-15.64	53.62	26.40	1.00	10.58	Average
5	0.28	35.83	-15.02	50.85	24.61	0.78	10.44	Average
6	0.28	40.73	-20.12	60.85	29.51	0.78	10.44	QP
7	0.34	37.72	-11.59	49.31	26.89	0.49	10.34	Average
8	0.34	39.22	-20.09	59.31	28.39	0.49	10.34	QP
9	0.76	31.38	-24.62	56.00	21.00	0.18	10.20	QP
10	0.76	20.88	-25.12	46.00	10.50	0.18	10.20	Average
11	1.49	13.79	-32.21	46.00	3.50	0.10	10.19	Average
12	1.49	21.79	-34.21	56.00	11.50	0.10	10.19	QP



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Eligah Wang	Relative Humidity :	35~37%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	USB Cable (Charging from Adapter) + Bluetooth Idle + WLAN Idle + Battery 1 + Camera + Earphone		




Site : C001-KS
 Condition: FCC CLASS-B LISN-N20130306 NEUTRAL
 Project : (FC) 410304-01
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	49.09	-6.82	55.91	36.50	1.88	10.71	Average
2	0.15	52.59	-13.32	65.91	40.00	1.88	10.71	QP
3	0.28	38.16	-12.74	50.90	26.90	0.82	10.44	Average
4	0.28	41.66	-19.24	60.90	30.40	0.82	10.44	QP
5	0.34	39.99	-19.32	59.31	29.10	0.55	10.34	QP
6	0.34	38.79	-10.52	49.31	27.90	0.55	10.34	Average
7	0.56	30.52	-25.48	56.00	20.00	0.27	10.25	QP
8	0.56	27.42	-18.58	46.00	16.90	0.27	10.25	Average
9	0.78	25.87	-30.13	56.00	15.49	0.18	10.20	QP
10	0.78	19.87	-26.13	46.00	9.49	0.18	10.20	Average
11	1.59	17.19	-28.81	46.00	6.90	0.10	10.19	Average
12	1.59	28.79	-27.21	56.00	18.50	0.10	10.19	QP



Test Mode :	Mode 3	Temperature :	20~22°C
Test Engineer :	Eligah Wang	Relative Humidity :	35~37%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	USB Cable (Data Link with Notebook) + Bluetooth Idle + WLAN Idle + Battery 1 + GPS Rx + Earphone		




Site : C001-KS
 Condition: FCC CLASS-B LISN-L20130306 LINE
 Project : (FC) 410304-01
 mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.16	37.03	-18.62	55.65	24.49	1.85	10.69	Average
2	0.16	45.03	-20.62	65.65	32.49	1.85	10.69	QP
3	0.19	30.18	-23.75	53.93	18.50	1.09	10.59	Average
4	0.19	37.48	-26.45	63.93	25.80	1.09	10.59	QP
5	0.47	34.00	-12.58	46.58	23.50	0.23	10.27	Average
6	0.47	39.40	-17.18	56.58	28.90	0.23	10.27	QP
7	0.49	36.37	-9.73	46.10	25.91	0.20	10.26	Average
8	0.49	42.67	-13.43	56.10	32.21	0.20	10.26	QP
9	0.67	37.92	-18.08	56.00	27.50	0.20	10.22	QP
10	0.67	26.12	-19.88	46.00	15.70	0.20	10.22	Average
11	0.69	37.31	-18.69	56.00	26.90	0.20	10.21	QP
12	0.69	27.31	-18.69	46.00	16.90	0.20	10.21	Average



Test Mode :	Mode 3	Temperature :	20~22°C
Test Engineer :	Eligah Wang	Relative Humidity :	35~37%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	USB Cable (Data Link with Notebook) + Bluetooth Idle + WLAN Idle + Battery 1 + GPS Rx + Earphone		



Site : C001-KS
 Condition: FCC CLASS-B LISN-N20130306 NEUTRAL
 Project : (FC) 410304-01
 mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.16	44.07	-21.53	65.60	31.60	1.79	10.68	QP
2	0.16	40.07	-15.53	55.60	27.60	1.79	10.68	Average
3	0.28	38.86	-22.04	60.90	27.60	0.82	10.44	QP
4	0.28	34.86	-16.04	50.90	23.60	0.82	10.44	Average
5	0.46	32.90	-13.77	46.67	22.30	0.33	10.27	Average
6	0.46	38.00	-18.67	56.67	27.40	0.33	10.27	QP
7	0.49	42.47	-13.72	56.19	31.89	0.31	10.27	QP
8	0.49	36.37	-9.82	46.19	25.79	0.31	10.27	Average
9	0.67	37.23	-18.77	56.00	26.80	0.21	10.22	QP
10	0.67	26.23	-19.77	46.00	15.80	0.21	10.22	Average
11	0.71	35.01	-20.99	56.00	24.60	0.20	10.21	QP
12	0.71	24.21	-21.79	46.00	13.80	0.20	10.21	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	23~24°C
Test Engineer :	Leo Liao	Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	USB Cable (Data Link with Notebook) + Bluetooth Idle + WLAN Idle + Battery 1 + GPS Rx + Earphone		




Site : 03CH01-SZ
 Condition : FCC CLASS-B 3m LF_ANT_131026 HORIZONTAL
 Project : (FC) 410304-01
 Mode : Mode 1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	132.87	22.33	-21.17	43.50	39.10	11.77	1.40	29.94	---	---	Peak
2 P	187.68	35.07	-8.43	43.50	54.85	8.52	1.64	29.94	---	---	Peak
3 Q	240.06	43.26	-2.74	46.00	60.02	11.35	1.82	29.93	100	156	QP
4	479.90	33.44	-12.56	46.00	43.48	17.40	2.48	29.92	---	---	Peak
5	720.00	28.58	-17.42	46.00	36.22	19.30	2.99	29.93	---	---	Peak
6	960.10	30.08	-23.92	54.00	35.29	21.30	3.43	29.94	---	---	Peak
7	2498.00	41.06	-32.94	74.00	59.61	32.50	5.74	56.79	---	---	Peak
8	4614.00	38.61	-35.39	74.00	54.71	33.37	8.15	57.62	---	---	Peak
9	6444.00	38.91	-35.09	74.00	51.74	34.00	9.75	56.58	---	---	Peak
10	8746.00	38.84	-35.16	74.00	47.08	36.10	11.08	55.42	---	---	Peak
11	9928.00	41.07	-32.93	74.00	48.50	36.90	12.54	56.87	---	---	Peak
12	12578.00	41.97	-32.03	74.00	45.82	38.05	14.23	56.13	132	254	Peak



Test Mode :	Mode 3	Temperature :	23~24°C
Test Engineer :	Leo Liao	Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Function Type :	USB Cable (Data Link with Notebook) + Bluetooth Idle + WLAN Idle + Battery 1 + GPS Rx + Earphone		



Site : 03CH01-SZ
 Condition : FCC CLASS-B 3m LF_ANT_131026 VERTICAL
 Project : (FC) 410304-01
 Mode : Mode 1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	132.87	23.43	-20.07	43.50	40.20	11.77	1.40	29.94	---	---	Peak
2	187.68	35.22	-8.28	43.50	55.00	8.52	1.64	29.94	---	---	Peak
3 P	240.06	42.14	-3.86	46.00	58.90	11.35	1.82	29.93	152	321	Peak
4	479.90	36.68	-9.32	46.00	46.72	17.40	2.48	29.92	---	---	Peak
5	781.60	26.60	-19.40	46.00	33.58	19.82	3.13	29.93	---	---	Peak
6	960.10	36.01	-17.99	54.00	41.22	21.30	3.43	29.94	---	---	Peak
7	2238.00	41.93	-32.07	74.00	61.99	31.21	5.44	56.71	---	---	Peak
8	3194.00	44.47	-29.53	74.00	62.15	33.04	6.57	57.29	152	321	Peak
9	5384.00	37.89	-36.11	74.00	51.43	34.05	8.93	56.52	---	---	Peak
10	7362.00	42.31	-31.69	74.00	55.48	33.92	10.01	57.10	---	---	Peak
11	10020.00	40.87	-33.13	74.00	48.20	36.98	12.68	56.99	---	---	Peak
12	12138.00	41.74	-32.26	74.00	46.01	38.12	13.69	56.08	---	---	Peak

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	May 23, 2013	Mar. 28, 2014	May 22, 2014	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Dec. 10, 2013	Mar. 28, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Dec. 10, 2013	Mar. 28, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	May 25, 2013	Mar. 28, 2014	May 24, 2014	Conduction (CO01-KS)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	Apr. 04, 2013	Mar. 14, 2014	Apr. 03, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 26, 2013	Mar. 14, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30MHz~2GHz	Dec. 23, 2013	Mar. 14, 2014	Dec. 22, 2014	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz	Mar. 29, 2013	Mar. 14, 2014	Mar. 28, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 29, 2013	Mar. 14, 2014	Mar. 28, 2014	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0~360 degree	NCR	Mar. 14, 2014	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m~4 m	NCR	Mar. 14, 2014	NCR	Radiation (03CH01-SZ)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.90
---	------