
TEST REPORT

Report No.: SRTC2014-H024-E0009

Product Name: GSM/GPRS/EDGE/UMTS

Digital Mobile Phone with Bluetooth and WiFi

Marketing Name: ONE TOUCH 7040F

Product Model: Yaris-5

Applicant: TCT Mobile Limited

Manufacturer: TCT Mobile Limited

Specification: FCC Part 24E, Part 22H, Part 2

(April 25, 2013 edition)

FCC ID: RAD474

The State Radio_monitoring_center Testing Center (SRTC)

No.80 Beilishi Road Xicheng District Beijing, China

Tel: 86-10-68009202 Fax: 86-10-68009205

CONTENTS

1. General information	2
1.1 Notes of the test report	2
1.2 Information about the testing laboratory	2
1.3 Applicant's details	2
1.4 Manufacturer's details	2
1.5 Application details	3
1.6 Reference specification	3
1.7 Information of EUT	3
1.7.1 General information	3
1.7.2 EUT details	4
1.7.3 Auxiliary equipment details	4
2. Test information	6
2.1 Summary of the test results	6
2.2 Test result	7
2.2.1 GSM850	7
2.2.1.1 RF Power Output-FCC Part2.1046	7
2.2.1.2 Effective Radiated Power-FCC Part22.913(a)	8
2.2.1.3 Occupied Bandwidth-FCC Part2.1049	11
2.2.1.4 Emission Bandwidth-FCC Part22.917(b)	15
2.2.1.5 Spurious Emissions at antenna terminal-FCC Part2.1051/22.917(a)	16
2.2.1.6 Band Edges Compliance-FCC Part2.1051/22.917(a)	20
2.2.1.7 Frequency Stability-FCC Part2.1055/22.355	23
2.2.1.8 Radiated Spurious Emissions-FCC Part2.1053/22.917(a)	25
2.2.2 PCS1900	30
2.2.2.1 RF Power Output-FCC Part2.1046	30
2.2.2.2 Effective Isotropic Radiated Power-FCC Part24.232(c)	31
2.2.2.3 Occupied Bandwidth-FCC Part2.1049	34
2.2.2.4 Emission Bandwidth-FCC Part24.238(b)	38
2.2.2.5 Spurious Emissions at antenna terminal-FCC Part2.1051/24.238(a)	39
2.2.2.6 Band Edges Compliance-FCC Part2.1051/24.238(a)	43
2.2.2.7 Frequency Stability-FCC Part2.1055/24.235	46
2.2.2.8 Radiated Spurious Emissions-FCC Part2.1053/24.238(a)	48
2.3. List of test equipments	53
Appendix	54

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Address: No.80 Beilishi Road, Xicheng District, Beijing China
City: Beijing
Country or Region: China
Contacted person: Wang Junfeng
Tel: +86 10 68009181 +86 10 68009202
Fax: +86 10 68009195 +86 10 68009205
Email: wangjf@srrc.org.cn / wangjunfeng@srtc.org.cn

1.3 Applicant's details

Company: TCT Mobile Limited
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang
High-Tech Park, Pudong Area
City: Shanghai
Country or Region: P.R.China
Grantee Code: RAD
Contacted person: Gong Zhizhou
Tel: +86-21-61460890
Fax: +86-21-61460602
Email: zhizhou.gong@tcl.com

1.4 Manufacturer's details

Company: TCT Mobile Limited
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang
High-Tech Park, Pudong Area
City: Shanghai
Country or Region: P.R.China
Contacted person: Gong Zhizhou
Tel: +86-21-61460890
Fax: +86-21-61460602
Email: zhizhou.gong@tcl.com

1.5 Application details

Date of reception of test sample: 9th September 2013

Date of test: 9th September 2013 to 17th February 2014

1.6 Reference specification

FCC Part 24E, Part22H, Part 2 (April 25, 2013 edition)

1.7 Information of EUT

1.7.1 General information

Name of EUT	GSM/GPRS/EDGE/UMTS Digital Mobile Phone with Bluetooth and WiFi
FCC ID	RAD474
Frequency Range	GSM850: Tx:824~849MHz Rx:869~894MHz PCS1900: Tx:1850~1910MHz Rx:1930~1990MHz
Rated Output Power	GSM850:33.0dBm PCS1900:30.0dBm
Modulation Type	GSM/GPRS:GMSK EDGE: GMSK(Uplink direction) 8PSK(Downlink direction)
Emission Designator	300KGXW
Duplex Mode	FDD
Duplex Spacing	GSM850:45MHz PCS1900:80MHz
Antenna Type	Fixed Internal
Power Supply	Battery or Charger
Rated Power Supply Voltage	3.8V
Extreme Temperature	Lowest: -30°C Highest: +50°C
Extreme Voltage	Minimum: 3.5V Maximum: 4.35V
HW Version	PIO07
SW Version	AGJ

1.7.2 EUT details

Product Name	Marketing Name	Product Model	IMEI
GSM/GPRS/EDGE/UMTS Digital Mobile Phone with Bluetooth and WiFi	ONE TOUCH 7040F	Yaris-5	014039005202801

1.7.3 Auxiliary equipment details

Equipment	Charger
Manufacturer	Ten Pao Industrial Co., Ltd.
Model Number	S005UU0500100
Input Voltage	100V-240V a.c.
Output Voltage	5.0V d.c.
Frequency	50/60Hz

Equipment	Charger
Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD.
Model Number	TUUS050100-A00
Input Voltage	100V-240V a.c.
Output Voltage	5.0V d.c.
Frequency	50/60Hz

Equipment	Battery
Manufacturer	BYD COMPANY LIMITED
Model Number	TLi020F1
Capacity	2000mAh
Rated Voltage	4.35V d.c.

Equipment	Battery
Manufacturer	BYD COMPANY LIMITED
Model Number	TLi019B1
Capacity	1900mAh
Rated Voltage	4.35V d.c.

Equipment	Battery
Manufacturer	SCUD (FUJIAN) Electronics Co., Ltd.
Model Number	TLi019B2
Capacity	1900mAh
Rated Voltage	4.35V d.c.

Equipment	Data Cable
Manufacturer	Shenzhen Juwei Electronics Co., Ltd.
Model Number	CDA3122002C1

Equipment	Data Cable
Manufacturer	Huizhou Shenghua Industry Co., Ltd.
Model Number	CDA3122002C2


Note: As the information described above, there are two different models of charger manufactured by two different companies, three different models of battery manufactured by two different companies and two different models of data cable manufactured by two different companies.

The relevant tests have been performed in order to verify in which combination case (EUT exercised by only one model of charger, one model of battery and one model of data cable) the EUT would have the worst features. So all the tests shown in this test report are performed when the EUT exercised by the charger S005UU0500100, the battery TLi019B2 and the data cable CDA3122002C1.

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	RF Power Output	2.1046	Pass
2	Effective Radiated Power and Effective Isotropic Radiated Power	22.913(a)/24.232(c)	Pass
3	Occupied Bandwidth	2.1049	Pass
4	Emission Bandwidth	22.917(b)/24.238(b)	Pass
5	Spurious Emissions at antenna terminals	2.1051/22.917(a)/24.238(a)	Pass
6	Band Edges Compliance	2.1051/22.917(a)/24.238(a)	Pass
7	Frequency Stability	2.1055/22.355/24.235	Pass
8	Radiated Spurious Emissions	2.1053/22.917(a)/24.238(a)	Pass

This Test Report Is Issued by: Mr. Song Qizhu Director of the test lab 	Checked by: Mr. Wang Junfeng Deputy director of the test lab 
Tested by: Mr. Li Bin Test engineer 	Issued date: 2014.02.28

2.2 Test result


2.2.1 GSM850

2.2.1.1 RF Power Output-FCC Part2.1046

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits	$\leq 33\text{dBm}$
--------	---------------------

Test result:

GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
824.2	128	32.51
836.4	189	32.54
848.8	251	32.67

EDGE (GMSK, 1Slot) MODE:


Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
824.2	128	32.52
836.4	189	32.54
848.8	251	32.66

2.2.1.2 Effective Radiated Power-FCC Part22.913(a)


Ambient condition:

Temperature	Relative humidity	Pressure
20.5°C	38.3%	100.1kPa

Test setup:



Step 1



Step 2

Test procedure:

The measurements procedures in TIA-603C-2004 are used.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meters high non-conductive table at a 3 meters test distance from the

test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used and RBW is set to 3MHz. Then the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum power value on spectrum analyzer or receiver. And the maximum value of the receiver should be recorded as (Pr).

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator. To repeat the same procedure as step1 and the level of signal generator will be adjusted till the same power value on the spectrum analyzer or receiver. The ERP/EIRP of the EUT can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A "reference path loss" should be calculated after test. The attenuation of "reference path loss" is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (G_a).

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{\text{mea}} + P_{\text{ca}} + G_{\text{a}}$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15 \text{ (dB)}$.

The measurement will be done at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits:

Operation Mode	Power Step	E.R.P. (dBm)
GSM	5	≤38.45
GPRS	3	≤38.45
EDGE	6	≤38.45

Test result:

GSM/GPRS MODE:

Frequency (MHz)	Power step	Peak ERP (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Correction (dB)	Pmea (dBm)	Polarization
824.2	5	32.90	-3.8	8.6	2.15	30.25	Vertical
836.4	5	33.00	-3.8	8.6	2.15	30.35	Vertical
848.8	5	32.70	-3.8	8.6	2.15	30.05	Vertical

EDGE (GMSK, 1Slot) MODE:

Frequency (MHz)	Power step	Peak ERP (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Correction (dB)	Pmea (dBm)	Polarization
824.2	5	33.40	-3.8	8.6	2.15	30.75	Vertical
836.4	5	32.80	-3.8	8.6	2.15	30.15	Vertical
848.8	5	32.60	-3.8	8.6	2.15	29.95	Vertical

Frequency: 824.2MHz


Peak ERP(dBm) = Pmea(30.75dBm)+Pca(-3.8dB)+Ga(8.6dB)-2.15dB = 33.40dBm

2.2.1.3 Occupied Bandwidth-FCC Part2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
824.2	128	247.77
836.4	189	247.77
848.8	251	247.37


EDGE (GMSK) MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
824.2	128	247.64
836.4	189	246.55
848.8	251	247.46


GSM/GPRS MODE:



Channel 128




Channel 189




Channel 251


EDGE (GMSK) MODE:



Channel 128



Channel 189




Channel 251

2.2.1.4 Emission Bandwidth-FCC Part22.917(b)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The emission bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of -26dB transmitter power can be read on spectrum analyzer.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits: No specific emission bandwidth requirements in part 22.917(b)

Test result:

GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
824.2	128	313.9
836.4	189	311.7
848.8	251	309.9

EDGE (GMSK) MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
824.2	128	308.5
836.4	189	311.2
848.8	251	310.3

2.2.1.5 Spurious Emissions at antenna terminal-FCC Part2.1051/22.917(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 9GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.


The measurement will be conducted at one channel No189 (middle channel of GSM850 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------


Test result:

Refer to the following figures.

GSM/GPRS MODE:




Channel 189, 30MHz~824MHz




Channel 189, 824MHz~849MHz

Note: The signal beyond the limit is the base station simulator carrier.




Channel 189, 849MHz~9GHz

EDGE (GMSK) MODE:




Channel 189, 30MHz~824MHz



Channel 189, 824MHz~849MHz

Note: The signal beyond the limit is the base station simulator carrier.




Channel 189, 849MHz~9GHz

2.2.1.6 Band Edges Compliance-FCC Part2.1051/22.917(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to at least 1% of the emission bandwidth on spectrum analyzer.


The measurement will be conducted at two channels No128 and No251 (Bottom and top channels of GSM850 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------


Test result:

Refer to the following figures.

GSM/GPRS MODE:




Channel 128




Channel 251

EDGE (GMSK) MODE:



Channel 128




Channel 251

2.2.1.7 Frequency Stability-FCC Part2.1055/22.355

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test setup:



Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50°C in 10°C step size, and also the DC power supply voltage to the EUT is varied from 3.5 to 4.35V. The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 22.355.

Test result:

GSM/GPRS MODE:

Temperature(°C)	Test Result (ppm)@3.8V		
	Channel 128	Channel 189	Channel 251
-30	0.016	0.015	0.015
-20	0.014	0.013	0.015
-10	0.011	0.012	0.014
0	0.010	0.011	0.012
+10	0.010	0.012	0.010
+20	0.010	0.012	0.010
+30	0.009	0.014	0.010
+40	0.013	0.016	0.011
+50	0.014	0.017	0.012

Voltage (V)	Test Result (ppm)@20°C		
	Channel 128	Channel 189	Channel 251
3.5	0.010	0.007	0.012
4.35	0.010	0.006	0.012

EDGE (GMSK) MODE:

Temperature(°C)	Test Result (ppm)@3.8V		
	Channel 128	Channel 189	Channel 251
-30	0.013	0.012	0.016
-20	0.011	0.010	0.015
-10	0.014	0.012	0.015
0	0.008	0.013	0.014
+10	0.009	0.010	0.013
+20	0.007	0.011	0.013
+30	0.008	0.012	0.015
+40	0.009	0.011	0.019
+50	0.008	0.013	0.016


Voltage (V)	Test Result (ppm)@20°C		
	Channel 128	Channel 189	Channel 251
3.5	0.010	0.011	0.013
4.35	0.009	0.012	0.015

2.2.1.8 Radiated Spurious Emissions-FCC Part2.1053/22.917(a)


Ambient condition

Temperature	Relative humidity	Pressure
20.5°C	38.3%	100.1kPa

Test Setup:



Step 1



Step 2

Test procedure:

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30MHz to the 10th harmonic of the highest frequency generated within the equipment.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed

on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A “reference path loss” should be calculated after test. The attenuation of “reference path loss” is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (G_a).

Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power(EIRP)} = P_{mea} + P_{ca} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15 \text{ (dB)}$.

Assumed the power of signal source record is -20dBm. A cable loss of -30dB, and an antenna gain of 11dB are added.

$$P = P_{\text{mea}} + P_{\text{ca}} + G_a = (-20\text{dBm}) + (-30\text{dB}) + (11\text{dB}) = -39\text{dBm}$$

The measurement will be done at carrier frequencies that pertain to bottom (Channel 128), middle (Channel 189) and top (Channel 251) channels of the GSM 850 band.

Test result

GSM/GPRS MODE Channel 128:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
1606.34	-41.2	-4.6	8.3	-44.9	-13	Vertical
2574.35	-41.3	-5.9	8.9	-44.3	-13	Vertical
2785.03	-42.7	-5.9	8.9	-45.7	-13	Horizontal
3303.23	-50.2	-7.5	10.2	-52.9	-13	Vertical
7034.23	-54.3	-9.4	12.0	-56.9	-13	Vertical
9947.31	-54.5	-11.4	13.8	-56.9	-13	Vertical

EDGE (GMSK) MODE Channel 128:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
1633.95	-41.5	-4.6	8.3	-45.2	-13	Vertical
2582.31	-42.4	-5.9	8.9	-45.4	-13	Vertical
2836.64	-43.1	-5.9	8.9	-46.1	-13	Vertical
3356.78	-52.5	-7.5	10.2	-55.2	-13	Vertical
7014.38	-54.5	-9.4	12.0	-57.1	-13	Horizontal
9957.95	-55.3	-11.4	13.8	-57.7	-13	Vertical

GSM/GPRS MODE Channel 189:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
1631.76	-41.5	-4.6	8.3	-45.2	-13	Vertical
2563.21	-42.6	-5.9	8.9	-45.6	-13	Vertical
2856.67	-42.1	-5.9	8.9	-45.1	-13	Vertical
3324.49	-52.3	-7.5	10.2	-55.0	-13	Vertical
6966.35	-54.2	-9.4	12.0	-56.7	-13	Vertical
9945.78	-55.2	-11.4	13.8	-57.6	-13	Vertical

EDGE (GMSK) MODE Channel 189:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
1652.57	-41.4	-4.6	8.3	-45.1	-13	Vertical
2534.78	-42.2	-5.9	8.9	-45.2	-13	Vertical
2752.78	-43.5	-5.9	8.9	-46.5	-13	Vertical
3366.56	-52.2	-7.5	10.2	-54.9	-13	Vertical
6953.32	-54.9	-9.4	12.0	-57.5	-13	Horizontal
9965.12	-55.1	-11.4	13.8	-57.5	-13	Vertical

GSM/GPRS MODE Channel 251:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
1652.57	-42.1	-4.6	8.3	-45.8	-13	Vertical
2551.21	-42.5	-5.9	8.9	-45.5	-13	Horizontal
2847.48	-42.5	-5.9	8.9	-45.5	-13	Vertical
3353.32	-54.2	-7.5	10.2	-56.9	-13	Vertical
7037.75	-54.1	-9.4	12.0	-56.7	-13	Vertical
9973.31	-54.9	-11.4	13.8	-57.3	-13	Vertical

EDGE (GMSK) MODE Channel 251:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
1634.62	-41.7	-4.6	8.3	-45.4	-13	Vertical
2544.31	-42.1	-5.9	8.9	-45.1	-13	Vertical
2788.42	-42.4	-5.9	8.9	-45.4	-13	Vertical
3357.75	-53.4	-7.5	10.2	-56.1	-13	Vertical I
6994.83	-54.3	-9.4	12.0	-56.9	-13	Horizontal
9937.74	-55.5	-11.4	13.8	-57.9	-13	Vertical


2.2.2 PCS1900

2.2.2.1 RF Power Output-FCC Part2.1046

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits	$\leq 30\text{dBm}$
--------	---------------------

Test result:

GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
1850.2	512	29.57
1880.0	661	29.66
1909.8	810	29.62

EDGE (GMSK, 1Slot) MODE:


Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
1850.2	512	29.63
1880.0	661	29.67
1909.8	810	29.62

2.2.2.2 Effective Isotropic Radiated Power-FCC Part24.232(c)


Ambient condition:

Temperature	Relative humidity	Pressure
20.5°C	38.3%	100.1kPa

Test setup:



Step 1



Step 2

Test procedure:

The measurements procedures in TIA-603C-2004 are used.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed

on a 2.4 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used and RBW is set to 3MHz. Then the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum power value on spectrum analyzer or receiver. And the maximum value of the receiver should be recorded as (Pr).

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator. To repeat the same procedure as step1 and the level of signal generator will be adjusted till the same power value on the spectrum analyzer or receiver. The ERP/EIRP of the EUT can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A “reference path loss” should be calculated after test. The attenuation of “reference path loss” is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (Ga).

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{\text{mea}} + P_{\text{ca}} + G_a$$

The measurement will be done at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits:

Operation Mode	Power Step	E.I.R.P. (dBm)
GSM	0	≤33
GPRS	3	≤33
EDGE	5	≤33

Test result:

GSM/GPRS MODE:

Frequency (MHz)	Power step	Peak EIRP(dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Polarization
1850.2	0	30.4	-4.8	8.6	26.6	Vertical
1880.0	0	30.2	-4.8	8.6	26.4	Vertical
1909.8	0	30.3	-4.8	8.6	26.5	Vertical

EDGE (GMSK, 1Slot) MODE:

Frequency (MHz)	Power step	Peak EIRP(dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Polarization
1850.2	5	29.7	-4.8	8.6	25.9	Vertical
1880.0	5	29.9	-4.8	8.6	26.1	Vertical
1909.8	5	29.4	-4.8	8.6	25.6	Vertical

Frequency: 1850.2MHz


Peak EIRP(dBm) = Pmea(26.6Bm)+Pca(-4.8dB)+Ga(8.6dB) = 30.4dBm

2.2.2.3 Occupied Bandwidth-FCC Part2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
1850.2	512	247.70
1880.0	661	247.89
1909.8	810	248.03


EDGE (GMSK) MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
1850.2	512	247.25
1880.0	661	247.26
1909.8	810	248.03


GSM/GPRS MODE:



Channel 512




Channel 661




Channel 810


EDGE (GMSK) MODE:



Channel 512



Channel 661




Channel 810

2.2.2.4 Emission Bandwidth-FCC Part24.238(b)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The emission bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of -26dB transmitter power can be read on spectrum analyzer.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits: No specific emission bandwidth requirements in part 24.238(b)

Test result:

GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
1850.2	512	305.2
1880.0	661	309.9
1909.8	810	314.9

EDGE (GMSK) MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
1850.2	512	314.4
1880.0	661	318.8
1909.8	810	314.9

2.2.2.5 Spurious Emissions at antenna terminal-FCC Part2.1051/24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.


The measurement will be conducted at one channel No661 (middle channel of PCS1900 band)

Limits	≤-13dBm
--------	---------


Test result:

Refer to the following figures.

GSM/GPRS MODE:




Channel 661, 30MHz~1850MHz




Channel 661, 1850MHz~1910MHz

Note: The signal beyond the limit is the base station simulator carrier.




Channel 661, 1910MHz~20GHz

EDGE (GMSK) MODE:



Channel 661, 30MHz~1850MHz



Channel 661, 1850MHz~1910MHz

Note: The signal beyond the limit is the base station simulator carrier.




Channel 661, 1910MHz~20GHz

2.2.2.6 Band Edges Compliance-FCC Part2.1051/24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to at least 1% of the emission bandwidth on spectrum analyzer.


The measurement will be conducted at two channels No512 and No810 (Bottom and top channels of PCS1900 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------


Test result:

Refer to the following figures.

GSM/GPRS MODE:




Channel 512




Channel 810

EDGE (GMSK) MODE:



Channel 512




Channel 810

2.2.2.7 Frequency Stability-FCC Part2.1055/24.235

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test setup:



Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50°C in 10°C step size, and also the DC power supply voltage to the EUT is varied from 3.5 to 4.35V. The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 24.235.

Test result:

GSM/GPRS MODE:

Temperature(°C)	Test Result (ppm)@3.8V		
	Channel 512	Channel 661	Channel 810
-30	0.017	0.022	0.020
-20	0.016	0.020	0.016
-10	0.014	0.017	0.015
0	0.013	0.015	0.013
+10	0.011	0.013	0.011
+20	0.011	0.012	0.010
+30	0.011	0.015	0.012
+40	0.010	0.014	0.013
+50	0.011	0.016	0.019

Voltage (V)	Test Result (ppm)@20°C		
	Channel 512	Channel 661	Channel 810
3.5	0.014	0.010	0.014
4.35	0.012	0.008	0.015

EDGE (GMSK) MODE:

Temperature(°C)	Test Result (ppm)@3.8V		
	Channel 512	Channel 661	Channel 810
-30	0.024	0.014	0.017
-20	0.020	0.013	0.015
-10	0.019	0.012	0.019
0	0.024	0.015	0.013
+10	0.022	0.019	0.015
+20	0.019	0.015	0.016
+30	0.018	0.014	0.013
+40	0.019	0.017	0.015
+50	0.017	0.013	0.014


Voltage (V)	Test Result (ppm)@20°C		
	Channel 512	Channel 661	Channel 810
3.5	0.020	0.015	0.013
4.35	0.019	0.011	0.015

2.2.2.8 Radiated Spurious Emissions-FCC Part2.1053/24.238(a)


Ambient condition

Temperature	Relative humidity	Pressure
20.5°C	38.3%	100.1kPa

Test Setup:



Step 1



Step 2

Test procedure:

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30MHz to the 10th harmonic of the highest frequency generated within the equipment.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed

on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A “reference path loss” should be calculated after test. The attenuation of “reference path loss” is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (G_a).

Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power(EIRP)} = P_{mea} + P_{ca} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15 \text{ (dB)}$.

Assumed the power of signal source record is -20dBm. A cable loss of -30dB and an antenna gain of 11dB are added.

$$P = P_{\text{mea}} + P_{\text{ca}} + G_a = (-20\text{dBm}) + (-30\text{dB}) + (11\text{dB}) = -39\text{dBm}$$

The measurement will be done at carrier frequencies that pertain to bottom (Channel 512), middle (Channel 661) and top (Channel 810) channels of PCS 1900 band.

Test result:

GSM/GPRS MODE Channel 512:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
2843.54	-53.5	-5.8	8.9	-56.6	-13	Vertical
2857.45	-53.3	-5.8	8.9	-56.4	-13	Vertical
3655.35	-54.3	-7.9	10.4	-56.8	-13	Horizontal
6984.16	-54.1	-9.4	12.0	-56.8	-13	Vertical
7567.13	-55.1	-10.8	12.0	-56.3	-13	Vertical
17365.22	-55.3	-13.9	12.3	-53.7	-13	Vertical

EDGE (GMSK) MODE Channel 512:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
2876.32	-52.9	-5.8	8.9	-56.0	-13	Vertical
2891.35	-53.4	-5.8	8.9	-56.5	-13	Vertical
3680.45	-54.7	-7.9	10.4	-57.2	-13	Vertical
6987.57	-54.7	-9.4	12.0	-57.3	-13	Vertical
7543.64	-55.3	-10.8	12.0	-56.5	-13	Vertical
17334.21	-56.1	-13.9	12.3	-54.5	-13	Vertical

GSM/GPRS MODE Channel 661:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
2837.45	-52.4	-5.8	8.9	-55.5	-13	Vertical
2902.32	-53.3	-5.8	8.9	-56.4	-13	Vertical
3728.75	-53.7	-7.9	10.4	-56.2	-13	Vertical
6986.78	-53.9	-9.4	12.0	-56.5	-13	Vertical
7562.17	-54.2	-10.8	12.0	-55.4	-13	Vertical
17355.39	-55.1	-13.9	12.3	-53.5	-13	Horizontal

EDGE (GMSK) MODE Channel 661:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
2817.96	-53.4	-5.8	8.9	-56.5	-13	Vertical
2853.24	-53.1	-5.8	8.9	-56.2	-13	Vertical
3777.42	-53.7	-7.9	10.4	-56.4	-13	Vertical
6963.35	-54.4	-9.4	12.0	-57.0	-13	Horizontal
7535.85	-55.4	-10.8	12.0	-56.6	-13	Vertical
17377.16	-56.5	-13.9	12.3	-54.9	-13	Vertical

GSM/GPRS MODE Channel 810:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
2837.57	-52.5	-5.8	8.9	-55.7	-13	Vertical
2874.35	-52.5	-5.8	8.9	-55.6	-13	Vertical
3765.18	-53.3	-7.9	10.4	-55.8	-13	Vertical
6985.87	-54.7	-9.4	12.0	-57.3	-13	Horizontal
7537.58	-55.2	-10.8	12.0	-56.4	-13	Vertical
17315.83	-56.3	-13.9	12.3	-54.7	-13	Vertical

EDGE (GMSK) MODE Channel 810:

Frequency (MHz)	Power (dBm)	Pca Cable loss(dB)	Ga Antenna Gain (dB)	Pmea (dBm)	Limited (dBm)	Polarization
2842.92	-52.7	-5.8	8.9	-55.8	-13	Vertical
2877.42	-53.4	-5.8	8.9	-56.5	-13	Vertical
3782.63	-53.4	-7.9	10.4	-55.9	-13	Vertical
6994.73	-54.5	-9.4	12.0	-57.1	-13	Vertical
7568.87	-55.4	-10.8	12.0	-56.6	-13	Horizontal
17374.55	-56.3	-13.9	12.3	-54.7	-13	Vertical

2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date
1	E5515C(8960) Mobile Station Tester	Agilent	MY48367401	2014.8
2	N9020A Spectrum Analyzer	Agilent	MY48010771	2014.8
3	DC Power Supply E3645A	Agilent	MY40000740	2014.8
4	Power Splitter 11850C	Agilent	026057	2014.8
5	Temperature chamber SH241	ESPEC	92000390	2014.8
6	12.65m×8.03m×7.50m Fully-Anechoic Chamber	FRANKONIA	-----	-----
7	Turn table Diameter:1m	HD	-----	-----
8	Antenna master FAC(MA4.0)	MATURO	-----	-----
9	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100030	2014.8
10	HL562 Ultra log antenna	R&S	100016	2014.8
11	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2014.8
12	ESI 40 EMI test receiver	R&S	100015	2014.8
13	Radio tester	CMU 200	114667	2014.8

Appendix

Appendix1 Test Setup