

#01_GSM850_GPRS(2Tx slots)_Left Cheek_Ch128


Communication System: GPRS/EDGE (2 Tx slots) (0); Frequency: 824.2 MHz; Duty Cycle: 1:4.15
Medium: HSL_835_150415 Medium parameters used: $f = 824.2$ MHz; $\sigma = 0.894$ mho/m; $\epsilon_r = 42.395$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.7 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(9.41, 9.41, 9.41); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch128/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.767 mW/g

Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 27.615 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 2.187 W/kg
SAR(1 g) = 1.090 mW/g; SAR(10 g) = 0.643 mW/g
Maximum value of SAR (measured) = 1.532 mW/g



#02_GSM1900_GSM Voice_Left Cheek_Ch810


Communication System: General GSM (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.3
Medium: HSL_1900_150415 Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.434$ mho/m; $\epsilon_r = 38.942$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.4, 8.4, 8.4); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch810/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.557 mW/g

Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 17.596 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 2.119 W/kg
SAR(1 g) = 0.959 mW/g; SAR(10 g) = 0.406 mW/g
Maximum value of SAR (measured) = 1.595 mW/g



0 dB = 1.600mW/g

#05_LTE Band 4_20M_QPSK(50,0)_Left Cheek_Ch20175


Communication System: FDD_LTE (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1
Medium: HSL_1750_150217 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.355$ mho/m; $\epsilon_r = 41.479$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.8 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.55, 8.55, 8.55); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 2.084 mW/g

Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.475 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 2.707 W/kg
SAR(1 g) = 1.330 mW/g; SAR(10 g) = 0.612 mW/g
Maximum value of SAR (measured) = 2.067 mW/g



0 dB = 2.070mW/g

#06_LTE Band 2_20M_QPSK(1,0)_Left Cheek_Ch19100


Communication System: FDD_LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: HSL_1900_150216 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.425$ mho/m; $\epsilon_r = 38.906$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.4, 8.4, 8.4); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.958 mW/g

Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.391 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 2.580 W/kg
SAR(1 g) = 1.210 mW/g; SAR(10 g) = 0.522 mW/g
Maximum value of SAR (measured) = 2.022 mW/g



0 dB = 2.020mW/g

#08_WLAN 2.4GHz_802.11b_1Mbps_Right Cheek_Ch11


Communication System: WIFI (0); Frequency: 2462 MHz; Duty Cycle: 1:1.024
Medium: HSL_2450_150416 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.856$ mho/m; $\epsilon_r = 39.882$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.7 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.48, 7.48, 7.48); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x141x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (interpolated) = 0.394 mW/g

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.551 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.587 W/kg
SAR(1 g) = 0.245 mW/g; SAR(10 g) = 0.113 mW/g
Maximum value of SAR (measured) = 0.394 mW/g



0 dB = 0.390mW/g

#11_WCDMA Band V_RMC12.2Kbps_Left Side 1cm_Ch4132


Communication System: UMTS (0); Frequency: 826.4 MHz; Duty Cycle: 1:1
Medium: MSL_835_150304 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r = 54.926$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(9.31, 9.31, 9.31); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (41x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.912 mW/g

Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 28.683 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 1.040 W/kg
SAR(1 g) = 0.743 mW/g; SAR(10 g) = 0.514 mW/g
Maximum value of SAR (measured) = 0.910 mW/g



0 dB = 0.910mW/g

#14_LTE Band 2_20M_QPSK(1,49)_Front 1cm_Ch19100


Communication System: FDD_LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: MSL_1900_150228 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.552$ mho/m; $\epsilon_r = 53.303$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.9 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.56, 7.56, 7.56); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.617 mW/g

Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.423 V/m; Power Drift = -0.0063 dB
Peak SAR (extrapolated) = 2.015 W/kg
SAR(1 g) = 1.170 mW/g; SAR(10 g) = 0.608 mW/g
Maximum value of SAR (measured) = 1.620 mW/g



0 dB = 1.620mW/g

#15_LTE Band 7_20M_QPSK(50,0)_Bottom Side 1cm_Ch20850


Communication System: FDD_LTE (0); Frequency: 2510 MHz; Duty Cycle: 1:1
Medium: MSL_2600_150326 Medium parameters used: $f = 2510$ MHz; $\sigma = 2.113$ mho/m; $\epsilon_r = 51.294$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.82, 6.82, 6.82); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch20850/Area Scan (41x81x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (interpolated) = 1.840 mW/g

Ch20850/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 19.832 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 2.442 W/kg
SAR(1 g) = 1.180 mW/g; SAR(10 g) = 0.525 mW/g
Maximum value of SAR (measured) = 1.812 mW/g



0 dB = 1.810mW/g

#16_WLAN 2.4GH_802.11b_1Mbps_Back 1cm_Ch11


Communication System: WIFI (0); Frequency: 2462 MHz; Duty Cycle: 1:1.024
Medium: MSL_2450_150416 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.959$ mho/m; $\epsilon_r = 50.912$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.14, 7.14, 7.14); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x141x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (interpolated) = 1.488 mW/g

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.273 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 2.589 W/kg
SAR(1 g) = 1.140 mW/g; SAR(10 g) = 0.470 mW/g
Maximum value of SAR (measured) = 1.794 mW/g



0 dB = 1.790mW/g

#23_LTE Band 7_20M_QPSK(1,0)_Back 1.5cm_Ch20850


Communication System: FDD_LTE (0); Frequency: 2510 MHz; Duty Cycle: 1:1
Medium: MSL_2600_150301 Medium parameters used: $f = 2510$ MHz; $\sigma = 2.085$ mho/m; $\epsilon_r = 52.993$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.82, 6.82, 6.82); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch20850/Area Scan (81x141x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (interpolated) = 1.612 mW/g

Ch20850/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.021 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 1.989 W/kg
SAR(1 g) = 1.050 mW/g; SAR(10 g) = 0.520 mW/g
Maximum value of SAR (measured) = 1.521 mW/g



0 dB = 1.520mW/g

#24_WLAN 2.4GHz_802.11b_1Mbps_Back 1.5cm_Ch11


Communication System: WIFI (0); Frequency: 2462 MHz; Duty Cycle: 1:1
Medium: MSL_2450_150416 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.959$ mho/m; $\epsilon_r = 50.912$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.0 °C ; Liquid Temperature : 22.0 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.14, 7.14, 7.14); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x141x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (interpolated) = 0.597 mW/g

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 3.544 V/m; Power Drift = -0.031 dB
Peak SAR (extrapolated) = 0.872 W/kg
SAR(1 g) = 0.423 mW/g; SAR(10 g) = 0.196 mW/g
Maximum value of SAR (measured) = 0.635 mW/g



#01-1 GSM850_GPRS (2 Tx slots)_Left Cheek_Ch128

Communication System: UID 0, GPRS (GMSK 2 Tx slot) (0); Frequency: 824.2 MHz; Duty Cycle: 1:4.15

Medium: HSL_835_150528 Medium parameters used: $f = 824.2$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 42.316$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(9.62, 9.62, 9.62); Calibrated: 2014/10/2;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2015/4/28
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1754
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch128/Area Scan (61x111x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.60 W/kg



Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.95 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.82 W/kg

SAR(1 g) = 0.926 W/kg; SAR(10 g) = 0.569 W/kg

Maximum value of SAR (measured) = 1.27 W/kg



0 dB = 1.27 W/kg

#02-1 GSM1900_GSM Voice_Left Cheek_Ch810

Communication System: UID 0, GSM Voice (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HSL_1900_150531 Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.466$ S/m; $\epsilon_r = 40.792$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.9 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(7.95, 7.95, 7.95); Calibrated: 2014/10/2;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2015/4/28
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1753
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch810/Area Scan (61x111x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.22 W/kg


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.37 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.65 W/kg

SAR(1 g) = 0.786 W/kg; SAR(10 g) = 0.342 W/kg

Maximum value of SAR (measured) = 1.15 W/kg



0 dB = 1.15 W/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/28

#04-1 WCDMA Band IV_RMC 12.2Kbps_Left Cheek_Ch1513


Communication System: UID 0, WCDMA (0); Frequency: 1752.6 MHz; Duty Cycle: 1:1
Medium: HSL_1750_150523 Medium parameters used: $f = 1752.6$ MHz; $\sigma = 1.398$ S/m; $\epsilon_r = 41.228$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(8.18, 8.18, 8.18); Calibrated: 2014/10/2;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2015/4/28
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1754
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch1513/Area Scan (61x111x1): Interpolated grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.53 W/kg

Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.26 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 2.06 W/kg
SAR(1 g) = 0.983 W/kg; SAR(10 g) = 0.440 W/kg
Maximum value of SAR (measured) = 1.41 W/kg



0 dB = 1.41 W/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

#05-1 WCDMA Band II_RMC 12.2Kbps_Left Tilted_Ch9538

Communication System: UID 0, WCDMA (0); Frequency: 1907.6 MHz;Duty Cycle: 1:1
Medium: HSL_1900_150531 Medium parameters used: f=

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/28

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/28

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/23

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/6/2

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/30

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/30

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/29

#1

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/29

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/30

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/29

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/6/3

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/30

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

#27-1 WCDMA Band V_RMC 12.2Kbps_Back_1.5cm_Ch4233


Communication System: UID 0, WCDMA (0); Frequency: 846.6 MHz; Duty Cycle: 1:1
Medium: MSL_835_150530 Medium parameters used: $f = 846.6$ MHz; $\sigma = 0.987$ S/m; $\epsilon_r = 54.286$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(9.66, 9.66, 9.66); Calibrated: 2014/10/2;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2015/4/28
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1753
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch4233/Area Scan (61x101x1): Interpolated grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.617 W/kg

Ch4233/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.21 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.684 W/kg
SAR(1 g) = 0.535 W/kg; SAR(10 g) = 0.409 W/kg
Maximum value of SAR (measured) = 0.617 W/kg



0 dB = 0.617 W/kg

#28-1 WCDMA Band IV_RMC 12.2Kbps_Front_1.5cm_Ch1312


Communication System: UID 0, WCDMA (0); Frequency: 1712.4 MHz; Duty Cycle: 1:1
Medium: MSL_1750_150529 Medium parameters used: $f = 1712.4$ MHz; $\sigma = 1.452$ S/m; $\epsilon_r = 53.496$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(7.93, 7.93, 7.93); Calibrated: 2014/10/2;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2015/4/28
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1754
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch1312/Area Scan (61x111x1): Interpolated grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.797 W/kg

Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.447 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.923 W/kg
SAR(1 g) = 0.600 W/kg; SAR(10 g) = 0.358 W/kg
Maximum value of SAR (measured) = 0.784 W/kg



0 dB = 0.784 W/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/29

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/30

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/29

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/5/31

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2015/6/3

